

HYPERZONE

Brightest in Class Outdoor Washbeam

SPEC SHEET



Foshan YiFeng Electric Industrial Co.,Ltd.

No.898, Gaoming Avenue East, Hecheng Blvd, Gaoming District, Foshan, Guangdong, China.

Web: www.acmelighting.com Email: sales@acmelighting.com

All rights reserved by Acme®. Features, specifications and appearance are subject to change without notice.

REV: 07/09/2026

Acme®

HYPERZONE

Brightest in Class Outdoor Washbeam

SPEC SHEET

FIXTURE OVERVIEW

- The ACME **HYPERZONE** is a next-generation moving LED wash beam light, driven by 7 x 150W RGBL LEDs, delivering vibrant, saturated colors that stand out on any stage.
- With individual pixel control and built-in color macros, you can craft additional layers of creativity with ease. Designed for ultimate flexibility, the **HYPER-ZONE** features a variable beam angle of 3° to 32° and a field angle of 4.8° to 45°, offering both tight, punchy beams and wide, soft washes.
- A variable CTO enables seamless transitions from cool to warm temperatures for natural color rendering. Fast and precise pan/tilt movement adds dynamic energy to your show. While its IP66 rating ensures reliable performance in all weather conditions with minimal maintenance.
- Redefining what a wash light can be, the ACME **HYPERZONE** delivers high performance and vibrant visuals—wherever your vision takes you.



FEATURE HIGHLIGHTS

- LED engine comprised of 7 x 150W RGBL LEDs
- Individual pixel control
- Beam Angle: 3°-32°
- Field Angle: 4.8°-45°
- Fixture Luminous Output:
 - Auto Mode: 19,500 lumens
 - Quiet Mode: 10,000 lumens
 - Theatre Mode: 9,500 lumens
- Color Temperature Output: 8,000K
- Sharp and saturated beam effects
- Variable CTO ranging from 2,500K-8,000K
- Dimming frequency from 900Hz to 25,000Hz
 - Smooth dimming 0-100%
- (4 user selectable dimming curves)
- Outstanding color macro effects
- Excellent color mixing
- IP66 rated

TECHNICAL SPECIFICATIONS

Light Source

- Light Source: 7 x 150W RGBL LEDs
- Color Temperature Output of Fixture: 8,000K
- Life Expectancy: 20,000 hours
- *Source manufacturer specification

Photometric Data

- Fixture Luminous Output:
 - Auto Mode: 19,500 lumens
 - Quiet Mode: 10,000 lumens
 - Theatre Mode: 9,500 lumens
- CCT: 8,000K (+/- 200K)
- Ra: 86
- TM-30 Rf (IES TM-30-15 Fidelity Index): 88
- TM-30 Rg (IES TM-30-15 Fidelity Index): 106
- TLCI: 90
- Peak Luminous Intensity: 2,319,000 cd

Optical System

- Beam Angle: 3°-32°
- Field Angle: 4.8°-45°

Control & Program

- 4 touch button control panel
- Display: LCD display
- Protocols: DMX512, RDM, Art-Net, sACN
- DMX Protocol Modes: 6
- Control Channels: 19/20/21/41/42/43
- Firmware Upgrade: Upgrade via DMX link or USB stick

Pan & Tilt

- Pan Movement: 540°
- Tilt Movement: 210°
- Automatic Pan/Tilt position correction
- Resolution: 16 bit
- Fixation: Pan/Tilt lock

Color Correction

- Linear CTO Color Correction: 2,500K-8,000K

Electrical

- Input Voltage Range: 100-240Vac; 50/60Hz
- Power Consumption: 1,370W

- Power In/Out: Waterproof power connector in/out
- Data In/Out: 3-pin or 5-pin waterproof XLR, RJ45 connector

Physical

- Weight: 26.3 kg (58.0 lbs)
- Length (Head): 304 mm (12.0")
- Length (Base): 380 mm (15.0")
- Width (Across Yoke): 374 mm (14.7")
- Height (Head Up): 500 mm (19.7")

Construction

- Housing: Magnesium alloy
- Color: Black
- Protection Rating: IP66

Work Environment

- Maximum Ambient Temperature: 40°C
- Minimum Operating Temperature: -10°C
- Maximum Surface Temperature: 75°C

Acoustic Data

- Noise Level:
 - Auto Mode: 50 dB(A) @ 1 m
 - Quiet Mode: 36 dB(A) @ 1 m
 - Theatre Mode: 29 dB(A) @ 1 m

Installation

- Universal working position
- 2 omega brackets
- Safety cable attachment point

Approvals

- CE compliant
- EMC directive 2014/30/EU
- LVD directive 2014/35/EU
- UKCA compliant
- Electromagnetic Compatibility Regulations 2016
- Electrical Equipment (Safety) Regulations 2016
- cETLus compliant
- UL 1573
- CSA C22.2 #166



INCLUDED ITEMS

Included Items

- Digital user manual
- Power cable
- 2 omega brackets (3002003003)

ORDERING INFORMATION

Optional Accessories

(With Order Code)

- Flight Case:
 - Standard: Two-pack loader case (63584070)
 - North American Standard :
 - Three-pack loader case (63584124)
- Signal Cable:
 - 3-pin waterproof signal cable (3017013468) or
 - 5-pin waterproof signal cable (3017013473)
- Safety Cable: SW-05 (2060001603-E)
- Clamp: C-250B (2060001632-B)

Carton Dimensions

- Width: 490 mm (19.3")
- Depth: 450 mm (17.7")
- Height: 675 mm (26.6")
- Weight:
 - G.W.: 32 kg (70.6 lbs) (one-pack loader carton)



3-pin/5-pin waterproof
signal cable: 3017013468/3017013473



SW-05: 2060001603-E



C-250B: 2060001632-B



Standard(Two-pack loader
case): 63584070

HYPERZONE

Brightest in Class Outdoor Washbeam

SPEC SHEET

(STANDARD) FLIGHT CASE

APPLICABLE MODELS

- HYPERZONE (CM 7 IP)

ORDER CODE

- 63584070 HYPERZONE (CM 7 IP)

CASE WEIGHT

- 46 kg (101.5 lbs)

MEAS





- 980 x 580 x 825 mm (38.6" x 22.8" x 32.5")

LOADING Q'TY

- Two-pack loader case

MAXIMUM STACKING

- 2 stacks



ACME by ACME Version: 20250519-A

Foshan YiFeng Electric Industrial Co.,Ltd.

No.898, Gaoming Avenue East, Hecheng Blvd, Gaoming District, Foshan, Guangdong, China.

Web: www.acmelighting.com Email: sales@acmelighting.com

All rights reserved by Acme®. Features, specifications and appearance are subject to change without notice.

REV: 07/09/2026


ACME®

HYPERZONE

Brightest in Class Outdoor Washbeam

SPEC SHEET

DIMENSIONS



Foshan YiFeng Electric Industrial Co., Ltd.

No.898, Gaoming Avenue East, Hecheng Blvd, Gaoming District, Foshan, Guangdong, China.


Web: www.acmelighting.com Email: sales@acmelighting.com

All rights reserved by Acme®. Features, specifications and appearance are subject to change without notice.

REV: 07/09/2026

ACME®

HANGING DIMENSIONS



HYPERZONE


Brightest in Class Outdoor Washbeam

SPEC SHEET


PHOTOMETRIC

Auto Mode

Beam Angle:



Field Angle:



HYPERZONE

Brightest in Class Outdoor Washbeam


SPEC SHEET

PHOTOMETRIC

Quiet Mode

Beam Angle:


Distance m (ft) 5 (16.4) 10 (32.8) 15 (49.2) 20 (65.6)



3° Lux	140,000	35,000	15,555	8,750
Diameter m (ft)	0.3(1)	0.6(2)	0.8(2.6)	1.1(3.6)
32° Lux	3,520	880	391	220
Diameter m (ft)	2.9(9.5)	5.8(19)	8.7(28.5)	11.6(38.1)

Field Angle:

Distance m (ft) 5 (16.4) 10 (32.8) 15 (49.2) 20 (65.6)



4.8° Lux	140,000	35,000	15,555	8,750
Diameter m (ft)	0.4(1.3)	0.8(2.6)	1.3(4.3)	1.7(5.6)
45° Lux	3,520	880	391	220
Diameter m (ft)	4.2(13.8)	8.3(27.2)	12.5(41)	16.8(55.1)

HYPERZONE


Brightest in Class Outdoor Washbeam

SPEC SHEET


PHOTOMETRIC

Theatre Mode

Beam Angle:




Field Angle:




PHOTOMETRIC REPORT – CHROMATICITY


Spectral Distribution




CRI: 85.9 (R1-R8)



CIE 1931 EVERFINE



CQS: 90.2 (Q1-Q8)



CRI C Values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
97.2	88.2	75.5	82.1	94.5	84.7	84.0	80.7	63.7	71.4	79.6	66.3	94.7	86.1	95.7	85.9

TM30 R Values

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97.2	88.2	75.5	82.1	94.5	84.7	84.0	80.7	63.7	71.4	79.6	66.3	94.7	86.1	95.7

CQS Q Values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
90.5	90.9	93.4	94.7	89.6	88.2	85.8	88.7	90.7	92.0	95.3	97.8	91.7	88.1	87.8

Colour Parameters

Color temperature	Color rendering index	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
7,386K	85.9	88	106	90.2	0.2998	0.3188	0.1926	0.4609	0.0047

HYPERZONE

Brightest in Class Outdoor Washbeam







SPEC SHEET

PHOTOMETRIC REPORT – TM-30

TM-30 Rf (IES TM-30-15 Fidelity Index): 88


TM-30 Rg (IES TM-30-15 Fidelity Index): 106

Hue Bin	Hue Angle	Graphic shift(%)		
		Rf	Chroma	Hue
1	0.0° – 22.5°	89	5	-4
2	22.5° – 45.0°	90	1	-4
3	45.0° – 67.5°	94	1	2
4	67.5° – 90.0°	91	0	5
5	90.0° – 112.5°	88	5	5
6	112.5° – 135.0°	88	8	2
7	135.0° – 157.5°	88	7	-4
8	157.5° – 180.0°	88	2	-7
9	180.0° – 202.5°	93	-2	-5
10	202.5° – 225.0°	91	-5	0
11	225.0° – 247.5°	87	-2	10
12	247.5° – 270.0°	79	2	11
13	270.0° – 292.5°	89	5	8
14	292.5° – 315.0°	83	9	8
15	315.0° – 337.5°	86	10	1
16	337.5° – 360.0°	85	7	-4



PHOTOMETRIC REPORT – TM-30

Color Evaluation Sample



PHOTOMETRIC REPORT – TLCI-90

Color Evaluation Sample



Sector	Lightness	Chroma	Hue
R	-2	-1	0
R/Y	0	0	-1
Y	-1	-1	-1
Y/G	-1	-2	-1
G	-1	-2	0
G/C	0	-2	3
C	0	-1	2
C/B	0	0	0
B	0	-2	-1
B/M	0	-2	0
M	0	-2	0
M/R	-1	-2	0