

iT10 Profile™

Retaining all the tools, features, options and light quality of the larger iT12 Profile™, the space saving, more compact iT10 Profile™ again delivers accurate, repeatable, high impact static profile performance in all weathers.

**Light source**

iSE-MSL-TE™ 200W LED Engine

**Light output**

9.700 lm

**Zoom range**

5°-55°

**Effects**

Frost, optional drop-in module with framing shutters and iris, optional drop-in module with rotating gobo wheel and animation Wheel

IP65-protected and engineered for real-world use, the iT10 Profile™ thrives in demanding environments. Its advanced, self-managing, low-maintenance ingress protection ensures consistent, reliable performance across theatre, broadcast, concert and theme park applications - indoors or outdoors, whatever the weather.

Delivering the renowned Multi-Spectral colour finesse of the T-Series, the iT10 Profile™ features an iSE-MSL-TE™ 200W LED IP65-rated engine, generating over 8.100 lm (integrating sphere). With cost-effective exchange or replacement, this LED technology ensures identical colour characteristics, response and control across T-Series luminaires, maintaining absolute installation consistency.

Patented TRANSFERABLE ENGINE technology extends fixture life, enabling easy field exchange and future LED upgrades. With typical lumen maintenance of L70/B50 at 40.000 hours and a 4-year/20.000-hour warranty, it guarantees lasting performance with confidence.

Offering RGB, CMY or individual emitter control, the luminaire includes factory-calibrated whites, a variable CCT range of 2.700-8.000K (1.800K-10.000K extended range), DataSwatch™ virtual colour library, adjustable CRI from 80 to 95+, and lamp-selectable tungsten emulation.

The 11:1 5°-55° motorised zoom with high-definition optics delivers exceptional flexibility.

For precise beam shaping, the optional drop-in motorised Plano4 FC™ full curtain framing shutters module, including an iris, provides four blades in separate planes, each with full 120° rotation cover all angles. A 5° medium frost, using the MagFrost™ quick-change system, is fitted as standard.

The patented BARS™ system locks motorised focus and zoom firmly in place, ensuring accurate, repeatable cue playback - even after power cycling.

An Optional gobo module expands creative possibilities with static and fully rotating, indexable wheels with replaceable gobos, plus an animation wheel with speed and directional control.

At the core of protection is RAINS™, actively managing the internal microclimate to prevent moisture build-up and maximise longevity. A fast Self Pressure Test verifies fixture integrity in under three minutes, ensuring correct sealing after maintenance.

Magnesium alloy covers and an aluminium substructure create a sealed, dust-free optical environment, reducing cleaning requirements and preventing UV damage. The parCoat™ hydrophobic and oleophobic lens coating repels water, dirt and haze, maintaining maximum output and enabling easy cleaning.

POLAR+™ technology allows instant operation in extreme cold, maintaining internal conditions down to -50 °C while reducing standby power consumption. The fixture is also available in a harsh environment finish for ultimate protection.

For remote installations, REAP™ provides browser-based monitoring with real-time fixture data, including RAINS™ status. NFC technology enables setup and diagnostic via mobile devices with the Robe Com app, even without power.

iT10 Profile™ - Robe reliability in all weathers.

Technical Specification

Source

Light source type: iSE-MSL-TE™ 200W LED Engine (Patented)

LED Engine output: 9.700 lm

LED life expectancy: min. 40.000 hours

Colour rendition: CRI: 95, CRI R9: 96, TM30-18 Rf: 92, TM30-18 Rg: 106, TLCI: 91

Typical lumen maintenance: L70/B50 @ 40.000 hours

Light source warranty: 4 years or 20.000 hours

Optical system

Robe's proprietary optical design

High-efficiency zoom optical system, ratio 11:1

Zoom range: 5°-55°

Fixture total lumen output: 8.100 lm (integrating sphere) 6.450 lm (goniophotometer)

parCoat™ (particle resistant coating) unique hydrophobic and oleophobic coating helps prevent water, dirt, dust, haze and smoke from adhering to the output lens

Main features

Colour mixing: CMY/RGB or RGBAL

White light: Variable CCT standard range 2.700K-8.000K, extended range 1.800K-10.000K

DataSwatch™ filters: pre-programmed 66 colours and tones including most used whites 2.700K, 3.200K, 4.200K, 5.600K

Factory calibrated whites and colours via the new RCC™ (Robe Colour Calibration) system, automatic or on-call self-re-calibration of the LED engine without the use of any external tool (Patented)

Tungsten lamp effect: 750W, 1.000W, 1.200W, 2.000W, 2.500W lamp emulation for whites from 2.700K to 4200K (red shift and thermal delay)

+/- Green correction function

Adjustable CRI: from 80 to 95+

Optional drop-in framing and iris module: Patented Plano4 FC™ framing shutters module with 4 individually positionable blades plus rotation of the complete frame system +/- 60°

Optional drop-in gobo module: Rotating gobo wheel and animation wheel

Rotating gobo wheel: 7 rotating, indexable and replaceable breakup and aerial gobos + open, patented slot & lock system

Animation wheel: Aluminium animation wheel, used alone or in combination with gobos, rotating in both directions at variable speed

Iris: Motorized, stepless, pulse effects up to 3 Hz (with optional drop-in framing and iris module)

Hot-Spot: from flat field to 6:1 hot-spot (optional)

MagFrost™ - magnetic paddle fast change system providing exchangeable frost containing as standard a medium 5° for even wash

Electronic strobe effect with variable speed up to 20 Hz, pre-programmed random strobe & pulse effects

High resolution electronic dimming: 0-100 %

L3™ - (Low Light Linearity) Imperceptible 18 bit dimming for ultra smooth fade to black

Dimmer profile selection: Linear, Square law

Cpulse™ special flicker-free management for HD and UHD cameras, ready for 8K and 16K

Extremely quiet operation suitable for all types of production in Theatre and TV

AirLOC™ (Less Optical Cleaning) technology greatly reduces the level of airborne particles drawn over the optical elements. This increases the overall performance, light quality and time between routine cleaning and maintenance.

POLAR+™ for power saving and instant operation in extremely cold weather conditions

Control and programming

Setting & Addressing: ROBE Navigation System 2 (RNS2)

Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding, NFC app controller

Protocols: USITT DMX-512, RDM ArtNet, MA Net, MA Net2, sACN

REAP™ - Robe Ethernet Access Portal

Wireless CRMX™ technology from Lumen Radio

Epass™: Ethernet pass through switch which sustains Ethernet integrity, when the fixture has no power, to automatically maintain network connectivity

RAINS™ (Robe Automatic Ingress Neutralization System) manages humidity, temperature and pressure control using an active monitoring system to automatically remove any moisture detected within the fixture and provides constant monitoring to ensure peak performance

DMX Protocol modes: 8

Control channels: 24, 28, 35, 39, 32, 36, 43, 47

Variable CCT: 8 bit

+/- Green correction: 8 bit

Colour mixing: 8 or 16 bit (internal 18 bit)

Framing shutters module movement & rotation: 8 bit

Gobo indexing & rotation: 8 or 16 bit

Animation wheel: 8 bit

Animation wheel rotation: 8 bit

Iris: 8 or 16 bit

Frost: 8 bit

Zoom: 8 or 16 bit

Focus: 8 or 16 bit

Dimmer: 8 or 16 bit (internal 18 bit)

Rotating gobos

7x rotating glass gobos: (with optional drop-in gobo module)

Outside diameter: 22 mm

Image diameter: 18 mm

Thickness: 1,1 mm

Max. thickness: 3,5 mm

High temperature borofloat or better glass

Patented slot & lock system for easy replacement of gobo

Effect wheel

Single animation wheel: (with optional drop-in gobo module)

Material: Aluminium

Can be used alone or in combination with rotating gobos

Diameter: 109 mm

Rotating in both directions at variable speed

Framing shutters system

Patented Plano4 FC™ framing shutters module: (with optional dropin framing and iris module)

Shutters: 4 Blades, each with separate movement and +/- 25° rotation control

Movement: Smooth with variable speed, ultrafast blade movements for creating mid-air effects

Pre-programmed: Shape and blade sequences

Rotation: +/- 60° of the complete framing system

Thermal specification

Maximum ambient temperature: 50 °C (122 °F)

Maximum surface temperature: 90 °C (176 °F)

Minimum operating temperature: -50 °C (-58 °F)

Total heat dissipation: max. 1125 BTU/h (calculated)

Electrical specification and connections

Power supply: Electronic auto-ranging

Input voltage range: 100-240 V, 50/60 Hz

Power consumption: Max. 350 W

Power connector in/out: IP65 TRUE1 compatible in/out

DMX and RDM data in/out: IP65 Locking 5-pin XLR connectors

Ethernet port in/out: IP65 RJ45 for Embedded Epass™ switch 10/100 Mbps

Approvals

CE Compliant

cETLus Compliant

UKCA Compliant

Mechanical specification

Height: 493 mm (19,4") with yoke

Width: 367 mm (14,4")

Depth: 563 mm (22,2")

Weight: 19,8 kg (43,6 lbs)

Ingress protection rating: IP65

Rigging

Mounting horizontally or vertically via mounting yoke

Mounting points: M12 bolt

Safety cable attachment point

Included items

User Manual

Gel frame adaptor

Power cord including:

powerCON TRUE1 In connector: US:13052277-01

powerCON TRUE1 In connector: EU:13052276-01

Optional accessories

Doughty Trigger Clamp

Safety wire 36 kg: 99011963

Floor stand: 10981014

Frost 0,5° (exchange) assembled: 10981149

Frost 1° (exchange) assembled: 10981150

Frost 5° (exchange) assembled: 10981151

Frost 10° (exchange) assembled: 10981152

Frost 20° (exchange) assembled: 10981153

Frost 30° (exchange) assembled: 10981154

Single Top Loader Case 10120415

Single Top Loader Trolley case 10120417

Dual Top Loader Case 10120416

Foam Shell 20020554

Legal

iT10 Profile™ is a Trademark of ROBE lighting s.r.o.

iT10 Profile™ is patented by ROBElighting s.r.o. and is protected by one or more pending or issued patents