

## COLORDash PAR Bar 4

A complete wash light solution featuring four independently focusable RGBAW-UV LED heads, included accessories for versatile light shaping, and advanced flicker-free electronics.

Designed for convenience, this system is ideal for small theatres, events, and multi-use spaces requiring a comprehensive, easy-to-deploy, and on-camera-ready lighting package.

- Generates a comprehensive color palette, including true UV, from four high-power LED arrays.
- Offers flexible beam control, adjusting from 15° to 30° with an included wide filter.
- Supports DMX and RDM control via 5-pin XLR or a standard CAT6 Ethernet connection.
- Features adjustable PWM to eliminate on-camera flicker for broadcast and recording applications.
- Delivers exceptionally smooth fades with a choice of four selectable dimming curves.
- Simplifies setup with power linking for up to 4 units at 208 V.



### SPECIFICATIONS

#### Optical

**Light Source:** 1, RGBAW-UV LED Array (per head)  
**Beam Angle narrow (Single Par):** 15.3°  
**Field Angle narrow (Single Par):** 29.8°  
**Beam Angle wide (Single Par):** 30.4°  
**Field Angle wide (Single Par):** 49.4°  
**Lumens (Single Par):** 4305 lm  
**Lumens (All Pars):** 17930 lm  
**Illuminance Narrow (Single Par):** 1482 lux @ 5 m  
**Illuminance Wide (Single Par):** 510 lux @ 5 m  
**Selectable PWM:** 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 6000 Hz, 25,000 Hz

#### Dynamic Effects

**Dimmer:** Electronic  
**Strobe Rate:** 0 to 20 Hz  
**Standalone Color Mixing:** Yes  
**Color Temperature Presets:** Yes  
**Dim Modes:** 4  
**Built-in Automated Programs:** Yes

#### Construction / Physical

**Dimensions:** 45.3 x 5.16 x 11.08 in ( 1150.6 x 131 x 281.4 mm)  
**Weight:** 28.8 lb (12 kg)  
**Exterior Color:** Black  
**Housing Material:** Aluminum Alloy

#### Connections

**Power Connection:** Edison (Local) plug to Seetronic Powerkon IP65  
**Power Input:** Seetronic Powerkon IP65  
**Power Output:** Seetronic Powerkon IP65  
**Data Connectors:** 5-pin XLR, Neutrik etherCON or Amphenol XLRnet (etherCON Compatible)  
**Cable Length (power):** 5 ft (1.5 m)

#### Control

**Control Protocol:** DMX, RDM  
**DMX Channels:** 6,8,9,14,24,32,36,41  
**Modes/Personalities:** 8 personalities (6,8,9,14,24,32,36,41)

#### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)  
**Power Linking:** 2 units @ 100 V; 2 units @ 120V; 4 units @ 208 V; 4 units @ 230 V; 5 units @ 240 V  
**Power and Current:** 557W, 5.55 A @ 100 V, 60 Hz  
**Power and Current:** 551W, 4.63 A @ 120 V, 60 Hz  
**Power and Current:** 546 W, 2.63 A @ 208 V, 60 Hz  
**Power and Current:** 550W, 2.41 A @ 230 V, 50 Hz  
**Power and Current:** 559W, 2.33 A @ 240 V, 50 Hz

#### Certifications / Qualifications

**Certifications:** CE, MET, FCC, UKCA  
**IP Rating:** IP20, dry location  
**Temperature (Ambient):** 32 °F to 104 °F (0 °C to 40 °C)

### Optional Accessories

Professional Clamps : CTC-50HC, CTC-50HCN  
Seetronic Powercon power linking cables.  
5-pin IP or Non-IP DMX Cables  
Ethernet or etherCON compatible cables

### What's Included

COLORDash Par Bar  
Seetronic Powercon IP65 power cord  
Wide Filter (4pc)  
Barndoors (4pc)  
Tripod mount