



# Maverick Storm 1 Beam

A powerful and compact IP65-rated moving head beam fixture that delivers sharp, stadium-scale aerial effects with CMY color mixing, dual layerable prisms, and frost.

Perfect for stadium tours, large outdoor festivals, and any large-scale production where powerful, weather-proof aerial beam effects are essential.

- Features a powerful OSRAM SIRIUS HRI 310 W lamp for intense, focused aerial effects.
- Projects a razor-sharp 1.3-degree beam for creating precise mid-air effects.
- Offers a 14-color wheel plus white for quick color changes and split-color effects.
- Features a 17-slot static gobo wheel and two layerable, independent prisms for complex looks.
- Built with a lightweight, rugged aluminum and magnesium alloy housing for touring and events.
- Supports DMX, RDM, ArtNet, sACN, and W-DMX for versatile system integration.

## SPECIFICATIONS

### Optical

**Light Source:** SIRIUS HRI 310 W lamp 7650K, 6,000 hours life expectancy

**Color Temperature (at full):** 7178 K

**CRI:** 80.1

**Beam Angle:** 1.3°

**Field Angle:** 2.3°

**Cutoff Angle:** 3 °

**Lumens – Output:** 30,639

**Illuminance (total):** 190,709 lux @ 15 m

### Dynamic Effects

**Pan and Tilt:** 540°/270°

**Pan and Tilt Ranges:** 540°, 360°, 180° pan/270°, 180°, 90° tilt

**Colors:** 14 + white, split colors, continuous scroll at variable speeds

**Dynamic Effects:** CMY, CTO

**Gobos:** 17 + open (17 metal), continuous scroll at variable speeds

**Gobo Size (1):** Gobo Wheel 1 (static): 123 mm (outside), 6 mm (image), 1 mm (max. thickness)

**Dimmer:** Motorized

**Shutter/Strobe:** Motorized

**Focus:** Motorized

**Frost:** Motorized

**Prism:** 5 Facets, motorized, rotating

**Prism:** 8 Facets, motorized, rotating

**Move-in-Black:** Yes

### Construction / Physical

**Dimensions:** 15.28 x 10.04 x 25.91 in (388 x 255 x 658 mm)

**Weight:** 51.2lb (23.3 kg)

**Exterior Color:** Black

**Housing Material:** Aluminum diecast, High-impact flame-retardant polymer, Steel

### Connections

**Power Connection:** Edison plug to Seetronic Powerkon IP65

**Power Input:** Seetronic Powerkon IP65

**Data Connectors:** 5-pin IP rated

**Cable Length (power):** 5 ft (1.5 m)

### Control

**Control Protocol:** DMX, RDM, ArtNet, sACN, Lumen Radio

**DMX Channels:** 19 or 21

**Modes/Personalities:** 2 personalities (19, 21)

### Electrical

**Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)

**Power and Current:** 482 W, 4.070 A @ 120 V, 60 Hz

**Power and Current:** 469 W, 2.334 A @ 208 V, 60 Hz

**Power and Current:** 467 W, 2.011 A @ 230 V, 50 Hz

## Certifications / Qualifications

**Certifications:** CE, MET, FCC, UKCL, CB

**IP Rating:** IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve

### Noise Levels:

**Idle:** 52.0 dB(A) @ 1 m

**Max:** 52.4 dB(A) @ 1 m

**Temperature (Ambient):** 14 °F to 113 °F (-10 °C to 45 °C)

## Optional Accessories

Professional Clamps : CTC-50HC, CTC-50HCN

Safety Cable: SC-07

DMX Cables

IP Rated Seetronic® Powerkon Extensions

Upload 08 Software Uploader

Micro T-1 TRX G6 WDMX Transceiver

## What's Included

Maverick Storm 1 Beam

Seetronic Powerkon IP65 power cord

2 Omega brackets with mounting hardware

Quick Reference Guide