



Maverick Storm 4 SoloWash

A powerful, outdoor-ready IP65-rated 1250W single-source LED wash engineered for classic looks and modern versatility with CMY+CTO color mixing, framing shutters, a rotating gobo wheel, and an animation wheel.

Ideal for stadium-level productions, large-scale tours, festivals, and any indoor or outdoor venue demanding a powerful, feature-packed, and weather-resistant wash fixture.

- Delivers a massive 78,300 lumens for stadium-level long throw applications.
- Features an expansive 7.1° to 74.1° zoom range for creating variable beam sizes.
- Includes a dedicated color wheel with CRI and CTB filters for superior color rendering.
- Offers a fully rotatable four-blade framing system for precise, articulate beam shaping.
- Provides additional beam control with an integrated iris and a variable frost filter.
- Supports DMX, W-DMX, sACN, and Art-Net for versatile and integrated control solutions.

SPECIFICATIONS

Optical

Light Source: 1 LEDs (CW) 1250 W, (35.84A), 7464 K, 50,000 hours life expectancy.

Color Temperature (at full): 7252K

Front lens diameters: 225 mm

CRI: 69.5

CQS: 69.4

TLCI: 47

CRI with CRI filter: 89.6

CQS with CRI filter: 88.2

TLCI with CRI filter: 82

CTO color temperature at full: 3323K

Cutoff Angle: 15.7° to 74.1°

Zoom Range: 7.1° to 74.1°

Lumens: 78,300

Illuminance:

Illuminance (6.8°): 162,410 lux @ 5 m

Illuminance (71.6°): 4,798 lux @ 5 m

Selectable PWM: 600 Hz, 1200 Hz, 4000 Hz, 6000 Hz, 15000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt

Colors: Colors: Colors: 5 (Red, Yellow, Green, UV, and CRI) + white, split colors, continuous scroll at variable speeds

Colors: CMY flags, CTO flag, color correction

Gobos (1): 6 + open (6 metal), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds

Gobo Size: Gobo Wheel 1 (rotating): 30 mm (outside), 26 mm (image), 0.6 mm (max. thickness)

Effect Wheel: 1 effects

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Frost: Motorized

Strobe Rate: 0 to 25.6Hz

Move-in-Black: Yes

Dim Curves: 5

Construction / Physical

Dimensions: 18.46 x 12.04 x 32.16 in (469 x 306 x 817 mm)

Weight: 100.2 lb (45.5 kg)

Exterior Color: Black

Housing Material: Magnesium Aluminum die-cast, High-impact flame-retardant polymer, Steel

Connections

Power Connection: Seetronic Powercon IP65

Power Input: Seetronic Powercon IP65

Data Connectors: 5-pin IP rated XLR, Neutrik IP rated RJ45
Connectors in/out

Cable Length (power): 5 ft (1.5 m)

Software Update: USB-C

Control

Control Protocol: Art-Net, DMX, RDM, W-DMX, sACN

DMX Channels: 31 or 46

Art-Net Channels: 31 or 46

Modes/Personalities: 2 personalities (31ch, 46ch)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power and Current: 1720 W, 14.67 A @ 120 V, 60 Hz

Power and Current: 1690 W, 8.35 A @ 208 V, 60 Hz

Power and Current: 1680 W, 7.48 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve

Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

Optional Accessories

Clamps

Neutrik powerCON cables

Neutrik etherCON cables

DMX Cables

Flight Cases

IP Tester

CP Rack

What's Included

Maverick Storm 4 Solo Wash

Seetronic Powercon IP65

(2) 140-D Omega bracket with mounting hardware

(2) handles and (8) screws