

P6

HIGH OUTPUT FULL-SPECTRUM ELLIPSOIDAL



FEATURES

- ▶ Future-proof LED Profile Spotlight meeting coming EU regulations
- ▶ 16,000 lm luminous flux replaces conventional 2.5 kW halogen profile lights
- ▶ 600 W RGBALC LED (RGB, Amber, Lime, Cyan)
- ▶ High CRI (98 @ 5,600 K) and TLCI (94 @ 5,600 K) for natural colour rendering
- ▶ Seamless colour temperature adjustment from 1,800 K to 10,000 K
- ▶ Extremely precise, calibrated XColour™ colour mixing
- ▶ Manually operated zoom range (5° - 50°) and additional focus
- ▶ Protected and registered stepless, linear frost for versatile and seamless beam shaping
- ▶ 360° rotatable four-blade framing system
- ▶ Dual slot-in system for flexible combination of iris and gobo holder, with manual rotation
- ▶ Whisper-quiet operation

DESCRIPTION

The P6 is a future-proof LED profiler with a powerful 600 W RGBALC engine and 16,000 lumens, making it the perfect energy-efficient replacement for traditional 2.5 kW halogen profile lights in theaters and venues. It unites excellent lighting quality and natural colour reproduction with flexible lighting design tools in a modern lighting solution, which not only impresses in theatres, musicals, and TV studios, but also at congresses or event stages in the live performance sector and corporate world.

Thanks to the XColour™ technology designed & engineered in Germany, the P6 works with an extremely precise colour calibration mixing system based on the RGBALC (RGB + Amber + Lime + Cyan) LED engine. At the same time, the high CRI of 98 @ 5,600 K and a TLCI value of 94 @ 5,600 K ensure that people and objects are always vibrantly presented in clear and dynamic colours. In the white light range, the colour temperature can be continuously adjusted between 1,800 K and 10,000 K.

To flexibly adapt the P6's powerful light to different stage requirements, the LED profiler is equipped with an integrated zoom in the 5° to 50° range. In combination with the 360° rotatable four-blade framing system and the infinitely variable integrated frost filter (the iris and gobo holders supplied can be optionally added via a slot system), users have a wide array of creative light-shaping options at their disposal.

With an LED service life of around 50,000 hours and significantly reduced power consumption compared to old 2.5 kW halogen profile lights, the P6 is a future-proof lighting solution. This not only contributes to lower energy costs and reduced environmental impact but also aligns with the overarching 'Green Deal' (aiming for climate neutrality by 2050) and the harmonisation of eco-design guidelines for light sources within the European Union.

P6

HIGH OUTPUT FULL-SPECTRUM ELLIPSOIDAL

Specifications

Photometric values

Illuminant type	LED RGBALC
Illuminant power	600 W
Luminous flux	16000 lm
Front lens diameter	150 mm
Exchangable lens	Yes
Exchangable optics	No
Zoom range	5 – 50 °
Focusing type	Manual
LED PWM frequency	1,530 Hz, 3,600 Hz, 12 kHz, 18.9 kHz, 25 kHz
Dimmer resolution	16 Bit
Dimmer curves	Linear, Exponential, Logarithmic, S curve, Tungsten

Colours

LED colours	Red, Green, Blue, Amber, Lime, Cyan
Correlated colour temperature (CCT)	1800 – 10000 K
Halogen simulation redshift/DTW	Yes
Calibration	Smart calibration
Colour rendering index (CRI)	> 98
Min. TLCI	94

Effects

Iris	Yes
Framing blades	Yes
Module rotation	0 – 360 °

Control

Controller protocols	DMX512, RDM, Art-Net, sACN, iDMX® (Transceiver)
Number of DMX control modes	17

Stand alone operating modes	Master/slave, Static
Data in connector	XLR 5-pole male, RJ-45 with housing
Data out connector	XLR 5-pole female, RJ-45 with housing

Mains operation

Operation voltage	100 V AC - 240 V AC / 50 - 60 Hz
Rated power	620 W
Rated current	2.7 A
Mains fuse	T10AL/250 V
Fuse replacement	Possible from the outside without opening

Housing

Chassis material	Metal
Colour	Black

Cooling

Cooling system	Temperature controlled fan cooling
Cooling modes	On/Off, Auto, Constant Low, Constant Mid, Constant High

Environmental

Protection class	IP20
Risk group	2
Ambient temperature	0 – 40 °C

Dimensions & weight

Width	730 mm
Height	579 mm
Depth	410 mm
Weight	20.9 kg

Other properties

Included Accessories	Mains cable
----------------------	-------------

P6

HIGH OUTPUT FULL-SPECTRUM ELLIPSOIDAL



P6

HIGH OUTPUT FULL-SPECTRUM ELLIPSOIDAL

