

Static initialization blocks are executed when the class is loaded, and you can initialize static variables in those blocks.

[Change Theme](#)

Language

Java 7



Problem

It's time to test your knowledge of Static initialization blocks. You can read about it [here](#).

You are given a class Solution with a main method. Complete the given code so that it outputs the area of a parallelogram with breadth **B** and height **H**. You should read the variables from the standard input.

If $B \leq 0$ or $H \leq 0$, the output should be "java.lang.Exception: Breadth and height must be positive" without quotes.

Submissions

Input Format

There are two lines of input. The first line contains **B**: the breadth of the parallelogram. The next line contains **H**: the height of the parallelogram.

Constraints

- $-100 \leq B \leq 100$
- $-100 \leq H \leq 100$

Leaderboard

Output Format

If both values are greater than zero, then the main method must output the area of the parallelogram. Otherwise, print "java.lang.Exception: Breadth and height must be positive" without quotes.

Discussions

Sample input 1

1
3

Sample output 1

3

Editorial

Sample input 2

-1
2

Sample output 2

java.lang.Exception: Breadth and height must be posit



```
1  import java.io.*; ...
8
9  static int B = 0;
10 static int H = 0;
11 static boolean flag = true;
12
13 static {
14     Scanner sc = new Scanner(System.in);
15     B = sc.nextInt();
16     H = sc.nextInt();
17     flag = true;
18     if(B <= 0 || H <= 0){
19         System.out.print("java.lang.Exception:
20             height must be positive");
21         flag=false;
21     }
```

Line: 8 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input