

Problem

In computer science, a double-ended queue (dequeue, often abbreviated to deque, pronounced deck) is an abstract data type that generalizes a queue, for which elements can be added to or removed from either the front (head) or back (tail).

Deque interfaces can be implemented using various types of collections such as `LinkedList` or `ArrayDeque` classes. For example, deque can be declared as:

Submissions

```
Deque deque = new LinkedList<>();
or
Deque deque = new ArrayDeque<>();
```

You can find more details about Deque [here](#).

Leaderboard

In this problem, you are given N integers. You need to find the maximum number of unique integers among all the possible contiguous subarrays of size M .

Note: Time limit is **3** second for this problem.

Input Format

The first line of input contains two integers N and M : representing the total number of integers and the size of the subarray, respectively.

The next line contains N space separated integers.

Discussions

Constraints

$$1 \leq N \leq 100000$$

$$1 \leq M \leq 100000$$

$$M \leq N$$

The numbers in the array will range between $[0, 10000000]$.

Editorial

Output Format

Print the maximum number of unique integers among all possible contiguous subarrays of size M .

Sample Input

```
6 3
5 3 5 2 3 2
```

Sample Output

```
3
```

Explanation

In the sample testcase, there are 4 subarrays of contiguous numbers.

$s1 = \langle 5, 3, 5 \rangle$ - Has **2** unique numbers.

$s2 = \langle 3, 5, 2 \rangle$ - Has **3** unique numbers.

$s3 = \langle 5, 2, 3 \rangle$ - Has **3** unique numbers.

$s4 = \langle 2, 3, 2 \rangle$ - Has **2** unique numbers.

[Change Theme](#)

Language

Java 15



```
1 import java.io.*;
2 import java.util.*;
3
4 public class Solution {
5
6     public static void main(String[] args) {
7         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should have a main method. */
8     }
9 }
```

Line: 1 Col: 1

☐ Test against custom input