

Module `java.base`

Package `java.util`

Interface `Collection<E>`

Type Parameters:

`E` - the type of elements in this collection

All Superinterfaces:

`Iterable<E>`

All Known Subinterfaces:

`BeanContext`, `BeanContextServices`, `BlockingDeque<E>`, `BlockingQueue<E>`, `Deque<E>`, `EventSet`, `List<E>`, `NavigableSet<E>`, `Queue<E>`, `Set<E>`, `SortedSet<E>`, `TransferQueue<E>`

All Known Implementing Classes:

`AbstractCollection`, `AbstractList`, `AbstractQueue`, `AbstractSequentialList`, `AbstractSet`, `ArrayBlockingQueue`, `ArrayDeque`, `ArrayList`, `AttributeList`, `BeanContextServicesSupport`, `BeanContextSupport`, `ConcurrentHashMap.KeySetView`, `ConcurrentLinkedDeque`, `ConcurrentLinkedQueue`, `ConcurrentSkipListSet`, `CopyOnWriteArrayList`, `CopyOnWriteArraySet`, `DelayQueue`, `EnumSet`, `HashSet`, `JobStateReasons`, `LinkedBlockingDeque`, `LinkedBlockingQueue`, `LinkedHashSet`, `LinkedList`, `LinkedTransferQueue`, `PriorityBlockingQueue`, `PriorityQueue`, `RoleList`, `RoleUnresolvedList`, `Stack`, `SynchronousQueue`, `TreeSet`, `Vector`

```
public interface Collection<E>
extends Iterable<E>
```

The root interface in the *collection hierarchy*. A collection represents a group of objects, known as its *elements*. Some collections allow duplicate elements and others do not. Some are ordered and others unordered. The JDK does not provide any *direct* implementations of this interface: it provides implementations of more specific subinterfaces like `Set` and `List`. This interface is typically used to pass collections around and manipulate them where maximum generality is desired.

Bags or *multisets* (unordered collections that may contain duplicate elements) should implement this interface directly.

All general-purpose `Collection` implementation classes (which typically implement `Collection` indirectly through one of its subinterfaces) should provide two "standard" constructors: a void (no arguments) constructor, which creates an empty collection, and a constructor with a single argument of type `Collection`, which creates a new collection with the same elements as its argument. In effect, the latter constructor allows the user to copy any collection, producing an equivalent collection of the desired implementation type. There is no way to enforce this convention (as interfaces cannot contain constructors) but all of the general-purpose `Collection` implementations in the Java platform libraries comply.

Certain methods are specified to be *optional*. If a collection implementation doesn't implement a particular operation, it should define the corresponding method to throw `UnsupportedOperationException`. Such methods are marked "optional operation" in method specifications of the collections interfaces.

Some collection implementations have restrictions on the elements that they may contain. For example, some implementations prohibit null elements, and some have restrictions on the types of

their elements. Attempting to add an ineligible element throws an unchecked exception, typically `NullPointerException` or `ClassCastException`. Attempting to query the presence of an ineligible element may throw an exception, or it may simply return `false`; some implementations will exhibit the former behavior and some will exhibit the latter. More generally, attempting an operation on an ineligible element whose completion would not result in the insertion of an ineligible element into the collection may throw an exception or it may succeed, at the option of the implementation. Such exceptions are marked as "optional" in the specification for this interface.

It is up to each collection to determine its own synchronization policy. In the absence of a stronger guarantee by the implementation, undefined behavior may result from the invocation of any method on a collection that is being mutated by another thread; this includes direct invocations, passing the collection to a method that might perform invocations, and using an existing iterator to examine the collection.

Many methods in Collections Framework interfaces are defined in terms of the `equals` method. For example, the specification for the `contains(Object o)` method says: "returns `true` if and only if this collection contains at least one element `e` such that `(o==null ? e==null : o.equals(e))`." This specification should *not* be construed to imply that invoking `Collection.contains` with a non-null argument `o` will cause `o.equals(e)` to be invoked for any element `e`. Implementations are free to implement optimizations whereby the `equals` invocation is avoided, for example, by first comparing the hash codes of the two elements. (The `Object.hashCode()` specification guarantees that two objects with unequal hash codes cannot be equal.) More generally, implementations of the various Collections Framework interfaces are free to take advantage of the specified behavior of underlying `Object` methods wherever the implementor deems it appropriate.

Some collection operations which perform recursive traversal of the collection may fail with an exception for self-referential instances where the collection directly or indirectly contains itself. This includes the `clone()`, `equals()`, `hashCode()` and `toString()` methods. Implementations may optionally handle the self-referential scenario, however most current implementations do not do so.

View Collections

Most collections manage storage for elements they contain. By contrast, *view collections* themselves do not store elements, but instead they rely on a backing collection to store the actual elements. Operations that are not handled by the view collection itself are delegated to the backing collection. Examples of view collections include the wrapper collections returned by methods such as `Collections.checkedCollection`, `Collections.synchronizedCollection`, and `Collections.unmodifiableCollection`. Other examples of view collections include collections that provide a different representation of the same elements, for example, as provided by `List.subList`, `NavigableSet.subSet`, or `Map.entrySet`. Any changes made to the backing collection are visible in the view collection. Correspondingly, any changes made to the view collection — if changes are permitted — are written through to the backing collection. Although they technically aren't collections, instances of `Iterator` and `ListIterator` can also allow modifications to be written through to the backing collection, and in some cases, modifications to the backing collection will be visible to the `Iterator` during iteration.

Unmodifiable Collections

Certain methods of this interface are considered "destructive" and are called "mutator" methods in that they modify the group of objects contained within the collection on which they operate. They can be specified to throw `UnsupportedOperationException` if this collection implementation does not support the operation. Such methods should (but are not required to) throw an `UnsupportedOperationException` if the invocation would have no effect on the collection. For example, consider a collection that does not support the `add` operation. What will happen if the

`addAll` method is invoked on this collection, with an empty collection as the argument? The addition of zero elements has no effect, so it is permissible for this collection simply to do nothing and not to throw an exception. However, it is recommended that such cases throw an exception unconditionally, as throwing only in certain cases can lead to programming errors.

An *unmodifiable collection* is a collection, all of whose mutator methods (as defined above) are specified to throw `UnsupportedOperationException`. Such a collection thus cannot be modified by calling any methods on it. For a collection to be properly unmodifiable, any view collections derived from it must also be unmodifiable. For example, if a `List` is unmodifiable, the `List` returned by `List.subList` is also unmodifiable.

An unmodifiable collection is not necessarily immutable. If the contained elements are mutable, the entire collection is clearly mutable, even though it might be unmodifiable. For example, consider two unmodifiable lists containing mutable elements. The result of calling `list1.equals(list2)` might differ from one call to the next if the elements had been mutated, even though both lists are unmodifiable. However, if an unmodifiable collection contains all immutable elements, it can be considered effectively immutable.

Unmodifiable View Collections

An *unmodifiable view collection* is a collection that is unmodifiable and that is also a view onto a backing collection. Its mutator methods throw `UnsupportedOperationException`, as described above, while reading and querying methods are delegated to the backing collection. The effect is to provide read-only access to the backing collection. This is useful for a component to provide users with read access to an internal collection, while preventing them from modifying such collections unexpectedly. Examples of unmodifiable view collections are those returned by the `Collections.unmodifiableCollection`, `Collections.unmodifiableList`, and related methods.

Note that changes to the backing collection might still be possible, and if they occur, they are visible through the unmodifiable view. Thus, an unmodifiable view collection is not necessarily immutable. However, if the backing collection of an unmodifiable view is effectively immutable, or if the only reference to the backing collection is through an unmodifiable view, the view can be considered effectively immutable.

Serializability of Collections

Serializability of collections is optional. As such, none of the collections interfaces are declared to implement the `Serializable` interface. However, serializability is regarded as being generally useful, so most collection implementations are serializable.

The collection implementations that are public classes (such as `ArrayList` or `HashMap`) are declared to implement the `Serializable` interface if they are in fact serializable. Some collections implementations are not public classes, such as the *unmodifiable collections*. In such cases, the serializability of such collections is described in the specification of the method that creates them, or in some other suitable place. In cases where the serializability of a collection is not specified, there is no guarantee about the serializability of such collections. In particular, many *view collections* are not serializable.

A collection implementation that implements the `Serializable` interface cannot be guaranteed to be serializable. The reason is that in general, collections contain elements of other types, and it is not possible to determine statically whether instances of some element type are actually serializable. For example, consider a serializable `Collection<E>`, where `E` does not implement the `Serializable` interface. The collection may be serializable, if it contains only elements of some serializable subtype of `E`, or if it is empty. Collections are thus said to be *conditionally serializable*, as the serializability of

the collection as a whole depends on whether the collection itself is serializable and on whether all contained elements are also serializable.

An additional case occurs with instances of `SortedSet` and `SortedMap`. These collections can be created with a `Comparator` that imposes an ordering on the set elements or map keys. Such a collection is serializable only if the provided `Comparator` is also serializable.

This interface is a member of the [Java Collections Framework](#).

Implementation Requirements:

The default method implementations (inherited or otherwise) do not apply any synchronization protocol. If a `Collection` implementation has a specific synchronization protocol, then it must override default implementations to apply that protocol.

Since:

1.2

See Also:

[Set](#), [List](#), [Map](#), [SortedSet](#), [SortedMap](#), [HashSet](#), [TreeSet](#), [ArrayList](#), [LinkedList](#), [Vector](#), [Collections](#), [Arrays](#), [AbstractCollection](#)

Method Summary

All Methods	Instance Methods	Abstract Methods	Default Methods
Modifier and Type	Method		Description
boolean	<code>add(E e)</code>		Ensures that this collection contains the specified element (optional operation).
boolean	<code>addAll(Collection<? extends E> c)</code>		Adds all of the elements in the specified collection to this collection (optional operation).
void	<code>clear()</code>		Removes all of the elements from this collection (optional operation).
boolean	<code>contains(Object o)</code>		Returns true if this collection contains the specified element.
boolean	<code>containsAll(Collection<?> c)</code>		Returns true if this collection contains all of the elements in the specified collection.
boolean	<code>equals(Object o)</code>		Compares the specified object with this collection for equality.
int	<code>hashCode()</code>		Returns the hash code value for this collection.
boolean	<code>isEmpty()</code>		Returns true if this collection contains no elements.

Iterator<E>	iterator()	Returns an iterator over the elements in this collection.
default Stream<E>	parallelStream()	Returns a possibly parallel Stream with this collection as its source.
boolean	remove(Object o)	Removes a single instance of the specified element from this collection, if it is present (optional operation).
boolean	removeAll(Collection<?> c)	Removes all of this collection's elements that are also contained in the specified collection (optional operation).
default boolean	removeIf(Predicate<? super E> filter)	Removes all of the elements of this collection that satisfy the given predicate.
boolean	retainAll(Collection<?> c)	Retains only the elements in this collection that are contained in the specified collection (optional operation).
int	size()	Returns the number of elements in this collection.
default Splitter<E>	splitter()	Creates a Splitter over the elements in this collection.
default Stream<E>	stream()	Returns a sequential Stream with this collection as its source.
Object[]	toArray()	Returns an array containing all of the elements in this collection.
default <T> T[]	toArray(IntFunction<T[]> generator)	Returns an array containing all of the elements in this collection, using the provided generator function to allocate the returned array.
<T> T[]	toArray(T[] a)	Returns an array containing all of the elements in this collection; the runtime type of the returned array is that of the specified array.

Methods declared in interface java.lang.Iterable

forEach

Method Details

size

```
int size()
```

Returns the number of elements in this collection. If this collection contains more than `Integer.MAX_VALUE` elements, returns `Integer.MAX_VALUE`.

Returns:

the number of elements in this collection

isEmpty

```
boolean isEmpty()
```

Returns `true` if this collection contains no elements.

Returns:

`true` if this collection contains no elements

contains

```
boolean contains(Object o)
```

Returns `true` if this collection contains the specified element. More formally, returns `true` if and only if this collection contains at least one element `e` such that `Objects.equals(o, e)`.

Parameters:

`o` - element whose presence in this collection is to be tested

Returns:

`true` if this collection contains the specified element

Throws:

[ClassCastException](#) - if the type of the specified element is incompatible with this collection (optional)

[NullPointerException](#) - if the specified element is null and this collection does not permit null elements (optional)

iterator

```
Iterator<E> iterator()
```

Returns an iterator over the elements in this collection. There are no guarantees concerning the order in which the elements are returned (unless this collection is an instance of some class that provides a guarantee).

Specified by:

`iterator` in interface [Iterable<E>](#)

Returns:

an Iterator over the elements in this collection

toArray

```
Object[] toArray()
```

Returns an array containing all of the elements in this collection. If this collection makes any guarantees as to what order its elements are returned by its iterator, this method must return the elements in the same order. The returned array's **runtime component type** is `Object`.

The returned array will be "safe" in that no references to it are maintained by this collection. (In other words, this method must allocate a new array even if this collection is backed by an array). The caller is thus free to modify the returned array.

API Note:

This method acts as a bridge between array-based and collection-based APIs. It returns an array whose runtime type is `Object[]`. Use `toArray(T[])` to reuse an existing array, or use `toArray(IntFunction)` to control the runtime type of the array.

Returns:

an array, whose **runtime component type** is `Object`, containing all of the elements in this collection

toArray

```
<T> T[] toArray(T[] a)
```

Returns an array containing all of the elements in this collection; the runtime type of the returned array is that of the specified array. If the collection fits in the specified array, it is returned therein. Otherwise, a new array is allocated with the runtime type of the specified array and the size of this collection.

If this collection fits in the specified array with room to spare (i.e., the array has more elements than this collection), the element in the array immediately following the end of the collection is set to `null`. (This is useful in determining the length of this collection *only* if the caller knows that this collection does not contain any `null` elements.)

If this collection makes any guarantees as to what order its elements are returned by its iterator, this method must return the elements in the same order.

API Note:

This method acts as a bridge between array-based and collection-based APIs. It allows an existing array to be reused under certain circumstances. Use `toArray()` to create an array whose runtime type is `Object[]`, or use `toArray(IntFunction)` to control the runtime type of the array.

Suppose `x` is a collection known to contain only strings. The following code can be used to dump the collection into a previously allocated `String` array:

```
String[] y = new String[SIZE];  
...
```

```
y = x.toArray(y);
```

The return value is reassigned to the variable `y`, because a new array will be allocated and returned if the collection `x` has too many elements to fit into the existing array `y`.

Note that `toArray(new Object[0])` is identical in function to `toArray()`.

Type Parameters:

`T` - the component type of the array to contain the collection

Parameters:

`a` - the array into which the elements of this collection are to be stored, if it is big enough; otherwise, a new array of the same runtime type is allocated for this purpose.

Returns:

an array containing all of the elements in this collection

Throws:

`ArrayStoreException` - if the runtime type of any element in this collection is not assignable to the runtime component type of the specified array

`NullPointerException` - if the specified array is null

toArray

```
default <T> T[] toArray(IntFunction<T[]> generator)
```

Returns an array containing all of the elements in this collection, using the provided generator function to allocate the returned array.

If this collection makes any guarantees as to what order its elements are returned by its iterator, this method must return the elements in the same order.

API Note:

This method acts as a bridge between array-based and collection-based APIs. It allows creation of an array of a particular runtime type. Use `toArray()` to create an array whose runtime type is `Object[]`, or use `toArray(T[])` to reuse an existing array.

Suppose `x` is a collection known to contain only strings. The following code can be used to dump the collection into a newly allocated array of `String`:

```
String[] y = x.toArray(String[]::new);
```

Implementation Requirements:

The default implementation calls the generator function with zero and then passes the resulting array to `toArray(T[])`.

Type Parameters:

`T` - the component type of the array to contain the collection

Parameters:

`generator` - a function which produces a new array of the desired type and the provided length

Returns:

an array containing all of the elements in this collection

Throws:

`ArrayStoreException` - if the runtime type of any element in this collection is not assignable to the runtime component type of the generated array

`NullPointerException` - if the generator function is null

Since:

11

add

```
boolean add(E e)
```

Ensures that this collection contains the specified element (optional operation). Returns `true` if this collection changed as a result of the call. (Returns `false` if this collection does not permit duplicates and already contains the specified element.)

Collections that support this operation may place limitations on what elements may be added to this collection. In particular, some collections will refuse to add `null` elements, and others will impose restrictions on the type of elements that may be added. Collection classes should clearly specify in their documentation any restrictions on what elements may be added.

If a collection refuses to add a particular element for any reason other than that it already contains the element, it *must* throw an exception (rather than returning `false`). This preserves the invariant that a collection always contains the specified element after this call returns.

Parameters:

`e` - element whose presence in this collection is to be ensured

Returns:

`true` if this collection changed as a result of the call

Throws:

`UnsupportedOperationException` - if the add operation is not supported by this collection

`ClassCastException` - if the class of the specified element prevents it from being added to this collection

`NullPointerException` - if the specified element is null and this collection does not permit null elements

`IllegalArgumentException` - if some property of the element prevents it from being added to this collection

`IllegalStateException` - if the element cannot be added at this time due to insertion restrictions

remove

```
boolean remove(Object o)
```

Removes a single instance of the specified element from this collection, if it is present (optional operation). More formally, removes an element `e` such that `Objects.equals(o, e)`, if this collection contains one or more such elements. Returns `true` if this collection contained the specified element (or equivalently, if this collection changed as a result of the call).

Parameters:

`o` - element to be removed from this collection, if present

Returns:

true if an element was removed as a result of this call

Throws:

[ClassCastException](#) - if the type of the specified element is incompatible with this collection (optional)

[NullPointerException](#) - if the specified element is null and this collection does not permit null elements (optional)

[UnsupportedOperationException](#) - if the remove operation is not supported by this collection

containsAll

```
boolean containsAll(Collection<?> c)
```

Returns true if this collection contains all of the elements in the specified collection.

Parameters:

`c` - collection to be checked for containment in this collection

Returns:

true if this collection contains all of the elements in the specified collection

Throws:

[ClassCastException](#) - if the types of one or more elements in the specified collection are incompatible with this collection (optional)

[NullPointerException](#) - if the specified collection contains one or more null elements and this collection does not permit null elements (optional), or if the specified collection is null.

See Also:

[contains\(Object\)](#)

addAll

```
boolean addAll(Collection<? extends E> c)
```

Adds all of the elements in the specified collection to this collection (optional operation). The behavior of this operation is undefined if the specified collection is modified while the operation is in progress. (This implies that the behavior of this call is undefined if the specified collection is this collection, and this collection is nonempty.)

Parameters:

`c` - collection containing elements to be added to this collection

Returns:

true if this collection changed as a result of the call

Throws:

[UnsupportedOperationException](#) - if the addAll operation is not supported by this collection

ClassCastException - if the class of an element of the specified collection prevents it from being added to this collection

NullPointerException - if the specified collection contains a null element and this collection does not permit null elements, or if the specified collection is null

IllegalArgumentException - if some property of an element of the specified collection prevents it from being added to this collection

IllegalStateException - if not all the elements can be added at this time due to insertion restrictions

See Also:

`add(Object)`

removeAll

```
boolean removeAll(Collection<?> c)
```

Removes all of this collection's elements that are also contained in the specified collection (optional operation). After this call returns, this collection will contain no elements in common with the specified collection.

Parameters:

`c` - collection containing elements to be removed from this collection

Returns:

true if this collection changed as a result of the call

Throws:

UnsupportedOperationException - if the `removeAll` method is not supported by this collection

ClassCastException - if the types of one or more elements in this collection are incompatible with the specified collection (optional)

NullPointerException - if this collection contains one or more null elements and the specified collection does not support null elements (optional), or if the specified collection is null

See Also:

`remove(Object)`, `contains(Object)`

removeIf

```
default boolean removeIf(Predicate<? super E> filter)
```

Removes all of the elements of this collection that satisfy the given predicate. Errors or runtime exceptions thrown during iteration or by the predicate are relayed to the caller.

Implementation Requirements:

The default implementation traverses all elements of the collection using its `iterator()`. Each matching element is removed using `Iterator.remove()`. If the collection's iterator does not support removal then an `UnsupportedOperationException` will be thrown on the first matching element.

Parameters:

`filter` - a predicate which returns true for elements to be removed

Returns:

true if any elements were removed

Throws:

[NullPointerException](#) - if the specified filter is null

[UnsupportedOperationException](#) - if elements cannot be removed from this collection. Implementations may throw this exception if a matching element cannot be removed or if, in general, removal is not supported.

Since:

1.8

retainAll

```
boolean retainAll(Collection<?> c)
```

Retains only the elements in this collection that are contained in the specified collection (optional operation). In other words, removes from this collection all of its elements that are not contained in the specified collection.

Parameters:

c - collection containing elements to be retained in this collection

Returns:

true if this collection changed as a result of the call

Throws:

[UnsupportedOperationException](#) - if the retainAll operation is not supported by this collection

[ClassCastException](#) - if the types of one or more elements in this collection are incompatible with the specified collection (optional)

[NullPointerException](#) - if this collection contains one or more null elements and the specified collection does not permit null elements (optional), or if the specified collection is null

See Also:

[remove\(Object\)](#), [contains\(Object\)](#)

clear

```
void clear()
```

Removes all of the elements from this collection (optional operation). The collection will be empty after this method returns.

Throws:

[UnsupportedOperationException](#) - if the clear operation is not supported by this collection

equals

```
boolean equals(Object o)
```

Compares the specified object with this collection for equality.

While the `Collection` interface adds no stipulations to the general contract for the `Object.equals`, programmers who implement the `Collection` interface "directly" (in other words, create a class that is a `Collection` but is not a `Set` or a `List`) must exercise care if they choose to override the `Object.equals`. It is not necessary to do so, and the simplest course of action is to rely on `Object`'s implementation, but the implementor may wish to implement a "value comparison" in place of the default "reference comparison." (The `List` and `Set` interfaces mandate such value comparisons.)

The general contract for the `Object.equals` method states that equals must be symmetric (in other words, `a.equals(b)` if and only if `b.equals(a)`). The contracts for `List.equals` and `Set.equals` state that lists are only equal to other lists, and sets to other sets. Thus, a custom equals method for a collection class that implements neither the `List` nor `Set` interface must return `false` when this collection is compared to any list or set. (By the same logic, it is not possible to write a class that correctly implements both the `Set` and `List` interfaces.)

Overrides:

`equals` in class `Object`

Parameters:

`o` - object to be compared for equality with this collection

Returns:

`true` if the specified object is equal to this collection

See Also:

`Object.equals(Object)`, `Set.equals(Object)`, `List.equals(Object)`

hashCode

```
int hashCode()
```

Returns the hash code value for this collection. While the `Collection` interface adds no stipulations to the general contract for the `Object.hashCode` method, programmers should take note that any class that overrides the `Object.equals` method must also override the `Object.hashCode` method in order to satisfy the general contract for the `Object.hashCode` method. In particular, `c1.equals(c2)` implies that `c1.hashCode()==c2.hashCode()`.

Overrides:

`hashCode` in class `Object`

Returns:

the hash code value for this collection

See Also:

`Object.hashCode()`, `Object.equals(Object)`

spliterator

```
default Spliterator<E> spliterator()
```

Creates a `Splitterator` over the elements in this collection. Implementations should document characteristic values reported by the splitterator. Such characteristic values are not required to be reported if the splitterator reports `Splitterator.SIZED` and this collection contains no elements.

The default implementation should be overridden by subclasses that can return a more efficient splitterator. In order to preserve expected laziness behavior for the `stream()` and `parallelStream()` methods, splitterators should either have the characteristic of `IMMUTABLE` or `CONCURRENT`, or be *late-binding*. If none of these is practical, the overriding class should describe the splitterator's documented policy of binding and structural interference, and should override the `stream()` and `parallelStream()` methods to create streams using a `Supplier` of the splitterator, as in:

```
Stream<E> s = StreamSupport.stream(() -> splitterator(), splitteratorCharacteristics)
```

These requirements ensure that streams produced by the `stream()` and `parallelStream()` methods will reflect the contents of the collection as of initiation of the terminal stream operation.

Specified by:

`splitterator` in interface `Iterable<E>`

Implementation Requirements:

The default implementation creates a *late-binding* splitterator from the collection's `Iterator`. The splitterator inherits the *fail-fast* properties of the collection's iterator.

The created `Splitterator` reports `Splitterator.SIZED`.

Implementation Note:

The created `Splitterator` additionally reports `Splitterator.SUBSIZED`.

If a splitterator covers no elements then the reporting of additional characteristic values, beyond that of `SIZED` and `SUBSIZED`, does not aid clients to control, specialize or simplify computation. However, this does enable shared use of an immutable and empty splitterator instance (see `Splitterators.emptySplitterator()`) for empty collections, and enables clients to determine if such a splitterator covers no elements.

Returns:

a `Splitterator` over the elements in this collection

Since:

1.8

stream

default `Stream<E> stream()`

Returns a sequential `Stream` with this collection as its source.

This method should be overridden when the `splitterator()` method cannot return a splitterator that is `IMMUTABLE`, `CONCURRENT`, or *late-binding*. (See `splitterator()` for details.)

Implementation Requirements:

The default implementation creates a sequential Stream from the collection's `Splitter`.

Returns:

a sequential Stream over the elements in this collection

Since:

1.8

parallelStream

```
default Stream<E> parallelStream()
```

Returns a possibly parallel Stream with this collection as its source. It is allowable for this method to return a sequential stream.

This method should be overridden when the `splitter()` method cannot return a splitter that is `IMMUTABLE`, `CONCURRENT`, or *late-binding*. (See `splitter()` for details.)

Implementation Requirements:

The default implementation creates a parallel Stream from the collection's `Splitter`.

Returns:

a possibly parallel Stream over the elements in this collection

Since:

1.8

[Report a bug or suggest an enhancement](#)

For further API reference and developer documentation see the [Java SE Documentation](#), which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. [Other versions](#). Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.

Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.

All rights reserved. Use is subject to [license terms](#) and the [documentation redistribution policy](#). [Modify Cookie Preferences](#). [Modify Ad Choices](#).