

Quick Comparison: The 4 Flattening Operators

To truly understand `mergeMap`, it helps to see it next to its siblings. Choosing the right one depends entirely on how you want to handle concurrency:

Operator	Behavior	Best Used For...
<code>mergeMap</code>	Runs everything concurrently . No cancellation, no waiting.	Independent saves, background deletes.
<code>switchMap</code>	Cancels the previous inner Observable if a new outer value arrives.	Search autocompletes, switching tabs.
<code>concatMap</code>	Waits for the previous inner Observable to finish before starting the next one (sequential).	Order-dependent actions (e.g., sequential queue).
<code>exhaustMap</code>	Ignores new outer values until the current inner Observable finishes.	Login buttons (prevents double-clicks).

mergeMap, switchMap, concatMap, exhaustMap

```
app.component.html M  app-routing.module.ts M  merge-map-component.component.ts U  app.module.ts M
src > app > pages > merge-map-component > merge-map-component.component.ts > MergeMapComponentComponent > ngOnInit > subscribe() callback
6   selector: 'app-merge-map-component',
7   templateUrl: './merge-map-component.component.html',
8   styleUrls: ['./merge-map-component.component.css'],
9 })
10 export class MergeMapComponentComponent implements OnInit {
11   constructor(private http: HttpClient) {}
12
13   ngOnInit(): void {
14     let postIds = of(1, 2, 3, 4, 5);
15     postIds
16       .pipe(
17         mergeMap((id) => {
18           return this.http.get(
19             `https://jsonplaceholder.typicode.com/posts/${id}`
20           );
21         })
22       )
23       .subscribe((postData) => {
24         console.log(data);
25       });
26   }
27 }
28
```

