



# **Algorithms: Dynamic Programming**

## **Coin Change Problem**

# Coin Change Problem

Given unlimited amounts of coins of denominations  $c_1 > \dots > c_d$ , give change for amount  $M$  with the least number of coins.

**Example:**  $c_1 = 25$ ,  $c_2 = 10$ ,  $c_3 = 5$ ,  $c_4 = 1$  and  $M = 48$

**Greedy solution:**  $25*1 + 10*2 + 1*3 = c_1 + 2c_2 + 3c_4$

Greedy solution is

- optimal for any amount and “normal” set of denominations
- may not be optimal for arbitrary coin denominations

# Greedy Choice Principles

- Suppose you want to count out a certain amount of money, using the fewest possible coins.
- At each step, take the largest possible coin that does not overshoot.
- Example: To make Tk. 157/-, you,
  - Choose a Tk. 100/- note,
  - Choose a Tk. 50/- note,
  - Choose a Tk. 5/- coin,
  - Choose a Tk. 2/- coin.



# Greedy Choice Principles: Failure

- To find the minimum number of US coins to make any amount, the greedy method always works
  - At each step, just choose the largest coin that does not overshoot the desired amount:  $31\text{¢} = (25+5+1)$
- The greedy method would not work if we did not have 5¢ coins
  - For 31 cents, the greedy method gives seven coins  $(25+1+1+1+1+1+1)$ , but we can do it with four  $(10+10+10+1)$
- The greedy method also would not work if we had a 21¢ coin
  - For 63 cents, the greedy method gives six coins  $(25+25+10+1+1+1)$ , but we can do it with three  $(21+21+21)$
- The greedy algorithm results in a solution, but always not in an optimal solution
- How can we find the minimum number of coins for any given coin set?



# Coin Change Problem: Example

Given the denominations 1, 3, and 5, what is the minimum number of coins needed to make change for a given value?


Value	1	2	3	4	5	6	7	8	9	10
Min # of coins	<b>1</b>		<b>1</b>		<b>1</b>					

Only one coin is needed to make change for the values 1, 3, and 5

# Coin Change Problem: Example

Given the denominations 1, 3, and 5, what is the minimum number of coins needed to make change for a given value?

Value	1	2	3	4	5	6	7	8	9	10
Min # of coins	1	2	1	2	1	2		2		2




However, two coins are needed to make change for the values 2, 4, 6, 8, and 10.

# Coin Change Problem: Example

Given the denominations 1, 3, and 5, what is the minimum number of coins needed to make change for a given value?

Value	1	2	3	4	5	6	7	8	9	10
Min # of coins	1	2	1	2	1	2	3	2	3	2



Lastly, three coins are needed to make change for the values 7 and 9



# Coin Change Problem: Recurrence

This example is expressed by the following recurrence relation:

$$\text{minNumCoins}(M) = \min_{\text{of}} \left\{ \begin{array}{l} \text{minNumCoins}(M-1) + 1 \\ \text{minNumCoins}(M-3) + 1 \\ \text{minNumCoins}(M-5) + 1 \end{array} \right.$$

# Coin Change Problem: Recurrence

Given the denominations **c**:  $c_1, c_2, \dots, c_d$ , the recurrence relation is:

$$\text{minNumCoins}(M) = \begin{matrix} \text{min} \\ \text{of} \end{matrix} \left\{ \begin{array}{l} \text{minNumCoins}(M - c_1) + 1 \\ \text{minNumCoins}(M - c_2) + 1 \\ \dots \\ \text{minNumCoins}(M - c_d) + 1 \end{array} \right.$$

# Coin Change Problem: A Recursive Algorithm

```
1.  RecursiveChange(M, c, d)
2.    if  $M = 0$ 
3.      return 0
4.     $bestNumCoins \leftarrow \text{infinity}$ 
5.    for  $i \leftarrow 1$  to  $d$ 
6.      if  $M \geq c_i$ 
7.         $numCoins \leftarrow \text{RecursiveChange}(M - c_i, c, d)$ 
8.        if  $numCoins + 1 < bestNumCoins$ 
9.           $bestNumCoins \leftarrow numCoins + 1$ 
10.   return  $bestNumCoins$ 
```

# RecursiveChange is not Efficient

- It recalculates the optimal coin combination for a given amount of money repeatedly
- i.e.,  $M = 77$ ,  $c = (1, 3, 7)$ :
  - Optimal coin for 70 cents is computed **9** times!



# We Can Do Better

- We are re-computing values in our algorithm more than once
- Save results of each computation for 0 to  $M$
- This way, we can do a reference call to find an already computed value, instead of re-computing each time
- Running time  $M*d$ , where  $M$  is the value of money and  $d$  is the number of denominations

# Coin Change Problem: Dynamic Programming

1. DPCChange(**M**, **c**, **d**)

2.  $\text{bestNumCoins}_0 \leftarrow 0$

3. **for**  $m \leftarrow 1$  to  $M$

4.  $\text{bestNumCoins}_m \leftarrow \text{infinity}$

5. **for**  $i \leftarrow 1$  to  $d$

6. **if**  $m \geq c_i$



7. **if**  $\text{bestNumCoins}_{m-c_i} + 1 < \text{bestNumCoins}_m$

8.  $\text{bestNumCoins}_m \leftarrow \text{bestNumCoins}_{m-c_i} + 1$

9. **return**  $\text{bestNumCoins}_M$

**Running time:  $O(M*d)$**

# DPChange: Example



$$\mathbf{c} = (1, 3, 7)$$
$$\mathbf{M} = 9$$



# Coin Change Problem

**Goal**: Convert some amount of money  $M$  into given denominations, using the fewest possible number of coins

**Input**: An amount of money  $M$ , and an array of  $d$  denominations  $\mathbf{c} = (c_1, c_2, \dots, c_d)$ , in a decreasing order of value ( $c_1 > c_2 > \dots > c_d$ )

**Output**: A list of  $d$  integers  $i_1, i_2, \dots, i_d$  such that  $c_1 i_1 + c_2 i_2 + \dots + c_d i_d = M$  and  $i_1 + i_2 + \dots + i_d$  is minimal