FRONT MATTER

Title Page

SIGILITH

A Structural Method for the Analysis of Symbolic Systems

By Ky Nash

Abstract — Structural Analysis of the Voynich Manuscript Using Sigilith

This study applies the Sigilith v1.0 structural analysis protocol to selected regions of the Voynich Manuscript, with the aim of characterising its symbolic behaviour without reference to language, meaning, or cryptographic interpretation. The method evaluates the manuscript's labels and short sequences under a reproducible pipeline consisting of canonical segmentation, behaviour-preserving transformations, metric extraction, and three structural constraints (SSC-1', SSC-2, SSC-3'). Results show that the Voynich label sequences exhibit stable boundary behaviour, narrow length distribution, and drift-present but strongly localised internal variation. Under Sigilith's classification framework, this combination corresponds to a system with constrained internal dynamics and representation-invariant structural regularities. The analysis does not propose linguistic, semantic, or historical interpretations; instead, it demonstrates that the Voynich Manuscript occupies a distinct structural regime relative to natural language, random systems, and rigid templatic sequences. These findings provide a falsifiable, methodologically conservative basis for future comparative work and establish a reproducible foundation for analysing symbolic systems of uncertain origin.

Edition Note

This revised edition presents the complete, stabilised form of the Sigilith framework. It incorporates the structural ontology, the 30-Phase Architecture, the Behaviour-Preserving Segmentation method, the Structural Signature Suite, and the expanded control-dataset analysis. It reflects all methodological refinements developed during the reconstruction of the manuscript, including the integration of adversarial system testing and the formal articulation of Sigilith's classification criteria.

This edition supersedes all previous drafts. It represents the most current and coherent articulation of the discipline.

Copyright Page

Copyright © Ky Nash. All rights reserved.

No part of this work may be reproduced, distributed, or transmitted in any form or by any means without prior written permission from the author, except in the case of brief quotations used in critical articles or reviews.

Sigilith is a protected intellectual framework. All structural models, diagrams, definitions, and methodological components are the property of the author.

Dedication

For those who listen to structure before meaning.

This manuscript could not have reached its present form without the generosity, clarity, and structural insight of several individuals whose contributions shaped its development.

I am grateful to D. N. O'Donovan, whose careful observations, comparative references, and long-standing scholarship on manuscript structure provided essential grounding during the refinement of several sections. Her notes on stylistic correspondences and proportional analysis—particularly in relation to folio-level imagery—offered a level of precision that strengthened the architectural stability of the work.

My thanks extend to those who engaged with early drafts, asked difficult questions, or challenged assumptions in ways that clarified the discipline's commitments to falsifiability and representation-invariance. Their contributions helped ensure that Sigilith remained a structural method rather than an interpretive one.

Finally, I am indebted to the broader community of researchers who continue to approach symbolic systems with patience, discipline, and respect for structure. Their work forms the environment in which Sigilith was able to take shape.

Preface

Sigilith began as a response to a simple problem: symbolic systems often refuse to reveal meaning, but they never refuse to reveal behaviour. This manuscript presents the complete articulation of a structural discipline designed to analyse symbolic behaviour without relying on interpretation, translation, or assumed semantics. The method is built on falsifiability, representation-invariance, and cross-domain structural comparison.

Sigilith does not claim to decode meaning. It claims to model structure. And structure, unlike meaning, is always present.

PART I — FOUNDATIONS

Chapter 1 — What Sigilith Is

Sigilith is a structural discipline for analysing symbolic systems without relying on meaning, translation, or interpretation. It treats symbols as behavioural objects rather than linguistic ones. Instead of asking what a symbol signifies, Sigilith asks how it behaves, how it interacts with other symbols, and how it participates in the internal logic of the system that contains it.

The central premise of Sigilith is simple: every symbolic system, no matter how opaque, exhibits structure. That structure may be stable or unstable, rigid or fluid, simple or complex, but it is always present. Structure is the one property that cannot be hidden, faked, or erased. Even systems designed to obscure meaning cannot obscure behaviour.

Sigilith is not a decipherment method. It does not attempt to translate symbols into words or concepts. It does not assume that a system encodes language, nor does it assume that a system encodes anything at all. Instead, Sigilith models the internal architecture of a system as it exists, without imposing external frameworks.

The discipline is built on three commitments.

The first is falsifiability. Every structural claim must be testable, and every test must be capable of failing.

The second is representation-invariance. Structural observations must survive changes in segmentation, encoding, and symbol boundaries.

The third is cross-domain applicability. A method that works only on one system is not a method; it is a description. Sigilith must work across manuscripts, ciphers, diagrams, ritual systems, hybrid constructs, and emergent symbolic behaviours in artificial agents.

Sigilith treats symbolic systems as dynamic environments. Symbols are not static units but participants in a network of pressures, constraints, and flows. Systems evolve, drift, stabilise, collapse, and reorganise. Sigilith models these behaviours without assuming intention or meaning. A system may be linguistic, artistic, ritualistic, computational, or entirely unknown. Sigilith does not require a system to be anything other than structured.

The goal of Sigilith is not to decode. The goal is to understand how a system holds itself together. Structure is the foundation upon which meaning may or may not rest. By focusing on structure alone, Sigilith avoids the interpretive traps that have hindered the study of many symbolic systems. It provides a way to analyse what is present rather than speculate about what might be hidden.

Sigilith is a discipline of observation, stabilisation, differentiation, architecture, and prediction. It is a method for listening to symbolic behaviour. And behaviour, unlike meaning, is always available.

2. Chapter — Why Structure, Not Meaning

Meaning is the most seductive trap in the study of symbolic systems. It promises clarity, purpose, and resolution. It offers the illusion that if we can only translate the symbols, everything else will fall into place. But meaning is also the least reliable property a symbolic system can offer. It is the first to be lost, the easiest to distort, and the most vulnerable to projection.

Sigilith rejects meaning as a starting point because meaning is not observable. It cannot be measured, tested, or falsified. It depends on assumptions about language, culture, intention, and context. When these assumptions are wrong, every conclusion built on them

collapses. Many symbolic systems have been misinterpreted for decades because researchers began with meaning instead of structure.

Structure, by contrast, is always present. It is the one property that cannot be faked. Even a system designed to obscure meaning cannot obscure its own behaviour. Symbols must appear in some order. They must recur with some frequency. They must form patterns of adjacency, distribution, and drift. They must obey constraints, even if those constraints are not linguistic. Structure is the skeleton of a symbolic system. Meaning, if it exists at all, is only one possible layer on top of that skeleton.

Sigilith begins with structure because structure is falsifiable. A structural claim can be tested. It can survive or fail. It can be compared across systems. It can be measured without knowing what the symbols represent. Structure allows analysis to proceed even when meaning is inaccessible, ambiguous, or nonexistent.

Meaning also introduces bias. When researchers assume a system encodes language, they begin to see linguistic patterns even when none exist. When they assume a system encodes ritual, they see ritual patterns. When they assume a system encodes astronomy, they see astronomical patterns. Meaning invites projection. Structure resists it.

Sigilith treats symbolic systems as behavioural environments. Symbols behave. They move, cluster, avoid, drift, stabilise, and interact. These behaviours can be observed directly. They do not require translation. They do not require cultural knowledge. They do not require assumptions about purpose. Structure is the only property that remains stable across all symbolic systems, regardless of origin or intention.

By focusing on structure, Sigilith avoids the interpretive traps that have hindered the study of many complex systems. It provides a way to analyse what is present rather than speculate about what might be hidden. Meaning may eventually emerge, but it is not required. Structure is sufficient.

Sigilith does not deny the possibility of meaning. It simply refuses to begin with it. Meaning, if it exists, must be earned through structure, not assumed in advance. A system that cannot be structurally modelled cannot be meaningfully interpreted. Structure is the foundation. Meaning is optional.

Chapter 3 — The Five Laws of Symbolic Behaviour

Every symbolic system, no matter how obscure or resistant to interpretation, obeys a set of structural behaviours. These behaviours are not cultural, linguistic, or semantic. They are universal properties of systems that use symbols to encode, express, or stabilise information. Sigilith identifies five such behaviours. They are called laws not because they are metaphysical truths, but because no symbolic system has yet been observed that violates them without ceasing to be symbolic.

These laws are descriptive, not prescriptive. They do not tell a system how to behave. They describe how systems behave when they are functioning as symbolic environments. They are the foundation upon which Sigilith builds its analytical framework.

3.1 Recurrence

Symbols recur. No symbolic system uses every symbol only once. Recurrence is the most basic indicator of structure. A system in which symbols never repeat is not a symbolic system; it is noise. Recurrence allows patterns to form, constraints to emerge, and behaviour to stabilise. Without recurrence, there is no structure to analyse.

3.2 Constraint

Symbols do not appear in all possible positions or combinations. They obey constraints. Some symbols prefer certain neighbours. Some avoid others. Some appear only at boundaries. Some appear only internally. Constraint is the signature of internal logic. It is the first sign that a system is negotiating with itself.

3.3 Drift

Symbolic systems change over time. They drift. Drift may be slow or rapid, local or global, stabilising or destabilising. Drift is not noise; it is behaviour. It reveals pressure, adaptation, and internal negotiation. Drift shows where the system is flexible and where it is rigid. It is one of the most powerful indicators of structure.

3.4 Domain Formation

Symbols cluster into functional groups. These clusters form domains. A domain is not a semantic category; it is a behavioural one. Domains emerge from patterns of adjacency, distribution, and drift. They reveal the internal architecture of the system. A symbolic system without domains is either extremely simple or not symbolic at all.

3.5 Thresholds

Symbolic systems contain thresholds—points where behaviour changes abruptly. A threshold may mark the boundary between domains, the transition between stable and unstable behaviour, or the point at which drift becomes collapse. Thresholds are the fault lines of symbolic structure. They reveal where the system is under pressure and where it reorganises itself.

3.6 The Behavioural Landscape

Together, these five laws define the behavioural landscape of symbolic systems. They provide the foundation for Sigilith's structural ontology, its analytical architecture, and its diagnostic instruments. They allow Sigilith to operate without meaning, without translation, and without assumptions about purpose. They allow the discipline to analyse systems that are linguistic, non-linguistic, hybrid, or entirely unknown.

The five laws do not explain why a system behaves as it does. They explain how it behaves. They provide the scaffolding upon which deeper analysis can be built. They are the starting point for all structural investigation. Without them, Sigilith would have no foundation. With them, the discipline can model any symbolic system that exhibits structure, regardless of origin or intention.

Chapter 4 — CDMQSRT: The Behavioural Grammar

Every symbolic system has an internal grammar, whether or not it encodes language. This grammar is not semantic. It is behavioural. It describes how symbols act, how they interact, and how they participate in the system's internal logic. Sigilith formalises this behavioural grammar as CDMQSRT: Concept, Domain, Modifier, Qualifier, Stability, Reflexivity, Threshold. These seven roles describe the structural functions that symbols can perform within a system.

CDMQSRT is not a taxonomy of meaning. It is a taxonomy of behaviour. A symbol is not a Concept because it represents an idea; it is a Concept because it behaves like one. A symbol is not a Modifier because it changes meaning; it is a Modifier because it changes behaviour. CDMQSRT allows Sigilith to classify symbols without assuming anything about what they signify.

4.1 Concept

Concept symbols are the anchors of a system. They are stable, recurrent, and structurally central. They define the core behaviours around which the rest of the system is organised. Concepts do not need to be frequent, but they must be consistent. They are the gravitational centres of symbolic behaviour.

4.2 Domain

Domain symbols define the boundaries of structural regions. They mark transitions between different behavioural environments. Domains emerge from adjacency patterns, drift profiles, and distributional clustering. A system with multiple domains exhibits internal differentiation; a system with a single domain is structurally uniform.

4.3 Modifier

Modifier symbols alter the behaviour of other symbols. They shift adjacency patterns, change drift trajectories, or adjust structural pressure. Modifiers do not act independently; they act relationally. Their behaviour is defined by how they interact with Concepts and Domains.

4.4 Qualifier

Qualifier symbols refine or constrain behaviour. They do not change the core structure of a sequence, but they adjust its expression. Qualifiers often appear in predictable positions relative to Concepts or Modifiers. They are subtle but essential components of symbolic architecture.

4.5 Stability

Stability symbols reinforce structural consistency. They appear in positions that maintain the integrity of sequences. They resist drift and anchor behaviour. Stability symbols often form the backbone of a system's internal logic. When they fail, the system becomes unstable.

4.6 Reflexivity

Reflexive symbols point back into the system. They reference or modify the system's own structure. Reflexivity is a sign of complexity. A system with reflexive behaviour is capable of

self-modification, self-reference, or internal recursion. Reflexive symbols are rare but powerful indicators of advanced structure.

4.7 Threshold

Threshold symbols mark points of behavioural change. They appear at boundaries, transitions, or moments of structural tension. Thresholds reveal where the system reorganises itself. They are the fault lines of symbolic behaviour. A threshold may indicate the start or end of a domain, the shift from stability to drift, or the collapse of a structural pattern.

4.8 Roles as Behaviour, Not Meaning

CDMQSRT is not a rigid classification. A symbol may perform different roles in different contexts. A symbol may behave as a Concept in one domain and as a Modifier in another. Roles are behavioural, not intrinsic. They emerge from observation, not assumption.

The purpose of CDMQSRT is to provide a vocabulary for describing symbolic behaviour. It allows Sigilith to model systems without relying on meaning. It provides a way to talk about structure in systems that cannot be translated. It is the grammar of behaviour, not the grammar of language.

With CDMQSRT, Sigilith can classify symbols, identify domains, detect drift, and map thresholds. It can analyse systems that are linguistic, non-linguistic, hybrid, or entirely unknown. CDMQSRT is the foundation upon which the rest of the discipline is built. It is the lens through which symbolic behaviour becomes visible.

PART II — THEORETICAL FRAMEWORK

Chapter 5 — Symbolic Systems as Behavioural Objects

A symbolic system is not defined by meaning. It is defined by behaviour. This is the foundational shift that allows Sigilith to operate where traditional methods fail. When meaning is inaccessible, behaviour remains. When translation is impossible, structure persists. When intention is unknown, patterns still form. A symbolic system is therefore best understood not as a message to be decoded, but as an environment in which symbols act.

To treat a symbolic system as a behavioural object is to observe it without assuming purpose. A system may encode language, ritual, computation, memory, or nothing at all. It may be expressive, functional, decorative, or emergent. Sigilith does not require the system to be any of these things. It requires only that the system exhibits structure. Structure is the minimum condition for symbolic behaviour.

A behavioural object is defined by the actions of its components. Symbols recur, cluster, avoid, drift, stabilise, and interact. These actions form patterns. Patterns form constraints. Constraints form architecture. Architecture forms the internal logic of the system. This logic is not semantic. It is structural. It is the logic of behaviour, not the logic of meaning.

When a symbolic system is treated as a behavioural object, several consequences follow.

The first is that symbols are not interpreted; they are observed. Their roles are not assigned; they are inferred. Their relationships are not assumed; they are measured. This removes the need for translation and eliminates the risk of projection. A system can be analysed even when its purpose is unknown.

The second consequence is that the system becomes falsifiable. Behaviour can be tested. Structural claims can be challenged. Patterns can be confirmed or rejected. A behavioural object is not a mystery to be solved; it is a structure to be modelled. This allows Sigilith to operate scientifically, even when the system itself is opaque.

The third consequence is that the system becomes comparable. Two symbolic systems may have nothing in common semantically, but they may share structural behaviours. They may exhibit similar drift patterns, domain formations, or threshold behaviours. By treating systems as behavioural objects, Sigilith can compare them without assuming shared meaning or purpose.

The fourth consequence is that the system becomes dynamic. Behaviour changes over time. Drift alters patterns. Pressure reshapes structure. Stability anchors resist collapse. A symbolic system is not a static artifact; it is a living environment of interacting behaviours. Even if the system is ancient or incomplete, its behaviour can still be reconstructed.

The final consequence is that the system becomes self-contained. Everything needed for analysis is inside the system itself. No external knowledge is required. No cultural context is necessary. No linguistic assumptions are made. The system is analysed on its own terms, according to its own behaviour.

To treat a symbolic system as a behavioural object is to remove the burden of meaning and replace it with the clarity of structure. It is to recognise that symbols do not need to be understood to be analysed. They need only to behave. And behaviour, unlike meaning, is always available.

Chapter 6 — Drift, Pressure, and Constraint

Symbolic systems do not remain static. They shift, adapt, and reorganise themselves over time. Even when a system appears fixed on the surface, its internal behaviours reveal

movement. This movement is not random. It follows patterns. It responds to pressures. It negotiates with constraints. Sigilith models this movement as drift.

Drift is the gradual change in symbolic behaviour across a system. It may appear in the form of shifting adjacency patterns, changing positional roles, altered recurrence rates, or the emergence of new structural tendencies. Drift is not noise. It is the system's response to internal pressure. Pressure is the force that pushes a system to reorganise itself. It may arise from structural imbalance, domain tension, threshold instability, or the natural evolution of symbolic behaviour.

Constraint is the counterforce to drift. It is the set of behaviours that resist change. Constraints stabilise the system. They maintain boundaries, preserve roles, and anchor patterns. Without constraint, drift would lead to collapse. Without drift, constraint would lead to stagnation. A symbolic system exists in the tension between these two forces.

6.1 Drift as Behaviour

Drift reveals where the system is flexible. It shows which symbols can shift roles, which adjacency patterns can change, and which domains can reorganise. Drift may be subtle or pronounced, local or global. It is one of the most informative indicators of internal negotiation.

6.2 Pressure as Structural Force

Pressure is not always visible. It must often be inferred from behaviour. When a symbol begins to appear in new positions, pressure is present. When a domain boundary becomes

unstable, pressure is present. When drift accelerates or decelerates, pressure is present. Pressure is the invisible force that shapes the system's evolution.

6.3 Constraint as Stabilisation

Constraint is the system's response to pressure. It manifests as stable adjacency patterns, consistent positional roles, or recurring structural anchors. Constraint is not imposed from outside the system. It emerges from the system's own behaviour. A system with strong constraints resists drift. A system with weak constraints is more susceptible to change.

6.4 Local vs Global Drift

Drift is not uniform.

Local drift affects specific symbols, domains, or adjacency patterns.

Global drift affects the entire system.

Local drift may be subtle, appearing only in certain contexts or positions. Global drift may be dramatic, reshaping the system's overall structure. Distinguishing between these forms of drift is essential for understanding how pressure is distributed.

6.5 Pressure Signatures

Pressure leaves signatures in the behaviour of symbols. These signatures may include:

- sudden shifts in adjacency
- instability at boundaries
- changes in recurrence
- the emergence of new structural tendencies

Pressure signatures reveal where the system is negotiating with itself. They show where the architecture is under strain and where reorganisation may occur.

6.6 The Dynamic Architecture of Systems

The interaction between drift, pressure, and constraint determines the system's trajectory. A system may move toward stability, instability, collapse, or reorganisation. Drift may reveal emerging domains. Pressure may reveal hidden thresholds. Constraint may reveal the system's core architecture.

Sigilith does not attempt to eliminate drift, pressure, or constraint. It seeks to understand them. They are the forces that shape symbolic behaviour. They are the indicators of structure. They are the keys to modelling systems that cannot be translated. By observing how a system moves, Sigilith reveals how it holds itself together.

Chapter 7 — Domains, Boundaries, and Thresholds

Symbolic systems are not uniform. They contain regions of distinct behaviour, separated by boundaries and shaped by internal pressures. These regions are called domains. A domain is not defined by meaning or content. It is defined by behaviour. Symbols inside a domain

interact differently from symbols outside it. They follow different adjacency patterns, exhibit different drift tendencies, and participate in different structural roles. Domains are the internal geography of a symbolic system.

A domain forms when a cluster of symbols begins to behave more like each other than like the rest of the system. This similarity may appear in recurrence patterns, positional roles, adjacency networks, or drift profiles. A domain may be large or small, stable or unstable, rigid or permeable. What matters is that the behaviour inside the domain is distinct. A symbolic system with multiple domains is structurally differentiated. A system with a single domain is structurally uniform.

7.1 Domain Formation

Domains emerge from behavioural clustering. Symbols that share adjacency preferences, drift tendencies, or positional roles naturally form structural regions. These regions may be sharply defined or diffuse. Domain formation is not imposed by the analyst; it is discovered through observation.

Domains reveal the system's internal architecture. They show where behaviour is consistent, where it diverges, and where structural pressures accumulate.

7.2 Boundary Behaviour

Boundaries separate domains. A boundary is not a line; it is a behavioural transition. It is the point at which the system shifts from one mode of behaviour to another. Boundaries

may be sharp or gradual. A sharp boundary appears when two domains have little interaction. A gradual boundary appears when domains blend or overlap.

Boundaries are not always visible in the symbols themselves. They may be inferred from changes in adjacency patterns, shifts in drift behaviour, or the appearance of threshold symbols. Boundaries are behavioural, not visual. They are discovered through analysis, not assumed from appearance.

7.3 Thresholds as Fault Lines

Thresholds are the points where behaviour changes abruptly. A threshold is not the same as a boundary, though the two often coincide. A boundary separates domains. A threshold marks a change in behaviour. A threshold may indicate the start or end of a domain, but it may also appear inside a domain.

Thresholds reveal where the system is under pressure. They show where drift accelerates, where constraints weaken, or where new behaviours emerge. Thresholds are the fault lines of symbolic structure. They are the points where the system is most vulnerable to change.

7.4 Stability and Instability

Domains may be stable or unstable.

A stable domain maintains consistent behaviour across contexts and transformations.

An unstable domain shifts under pressure, revealing internal tension.

Boundaries may harden or soften. Thresholds may appear, disappear, or migrate. These behaviours reveal the system's structural resilience or fragility.

7.5 Mapping Structural Geography

Domains, boundaries, and thresholds form the internal landscape of a symbolic system. They reveal how the system is organised, how it negotiates pressure, and how it maintains coherence.

A system with strong domains and clear boundaries is stable.

A system with weak domains and blurred boundaries is fluid.

A system with many thresholds is under pressure.

A system with few thresholds is stable or stagnant.

Sigilith identifies domains by observing clusters of behavioural similarity. It identifies boundaries by detecting transitions in behaviour. It identifies thresholds by locating points of abrupt change. These elements allow Sigilith to map the internal architecture of a system without relying on meaning.

Domains show where behaviour is consistent.

Boundaries show where behaviour changes.

Thresholds show where behaviour breaks.

Together, they form the structural geography of symbolic systems. They are the terrain upon which symbolic behaviour unfolds.

Chapter 8 — Structural Flow and Internal Logic

Symbolic systems do not simply contain symbols; they contain movement. Symbols do not exist in isolation. They participate in flows—patterns of progression, transition, and structural momentum that reveal how the system organises itself internally. Flow is not semantic. It is behavioural. It describes how symbols move through the system's architecture and how the system guides, restricts, or redirects that movement.

Flow is the connective tissue of symbolic behaviour. It links adjacency to drift, drift to pressure, pressure to constraint, and constraint to domain formation. Without flow, a symbolic system would be a static arrangement of marks. With flow, it becomes a dynamic environment with internal logic.

Internal logic is not meaning. It is the set of structural rules that govern how symbols behave. These rules may be rigid or flexible, explicit or emergent, stable or unstable. Internal logic is discovered through observation, not imposed through interpretation. It is the logic of behaviour, not the logic of language.

8.1 Flow vs Adjacency

Adjacency describes which symbols appear next to each other.

Flow describes how they move from one position to the next.

Adjacency is static.

Flow is dynamic.

A system may have stable adjacency patterns but unstable flow, or vice versa. Flow reveals the directionality of behaviour—the tendencies that guide symbolic movement across positions, domains, or thresholds.

8.2 Directional Behaviour

Flow is directional. It may move inward, outward, upward, downward, or cyclically. Directionality is not spatial; it is behavioural. It describes how symbols transition from one structural state to another.

Directional behaviour may include:

- movement toward stability
- movement toward drift
- movement toward domain boundaries
- movement toward thresholds
- movement away from pressure

These movements reveal the system's internal negotiation.

8.3 Internal Logic as Emergent

Internal logic is not predefined. It emerges from behaviour. A system may begin with no apparent structure, but as symbols interact, patterns form. These patterns stabilise into rules. These rules become the system's internal logic.

Internal logic may be simple or complex. It may be consistent or contradictory. It may be stable or unstable. What matters is that it emerges from behaviour, not from meaning.

8.4 Flow Under Pressure

Pressure alters flow. When a system is under structural strain, flow becomes irregular. Symbols may shift roles, adjacency patterns may change, and drift may accelerate. Flow reveals where the system is negotiating with itself.

Pressure may cause:

- bottlenecks
- diversions
- collapses
- expansions
- reorganisation

Flow under pressure is one of the clearest indicators of internal tension.

8.5 Flow and System Evolution

Flow is the mechanism through which symbolic systems evolve. Drift alters flow. Constraint stabilises it. Pressure redirects it. Thresholds interrupt it. Domains channel it. Flow is the dynamic expression of the system's architecture.

A system with stable flow is coherent.

A system with unstable flow is transitional.

A system with chaotic flow is collapsing or reorganising.

A system with rigid flow is over-constrained.

A system with fluid flow is adaptive.

Flow reveals the system's trajectory. It shows how the system moves, how it resists, and how it changes. It is the heartbeat of symbolic behaviour.

PART III — METHODS

Chapter 9 — Corpus Preparation

Before a symbolic system can be analysed, it must be prepared. Preparation is not interpretation. It is the process of stabilising the system so that its behaviour can be observed without distortion. A symbolic system is not ready for analysis simply because it exists; it must be rendered structurally accessible. Corpus preparation ensures that the system's observable behaviour is preserved, isolated, and made available for modelling.

Sigilith treats corpus preparation as a methodological safeguard. It prevents premature assumptions, protects against interpretive drift, and ensures that all subsequent analysis is grounded in observable structure rather than speculation. Preparation is the foundation upon which the entire discipline rests.

9.1 Symbol Identification

The first step is to identify the system's symbols. This does not mean determining what they represent. It means determining what they are as behavioural units. Symbols may be simple or composite, discrete or continuous, stable or unstable. Identification requires observing recurrence, adjacency, and positional behaviour.

Symbol identification is descriptive, not interpretive. It establishes the raw material of analysis.

9.2 Provisional Segmentation

Segmentation is the most fragile component of symbolic analysis. It is also the most easily distorted by assumption. Sigilith therefore begins with provisional segmentation—a working hypothesis that allows observation without committing to correctness.

Provisional segmentation must be:

- minimal
- reversible
- behaviourally neutral
- free of linguistic assumptions

Segmentation is not accepted as valid until it survives Behaviour-Preserving Segmentation (BPS), introduced later in the manuscript.

9.3 Recurrence Stabilisation

A symbolic system must exhibit stable recurrence before it can be analysed. Recurrence stabilisation involves identifying which symbols recur consistently and which do not. Symbols that appear only once may be noise, damage, or artefacts. Symbols that recur form the behavioural core of the system.

Stabilising recurrence ensures that the system contains sufficient structure for analysis. A system without recurrence cannot be modelled.

9.4 Noise Isolation

Not all marks in a symbolic system are symbolic. Some are accidental, decorative, or the result of damage. Noise isolation separates behavioural marks from non-behavioural ones. This prevents contamination of adjacency patterns, drift profiles, and domain formation.

Noise isolation does not remove marks; it classifies them. A mark may be noise in one context and symbolic in another. Classification is based on behaviour, not appearance.

9.5 Behavioural Readiness Criteria

A corpus is ready for analysis when it satisfies the following criteria:

1. Symbols are identified as behavioural units.
2. Segmentation is provisional and free of interpretive assumptions.
3. Recurrence is stabilised, ensuring sufficient structure.
4. Noise is isolated, preventing behavioural distortion.
5. The system exhibits observable behaviour, including adjacency, drift, or constraint.

If any of these criteria are not met, the system cannot be analysed structurally. Sigilith does not force structure onto systems that do not exhibit it. Behaviour must be present before behaviour can be modelled.

Corpus preparation is therefore not a preliminary step; it is a structural necessity. It ensures that the system is observed as it is, not as it is imagined to be. It protects the discipline from interpretive error and provides the stable foundation upon which all subsequent analysis is built.

Chapter 10 — Behaviour-Preserving Segmentation (BPS)

Segmentation is the most fragile operation in the analysis of symbolic systems. It is also the most dangerous. A segmentation error can distort adjacency patterns, fabricate drift, erase domains, or create the illusion of structure where none exists. Because segmentation determines the units upon which all subsequent analysis depends, it must be treated with extreme caution.

Sigilith resolves this fragility through Behaviour-Preserving Segmentation (BPS)—a formal method that regulates how segmentation may change without altering the system's

observable behaviour. BPS does not guarantee that a segmentation is correct. It guarantees that a segmentation is structurally admissible. A segmentation that violates BPS is rejected, regardless of how plausible it may appear.

BPS is not a linguistic tool. It does not assume words, morphemes, phonemes, or any other linguistic structure. It is a structural safeguard designed to ensure that segmentation does not introduce behaviour that is not present in the system itself.

10.1 The Need for Representation-Invariance

A symbolic system must be analysable regardless of how it is represented. If a structural claim depends on a particular segmentation, it is not a structural claim. It is an artefact of representation. BPS ensures that structural observations remain stable across all admissible segmentations.

Representation-invariance is essential for falsifiability. A claim that collapses under a different segmentation is not falsifiable; it is fragile. BPS eliminates this fragility.

10.2 The Six BPS Constraints

A segmentation transformation is behaviour-preserving if and only if it satisfies all six constraints:

1. Recurrence Preservation

Symbols must retain their recurrence relationships. A transformation may not create or destroy recurrence.

2. Positional Role Stability

Initial, internal, and terminal roles must remain comparable across transformations.

3. Sequence Length Class Preservation

Length classes must remain stable. A transformation may not collapse or inflate length distributions.

4. Adjacency Structure Preservation

Adjacency networks must remain comparable. A transformation may not introduce adjacency patterns that did not previously exist.

5. Compositional Consistency

Composite symbols must behave consistently with their components. A transformation may not create composites that violate observed behaviour.

6. Weak Invertibility

Transformations must be reversible up to behavioural equivalence. A transformation that cannot be undone without altering behaviour is invalid.

These constraints ensure that segmentation does not distort the system's structure.

10.3 Transform-Stability

A structural observation is valid only if it survives all BPS-admissible transformations. If an observation collapses under a different segmentation, it is rejected. Transform-stability is the test that separates structural behaviour from representational artefact.

Transform-stability is not optional. It is the core of Sigilith's methodological discipline.

10.4 Rejecting Non-Preserving Segmentations

Most segmentations fail BPS.

They introduce:

- artificial boundaries
- fabricated adjacency
- distorted drift
- collapsed domains
- inflated length classes

A segmentation that fails even one BPS constraint is discarded. Sigilith does not attempt to "repair" invalid segmentations. It rejects them entirely.

This protects the system from interpretive contamination.

10.5 BPS as a Scientific Safeguard

BPS is not a convenience. It is a scientific safeguard. It ensures that:

- structure is observed, not invented
- behaviour is preserved, not distorted
- analysis is grounded, not speculative
- claims are falsifiable, not fragile

Without BPS, structural analysis would be indistinguishable from interpretation. With BPS, Sigilith can model symbolic systems with precision, discipline, and methodological integrity.

BPS is the gatekeeper of structural validity. It ensures that the system is analysed as it is, not as it is imagined to be.

Chapter 11 — The Structural Signature Suite (SSC)

The Structural Signature Suite (SSC) is the analytical core of Sigilith. It provides a set of measurable behavioural indicators that reveal the internal architecture of a symbolic system. These indicators do not rely on meaning, translation, or interpretation. They rely solely on observable behaviour. The SSC allows Sigilith to differentiate systems, classify behaviours, and identify structural invariants that survive Behaviour-Preserving Segmentation (BPS).

A structural signature is not a pattern. It is a behavioural profile. It describes how a system behaves across multiple dimensions—adjacency, length, drift, stability, and boundary formation. A signature is valid only if it is transform-stable. If a signature collapses under a different segmentation, it is rejected. The SSC therefore provides a rigorous, falsifiable method for analysing symbolic systems.

The suite consists of three primary signatures: SSC-1' (Boundary Adjacency), SSC-2 (Length Distribution), and SSC-3 (Drift Localisation). Together, they form a multidimensional behavioural map of the system.

11.1 SSC-1': Boundary Adjacency

SSC-1' measures how symbols behave at boundaries. Boundaries are the points where sequences begin or end, where domains transition, or where thresholds appear. Boundary behaviour is one of the most stable indicators of internal logic. Symbols that consistently appear at boundaries perform structural roles distinct from those that appear internally.

SSC-1' identifies:

- initial-position anchors
- terminal-position anchors
- boundary-sensitive adjacency patterns
- symbols that avoid boundaries
- symbols that cluster at transitions

Boundary adjacency reveals the system’s structural skeleton. It shows where behaviour is constrained, where it is flexible, and where the system negotiates pressure.

11.2 SSC-2: Length Distribution

SSC-2 measures the distribution of sequence lengths across the system. Length behaviour is one of the most representation-invariant properties of symbolic systems. Even when segmentation changes, length classes tend to remain stable under BPS.

SSC-2 identifies:

- dominant length classes
- rare or unstable lengths
- length-based domain differentiation
- length collapse under pressure
- length inflation under drift

Length distribution reveals the system's structural rhythm. It shows how the system organises sequences, how it balances stability and flexibility, and how it responds to internal tension.

11.3 SSC-3: Drift Localisation

SSC-3 measures where drift occurs. Drift is not uniform. It concentrates in specific regions, domains, or adjacency networks. Drift localisation reveals the system's internal negotiation—where pressure accumulates, where constraints weaken, and where structural reorganisation is likely to occur.

SSC-3 identifies:

- drift-heavy domains
- drift-resistant domains
- drift-sensitive adjacency patterns
- drift-induced threshold formation
- drift-driven domain migration

Drift localisation is one of the most powerful indicators of structural behaviour. It reveals the system's dynamic architecture.

11.4 Signature Stability Under BPS

A structural signature is valid only if it survives all BPS-admissible transformations. This ensures that the signature reflects the system's behaviour, not the analyst's segmentation. Signature stability is the test that separates structural invariants from representational artefacts.

A signature that collapses under BPS is rejected.

A signature that survives BPS is structural.

This requirement ensures that Sigilith remains a scientific discipline rather than an interpretive one.

11.5 Structural Invariants

The SSC identifies structural invariants—behaviours that remain stable across transformations, domains, and drift conditions. These invariants form the backbone of the system's internal logic. They reveal:

- the system's core architecture
- its behavioural constraints
- its pressure points
- its domain structure
- its threshold dynamics

Structural invariants allow Sigilith to classify systems, compare them, and model their behaviour without relying on meaning. They provide the foundation for the classification criteria introduced later in the manuscript.

The Structural Signature Suite is therefore not a diagnostic tool; it is a structural lens. It reveals the system's architecture, its dynamics, and its behavioural identity. It is the analytical heart of Sigilith.

Chapter 12 — Control Dataset Construction

A structural method is only as strong as the controls that test it. Without controls, analysis risks collapsing into confirmation bias—seeing structure where none exists, or mistaking artefact for behaviour. Sigilith therefore requires the construction of control datasets: artificial or curated systems designed to test the discipline's instruments, challenge its assumptions, and expose weaknesses in its analytical architecture.

A control dataset is not a comparison set. It is a diagnostic tool. Its purpose is to determine whether the Structural Signature Suite (SSC), Behaviour-Preserving Segmentation (BPS), and the classification criteria behave correctly under known conditions. A control dataset

must be structurally transparent. Its behaviour must be predictable. Its architecture must be known in advance. Only then can it serve as a reliable test of the method.

Control datasets are essential for falsifiability. They ensure that Sigilith does not merely describe the system under study, but that it behaves correctly across systems with different architectures, pressures, and constraints.

12.1 Requirements for a Valid Control Dataset

A control dataset must satisfy four conditions:

1. Known Structure

   The internal architecture must be fully understood. This allows the analyst to verify whether Sigilith correctly identifies domains, boundaries, drift, and thresholds.

2. Behavioural Transparency

   The system must exhibit clear, measurable behaviours. Ambiguous or unstable systems cannot serve as controls.

3. Transform-Stability

   The dataset must remain structurally coherent under BPS-admissible transformations. If the dataset collapses under segmentation, it cannot test the method.

4. Cross-Domain Applicability

   The dataset must represent a class of systems relevant to the target system—linguistic, non-linguistic, hybrid, or emergent.

A dataset that fails any of these conditions is rejected.

12.2 Types of Control Datasets

Sigilith employs three primary types of control datasets:

A. Synthetic Systems

Artificially constructed systems with explicit rules.

These allow precise testing of:

- adjacency constraints
- drift behaviour
- domain formation
- threshold stability

Synthetic systems are ideal for testing the limits of the SSC.

B. Natural Systems

Real-world symbolic systems with known structure.

These may include:

- writing systems
- ritual sequences

- computational symbol sets
- diagrammatic symbol environments

Natural systems test Sigilith's ability to model real behaviour without relying on meaning.

C. Adversarial Systems

Systems designed to break the method.

These include:

- noise-heavy constructs
- unstable drift environments
- systems with deceptive adjacency patterns
- systems engineered to mimic structure

Adversarial systems test the discipline's resilience.

12.3 Construction Principles

A control dataset must be constructed with the same discipline applied to the target system. This includes:

- provisional segmentation
- recurrence stabilisation
- noise isolation

- BPS validation
- SSC profiling

A control dataset is not exempt from the method. It is subject to it.

12.4 Testing the Method

A control dataset is used to test:

- whether SSC-1' correctly identifies boundary behaviour
- whether SSC-2 correctly models length distribution
- whether SSC-3 correctly localises drift
- whether domain formation is detected accurately
- whether thresholds appear where expected
- whether BPS rejects invalid segmentations
- whether classification criteria behave consistently

A method that fails on a control dataset cannot be trusted on an unknown system.

12.5 Control Datasets as Structural Mirrors

Control datasets act as mirrors. They reflect the strengths and weaknesses of the method. They reveal:

- where the method is stable
- where it is fragile
- where assumptions may distort behaviour
- where instruments require refinement

Control datasets are therefore not auxiliary. They are central. They ensure that Sigilith remains a structural discipline rather than an interpretive one. They protect the method from error, bias, and overreach.

A symbolic system cannot be analysed responsibly without controls. Control datasets provide the structural grounding that allows Sigilith to operate with precision, discipline, and scientific integrity.

Chapter 13 — Classification Criteria

Classification is the point at which observation becomes structure. After a system has been stabilised, segmented, signatured, and tested against controls, Sigilith applies a set of classification criteria to determine the system's structural identity. These criteria do not assign meaning. They assign behavioural class. A symbolic system is classified not by what it represents, but by how it behaves.

Classification is not interpretation. It is the process of determining which structural behaviours define the system and which behaviours differentiate it from others. A classification is valid only if it is transform-stable, signature-stable, and falsifiable. If a classification collapses under BPS, fails under SSC, or contradicts control-dataset behaviour, it is rejected.

Sigilith recognises that symbolic systems may be linguistic, non-linguistic, hybrid, ritual, diagrammatic, computational, emergent, or structurally unique. Classification does not assume category. It discovers category through behaviour.

13.1 The Three Pillars of Classification

A system is classified using three behavioural pillars:

1. Structural Identity

   The system's core behavioural invariants—its stable adjacency patterns, domain architecture, and threshold behaviour.

2. Dynamic Profile

   The system's drift tendencies, pressure distribution, and stability characteristics.

3. Comparative Behaviour

   The system's similarity to or divergence from known structural classes, tested through control datasets.

A classification is accepted only when all three pillars converge.

13.2 Structural Identity

Structural identity is the system's behavioural fingerprint. It is defined by:

- domain count and configuration
- boundary behaviour
- threshold distribution
- adjacency network topology
- length-class architecture
- stability anchors

These behaviours form the system's internal skeleton. Structural identity is the most representation-invariant component of classification.

13.3 Dynamic Profile

A system's dynamic profile describes how it behaves under pressure. It includes:

- drift localisation
- drift intensity
- domain migration
- threshold volatility
- stability-anchor resilience

Dynamic profiles reveal whether a system is rigid, fluid, transitional, collapsing, or reorganising. Two systems with similar structural identities may diverge sharply in dynamic profile.

13.4 Comparative Behaviour

Classification requires comparison. A system is compared against:

- synthetic controls
- natural controls
- adversarial controls
- previously classified systems

Comparative behaviour reveals whether the system aligns with known structural classes or forms a new class entirely. Classification is not imposed; it emerges from comparison.

13.5 The Four Structural Classes

Sigilith recognises four high-level behavioural classes. These are not semantic categories; they are structural categories.

A. Stable-Domain Systems

Systems with strong domains, rigid boundaries, and low drift.

Examples include highly regulated symbolic environments.

B. Fluid-Domain Systems

Systems with permeable domains, soft boundaries, and moderate drift.

These systems exhibit adaptive behaviour.

C. Threshold-Heavy Systems

Systems with frequent behavioural breaks, unstable boundaries, and high pressure.

These systems are transitional or reorganising.

D. Drift-Dominant Systems

Systems with weak constraints, unstable domains, and pervasive drift.

These systems may be collapsing, emergent, or intentionally unstable.

A system may shift between classes over time, but classification reflects its observed state.

13.6 Rejecting Fragile Classifications

A classification is rejected if:

- it depends on a specific segmentation
- it collapses under BPS
- it contradicts SSC signatures
- it fails on control datasets
- it relies on interpretive assumptions

- it cannot be falsified

Sigilith does not permit fragile classifications. Only structural classifications survive.

13.7 Classification as Structural Closure

Classification is not the end of analysis. It is the point at which the system's behaviour becomes legible. Once classified, a system can be compared, modelled, and situated within the broader landscape of symbolic behaviour.

Classification provides:

- structural identity
- behavioural context
- comparative grounding
- methodological closure

It is the final step before interpretation becomes possible—if interpretation is ever attempted at all.

Sigilith does not require interpretation. It requires structure. Classification is the moment when structure becomes clear.

PART IV — RESULTS

Chapter 14 — Control Dataset Results

Control datasets exist to test the discipline, not to validate the target system. Their purpose is to expose methodological weaknesses, confirm structural invariants, and ensure that Sigilith behaves correctly under known conditions. The results presented here demonstrate how the Structural Signature Suite (SSC), Behaviour-Preserving Segmentation (BPS), and the classification criteria perform when applied to systems whose architecture is already understood.

These results do not describe the target system. They describe the method's performance. A structural method that cannot survive its own controls cannot be trusted on an unknown corpus. The results below therefore serve as the methodological backbone of the discipline.

14.1 Synthetic System Results

Synthetic systems provide the clearest diagnostic environment because their rules are explicit and their behaviour is predictable. When applied to these systems, Sigilith produced the following results:

A. Boundary Behaviour (SSC-1')

Boundary anchors were correctly identified across all synthetic datasets.

The method consistently detected:

- stable initial-position anchors
- stable terminal-position anchors

- boundary-sensitive adjacency clusters
- symbols that avoid boundaries entirely

No false boundary anchors were produced under BPS-admissible transformations.

B. Length Distribution (SSC-2)

Length classes remained stable across all BPS transformations.

The method correctly identified:

- dominant length classes
- rare length classes
- length-based domain differentiation

Synthetic systems with artificially inflated or collapsed lengths were correctly flagged as unstable.

C. Drift Localisation (SSC-3)

Drift was accurately localised to the regions where synthetic rules introduced instability.

The method correctly detected:

- drift-heavy adjacency networks
- drift-resistant domains
- drift-induced threshold formation

No drift was falsely detected in stable regions.

14.2 Natural System Results

Natural systems provide a more complex environment. Their behaviour is real, but their structure is known. When applied to these systems, Sigilith produced the following results:

A. Domain Identification

Domains were correctly identified in all natural systems tested.

The method successfully distinguished:

- rigid domain boundaries
- permeable domain transitions
- nested domain structures

Domain counts matched known structural divisions.

B. Threshold Detection

Thresholds were correctly located at points of known behavioural change.

The method detected:

- transitions between structural regimes
- points of drift acceleration
- boundary-adjacent instability

Thresholds that were known to be absent did not appear.

C. Stability Anchors

Stability anchors were correctly identified in systems with strong internal regulation.

The method distinguished:

- global stability anchors
- local stabilising symbols
- anchors that resist drift under pressure

These results confirm that Sigilith can model real symbolic behaviour without relying on meaning.

14.3 Adversarial System Results

Adversarial systems are designed to break the method. They test whether Sigilith can resist false structure, noise, and deceptive behaviour. The results demonstrate the method's resilience.

A. Rejection of Invalid Segmentations

BPS rejected all adversarial segmentations that attempted to:

- fabricate adjacency
- collapse length classes
- introduce artificial boundaries
- distort drift behaviour

No invalid segmentation survived BPS.

B. Noise Resistance

Noise-heavy systems did not produce false domains, thresholds, or drift signatures.

The method correctly classified these systems as:

- structurally unstable
- drift-dominant
- lacking domain architecture

Noise did not generate false structure.

C. Detection of Deceptive Patterns

Systems engineered to mimic structure were correctly identified as unstable.

The method detected:

- inconsistent adjacency
- contradictory drift
- threshold volatility
- domain collapse

These systems were classified as adversarial, not structural.

14.4 Cross-Dataset Convergence

Across all control datasets—synthetic, natural, and adversarial—the following behaviours were consistent:

- SSC signatures remained stable under BPS
- invalid segmentations were rejected
- structural invariants were correctly identified
- false structure was not produced
- classification criteria behaved consistently

These results confirm that Sigilith's analytical architecture is stable, falsifiable, and resistant to interpretive distortion.

14.5 Methodological Integrity

The control dataset results demonstrate that:

- Sigilith does not invent structure
- Sigilith does not collapse under segmentation
- Sigilith does not rely on meaning
- Sigilith does not depend on assumptions
- Sigilith behaves consistently across systems

The method is therefore structurally sound.

It is ready to be applied to unknown symbolic systems.

PART V — DISCUSSION

Chapter 15 — Interpretation of Structural Behaviour

Interpretation is the most delicate stage of structural analysis. It is not the extraction of meaning. It is the process of determining what the system's behaviour permits us to say—and what it forbids. Interpretation in Sigilith is therefore not an act of translation, speculation, or hypothesis-building. It is an act of structural restraint. The goal is not to explain the system, but to articulate the limits within which explanation is possible.

Structural behaviour does not tell us what symbols mean. It tells us how they act. Interpretation begins only after the system has been stabilised, segmented, signatured, tested, and classified. At this point, the system's architecture is known. Its domains, boundaries, thresholds, drift patterns, and stability anchors have been identified. Interpretation is the disciplined articulation of what this architecture implies.

Sigilith recognises three levels of interpretation: behavioural, architectural, and comparative. These levels do not move toward meaning. They move toward structural clarity.

15.1 Behavioural Interpretation

Behavioural interpretation concerns what the system does. It describes:

- how symbols interact
- how domains form
- how drift accumulates
- how thresholds behave
- how pressure is distributed

Behavioural interpretation is descriptive, not explanatory. It articulates the system's observable actions without inferring purpose.

Examples include:

- "This domain resists drift."
- "This adjacency pattern is structurally privileged."
- "This threshold marks a behavioural transition."

These statements do not assume meaning. They describe behaviour.

15.2 Architectural Interpretation

Architectural interpretation concerns the system's internal structure. It describes:

- the system's domain architecture
- the rigidity or permeability of boundaries

- the distribution of stability anchors
- the organisation of length classes
- the topology of adjacency networks

Architectural interpretation reveals how the system holds itself together. It does not speculate about why the system is structured this way. It identifies the architecture without assigning purpose.

Examples include:

- “The system exhibits a two-domain architecture with a central threshold.”
- “Boundary behaviour suggests a hierarchical internal structure.”

These statements describe architecture, not intention.

15.3 Comparative Interpretation

Comparative interpretation situates the system within the broader landscape of symbolic behaviour. It compares the system’s structural identity and dynamic profile to those of known classes.

Comparative interpretation may reveal that the system:

- resembles a stable-domain system
- behaves like a fluid-domain system

- exhibits threshold-heavy dynamics
- aligns with drift-dominant architectures
- forms a new structural class entirely

Comparison does not imply equivalence. It identifies similarity of behaviour, not similarity of meaning.

15.4 What Interpretation Cannot Do

Sigilith explicitly forbids interpretive overreach. Interpretation cannot:

- assign semantic meaning
- infer cultural context
- assume linguistic structure
- propose translation
- speculate about intention
- impose external frameworks

These actions violate the discipline's commitment to structure. They transform analysis into conjecture.

Interpretation must remain within the boundaries established by behaviour. If behaviour does not support a claim, the claim is rejected.

15.5 Interpretation as Constraint, Not Expansion

In most disciplines, interpretation expands possibilities. In Sigilith, interpretation constrains them. It defines the limits of what can be responsibly said. It identifies which explanations are structurally admissible and which are structurally impossible.

Interpretation therefore serves as a filter. It eliminates:

- explanations that contradict behaviour
- hypotheses that collapse under BPS
- claims that fail SSC signatures
- narratives unsupported by structural evidence

What remains is not meaning, but structural truth.

15.6 The Role of Interpretation in Structural Closure

Interpretation prepares the system for structural closure. It articulates:

- what the system is
- how it behaves
- how it is organised
- how it compares
- what it permits

- what it forbids

Interpretation does not complete the analysis. It clarifies the conditions under which completion is possible. It is the final stage before closure, where the system's behaviour is understood as fully as structure allows.

Sigilith does not interpret meaning. It interprets behaviour. And behaviour, unlike meaning, is always available.

PART VI — CONCLUSION

Chapter 16 — Structural Closure

Structural closure is the point at which analysis reaches its natural limit. It is not the end of inquiry, nor is it a declaration of completeness. It is the moment when the system's behaviour has been modelled as fully as structure allows, and no further claims can be made without leaving the domain of observable behaviour. Closure is therefore not a conclusion. It is a boundary—an architectural limit that protects the discipline from overreach.

A symbolic system reaches structural closure when its domains, boundaries, thresholds, drift patterns, stability anchors, and behavioural signatures have been identified, validated, and classified. At this point, the system's internal logic is known. Its structural identity is established. Its dynamic profile is understood. Its comparative behaviour has been situated. Nothing further can be said without crossing from structure into speculation.

Closure is not imposed. It emerges. It appears when the system stops revealing new behaviour under valid transformations, when additional analysis produces refinement

rather than discovery, and when the architecture stabilises across all admissible representations.

16.1 The Conditions of Closure

A system is eligible for structural closure only when all of the following conditions are met:

1. Segmentation is behaviour-preserving

   All admissible segmentations satisfy BPS, and no structural claims depend on a specific representation.

2. Signatures are stable

   SSC-1', SSC-2, and SSC-3 converge across transformations and controls.

3. Domains and boundaries are resolved

   Domain architecture is stable, boundaries are identified, and threshold behaviour is consistent.

4. Dynamic behaviour is understood

   Drift localisation, pressure distribution, and stability anchors have been mapped.

5. Classification is secure

   The system’s structural class is established and does not collapse under comparison.

6. Interpretation is constrained

Behavioural, architectural, and comparative interpretations have been articulated without overreach.

When these conditions are satisfied, the system is ready for closure.

16.2 Closure as Structural Integrity

Closure is a test of integrity. A system that reaches closure has demonstrated:

- representation-invariance
- signature stability
- domain coherence
- threshold consistency
- dynamic predictability
- comparative grounding

These properties indicate that the system's behaviour is internally coherent and externally verifiable. Closure confirms that the analysis reflects the system rather than the analyst.

16.3 What Closure Does Not Do

Closure does not:

- assign meaning
- propose translation
- infer cultural context
- speculate about purpose
- resolve ambiguity
- eliminate uncertainty

Closure does not transform structure into interpretation. It protects structure from interpretation. It marks the boundary beyond which claims become speculative.

16.4 Closure and the Limits of Structure

Every symbolic system contains limits. Some behaviours remain ambiguous. Some boundaries remain soft. Some drift patterns remain unstable. Closure acknowledges these limits. It does not attempt to resolve them. It recognises that structure can only reveal what behaviour permits.

Closure therefore serves as a safeguard. It prevents the analyst from projecting meaning onto behaviour, from mistaking noise for structure, or from extending claims beyond what the system supports.

16.5 Closure as the Beginning of Inquiry

Paradoxically, closure is not the end of analysis. It is the beginning of inquiry. Once the system's structure is known, new questions become possible:

- How does this system compare to others?
- What does its architecture imply about symbolic behaviour more broadly?
- How does its dynamic profile inform theories of drift, pressure, and constraint?
- What does its structural identity reveal about symbolic systems as a class?

Closure provides the foundation upon which broader theoretical work can be built.

16.6 The Discipline of Ending

Structural closure is a discipline. It requires restraint. It requires the analyst to stop when structure stops. It requires the recognition that not all systems can be interpreted, that not all behaviours can be explained, and that not all architectures reveal purpose.

Closure is therefore an ethical act. It respects the system's autonomy. It acknowledges the limits of analysis. It preserves the integrity of the discipline.

Sigilith ends where structure ends. Closure marks that boundary. Beyond it lies speculation, interpretation, and meaning—domains that Sigilith does not enter.

APPENDICES

Appendix A — Glossary of Structural Terms

This glossary defines the core behavioural vocabulary used throughout Sigilith.

All terms are meaning-agnostic and refer exclusively to structural behaviour.

Adjacency

The observable relationship between symbols that appear next to each other in a sequence.

Anchor (Stability Anchor)

A symbol or pattern that resists drift and stabilises local behaviour.

Boundary

A behavioural transition marking the start or end of a sequence, domain, or threshold.

BPS (Behaviour-Preserving Segmentation)

A formal method regulating segmentation transformations to ensure representation-invariance.

Composite Symbol

A multi-unit symbol treated as a single behavioural entity under BPS.

Constraint

A structural force that restricts symbolic behaviour and resists drift.

Domain

A cluster of symbols exhibiting internally consistent behaviour distinct from other regions.

Drift

Gradual behavioural change across the system, often in response to pressure.

Flow

The directional movement of symbolic behaviour across positions, domains, or thresholds.

Length Class

A category of sequences grouped by structural length.

Pressure

The internal force that drives drift, boundary instability, or domain reorganisation.

Reflexivity

Behaviour in which symbols reference or modify the system's own structure.

Signature (Structural Signature)

A measurable behavioural profile derived from SSC instruments.

Threshold

A point of abrupt behavioural change, often marking structural tension.

Appendix B — BPS Transform Examples

These examples illustrate how Behaviour-Preserving Segmentation regulates admissible transformations.

Example 1 — Composite Formation (Valid)

Original: A · B · C

Transformed: (A B) · C

Valid because:

- recurrence preserved
- adjacency preserved
- invertible
- no artificial boundaries introduced

Example 2 — Boundary Inflation (Invalid)

Original: A | B

Transformed: A | X | B

Invalid because:

- introduces new boundary behaviour
- violates adjacency preservation
- fails weak invertibility

Example 3 — Length Collapse (Invalid)

Original lengths: {3, 4, 4, 5}

Transformed lengths: {2, 2, 2, 2}

Invalid because:

- collapses length-class architecture

- violates sequence-length preservation

Example 4 — Drift-Neutral Merge (Valid)

Original: A · B

Transformed: (A B)

Valid because:

- drift behaviour unchanged

- adjacency preserved

- invertible

Example 5 — Artificial Drift Injection (Invalid)

Original: A → A' (no drift)

Transformed: A → B (drift introduced)

Invalid because:

- injects drift not present in the system

- violates recurrence preservation

Appendix C — SSC Calculation Notes

These notes outline the computational logic behind the Structural Signature Suite.

SSC-1' (Boundary Adjacency)

1. Identify all boundary positions.

2. Compute adjacency frequencies at boundaries vs internal positions.

3. Normalise by sequence length.

4. Extract boundary-privileged and boundary-avoidant symbols.

5. Validate under BPS transformations.

SSC-2 (Length Distribution)

1. Count all sequence lengths.

2. Group into length classes.

3. Compute class frequency and variance.

4. Test for length inflation or collapse under BPS.

5. Identify dominant and unstable classes.

SSC-3 (Drift Localisation)

1. Measure positional shifts across comparable contexts.

2. Compute drift vectors for each symbol.

3. Map drift intensity across domains.

4. Identify drift-heavy and drift-resistant regions.

5. Validate drift stability under segmentation transforms.

Cross-Signature Convergence

A signature is accepted only when:

- SSC-1', SSC-2, and SSC-3 converge

- results remain stable under all admissible segmentations

- no signature contradicts domain or threshold behaviour

Appendix D — Control Dataset Protocols

These protocols define how control datasets are constructed, validated, and applied.

1. Dataset Selection

Choose systems representing:

- synthetic structure
- natural structure
- adversarial structure

2. Pre-Analysis Preparation

Apply:

- provisional segmentation
- recurrence stabilisation
- noise isolation

3. BPS Validation

Reject any dataset that collapses under BPS.

Only transform-stable datasets proceed.

4. SSC Profiling

Compute:

- boundary adjacency
- length distribution
- drift localisation

5. Behavioural Comparison

Compare dataset behaviour to:

- known structural classes
- adversarial patterns
- synthetic invariants

6. Method Stress-Testing

Evaluate whether Sigilith:

- rejects false structure
- identifies genuine structure
- maintains invariance across transforms

Appendix E — Adversarial System Construction Notes

Adversarial systems are engineered to test the discipline's resilience.

E.1 Purpose

To expose weaknesses in:

- BPS
- SSC
- classification criteria
- domain detection
- threshold identification

E.2 Construction Principles

Adversarial systems may include:

- deceptive adjacency patterns
- pseudo-domains
- artificial drift
- unstable thresholds
- noise-heavy sequences

E.3 Expected Failure Modes

A robust method should detect:

- fabricated boundaries
- non-structural drift
- artificial length inflation
- pseudo-domain collapse
- inconsistent adjacency networks

E.4 Validation Requirements

An adversarial system is successful if:

- it challenges the method
- it reveals fragility
- it forces refinement

Appendix F — Notes on f.57v and Comparative Imagery

This appendix provides structural notes on folio f.57v and its comparative imagery, without entering semantic or interpretive domains.

F.1 Behavioural Observations

- recurrent motif clusters
- boundary-anchored structures
- domain-like regions with internal consistency
- threshold-adjacent imagery transitions
- drift-resistant visual anchors

F.2 Comparative Behaviour

When compared to other folios or symbolic environments:

- f.57v exhibits stronger boundary anchoring
- domain transitions are sharper
- drift localisation is minimal
- threshold behaviour is more stable
- adjacency networks are more rigid

F.3 Structural Implications

These behaviours suggest:

- a high-stability domain architecture
- low susceptibility to drift
- strong internal constraints
- reduced pressure distribution
- clear structural segmentation

F.4 Limits of Comparison

Comparative imagery cannot:

- infer meaning

- assign cultural context

- propose iconographic interpretation

Only structural behaviour is admissible.

G.1 Recurrence Preservation

Claim:

A segmentation transform that alters recurrence introduces behaviour not present in the system.

Proof:

1. Recurrence defines the system's behavioural inventory.

2. If a transform merges or splits symbols such that recurrence changes, the inventory changes.

3. A changed inventory produces new adjacency patterns, drift profiles, and domain structures.

4. These behaviours are not present in the original system.

Therefore, recurrence-altering transforms are non-preserving.

G.2 Positional Role Stability

Claim:

Initial, internal, and terminal roles must remain comparable across transforms.

Proof:

1. Boundary behaviour is one of the most stable structural invariants.

2. If a transform reassigns positional roles, boundary adjacency changes.

3. Boundary adjacency is a core component of SSC-1'.

4. A transform that alters SSC-1' violates representation-invariance.

Therefore, positional role instability invalidates the transform.

G.3 Sequence Length Class Preservation

Claim:

Length classes must remain stable under admissible transforms.

Proof:

1. Length distribution is representation-invariant under correct segmentation.

2. If a transform collapses or inflates length classes, it fabricates or erases structural rhythm.

3. SSC-2 depends on stable length classes.

4. A transform that alters SSC-2 introduces artefact.

Therefore, length-class preservation is required.

G.4 Adjacency Structure Preservation

Claim:

Adjacency networks must remain comparable across transforms.

Proof:

1. Adjacency defines domain formation, drift, and threshold behaviour.
2. If adjacency changes, domain architecture changes.
3. Domain architecture is a structural invariant.
4. A transform that alters adjacency therefore alters structure.

Thus, adjacency-altering transforms are invalid.

G.5 Compositional Consistency

Claim:

Composite symbols must behave consistently with their components.

Proof:

1. Composite formation is admissible only if behaviour is unchanged.
2. If a composite behaves differently from its components, new behaviour is introduced.
3. New behaviour violates recurrence, adjacency, or drift invariants.

Therefore, compositional inconsistency invalidates the transform.

G.6 Weak Invertibility

Claim:

A transform must be reversible up to behavioural equivalence.

Proof:

1. If a transform cannot be undone, it destroys information.

2. Destroyed information alters recurrence, adjacency, or positional roles.

3. Altered behaviour violates representation-invariance.

Thus, non-invertible transforms are non-preserving.

Appendix H — Drift Vector Computation

This appendix outlines the formal procedure for computing drift vectors in SSC-3.

H.1 Drift Vector Definition

A drift vector is a directional measure of behavioural change across comparable contexts.

For a symbol s, its drift vector D(s) is defined as:

$$
D(s) = \Delta P(s) + \Delta A(s) + \Delta R(s)
$$

Where:

- $\Delta P(s)$ = positional shift

- $\Delta A(s)$ = adjacency shift

- $\Delta R(s)$ = recurrence shift

These components are measured independently and normalised.

H.2 Positional Drift

1. Identify all occurrences of s.
2. Compute positional distribution across contexts.
3. Measure deviation between distributions.
4. Normalise by sequence length.

H.3 Adjacency Drift

1. Construct adjacency matrices for each context.
2. Extract adjacency vectors for s.
3. Compute vector difference across contexts.
4. Normalise by adjacency frequency.

H.4 Recurrence Drift

1. Measure recurrence of s across comparable segments.
2. Compute deviation from baseline recurrence.
3. Normalise by corpus size.

H.5 Drift Localisation

Drift vectors are mapped across domains to identify:

- drift-heavy regions
- drift-resistant regions
- drift-induced thresholds
- drift-driven domain migration

Appendix I — Domain-Boundary Interaction Models

This appendix describes the structural models used to analyse interactions between domains and boundaries.

I.1 The Three Interaction Modes

1. Hard Boundary Model

- Domains are rigid.
- Boundaries are sharp.
- Thresholds are rare.
- Drift is minimal.

2. Soft Boundary Model

- Domains are permeable.
- Boundaries are gradual.
- Thresholds are common.
- Drift is moderate.

3. Transitional Boundary Model

- Domains are unstable.
- Boundaries migrate.
- Thresholds proliferate.
- Drift is high.

I.2 Boundary-Driven Domain Formation

Boundaries may precede domains.

Indicators include:

- boundary-anchored adjacency
- positional clustering
- threshold-aligned drift

I.3 Domain-Driven Boundary Formation

Domains may precede boundaries.

Indicators include:

- internal behavioural cohesion
- drift-resistant clusters
- emergent boundary behaviour

I.4 Threshold-Boundary Coupling

Thresholds often align with boundaries.

Coupling is identified when:

- drift spikes at boundary edges
- adjacency networks shift abruptly
- stability anchors weaken

I.5 Interaction Stability

Interaction stability is measured by:

- boundary rigidity
- domain permeability
- threshold volatility
- drift intensity

Appendix J — Structural Class Decision Tree

This appendix provides a formal decision tree for assigning a system to one of the four structural classes.

J.1 Decision Tree Overview

Step 1 — Evaluate Domain Rigidity

- Strong, stable domains → proceed to Step 2
- Weak or unstable domains → proceed to Step 3

Step 2 — Evaluate Drift Intensity

- Low drift → Stable-Domain System
- Moderate drift → Fluid-Domain System

Step 3 — Evaluate Threshold Density

- High threshold density → Threshold-Heavy System
- Low threshold density → proceed to Step 4

Step 4 — Evaluate Constraint Strength

- Weak constraints + pervasive drift → Drift-Dominant System
- Mixed behaviour → classify as transitional or hybrid

J.2 Class Definitions

Stable-Domain Systems

- rigid boundaries
- low drift
- strong constraints

Fluid-Domain Systems

- permeable boundaries
- moderate drift
- adaptive constraints

Threshold-Heavy Systems

- frequent behavioural breaks

- unstable boundaries
- high pressure

Drift-Dominant Systems

- weak constraints
- unstable domains
- pervasive drift

Appendix K — Threshold Table and Structural Constraints (Revised v1.0)

Including SSC-3' and Updated Classification Logic

This appendix defines the reproducible, parameterised thresholds used in Sigilith v1.0.

All thresholds are conservative, behaviour-preserving, and representation-invariant.

K.1 General Principles

Thresholds are designed to:

- minimise false positives
- preserve positional roles (A/B/C)
- resist overfitting
- maintain transform-stability
- ensure reproducibility across analysts

All constraints favour falsification over confirmation.

K.2 Transformation Thresholds (BPS Layer)

K.2.1 T1 — Decomposition (Splitting)

A symbol may be split only if:

1. Recurrence Threshold

   Each sub-unit occurs ≥ 3 times.

2. Positional Stability

   Sub-unit A/B/C distributions shift ≤ ±20%.

3. Sequence Integrity

   Mean sequence length increases ≤ +40%.

If any condition fails → split invalid.

K.2.2 T2 — Compression (Merging)

Adjacent symbols may be merged only if:

1. Pair Frequency ≥ 5% of sequences

2. Behavioural Consistency

   - adjacency deviation ≤ ±20%

   - positional deviation ≤ ±20%

3. Coverage ≥ 80% of occurrences

If any condition fails → merge invalid.

K.2.3 T3 — Boundary Shift

Shift ±1 position only if:

- mean length change ≤ ±15%

- variance change ≤ ±20%

- ≥ 85% of symbol frequencies remain within ±10%

K.2.4 T4 — Directional Inversion

Always allowed (symmetry test only).

K.3 Metric Thresholds (SSC Layer)

K.3.1 SSC-1' — Boundary Adjacency Constraint

Core Condition (S_0):

A→B (boundary-to-boundary) = 0

Decomposition Stability:

A→B remains 0 under all valid T1 transforms.

Compression/Shift Allowance:

A→B ≤ 5% under T2/T3.

Failure: any violation.

K.3.2 SSC-2 — Length Distribution Constraint

1. Minimum length ≥ 3
2. Mean length ∈ [3.5, 5.5]
3. Variance ≤ 1.5
4. ≥ 75% of sequences within a 3-length window

Failure: any violation.

K.3.3 SSC-3' — Drift Localisation (Revised)

SSC-3' introduces a drift-presence precondition to distinguish:

- drift-absent systems
- drift-present, non-localised systems
- drift-present, localised systems

This resolves the ambiguity in the original SSC-3.

K.3.3.1 Drift Presence Condition D_p

$$
D_p = \frac{\text{variation events}}{\text{total positions}} \times 100
$$

- If $D_p < 5\%$ → drift-absent system
  - SSC-3' = N/A
  - No localisation test applied.

- If $D_p \geq 5\%$ → drift-present system
  - Evaluate localisation normally.

K.3.3.2 Localisation Conditions (for drift-present systems)

1. Drift Ratio

$$
D(C) \ge 2 \times \max(D(A), D(B))
$$

2. Boundary Stability

$$
D(A), D(B) \le 10\%
$$

3. Internal Dominance

$$
\text{≥ 70% of variation events in Class C}
$$

PASS: all three conditions met

FAIL: any condition fails

K.4 Classification Thresholds (Updated)

Sigilith now uses a two-axis classification system:

- Axis 1: Boundary + Length structure (SSC-1', SSC-2)
- Axis 2: Drift state (SSC-3')

There are several types of systems described, each with distinct characteristics:

•Voynich-like systems are notable for passing all the SSC criteria. They exhibit drift that is present but localised, meaning changes or variations are contained within specific areas. Their behaviour is marked by constrained internal variation, suggesting a structured and organised system with limited randomness.

•Language-like systems fail all the SSC criteria. The drift in these systems is present but non-localised, so changes are spread throughout rather than being confined. Their behaviour is noisy and unconstrained, indicating a lack of structure and a high degree of unpredictability.

•Random systems also fail all SSC criteria. Drift may be present or absent, and there is no underlying structure to their behaviour. These systems are essentially chaotic, with no discernible patterns.

•Cipher-like systems have mixed results, sometimes passing and sometimes failing the SSC criteria. Drift is present and non-localised, and their behaviour is mechanical but unstable. This means that while there may be some underlying rules, the system does not consistently maintain order.

•Rigid templatic systems pass the first two SSC criteria, but the third is not applicable. Drift is absent, and their behaviour is deterministic with low entropy. These systems are highly predictable and structured, with little to no randomness.

In summary, the systems range from highly structured and predictable (rigid templatic, Voynich-like) to completely unstructured and unpredictable (random, language-like), with cipher-like systems sitting somewhere in between due to their instability.

This classification replaces the earlier single-axis model.

K.5 Worked Example — Drift-Present System

This example demonstrates the full Sigilith pipeline, including SSC-3'.

Dataset (S_0)

Ten sequences:

1. A B C D
2. A B C D
3. A B C D
4. A B C D
5. A B C D
6. A B C E
7. A B C E
8. A B C E
9. A B C D
10. A B C E

Variation events occur only in the final position (D ↔ E).

Total positions: 40

Variation events: 4

\[

D_p = 10\% \ge 5\%

\]

The system is therefore drift-present.

Segmentation and BPS Transforms

- No valid splits (sub-units fail recurrence threshold).
- No valid merges (pair frequencies below threshold).
- Directional inversion allowed but not used.

S_0 remains the canonical dataset.

Role Classification

- Class A: A
- Class C: B, C
- Class B: D/E

Metric Extraction

Boundary adjacency (SSC-1'):

A→B (boundary-to-boundary) = 0 → PASS

Length distribution (SSC-2):

All sequences length = 4 → PASS

Drift distribution (SSC-3'):

- D(A) = 0
- D(B) = 40%
- D(C) = 0

Variation is entirely in Class B.

SSC-3' Evaluation

Since $D_p \geq 5\%$, localisation is evaluated:

- Drift ratio: FAIL
- Boundary stability: FAIL
- Internal dominance: FAIL

SSC-3' = FAIL (drift-present, non-localised)

Final Classification

The system exhibits:

- stable boundary behaviour (SSC-1' = PASS)
- narrow length distribution (SSC-2 = PASS)
- drift-present but non-localised variation (SSC-3' = FAIL)

It is therefore classified as a:

> drift-present, non-localised system
> (language-like / noisy structural behaviour)

3. Updated Classification Language

Sigilith classifies systems according to their SSC outcomes:

- Systems with SSC-1' PASS, SSC-2 PASS, and SSC-3' PASS
  exhibit localised internal drift under stable boundaries and narrow length distribution.
  These are referred to here as systems exhibiting Voynich-like behaviour.

- Systems with SSC-1' FAIL, SSC-2 FAIL, and SSC-3' FAIL
  exhibit diffuse drift, unstable boundaries, and wide length distribution.
  These are language-like systems.

- Systems with SSC-1' PASS and SSC-2 PASS but SSC-3' N/A
  exhibit rigid, deterministic, drift-absent behaviour.
  These are rigid templatic systems.

- Systems with SSC-1' PASS/FAIL, SSC-2 PASS/FAIL, and SSC-3' FAIL
  exhibit mechanical but non-localised drift.
  These are cipher-like systems.

- Systems failing all constraints without pattern
  are random systems.

This phrasing avoids defining categories around a single artefact and instead defines them around structural behaviour.

K.6 Summary

This appendix defines:

- the full reproducible threshold table
- the revised SSC-3' drift-localisation method
- the updated classification system

- a complete drift-present worked example

These constraints form the reproducible core of Sigilith v1.0.

K.X Threshold Justification

The numerical thresholds used in Sigilith v1.0 are intentionally conservative.

They are not tuned to any specific corpus; instead, they are calibrated to separate broad structural regimes across synthetic, natural, and adversarial control datasets.

The thresholds reflect three design principles:

1. Behavioural Separation Across Regimes

Each threshold was selected to maximise separation between:

- drift-absent systems
- drift-present, non-localised systems
- drift-present, localised systems
- random systems
- rigid templatic systems

The values (e.g., 5%, 10%, 70%) represent the smallest stable margins that consistently distinguish these regimes under repeated testing.

2. Robustness Under Variation

Thresholds were tested informally under ±10–20% perturbation.

The classification outcomes remained stable across these ranges, indicating that the method is not sensitive to small numerical shifts.

3. Representation-Invariance

Thresholds were chosen to remain stable under:

- symbol remapping
- segmentation variation
- admissible BPS transforms
- directional inversion

This ensures that the method evaluates behaviour, not encoding.

These thresholds are therefore calibrated, not arbitrary, and are designed to favour falsification over confirmation.

Appendix L — Reviewer Notes on SSC-3'

This appendix provides the methodological rationale for the revised drift-localisation constraint (SSC-3'). It is intended for reviewers, auditors, and researchers evaluating the internal logic, falsifiability, and reproducibility of the Sigilith framework.

L.1 Purpose of SSC-3'

SSC-3' was introduced to resolve a structural ambiguity present in the earlier formulation of SSC-3.

The original constraint evaluated drift localisation without distinguishing between:

- systems with no drift, and
- systems with drift that is present but not localised.

These two behaviours are structurally distinct and must not be conflated.

SSC-3' formalises this distinction by introducing a drift-presence precondition.

L.2 The Drift Presence Condition

The Drift Presence Condition D_p establishes whether drift exists at a meaningful level before localisation is evaluated.

$$
D_p = \frac{\text{variation events}}{\text{total positions}} \times 100
$$

A threshold of 5% is used to determine whether drift is present.

This threshold is conservative and was selected because:

1. It reliably separates rigid, templatic systems from systems exhibiting genuine variation.
2. It prevents noise-floor fluctuations from being misinterpreted as structural behaviour.
3. It ensures that localisation is only evaluated when drift is sufficiently frequent to be meaningful.

If $D_p < 5\%$, the system is classified as drift-absent, and SSC-3' is marked Not Applicable.

L.3 Why Drift-Absent Systems Require Special Handling

A system with no drift is not equivalent to a system with diffuse drift.

Drift-absent systems exhibit:

- deterministic behaviour
- rigid positional roles
- low entropy
- stable adjacency networks

These systems form a distinct structural class (“rigid templatic systems”) and must not be forced into the same evaluative pathway as systems with active variation.

SSC-3' ensures that drift-absent systems are recognised as such, rather than being incorrectly classified as failing localisation.

L.4 Localisation as a Behavioural Signature

When drift is present, SSC-3' evaluates whether variation is:

- boundary-stable
- internally concentrated

- structurally asymmetric

These behaviours are characteristic of systems with constrained internal dynamics.

The localisation thresholds (drift ratio, boundary stability, internal dominance) were selected to:

- distinguish structured internal variation from noise
- remain stable under admissible BPS transforms
- avoid overfitting to any specific corpus
- preserve representation-invariance

SSC-3' therefore acts as a behavioural discriminator rather than a statistical classifier.

L.5 Avoiding Overinterpretation

SSC-3' does not claim:

- semantic meaning
- linguistic structure
- cryptographic intent
- cultural or historical inference

It evaluates only behavioural distribution of variation under controlled segmentation and transformation conditions.

This constraint is designed to be falsifiable, conservative, and independent of interpretive assumptions.

L.6 Reviewer-Facing Summary

SSC-3' was introduced to address a methodological gap in the original SSC-3 formulation.

It ensures that:

- drift-absent systems are not misclassified
- drift-present systems are evaluated meaningfully
- localisation is only tested when variation is structurally significant
- classification outcomes reflect genuine behavioural differences
- the method remains falsifiable and representation-invariant

SSC-3' strengthens the internal logic of Sigilith and improves its robustness under peer review, adversarial testing, and independent replication.

Back Matter

Acknowledgements

The development of Sigilith reflects a long lineage of structural disciplines, analytical traditions, and methodological safeguards.

This work acknowledges:

- the researchers who advanced representation-invariant analysis
- the scholars who formalised behavioural modelling
- the practitioners who demonstrated the necessity of falsifiability
- the architects of comparative structural method
- the communities that preserved symbolic systems across time

Their contributions form the intellectual terrain upon which Sigilith stands.

This manuscript is indebted to their commitment to rigour, restraint, and structural clarity.

Edition Notes

Edition 1.0 — Foundational Release

This edition establishes the full theoretical architecture of Sigilith, including:

- CDMQSRT framework
- Behaviour-Preserving Segmentation (BPS)
- Structural Signature Suite (SSC)
- Control Dataset Protocols

- Classification Criteria
- Structural Closure

It also includes the complete appendix suite, providing formal proofs, computational notes, and comparative models.

Revision Policy

Future editions may refine:

- transform-stability proofs
- drift-vector computation models
- domain-boundary interaction frameworks
- adversarial system construction protocols

No edition will introduce interpretive content or semantic claims.

Licensing Footers

Sigilith is an original structural discipline authored and architected by Ky Nash.

All structural definitions, frameworks, modules, and analytical instruments—including CDMQSRT, BPS, SSC, and the comparative engine—are protected intellectual property.

Rights Reserved

- No component may be reproduced without attribution.
- No derivative frameworks may be created without explicit permission.
- No commercial use is permitted without licensing.

Permitted Use

- Academic citation
- Non-commercial research
- Structural comparison
- Methodological critique

Sigilith is a protected symbolic-analysis architecture.

All rights reserved.

Bibliographic Notes

Sigilith is a meaning-agnostic structural discipline.

Its foundations draw from:

- representation-invariant modelling
- adjacency-based structural analysis
- drift and pressure theory
- domain-boundary architecture
- comparative symbolic systems
- falsifiability-driven methodology

These traditions inform Sigilith's commitment to:

- behaviour over interpretation
- structure over narrative

- invariance over assumption
- discipline over speculation

No external semantic frameworks are used or referenced.

Index Model (Structural)

This manuscript does not include a semantic index.

Instead, it provides a structural index model, listing terms by behavioural category.

Structural Units

- adjacency
- boundary
- domain
- drift
- threshold
- anchor

Analytical Instruments

- BPS
- SSC-1'
- SSC-2
- SSC-3
- comparative engine

Dynamic Behaviours

- pressure
- constraint
- flow
- migration
- collapse

Architectural Constructs

- domain rigidity
- boundary permeability
- threshold volatility
- stability distribution

This index model preserves meaning-agnostic integrity.

Concluding Statement

Sigilith is a structural discipline built on restraint, falsifiability, and representation-invariance.

It does not interpret.

It does not translate.

It does not speculate.

It observes.

It models.

It classifies.

It closes.

This manuscript establishes the full architecture of the method—its foundations, instruments, safeguards, and limits.

It provides the analytical tools required to model symbolic systems without meaning, without assumption, and without interpretive drift.

Sigilith ends where structure ends.

Beyond that boundary lies meaning, culture, and narrative—domains reserved for other disciplines.

This work remains within its own domain: the architecture of behaviour.