# Project 2

Sigurd Riseth
*Department of Physics*
*University of Oslo*
Oslo, Norway
sigurri@uio.no

***Abstract*—abstract.**

***Index Terms*—classification, regression, neural networks, runge's function, MNIST**

## I. Introduction

Warren McCulloch and Walter Pitts (1943) should probably be mentioned. Breakthroughs like Rosenblatt (1958), Minsky & Papert (1969) with the XOR problem and the first *AI-winter*, Rumelhart, Hinton & Williams (1986) with backpropagation. This all made way for later deep learning with CNN, GANs, Transformers, and much more.

The remainder of this report is structured as follows. Section II presents the ... Section III describes the data, the preprocessing, the code and how it was verified. Section IV presents and discusses the results in the order ..., and section V summarizes our findings and outlines future work. Appendix A declares our use of large language models. The code and results behind every figure and table, are available in our publicly hosted repository [1].

## II. Method

This section presents the models, linear regression, logistic regression, and neural networks, and finally the evaluation methods used. We assume the reader has familiarity with basic linear algebra and statistics.

### A. Linear regression

### B. Logistic regression

Logistic regression is a natural choice as a baseline. It is a simple model in which everything can be computed, its cost function is convex, and it is exactly a neural network with no hidden layers [2].

### C. Neural networks

Linear and logistic regression share a common limitation: both act on a fixed design matrix $\boldsymbol{X}$, so the model can only be as expressive as the features we choose to put into it. A feed-forward neural network removes this limitation by inserting one or more *hidden layers* between the input and the output, each applying a linear map followed by a non-linear activation. The final layer is then nothing more than a linear or logistic regression, but it acts on features that are *learned* from the data rather than given in advance [2].

*1) The artificial neuron:* An artificial neuron computes a linear predictor, as in logistic regression, followed by an activation function. We number layers as $l = 0, 1, \ldots, L$, with $l = 0$ the input and $l = L$ the output, and $M_l$ the number of nodes in layer $L$. For a single neuron $j$ in layer $l$, the activation is

$$z_j^l = \sum_{i=1}^{M_{l-1}} w_{ij}^l a_i^{l-1} + b_j^l, \tag{1}$$

where $w_{ij}^l$ is the weight connecting node $i$ of layer $l-1$ to node $j$ of layer $l$, and $b_j^l$ is the bias of node $j$ in layer $l$. We can then obtain the output by applying the activation function [2],

$$a_j^l = f(z_j^l). \tag{2}$$

This whole process is depicted in fig. 1.





Fig. 1. The activation and output of a single neuron $j$ in layer $l$, as shown in eqs. (1) and (2).

*2) Forward pass:* We can write the activation and output of all neurons the layer $l$ in matrix-form, where eqs. (1) and (2) become

$$\boldsymbol{z}^l = (\boldsymbol{W}^l)^\top \boldsymbol{a}^{l-1} + \boldsymbol{b}^l, \qquad \boldsymbol{a}^l = \boldsymbol{f}(\boldsymbol{z}^l), \tag{3}$$

with $\boldsymbol{f}$ applied element-wise. Evaluating eq. (3) sequentially for all $l$-values is the feed-forward pass and returns the network output $\tilde{\boldsymbol{y}} = \boldsymbol{a}^L$ [2].

We can collect the weights and biases into a single parameter vector $\boldsymbol{\Theta} = \{\boldsymbol{w}^l, \boldsymbol{b}^l\}_{l=1}^L$, and solve the optimization problem

$$\hat{\boldsymbol{\Theta}} = \arg\min_{\boldsymbol{\Theta}} C(\boldsymbol{\Theta}), \quad C(\boldsymbol{\Theta}) = \frac{1}{n}\sum_{i=1}^{n} L(y_i, \tilde{y}_i) + \lambda\Omega(\boldsymbol{\Theta}), \tag{4}$$

where $L$ is the cost function and $\Omega$ is the regularization term [2].





Fig. 2. Illustration of a fully connected feed-forward neural network. Adapted from Love [3].

*3) Activation functions:* The activation function must be non-linear and differentiable almost everywhere. If it were linear, the composition of multiple layers would collapse into a single affine transformation, and the network would be no more expressive than a single layer [2]. Our study will revolve around the following three activation functions:

*a) Sigmoid:* The logistic or sigmoid function is given by

$$\sigma(z) = \frac{1}{1+e^{-z}}, \qquad \sigma'(z) = \sigma(z)(1-\sigma(z)),$$

and was the standard choice for decades. Its main drawback is that it saturates for large $|z|$, which leads to vanishing gradients and slow training [2].

*b) ReLU:* The rectified linear unit (ReLU),

$$\mathrm{ReLU}(z) = \max(0, z), \quad \mathrm{ReLU}'(z) = \begin{cases} 1, & \text{if } z > 0, \\ 0, & \text{if } z \leq 0, \end{cases}$$

is faster to compute, does not saturate for $z > 0$, and is a sound default choice for hidden layers. Its main drawback is that it can lead to dead neurons, which never activate and thus never learn [2].

The leaky ReLU (LReLU) repairs this issue by allowing a small gradient for negative values, so the gradient never completely vanishes. It is defined as

$$\mathrm{LReLU}(z) = \begin{cases} z, & \text{if } z > 0, \\ \alpha z, & \text{if } z \leq 0, \end{cases} \qquad \alpha \approx 0.01,$$

and its derivative is

$$\mathrm{LReLU}'(z) = \begin{cases} 1, & \text{if } z > 0, \\ \alpha, & \text{if } z \leq 0. \end{cases}$$

*4) Backpropagation:*

*5) Choice of output layer and loss function:*

*6) Weight initialization:*

*7) Regularization:*

### D. Evaluation

## III. Implementation

We implemented all methods ourselves in Python using NumPy [4], with the full source code, tests, and experiment scripts available in the project repository [1]. Below, we cover the data, preprocessing, code structure, and how we verified the implementation.

### A. Data and preprocessing

For the regression task we use Runge's function [5].

For the classification task we use the classic MNIST dataset [6], a collection of 70 000 handwritten digits and their corresponding labels (i.e., 0–9).

### B. Code structure

We reuse the structure and the gradient machinery of the previous project [7]. The code is structured in a package `fys_stk4155_p2`, containing the directories `nn`, `optimization`; which respectively hold the code for the models and gradient descent.

Thin constructor of the FFNN for logistic regression, which returns a single layer with softmax activation and cross entropy loss. This allows us to use this as a baseline model when evaluating the later neural networks.

### C. Verification

## IV. Results and Discussion

## V. Conclusion

TODO: conclusion.

## References


[1] S. Riseth, *FYS-STK4155 Project 2*, version v0.1.0, GitHub, Nov. 2026. [Online]. Available: https://github.com/sigurdriseth/FYS-STK4155-P2

[2] M. Hjorth-Jensen, *Machine Learning and the Physical Sciences: From Discriminative Methods to Generative Methods and Reinforcement Learning*. Springer, Oct. 9, 2026. [Online]. Available: https://github.com/EducationalMaterialUiO / MachineLearningUiO / blob / main/doc/BookML/Lecturebook.pdf

[3] F. Love, *NNTikZ: TikZ Diagrams for Deep Learning and Neural Networks*, 2024. Accessed: Oct. 15, 2026. [Online]. Available: https://github.com/fraserlove/nntikz

[4] C. R. Harris et al., "Array programming with NumPy," *Nature*, **585**, no. 7825, pp. 357–362, Sep. 17, 2020, ISSN: 0028-0836, 1476-4687. DOI: 10.1038/s41586-020-2649-2 Accessed: Aug. 23, 2026. [Online]. Available: https://www.nature.com/articles/s41586-020-2649-2

[5] C. Runge, "Über empirische Funktionen und die Interpolation zwischen äquidistanten Ordinaten," *Zeitschrift für Mathematik und Physik*, **46**, pp. 224–243, 1901.

[6] Y. LeCun, C. Cortes, and C. J. Burges, "MNIST handwritten digit database," *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, **2**, 2010.

[7] S. Riseth, *FYS-STK4155 Project 1*, version v0.1.0, GitHub, Oct. 2026. [Online]. Available: https://github.com/sigurdriseth/FYS-STK4155-P1

# APPENDIX

## A. Use of AI/LLM tools

Large language models were used throughout this project, following the course guidelines[1], which also define the contribution levels below. All code was tested, all derivations were checked, and every claim in the report was read, understood and verified by the author.

*1) Tools used:*

- TODO: tools, models, and dates.

TODO: summary of how each tool was used.

*2) Text writing and editing:* Table I gives the contribution level for each part of the report.

TABLE I
LLM CONTRIBUTION TO TEXT WRITING AND EDITING (LEVELS 0–3).

| Section | Level | Notes |
|---|---|---|
| Abstract | TODO | |
| Introduction | TODO | |
| Methods | TODO | |
| Implementation | TODO | |
| Results and discussion | TODO | |
| Conclusion | TODO | |
| Appendices | TODO | |

*3) Code generation and assistance:* Table II gives the level for each source file (levels 0–4). Functions with level 2 or above carry an `LLM-assisted` tag in their docstring.

*4) Declared and undeclared use:* TODO: one example of a use that must be declared, and one example of a use that need not be declared (e.g. using an LLM as a tutor and then writing about it in your own words).

## B. Additional results

TODO: additional results.

[1] https://github.com/EducationalMaterialUiO/MachineLearningUiO/blob/main/LLM_Usage_Declaration_Guidelines.md

TABLE II
LLM CONTRIBUTION TO THE CODE (LEVELS 0–4).

| File | Level | Description |
|---|---|---|
| TODO | TODO | |