

Production Database Seeding Guide

Investigation Summary

Local Database Status

- **Database Host:** `db-e62f243fc.db003.hosteddb.reai.io:5432`
- **Tournament Count:** 30 tournaments seeded
- **API Logic:** Working correctly (returns all 30 tournaments)
- **Sample Data:** Miami Open, Austin City Limits, San Diego Coastal Cup, etc.

Issue Analysis

The local database has data, but the production Vercel deployment shows 0 tournaments. This indicates:

- Vercel's `DATABASE_URL` environment variable points to a **different database**
 - OR the production database hasn't been seeded yet
-

Solution: Seed Production Database via Vercel

Method 1: Using Vercel CLI (Recommended)

1. **Install Vercel CLI** (if not already installed):

```
bash
npm i -g vercel
```

2. **Login to Vercel:**

```
bash
vercel login
```

3. **Pull environment variables:**

```
bash
cd /home/ubuntu/mindful-champion
vercel env pull .env.production
```

4. **Run seed script against production database:**

```
bash
# Use production DATABASE_URL
export $(cat .env.production | xargs)
npx tsx scripts/seed-tournaments.ts
```

5. **Verify seeding:**

```
bash
npx tsx scripts/check-db-connection.ts
```

Method 2: Via Vercel Dashboard (Alternative)

1. **Go to Vercel Dashboard** → Your Project → Settings → Environment Variables

2. Copy the production DATABASE_URL

3. Run seed script locally with production URL:

```
bash
cd /home/ubuntu/mindful-champion
DATABASE_URL="<paste-production-url-here>" npx tsx scripts/seed-tournaments.ts
```

Method 3: Deploy Seed Script as API Route

Create an admin API endpoint to seed the database:

```
// app/api/admin/seed-tournaments/route.ts
import { NextResponse } from 'next/server';
import { PrismaClient, SkillLevel, TournamentStatus, TournamentFormat } from '@prisma/client';

const prisma = new PrismaClient();

export async function POST(request: Request) {
  try {
    // Add authentication check here
    const authHeader = request.headers.get('authorization');
    if (authHeader !== `Bearer ${process.env.ADMIN_SECRET}`) {
      return NextResponse.json({ error: 'Unauthorized' }, { status: 401 });
    }

    // Clear existing tournaments
    await prisma.tournament.deleteMany({});

    // Seed 30 tournaments (use the same data from scripts/seed-tournaments.ts)
    const tournamentsToCreate = [
      // ... tournament data ...
    ];

    for (const tournament of tournamentsToCreate) {
      await prisma.tournament.create({ data: tournament });
    }

    const count = await prisma.tournament.count();

    return NextResponse.json({
      success: true,
      message: `Successfully seeded ${count} tournaments`
    });
  } catch (error) {
    console.error('Seeding error:', error);
    return NextResponse.json({ error: 'Seeding failed' }, { status: 500 });
  }
}
```

Usage:

```
# After deploying, call the endpoint
curl -X POST https://your-app.vercel.app/api/admin/seed-tournaments \
-H "Authorization: Bearer YOUR_ADMIN_SECRET"
```

Verification Steps

After seeding, verify the data is accessible:

1. **Check database directly:**

```
bash
npx tsx scripts/check-db-connection.ts
```

2. **Test API endpoint:**

```
bash
curl https://your-app.vercel.app/api/tournaments | jq '.tournaments | length'
```

3. **Check tournaments page:**

- Visit: <https://your-app.vercel.app/tournaments>
- Should display 30 tournaments with filters and sorting

Database Connection Verification

To confirm which database Vercel is using:

1. **Add a diagnostic API endpoint:**

```
``typescript
// app/api/admin/db-info/route.ts
import { NextResponse } from 'next/server';
import { prisma } from '@lib/db';

export async function GET() {
  const count = await prisma.tournament.count();
  const dbUrl = process.env.DATABASE_URL || '';
  const dbHost = dbUrl.split('@')[1]?.split('/')[0] || 'Unknown';
```

```
  return NextResponse.json({
    host: dbHost,
    tournamentCount: count,
    // Don't expose full URL in production
  });
}
```

```
``
```

1. **Call it to see the database host and count:**

```
bash
curl https://your-app.vercel.app/api/admin/db-info
```

Common Issues

Issue: “Connection refused” or “Too many connections”

Solution: The database connection pool might be exhausted. Restart Vercel deployment:

```
vercel --prod
```

Issue: Seeding takes too long or times out

Solution: Reduce batch size or use `createMany` :

```
await prisma.tournament.createMany({
  data: tournamentsToCreate,
  skipDuplicates: true,
});
```

Issue: Permission denied on production database

Solution: Verify the `DATABASE_URL` has write permissions. Check with your database provider.

Next Steps

1. Choose one of the seeding methods above
2. Run the seed script against production
3. Verify tournaments appear on the live site
4. If issues persist, check Vercel logs: `vercel logs --prod`

Files Referenced

- `/scripts/seed-tournaments.ts` - Seed script with 30 tournaments
- `/scripts/check-db-connection.ts` - Database verification script
- `/app/api/tournaments/route.ts` - Tournaments API endpoint
- `/lib/db.ts` - Prisma client configuration