

GraphQL & Apollo

JOANNA ZAKRZEWSKA

GraphQL?

QUERY LANGUAGE

FOR DYNAMIC API

BY FACEBOOK

request

```
query {  
  user(id: 1) {  
    firstName  
    lastName  
    posts {  
      id  
      votes  
    }  
  }  
}
```

response

```
{  
  user: {  
    firstName: "Tom",  
    lastName: "Smith"  
    posts: [{  
      id: 1,  
      votes: 2  
    }]  
  }  
}
```

request

```
mutation {  
  upvotePost(id: 1) {  
    votes  
    user {  
      firstName  
      lastName  
    }  
  }  
}
```

response

```
{  
  upvotePost: {  
    votes: 3,  
    user: {  
      firstName: "Tom",  
      lastName: "Smith"  
    }  
  }  
}
```



all you need

SINGLE ENDPOINT / SINGLE CALL

and just that

in a generic way

👍 simple & declarative

👍 design first

👍 technology agnostic

👍 typed

BACKEND LANGUAGE

TRANSFER PROTOCOL

👍 great for proxy



WRAPS BAD APIS

AGGREGATES APIS

COVERS API CHANGES

👍 auto-documenting

👍 less meetings

👎 HTTP caching

👎 not fully mature yet

👍 incremental adoption



Repositories 100

Apollo?

GRAPHQL TOOLS

ALL OF THEM

BY METEOR DEVS

schema

[Silhoue/graphql-demo](#)



```
const UserType = new GraphQLObjectType({  
  name: "User",  
  fields: {  
    id: { type: GraphQLInt },  
    firstName: { type: GraphQLString },  
    posts: {  
      type: new GraphQLList(PostType),  
      resolve: (user, args, context) => getPosts(...)  
    }  
  }  
})
```

Backend tools

Facebook stack

- [graphql](#) + [express-graphql](#)
- [dataloader](#)

Apollo stack

- [graphql](#) + [apollo-server-{express}](#)
- [graphql-tools](#)

client

[apollo-client/README.md](#)

```
const userQuery = gql`{  
  User(id: 1) {  
    firstName  
  }  
}`
```

```
const UserComponent = (props) => {  
  const { User, loading, error } = props.data  
  if (loading) { return <span>loading...</span> }  
  if (error) { return <span>error!</span> }  
  return <span>{User.firstname}</span>  
}
```

```
export default graphql(userQuery)(UserComponent)
```

Frontend tools

Facebook stack


- [relay](#)
- [graphql-relay-js](#) (backend)

Apollo stack

- [apollo-client](#)^{*} + e.g. [react-apollo](#)
- [apollo-link](#)

^{*}apollo-client-preset + graphql-tag + graphql

What about Redux?

 apollo-link-state 0.3.1

 Client Schema Extensions ⌚

[React State Management In a GraphQL Era](#)

by Kristijan Ristovski

[Apollo Client 2.0: More than just GraphQL](#)

by Peggy Rayzis

More tools

[GraphQL](#) - clientless

[Graphcool](#) - serverless

[Launchpad](#) - playground

[Apollo Client Developer Tools](#) - Chrome extension

More resources

facebook.github.io/graphql - spec

graphql.org (by Facebook)

graphql.com & apollographql.com (by Apollo)

github.com/chentsulin/awesome-graphql - even more links

graphql-europe.org (Berlin, June 15th, 2018)