Lab 07

Sharing Applications Between Groups

WSO2 API Manager 4.7.0 · Practical exercise

Before You Begin

URLs in this guide use placeholders. Replace them with the values of the API Manager you are using:

- **`<APIM_HOST>`** – host name or IP address of the API Manager server (localhost when API Manager runs on your own laptop).
- **`<HTTPS_PORT>`** – API Manager HTTPS port: 9443 plus any port offset (Publisher, Developer Portal, Admin Portal, Management Console, token endpoint).
- **`<GW_HTTPS_PORT>` / `<GW_HTTP_PORT>`** – API Gateway ports: 8243 (HTTPS) and 8280 (HTTP) plus any port offset.
- **`<APIM_HOME>`** – the folder where API Manager is extracted.

The servers use a self-signed certificate by default, so the browser shows a security warning the first time: choose Advanced and continue.

Training Objective

Learn how to share applications in the Developer Portal between groups of developers. Users who belong to the same group (by default, the same organization) can see and use each other's shared applications and subscriptions. Only the application owner can edit or delete a shared application.

Business Scenario

PizzaShack needs developer squads to share the applications they manage to avoid duplicate applications and to encourage the reuse of applications and APIs.

High-Level Steps

- Enable application sharing (once per API Manager)
- Register two users in the same organization
- Share an application and use it as the second user

Part 1 – Enable Application Sharing

On a shared training server, the trainer does this once for everyone. It needs a restart.

1. Stop API Manager.
2. Add the following to `<APIM_HOME>/repository/conf/deployment.toml`. If the file already has an uncommented `[apim.devportal]` section, add only the two lines under it (a TOML section can appear only once):

```
[apim.devportal]
enable_application_sharing = true
application_sharing_type = "default"
```

CC BY 4.0

3. Start API Manager.

Part 2 – Register Two Users in the Same Organization

With the default setting, the **Organization** entered at sign-up is the group ID.

4. Open the Developer Portal, click **Sign-in** and then **Create Account**:

```
https://<APIM_HOST>:<HTTPS_PORT>/devportal
```

Example:

```
https://localhost:9443/devportal
```

5. Enter the user name **user1**, click **Proceed to Self Register**, fill in the form with **Organization = org1** and click **Register**.
6. Repeat for **user2**, also with **Organization = org1**. (On a shared server, use your own names and a group such as `org-<initials>`.)

Part 3 – Share an Application

7. Sign in as **user1**, go to **Applications** and click **Add New Application**. Enter these values and click **Save**:

Field	Value
Application Name	App_A
Shared Quota for Application Tokens	Unlimited
Application Groups	type org1 and press Enter (you can enter more than one group)

Part 4 – Use the Shared Application

8. Sign out and sign in as **user2**. Go to **Applications**: **App_A**, created by user1, is listed.
9. As user2, subscribe **App_A** to the PizzaShack API (open the application, **Subscriptions > Subscribe**).
10. Sign in again as **user1** and open **App_A > Subscriptions**: the subscription that user2 added is shown.
11. user2 can use App_A but cannot edit or delete it: only the owner (user1) can. If the owner leaves, an admin can transfer the application to another user.

    Note: users who signed up without an organization, such as the **subscriber** user from the Users and Roles lab, do not see the shared application.

Expected Outcome

Application sharing is enabled. user1 and user2 belong to org1; App_A, created by user1, is visible to user2, user2's subscription is visible to user1, and only user1 can edit or delete App_A.

CC BY 4.0