Product Configurations

CC by 4.0

WSO2

Objectives

At the end of this module, attendees will:

- Learn the configuration model
- Learn how basic configurations are done

Configuration Model

- Configurations are handled by the deployment.toml file in the <APIM_HOME>/*repository/conf/* directory.
- All configurations are centralized.
- Configuration files

  deployment.toml - Includes the configuration properties

  log4j2.properties - Used for configuring logging options.
- Also the files that are not templated are allowed for direct edits.

Understanding the New Configuration Model

Configuration File: deployment.toml

```
[server]
pattern="value"
enable_port_forward=true

[key_mgr_node]
endpoints="value"

[gateway]
gateway_environments=["dev","test"]

[[database]]
pool_options.maxActiv=5
```

Configuration Catalog

Configuration Sample : Configure MySQL Database

```
[database.shared_db]
type = "mysql"
url = "jdbc:mysql://localhost:3306/shared_db"
username = "regadmin"
password = "regadmin"
pool_options.maxActive = 100
pool_options.maxWait = 10 000
pool_options.validationInterval = 10 000

[database.apim_db]
type = "mysql"
url = "jdbc:mysql://localhost:3306/apim_db"
username = "apimadmin"
password = "apimadmin"
pool_options.maxActive = 50
pool_options.maxWait = 30 000
```