

KTA EPOXY

FEATURES :

- ✓ STAIN-FREE, WATERPROOF FINISH
- ✓ HIGH CHEMICAL AND ABRASION RESISTANCE
- ✓ NON-POROUS & EASY TO CLEAN
- ✓ SUITABLE FOR JOINT WIDTHS UP TO 10MM
- ✓ PERFECT FOR WET AND HIGH-TRAFFIC AREAS



KTA EPOXY IS A PREMIUM TWO-COMPONENT GROUT DESIGNED FOR AREA THAT DEMAND SUPERIOR STAIN RESISTANCE, WATERPROOFING, AND CHEMICAL PROTECTION, IDEAL FOR USE IN BATHROOMS, KITCHENS, POOLS, HOSPITALS, AND INDUSTRIAL FLOORS, IT ENSURES HYGIENIC, LONG-LASTING TILE JOINTS IN BOTH RESIDENTAL AND COMMERCIAL ENVIORNMENTS.

KTA GROUT

FEATURES :

- ✓ CEMENT-BASED WITH ADDED POLYMERS
- ✓ SMOOTH, SHRINKAGE-FREE FINISH
- ✓ AVAILABLE IN MULTIPLE COLOR SHADES
- ✓ EASY TO APPLY AND CLEAN
- ✓ RESISTANT TO HAIRLINE CRACKS AND COLORATION



KTA GROUT IS A HIGH PERFORMANCE, SINGLE-COMPONENT GROUT DESIGNED TO ENHANCE THE AESTHETICS AND LONGEVITY OF TILED SURFACES. FORMULATED WITH ADVANCED POLYMERS, ITS OFFERS SUPERIOR ADHESION, CRACK RESISTANCE AND COLOR DURABILITY. SUITABLE FOR JOINTS UP TO 5MM, IT DELIVERS A SMOOTH FINISH THAT COMPLEMENTS ANY TILE DESIGN.

DIRECTIONS

**Surface Preparation**

1. Before grouting, remove excess adhesive and debris from the joints.

2. Clean the tile surface with a damp sponge to remove dirt, dust, adhesive, and stains.

**How to apply**

5. Fill the tile joints with KTA Epoxy Grout using a KTA Grout Spreader.

7. Hold the KTA Grout Spreader perpendicular to the tiled surface. Remove excess grout by dragging the float at a 45° angle to the joints. Ensure all joints are completely filled.

**How to mix**

3. Pour the full contents of Part A and Part B into a clean pail.

4. Mix Part A and Part B thoroughly for 1 minute using a margin trowel.

6. Add the contents of Part C (Filler Powder) and mix to achieve a smooth, consistent paste.

**How to clean**

8. Wipe the tile surface with a clean, wet towel to remove residual. Repeat as needed. Wipe the towel frequently until the tile surface feels clean and smooth.

10. After 2-3 hours, the joints may begin to stiffen. If rough or uneven, gently rub with a sponge or gloved finger soaked in a shampoo solution to smoothen the surface.

11. For final cleaning, use a solution of water and shampoo after approximately 18 hours of grouting.

**TEMPERATURE**

15°C - 35°C

**STORAGE**

24 HR

12°C

MANUFACTURED AND MARKETED BY  
SOBHRAJ DEVELOPEMENTS PVT. LTD.  
(An ISO 9001:2015 Certified Company)  
Mangliwas - Nasirabad Road  
Mangliwas, Ajmer - 305203  
Rajasthan, India

www.ktasolutions.in

@kta.solutions @KTASolutions KTA Solutions

IN CASE OF CONSUMER COMPLAINTS,  
CONTACT : SOBHRAJ DEVELOPEMENTS PVT. LTD.  
Mangliwas - Nasirabad Road  
Mangliwas, Ajmer - 305203

☎ : +91 94140-09900 ✉ : info@ktasolutions.in

The KTA logo is a registered trademark of Sobhraj Developments



KTA TILE GROUT AND  
KTA TILE EPOXY  
SHADECARD



KTA TILE GROUT

|                   |  |
|-------------------|--|
| WHITE 010         |  |
| IVORY 011         |  |
| SILK 012          |  |
| BEIGE 014         |  |
| LEMON YELLOW 020  |  |
| CORAL PINK 032    |  |
| BRICK RED 039     |  |
| SKY BLUE 041      |  |
| MIDNIGHT BLUE 049 |  |
| SMOKE GREY 074    |  |
| CHARCOAL GREY 079 |  |
| COCOA BROWN 082   |  |
| WALNUT 087        |  |
| MIDNIGHT GREY 090 |  |
| GALAXY BLACK 094  |  |
| JET BLACK 099     |  |

KTA EPOXY GROUT

|                   |  |
|-------------------|--|
| WHITE 010         |  |
| SILK 012          |  |
| BEIGE 014         |  |
| LEMON YELLOW 020  |  |
| GOLDEN YELLOW 025 |  |
| PINK GOLD 031     |  |
| ITALIAN RED 036   |  |
| SKY BLUE 041      |  |
| ROYAL BLUE 046    |  |
| MIDNIGHT BLUE 049 |  |
| OLVIE GREEN 051   |  |
| GREEN SMOKE 059   |  |
| SMOKE GREY 072    |  |
| STEEL GREY 076    |  |
| CHARCOAL GREY 079 |  |
| COPPER BROWN 080  |  |

KTA EPOXY GROUT

|                   |  |
|-------------------|--|
| WALNUT 087        |  |
| MOCHA BROWN 089   |  |
| MIDNIGHT GREY 090 |  |
| JET BLACK 099     |  |