ORDER FOR PRINTER

General information

Data utworzenia karty	21 September 2026
Internal reference	KSS Rolling Papers Jesse James Set with tips

Section I: Core parameters and materials

Product	Bletka
Other requirements	with filter
Rozmiar/typ filtra	King Size (108x25)
Filter colour	Eco
Box paper colour	Unbleached
Printing process	Offset Printing
Customer / order reference	Hempowo
Box quantity	5800
Cover quantity	5550
Display quantity	215

Section II: Print specification

Cover - substrate grammage	230
Cover - print specification	Double-sided (C1 + C2)
Cover - colour separation	CMYK
Cover - printing process	4/4
Okładka - Uszlachetniania druku	gloss varnish
Okładka - Uszlachetniania druku awers	Yes
Okładka - Uszlachetniania druku rewers	No
Cover - die-cutting tool	578
Roll box - print specification	No print
Roll box - colour separation	CMYK
Roll box - printing process	-
Box rolls - Uszlachetniania druku	None
Box rolls - Uszlachetniania druku awers	None
Box rolls - Uszlachetniania druku rewers	None

Roll box - die-cutting tool	594
Rolling paper booklet - substrate grammage	170
Rolling paper booklet - print specification	Front, double-sided (C1 + C2)
Rolling paper booklet - colour separation	CMYK
Rolling paper booklet - printing process	4/4
Bletka - Uszlachetniania druku	gloss varnish
Bletka - Uszlachetniania druku awers	Yes
Bletka - Uszlachetniania druku rewers	Yes
Rolling paper booklet - die-cutting tool	584
Filter sheet - substrate grammage	-
Filter sheet - print specification	No print
Filter sheet - colour separation	CMYK
Filter sheet - printing process	-
Arkusz filtra - Uszlachetniania druku	None
Arkusz filtra - Uszlachetniania druku awers	None
Arkusz filtra - Uszlachetniania druku rewers	None
Filter sheet - die-cutting tool	594
Number of perforations	None
Additional perforation	Yes
Number of leaves	-
Units per display	-
Units per master case	-
Print on master case	No

Section III: Display packaging

Display type	Offset White
Display - substrate grammage	250
Display - print specification	4/0
Display - colour separation	CMYK
Uszlachetniania druku (Display)	gloss varnish
Display - die-cutting tool	577
Uszlachetniania druku - opcje (Display)	Yes

Section IV: Additional requirements

Order notes	Paper laminated onto sheets, varnish with spot application.

OCENA BCT	
BCT nominalne	1265.1 kg
Bezpieczne BCT	702.8 kg
Maks. warstwy	71
Ryzyko	bezpieczne
Rekomendacja	Utrzymaj 3-warstwowa, falę Fala E (micro), minimum 480 g/m².
Status	do testu
Podpisy	/ /