

Risk-averse Distributional Reinforcement Learning

A CVaR optimization approach


Silvestr Stanko¹
Supervisor: Karel Macek, Ph.D.²

¹Department of Computer Science
Czech Technical University

²DHL Information Services

Monday 11th June, 2018

Reinforcement Learning



Reinforcement Learning goals

$$\pi^* = \arg \max_{\pi} \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t R(x_t, \pi(x_t)) \right]$$

Risk-averse Reinforcement Learning: Motivation

Example


You have to deliver a package fast. Choose between:

- ① Shorter route with the risk of running into traffic
- ② Longer but safe route



Figure: AI Safety

Training



Testing





Figure: Robustness



Figure: Critical Applications

Value-at-Risk, Conditional Value-at-Risk



Reinforcement Learning with CVaR

For a given α , our goal is to find a globally optimal policy π^*



$$\pi^* = \arg \max_{\pi} CVaR_{\alpha}(Z^{\pi}(x_0))$$

CVaR Value Iteration


$C(x, \alpha)$ represents CVaR_α when following the optimal CVaR policy

CVaR Value Iteration

$$\mathbf{T}C(x, \alpha) = \max_a \left[R(x, a) + \gamma \min_{\xi} \sum_{x'} p(x'|x, a) \xi(x') C(x', \alpha \xi(x')) \right]$$



Bonus: CVaR computation via quantile representation



Linear-time Computation

Theorem

Solution to minimization problem

$$\min_{\xi \in \mathcal{U}_{CVaR}(\alpha, p(\cdot|x, a))} \sum_{x'} p(x'|x, a) \xi(x') CVaR_{\xi(x')\alpha} (Z^\pi(x'))$$

can be computed by setting





$$\xi(x') = \frac{F_{Z(x')}(F_{Z(x,a)}^{-1}(\alpha))}{\alpha}$$

The computational complexity improvement is

$$O(m^{4.5}n^2) \rightarrow O(mn)$$

where m is the number of transition states and n is the number of atoms.

CVaR Value Iteration - Experiments



CVaR Q-learning

Pseudocode

- 1 Sample a transition x, a, x', r
- 2 Create a target distribution \mathbf{d}
- 3 Update current estimates of VaR and CVaR proportionally to the target distribution

Recursive CVaR Estimation

$$V_{t+1} = V_t + \beta_t \left[1 - \frac{1}{\alpha} \mathbb{1}_{(V_t \geq r)} \right]$$
$$C_{t+1} = (1 - \beta_t) C_t + \beta_t \left[V_t + \frac{1}{\alpha} (r - V_t)^- \right]$$

VaR-based Policy Improvement

Theorem

Let π be a fixed policy, $\alpha \in (0, 1]$. By following policy π' from the following algorithm, we will improve $CVaR_\alpha(Z)$ in expectation:

$$CVaR_\alpha(Z^\pi) \leq CVaR_\alpha(Z^{\pi'})$$

VaR-based Policy Improvement

$a = \arg \max_a CVaR_\alpha(Z(x_0, a))$

$s = VaR_\alpha(Z(x_0, a))$

Take action a , observe x, r

while x is not terminal **do**


$$s = \frac{s - r}{\gamma}$$

$a = \arg \max_a \mathbb{E}[(Z(x, a) - s)^-]$

Take action a , observe x, r

end while

CVaR Q-learning - Experiments



Approximate Q-learning

Problem

Q-learning is intractable for large state spaces.

Solution

Use approximate Q-learning:

- 1 Formulate CVaR Q-learning update as a minimizing argument
- 2 Use methods of convex optimization to find the optimal point

TD update \rightarrow loss function


VaR loss

$$\mathcal{L}_{\text{VaR}} = \sum_{i=1}^N \mathbb{E}_j \left[(r + \gamma d_j - V_i(x, a))(y_j - \mathbb{1}_{(V_i(x, a) \geq r + \gamma d_j)}) \right]$$

CVaR loss


$$\mathcal{L}_{\text{CVaR}} = \sum_{i=1}^N \mathbb{E}_j \left[\left(V_i(x, a) + \frac{1}{y_i} (r + \gamma d_j - V_i(x, a))^- - C_i(x, a) \right)^2 \right]$$

$$\mathcal{L} = \mathbb{E} [\mathcal{L}_{\text{VaR}} + \mathcal{L}_{\text{CVaR}}]$$



Deep CVaR Q-learning - Experiments

- Model: Convolutional Neural Network
- Environment: Ice Lake



- 1 Video: $\alpha = 1$
- 2 Video: $\alpha = 0.3$

Summary

① Faster CVaR Value Iteration

- $O(m^{4.5}n^2) \rightarrow O(mn)$
- Formally proved for increasing, unbounded distributions.
- Experimentally verified for general distributions.

② CVaR Q-learning

- Sampling version of CVaR Value Iteration.
- Based on the distributional approach.
- Experimentally verified.

③ Distributional Policy improvement

- Proved monotonic improvement for distributional RL.
- Used as a heuristic for extracting π^* from CVaR Q-learning.

④ Deep CVaR Q-learning

- TD update \rightarrow loss function.
- Experimentally verified in a deep learning context.