CSc 360: Operating Systems (Summer 2015)

Programming Assignment 2 (P2) Multi-Thread Scheduling (MTS)

Spec Out: May 29, 2015 Design Outlined: June 4, 2015 Code Due: June 26, 2015

1 Introduction

In P1 (Realistic Shell Interpreter, RSI), you have built a shell environment to interact with the host operating system. Good job! But very soon you find that RSI is missing one of the key features in a real multi-process or multi-thread operating system: scheduling, i.e., all processes or threads created by your RSI are still scheduled by the host operating system, not yours! Interested in building a multi-thread scheduling system for yourself? In this assignment, you will learn how to use the three programming constructs provided by the POSIX pthread library:

1. threads

12

13

14

15

16

17

18

19

20

21

22

23

24

25

- 2. mutexes
- 3. condition variables (convars)

to do so. Your goal is to construct a simulator of an automated control system for the railway track shown in Figure 1 (i.e., to emulate the scheduling of multiple threads sharing a common resource in a real operating system).

As shown in Figure 1, there are two stations (for high and low priority trains) on each side of the main track. At each station, one or more trains are loaded with commodities. Each train in the simulation commences its loading process at a <u>common</u> start time 0 of the simulation program. Some trains take more time to load, some less. After a train is loaded, it patiently awaits permission to cross the main track, subject to the requirements specified in Section 2.2. Most importantly, only one train can be on the main track at any given time. After a train finishes crossing, it magically disappears. You will use threads to simulate the trains approaching the main track from two different directions, and your program will schedule between them to meet the requirements in Section 2.2.

You will use C or C++ and the Linux workstation in ECS242 or the linux.csc.uvic.ca cluster to implement and test your work.

$_{26}$ 2 Trains

Each train, which will be simulated by a thread, has the following attributes:

1. Direction:




Figure 1: The railway system under consideration.

- If the direction of a train is Westbound, it starts from the East station and travels to the West station.
- If the direction of a train is Eastbound, it starts from the West station and travels to the East station.
- 2. **Priority**: The priority of the station from which it departs.
 - 3. Loading Time: The amount of time that it takes to load it (with goods) before it is ready to depart.
- 4. Crossing Time: The amount of time that the train takes to cross the main track.
- Loading time and crossing time are measured in 10ths of a second. These durations will be simulated by having your threads, which represent trains, usleep() for the required amount of time.

36 2.1 Step 1: Reading the input file

- Your program (mts) will accept two parameters on the command line:
 - 1. The first parameter is the name of the input file containing the definitions of the trains.
- 2. The second parameter, an integer > 0, is the number of trains specified in the input file.

10 2.1.1 Input file format

30

43

47

- The input files have a simple format. Each line contains the information about a single train, such that:
 - 1. The first character specifies the **direction** of the train. It is one of the following four characters:

```
e, E, w, or W
```

- e or E specify a train headed East (East-Bound): e represents an east-bound low-priority train, and E represents an east-bound high-priority train;
- w or W specify a train headed West (West-Bound): w presents a west-bound low-priority train, and W represents a west-bound high-priority train.
- 2. A colon(:) immediately follows the direction of the train.
- 3. Immediately following is an integer that indicates the **loading time** of the train.
- 4. A comma(,) immediately follows the previous number.
- 5. Immediately following is an integer that indicates the **crossing time** of the train.
- 6. A newline (\n) ends the line.
- You may assume that the file always contains data for at least the number of trains specified in the second parameter. During our testing, the file specified on the command line will exist, and it will contain valid data.

55 2.1.2 An Example

The following file specifies three trains, two headed East and one headed West.

```
e:10,6

W:6,7

E:3,10
```

60 It implies the following list of trains:

Train No.	Priority	Direction	Loading Time	Crossing Time
0	low	East	1.0s	0.6s
1	high	West	0.6s	0.7s
2	high	East	0.3s	1.0s

Note: Observe that Train 2 is actually the first to finish the loading process.

2.2Step 2: Simulation Rules

- The rules enforced by the automated control system are:
- 1. Only <u>one</u> train is on the <u>main</u> track at any given time.
 - 2. Only loaded trains can cross the main track.
 - 3. If there are multiple loaded trains, the one with the high priority crosses.
 - 4. If two loaded trains have the same priority, then:
 - (a) If they are both traveling in the same direction, the train which finished loading first gets the clearance to cross first. If they finished loading at the same time, the one appeared first in the input file gets the clearance to cross first.
 - (b) If they are traveling in opposite directions, pick the train which will travel in the direction opposite of which the last train to cross the main track traveled. If no trains have crossed the main track yet, the Westbound train has the priority.

Step 3: Output

For the example, shown in Section 2.1.2, the correct output is: 76

```
00:00:00.3 Train 2 is ready to go East
       00:00:00.3 Train 2 is ON the main track going East
78
       00:00:00.6 Train 1 is ready to go West
       00:00:01.0 Train 0 is ready to go East
80
       00:00:01.3 Train 2 is OFF the main track after going East
81
       00:00:01.3 Train 1 is ON the main track going West
82
       00:00:02.0 Train 1 is OFF the main track after going West
83
       00:00:02.0 Train 0 is ON the main track going East
84
       00:00:02.6 Train 0 is OFF the main track after going East
85
```

You must: 86

87

88

92

93

95

101

102

104

66

67

68

70

73

1. print the arrival of each train at its departure point (after loading) using the format string, prefixed by the simulation time:

```
"Train %2d is ready to go %4s"
```

2. print the crossing of each train using the format string, prefixed by the simulation time: 90

```
"Train %2d is ON the main track going %4s"
```

3. print the arrival of each train (at its destination) using the format string, prefixed by the simulation time:

```
"Train %2d is OFF the main track after going %4s"
```

where:

- there are only two possible values for direction: "East" and "West"
- trains have identifying numbers in the range of [0, 99]. The ID number of a train is specified *implicitly* in the input file. The train specified in the first line of the input file has ID number 0.
 - trains have loading and crossing times in the range of [1, 99].

Manual Pages

Be sure to study the man pages for the various functions to be used in the assignment. For example, the man page 100 for pthread_create can be found by typing the command:

```
$ man pthread_create
```

At the end of this assignment you should be familiar with the following functions: 103

1. File access functions:

```
(a) atoi
105
          (b) fopen
106
           (c) feof
107
          (d) fgetc and fgets
108
           (e) fclose
      2. Thread creation functions:
110
           (a) pthread_create
111
          (b) pthread_exit
112
           (c) pthread_join
113
      3. Mutex manipulation functions:
114
           (a) pthread_mutex_init
115
          (b) pthread_mutex_lock
116
           (c) pthread_mutex_unlock
117
      4. Condition variable manipulation functions:
118
           (a) pthread_cond_init
119
          (b) pthread_cond_wait
120
           (c) pthread_cond_broadcast
121
          (d) pthread_cond_signal
122
       It is absolutely critical that you read the man pages, and attend the tutorials.
123
       Your best source of information, as always, is the man pages.
124
       For help with the POSIX interface (in general):
125
         http://www.opengroup.org/onlinepubs/007908799/
126
       For help with POSIX threads:
127
         http://www.opengroup.org/onlinepubs/007908799/xsh/pthread.h.html
128
       A good overview of pthread can be found at: http://www.llnl.gov/computing/tutorials/pthreads/
129
```

3 Tutorial Schedule

130

In order to help you finish this programming assignment on time successfully, the schedule of this assignment has been synchronized with both the lectures and the tutorials. There are four tutorials arranged during the course of this assignment, besides one on pthread. NOTE: Please do attend the tutorials and follow the tutorial schedule closely.

Date	Tutorial	Milestones
May 28	pthread, mutex and condition variable calls	multi-threading programming
Jun 5	P2 spec go-through, design review/hints	design and code skeleton
Jun 12	more/feedback on system design and programming	alpha code done
Jun 19	more on pthread programming and testing	beta code done
Jun 26	final testing and last-minute help	final deliverable

¹³⁵ 4 Submission: Deliverable 1 (Design Due: Jun 4, 2015)

You will write a design document which answers the following questions. It is recommended that you think through the following questions *very carefully* before answering them.

Unlike P1, no amount of debugging will help after the basic design has been coded. Therefore, it is very important to ensure that the basic design is correct. Answering the following questions haphazardly will basically ensure that Deliverable 2 does not work.

So think about the following for a few days and then write down the answers.

- 1. How many threads are you going to use? Specify the work that you intend each thread to perform.
- 2. Do the threads work independently? Or, is there an overall "controller" thread?
 - 3. How many mutexes are you going to use? Specify the operation that each mutex will guard.
 - 4. Will the main thread be idle? If not, what will it be doing?
- 5. How are you going to represent stations (which are collections of loaded trains ready to depart)? That is, what type of data structure will you use?
 - 6. How are you going to ensure that data structures in your program will not be modified concurrently?
 - 7. How many convars are you going to use? For each convar:
 - (a) Describe the condition that the convar will represent.
 - (b) Which mutex is associated with the convar? Why?
 - (c) What operation should be performed once pthread_cond_wait() has been unblocked and re-acquired the mutex?
 - 8. In 15 lines or less, briefly sketch the overall algorithm you will use. You may use sentences such as:

If train is loaded, get station mutex, put into queue, release station mutex.

The marker will not read beyond 15 lines.

Note: Please submit answers to the above on 8.5"×11" paper in 10pt font, single spaced with 1" margins left, right, top, and bottom. 2 pages maximum (cover page excluded), on June 4 through connex. The design counts for 5%.

5 Bonus Features

136

137

138

140

142

144

148

149

150

151

152

153

155

160

162

163

164

165

166

173

Only a simple control system simulator with limited scheduling and synchronization features is required in this assignment. However, students have the option to propose bonus features to include more scheduling and synchronization functions (e.g., to address scheduling fairness issues).

If you want to design and implement a bonus feature, you should contact the course instructor for permission before the due date of Deliverable 1, and clearly indicate the feature in the submission of Deliverable 2. The credit for the correctly implemented bonus feature will not exceed 20% of the full marks for this assignment.

6 Submission: Deliverable 2 (Code Due: Jun 26, 2015)

The code is submitted through connex. The tutorial instructor will give the detailed instruction in the tutorial.

6.1 Submission Requirements

Your submission will be marked by an automated script. The script (which is not very smart) makes certain assumptions about how you have packaged your assignment submission. We list these assumptions so that your submission can be marked thus, in a timely, convenient, and hassle-free manner.

1. The name of the submission file must be p2.tar.gz

- 2. p2.tar.gz must contain all your files in a directory named p2
- 3. Inside the directory p2, there must be a Makefile.
- 4. Invoking make on it must result in an executable named mts being built, without user intervention.
- 5. You may *not* submit the assignment with a compiled executable and/or object (.o) files; the script will delete them before invoking make.

Note:

179

182

186

187

- 1. The script will give a time quota of 1 minute for your program to run on a given input. This time quota is given so that non-terminating programs can be killed.
 - Since your program simulates train crossing delays in 10ths of a second, this should not be an issue, at all.
- 2. Follow the output rules specified in the assignment specification, so that the script can tally the output produced by your program against text files containing the correct answer.
 - 3. The markers will read your C code after the script has run to ensure that the **pthread** library is used as required.
 - The code counts for 15%.

7 Plagiarism

This assignment is to be done individually. You are encouraged to discuss the design of the solution with your classmates, but each student must implement their own assignment. The markers will submit your code to an automated plagiarism detection service.

NOTE: Do not request/give source code from/to others.