

APPENDIX CSC 230

Operation	Assembler	Action
Move	MOV{S} Rd, <Oprnd2>	Rd := Oprnd2 {CPSR}
	MVN{S} Rd, <Oprnd2>	Rd := NOT Oprnd2 {CPSR}
Arithmetic	ADD{S} Rd, Rn, <Oprnd2>	Rd := Rn + Oprnd2 {CPSR}
	ADC{S} Rd, Rn, <Oprnd2>	Rd := Rn + Oprnd2 + Carry {CPSR}
	SUB{S} Rd, Rn, <Oprnd2>	Rd := Rn - Oprnd2 {CPSR}
	SBC{S} Rd, Rn, <Oprnd2>	Rd := Rn + Oprnd2 + Carry {CPSR}
	RSB{S} Rd, Rn, <Oprnd2>	Rd := Oprnd2 - Rn {CPSR}
	RSC{S} Rd, Rn, <Oprnd2>	Rd := Oprnd2 - Rn - NOTCarry {CPSR}
	MUL{S} Rd, Rm, Rs	Rd := Rm * Rs {CPSR}
	MLA{S} Rd, Rm, Rs, Rn	Rd := Rm * Rs + Rn {CPSR}
	CLZ Rd, Rm	Rd := # leading zero in Rm
Logical	AND{S} Rd, Rn, <Oprnd2>	Rd := Rn AND Oprnd2 {CPSR}
	EOR{S} Rd, Rn, <Oprnd2>	Rd := Rn EXOR Oprnd2 {CPSR}
	ORR{S} Rd, Rn, <Oprnd2>	Rd := Rn OR Oprnd2 {CPSR}
	TST Rn, <Oprnd2>	Update CPSR on Rn AND Oprnd2
	TEQ Rn, <Oprnd2>	Update CPSR on Rn EOR Oprnd2
	BIC{S} Rd, Rn, <Oprnd2>	Rd := Rn AND NOT Oprnd2 {CPSR}
	NOP	R0 := R0
Compare	CMP Rd, <Oprnd2>	Update CPSR on Rn - Oprnd2
Branch	B{cond} label	R15 := label
	BL{cond} label	R14 := R15-4; R15 := label
Swap	SWP Rd, Rm, [Rn]	temp := [Rn]; [Rn] := Rm; Rd := temp
Load	LDR Rd, <a_mode2>	Rd := address
	LDM <a_mode4L> Rd{!}, <reglist>	Load list of registers from [Rd]
Store	STR Rd, <a_mode2>	[address]:= Rd
	STM <a_mode4S> Rd{!}, <reglist>	Store list of registers to [Rd]
SWI	SWI <immed_24>	Software Interrupt

Addressing Mode 2 - Data Transfer		
Pre-indexed	Immediate offset	[Rn, #+/-<immed_12>]{!}
	Zero offset	[Rn]
	Register offset	[Rn, +/-Rm]{!}
	Scaled register offset	[Rn, +/-Rm, LSL #<immed_5>]{!}
		[Rn, +/-Rm, LSR #<immed_5>]{!}
		[Rn, +/-Rm, ASR #<immed_5>]{!}
		[Rn, +/-Rm, ROR #<immed_5>]{!}
		[Rn, +/-Rm, RRX]{!}
Post-indexed	Immediate offset	[Rn], #+/-<immed_12>
	Register offset	[Rn], +/-Rm
	Zero offset	[Rn]
	Scaled register offset	[Rn], +/-Rm, LSL #<immed_5>
		[Rn], +/-Rm, LSR #<immed_5>
		[Rn], +/-Rm, ASR #<immed_5>
		[Rn], +/-Rm, ROR #<immed_5>
		[Rn], +/-Rm, RRX

Key to tables	
{cond}	See Condition Field
<Oprnd2>	See Operand 2
{S}	Updates CPSR if present
<immed>	Constant
<a_mode2>	See Addressing Mode 2
<a_mode4>	See Addressing Mode 4
<reglist>	List of registers with commas
{!}	Updates base register if present

Operand 2	
Immediate value	#<immed_8>
Logical shift left immediate	Rm, LSL #<immed_5>
Logical shift right immediate	Rm, LSR #<immed_5>
Arithmetic shift right immediate	Rm, ASR #<immed_5>
Rotate right immediate	Rm, ROR #<immed_5>
Register	Rm
Rotate right extended	Rm, RRX
Logical shift left register	Rm, LSL Rs
Logical shift right register	Rm, LSR Rs
Arithmetic shift right register	Rm, ASR Rs
Rotate right register	Rm, ROR Rs

Condition Field	
EQ	Equal
NE	Not equal
CS	Carry Set
CC	Carry clear
MI	Negative
PL	Positive or zero
VS	Overflow
VC	No overflow
HI	Unsigned higher
LS	Unsigned lower or same
GE	Signed greater or equal
LT	Signed less than
GT	Signed greater than
LE	Signed less than or equal
AL	Always

Dec	Bin	Hex
0	00000000	00
1	00000001	01
2	00000010	02
3	00000011	03
4	00000100	04
5	00000101	05
6	00000110	06
7	00000111	07
8	00001000	08
9	00001001	09
10	00001010	0A
11	00001011	0B
12	00001100	0C
13	00001101	0D
14	00001110	0E
15	00001111	0F

Addressing Mode 4 - Multiple Data Transfer			
Block load		Stack pop	
IA	Increment After	FD	Full Descending
IB	Increment Before	ED	Empty Descending
DA	Decrement After	FA	Full Ascending
DB	Decrement Before	EA	Empty Ascending
Block store		Stack push	
IA	Increment After	EA	Empty Ascending
IB	Increment Before	FA	Full Ascending
DA	Decrement After	ED	Empty Descending
DB	Decrement Before	FD	Full Descending

D	BIN	H	D	BIN	H	D	BIN	H	D	BIN	H
0	00000000	00	4	00000100	04	8	00001000	08	12	00001100	0C
1	00000001	01	5	00000101	05	9	00001001	09	13	00001101	0D
2	00000010	02	6	00000110	06	10	00001010	0A	14	00001110	0E
3	00000011	03	7	00000111	07	11	00001011	0B	15	00001111	0F