TFXP 1kV

TFXP 1kV 4G25A



Nexans Ref.: 10022127
Country Ref.: 1017588
EAN 13: 7330000055810

STANDARDS

Product HD 603.5M

Test IEC 60332-1

USER BENEFITS:

TFXP has XLPE-insulated aluminium conductors.
The cable is specially devoloped for low temperature conditions.

Installation:

- Underground
- Outdoor

Usage

- **Energy distribution**

Marking

NEXANS GS TFXP n x mm2 1kV YEAR MONTH

Conductor marking/colour code

Black-Brown-Grey-Green/Yellow

Conductor flexibility
Stranded class 2

Rated Voltage Uo/U (Um)
0.6/ 1 (1.2) kV

Minimum repeated bending diameter
300 mm

Maximum operating temperature
90 °C

Minimum installation temperature
-10 °C

Bending factor when laying
6 (xD)

Flame retardant
IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

CHARACTERISTICS

Construction characteristics	
Conductor material	Aluminum
Conductor shape	Circular compacted
Insulation	XLPE (chemical)
With Green/Yellow core	Yes
Material of filler / inner sheath	PE
Outer sheath	PVC
Sheath colour	Green
Conductor flexibility	Stranded class 2
Dimensional characteristics	
Conductor cross-section	25 mm²
Conductor diameter	6.0 mm
Sector-shaped heigth	- mm
Sector-shaped width	- mm
Number of cores	4
Nominal outer diameter	25.0 mm
Approximate weight	0.6 kg/m
Diameter over inner sheath	- mm
Nominal insulation thickness	- mm
Nominal outer sheath thickness	- mm
Electrical characteristics	
Permissible current rating in open air	105 A
Permissible current rating when buried	125 A
Max. DC resistance of the conductor at 20°C	1.2 Ohm/km
Inductive reactance at 50Hz	0.082 Ohm/km
Nominal inductance	0.26 mH/km
Zero sequence reactance at 50HZ	0.33 Ohm/km
Zero sequence resistance at 20°C	4.8 Ohm/km
Capacity of phase cores approx.	0.09 µF / km
Permissible short circuit current conductor 1s	2.2 kA
Rated Voltage Uo/U (Um)	0.6/ 1 (1.2) kV
Mechanical characteristics	
Maximum Pulling Tension	3 kN
Minimum repeated bending diameter	300 mm
Usage characteristics	
Packaging	NX14
Length	1000 m
Maximum operating temperature	90 °C
Short-circuit max. conductor temperature	250 °C
Minimum installation temperature	-10 °C
Bending factor when laying	6 (xD)
Fire safety characteristics	
Flame retardant	IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.