TFXP 1kV

TFXP 1kV 4G150A



Nexans Ref.: 10022130
Country Ref.: 1017594
EAN 13: 7330000055858

STANDARDS

Product HD 603.5M

Test IEC 60332-1

USER BENEFITS:

TFXP has XLPE-insulated aluminium conductors.
The cable is specially devoloped for low temperature conditions.

Installation:

- Underground
- Outdoor

Usage

- **Energy distribution**

Marking

NEXANS GS TFXP n x mm2 1kV YEAR MONTH

Conductor marking/colour code

Black-Brown-Grey-Green/Yellow

Conductor flexibility
Stranded class 2

Rated Voltage Uo/U (Um)
0.6/ 1 (1.2) kV

Minimum repeated bending diameter
540 mm

Maximum operating temperature
90 °C

Minimum installation temperature
-10 °C

Bending factor when laying
6 (xD)

Flame retardant
IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

TFXP 1kV

TFXP 1kV 4G150A

CHARACTERISTICS

Construction characteristics	
Conductor material	Aluminum
Conductor shape	Sector-shaped stranded (SM)
Insulation	XLPE (chemical)
With Green/Yellow core	Yes
Material of filler / inner sheath	PE
Outer sheath	PVC
Sheath colour	Green
Conductor flexibility	Stranded class 2
Dimensional characteristics	
Conductor cross-section	150 mm²
Conductor diameter	- mm
Sector-shaped heigth	15.5 mm
Sector-shaped width	21 mm
Number of cores	4
Nominal outer diameter	45.0 mm
Approximate weight	2.38 kg/m
Diameter over inner sheath	2 mm
Nominal insulation thickness	1.4 mm
Nominal outer sheath thickness	1.6 mm
Electrical characteristics	
Permissible current rating in open air	320 A
Permissible current rating when buried	335 A
Max. DC resistance of the conductor at 20°C	0.206 Ohm/km
Inductive reactance at 50Hz	0.072 Ohm/km
Nominal inductance	0.23 mH/km
Zero sequence reactance at 50HZ	0.31 Ohm/km
Zero sequence resistance at 20°C	0.824 Ohm/km
Capacity of phase cores approx.	0.13 µF / km
Permissible short circuit current conductor 1s	13.5 kA
Rated Voltage Uo/U (Um)	0.6/ 1 (1.2) kV
Mechanical characteristics	
Maximum Pulling Tension	18 kN
Minimum repeated bending diameter	540 mm
Usage characteristics	
Packaging	NX16
Length	500 m
Maximum operating temperature	90 °C
Short-circuit max. conductor temperature	250 °C
Minimum installation temperature	-10 °C
Bending factor when laying	6 (xD)
Fire safety characteristics	
Flame retardant	IEC 60332-1

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.