

Replication_code_section3

September 13, 2024

1 Replication Section 3, Song et al. (2024)

This file replicates the output in Section 3 of ‘PyTimeVar: A Python Package for Trending Time-Varying Time Series Models’. Authors: Mingxuan Song, Bernhard van der Sluis, Yicong Lin. Date current version: September 2024

Section 3 illustrates our package on the Temperature dataset.

1.0.1 Load temperature data and set seed

```
[13]: # Load data
from PyTimeVar.datasets import temperature
import numpy as np
data = temperature.load(regions=['World'], start_date='1961-01-01',
    ↪end_date='2023-01-01')
vY = data.values
X = np.ones_like(vY)

# set seed
np.random.seed(123)
```

1.0.2 Illustration of local linear regression

```
[14]: from PyTimeVar import LocalLinear
model = LocalLinear(vY, X)
betaHatLLR = model.fit()
```

No bandwidth or selection method is specified.

Optimal bandwidth selected by individual method:

- AIC method: 0.435484
- GCV method: 0.435484
- LMCV-0 method: 0.0600
- LMCV-2 method: 0.1200
- LMCV-4 method: 0.0600
- LMCV-6 method: 0.0600

Optimal bandwidth used is the avg. of all methods: 0.1952

Note: If a residual-based bootstrap method (LBWB, WB, SB, SWB, AWB) is adopted, the avg. bandwidth 0.1952 is used.
If the MB is implemented, the GCV bandwidth is used.

```
[15]: # print summary
      model.summary()
```

Local Linear Regression Results

=====

Bandwidth: 0.1952

Number of observations: 63

Number of predictors: 1

=====

Beta coefficients (shape: (1, 63)):

Use the 'plot_betas()' method to plot the beta coefficients.

=====

Use the 'confidence_bands()' method to obtain the confidence bands and plots.


You can choose out of 6 types of Bootstrap to construct confidence bands:

SB, WB, SWB, MB, LBWB, AWB

=====

Use the 'plot_residuals()' method to plot the residuals.

```
[16]: # plot trend and data
      model.plot_predicted()
```



```
[17]: # plot confidence bands using LBWB
      cb = model.confidence_bands(bootstrap_type='LBWB', Gsubs=None, plots=True)
```

Calculating LBWB Bootstrap Samples

100%|

| 1299/1299 [00:12<00:00, 106.92it/s]




Illustration of parameter specifications for local linear regression

```
[18]: # auxiliary LLR model to illustrate kernel, bandwidth selection, and tau
      tau = np.linspace(0, 0.5, len(vY))
      model2LLR = LocalLinear(vY, X, kernel='Gaussian', bw_selection='lmcv_8',
      ↪tau=tau)
      beta_hat_model2 = model2LLR.fit()
```

Optimal bandwidth used is LMCV-8: 0.0750

Note: If a residual-based bootstrap method (LBWB, WB, SB, SWB, AWB) is adopted,
the LMCV-8 bandwidth 0.0750 is used.

If the MB is implemented, the GCV bandwidth is used.

1.0.3 Illustration of boosted HP filter

```
[19]: from PyTimeVar import BoostedHP
bHPmodel = BoostedHP(vY, dLambda=1600, iMaxIter=100)
bHPtrend, bHPresiduals = bHPmodel.fit(
    boost=True, stop="adf", dAlpha=0.05, verbose=False)
bHPmodel.summary()
bHPmodel.plot()
```

Boosted HP Filter Results:

Stopping Criterion: adf

Max Iterations: 100


Iterations Run: 1

Lambda: 1600

Alpha: 0.05

Information Criteria Values:

[3.54412124e-12]



1.0.4 Illustration of power-law model

```
[20]: from PyTimeVar import PowerLaw
PwrLaw = PowerLaw(vY, n_powers=1)
pwrTrend, pwrGamma = PwrLaw.fit()
PwrLaw.summary()
PwrLaw.plot()
```

yhat= 0.001 $t^{1.848}$




Illustration of parameter specifications for power-law model

```
[21]: # auxiliary power-law model to illustrate options
vgamma0 = np.arange(0, 0.1, 0.1)
options = {'maxiter': 5E5, 'disp': False}
auxPwr = PowerLaw(vY, n_powers=1, vgamma0=vgamma0, options=options)
auxPwrTrend, auxPwrGamma = auxPwr.fit()
auxPwr.summary()
```

yhat= 0.001 t^{1.848}

1.0.5 Illustration of state-space model

```
[22]: from PyTimeVar import Kalman
kalmanmodel = Kalman(vY=vY)
smooth_trend = kalmanmodel.fit('smoother')
kalmanmodel.summary()
kalmanmodel.plot()
```

```
C:\Users\bpvan\anaconda3\lib\site-packages\scipy\optimize\_optimize.py:284:
RuntimeWarning: Values in x were outside bounds during a minimize step, clipping
to bounds
```

```
warnings.warn("Values in x were outside bounds during a "
```


```
Optimization success
```

```
Kalman Filter specification:
```

```
H: [[[0.12777861]]]
```

```
Q: [[[0.03454909]]]
```

R: [[1.]]
T: [[1]]



1.0.6 Illustration of GAS models

```
[23]: from PyTimeVar import GAS
      N_gasmodel = GAS(vY=vY, mX=X, method='gaussian')
      N_GAStrend, N_GASparams = N_gasmodel.fit()
      N_gasmodel.plot()
```

Time taken: 0.60 seconds

