



Cross Validation

Train | Test Split



Cross Validation


- Begin with entire data set





Cross Validation


- Split into two sets Train and Test





Cross Validation


- Train model then evaluate error on Test.





Cross Validation

- We “allow” ourselves model adjustments.



ERROR 



Cross Validation

Train | Validation | Test Split



Cross Validation

- We just saw that Train | Test split method has a disadvantage of not having a portion of data that can report a performance metric on truly “unseen” data.
- If we want a truly fair and final set of performance metrics, we should get these metrics from a **final** test set that we do not allow ourselves to adjust on.



Cross Validation


- Begin with entire data set





Cross Validation

- Split into: Train, Validation, and Test.





Cross Validation

- Set aside Test set for final metrics.



TRAIN


VALIDATION

TEST



Cross Validation


- Fit model on Train set.





Cross Validation


- Evaluate performance on validation set.





Cross Validation


- Adjust hyperparameters as needed...





Cross Validation

- Train, validate, and adjust as necessary.





TEST



Cross Validation


- Perform final evaluation on Test set.





Cross Validation

- Do not adjust! Report this as final metric.



TRAIN

VALIDATION



TEST

FINAL
ERROR



Cross Validation

- Recall the entire reason to not adjust after the final test data set is to get the fairest evaluation of the model.
- The model was not fitted to the final test data **and** the model hyperparameters were not adjusted based off final test data.
- This is truly never before seen data!



Cross Validation

- To achieve this in Python with Scikit-Learn we simply perform the **train_test_split()** function call twice.
 - Once to split off larger training set.
 - Second time to split remaining data into a validation set and test set.



Cross Validation

Using the `cross_val_score` function



Cross Validation

- Start with entire data set:





Cross Validation


- Split data Training data and Test Data:





Cross Validation


- Split data Training data and Test Data:





Cross Validation

- Remove Test data for final evaluation:



TRAINING




TEST



Cross Validation

- Choose K-Fold Split Value for Training Data



TRAINING



TEST



Cross Validation

- Recall larger K means more computation!



TRAINING




TEST



Cross Validation

- Choose K-Fold Split Value for Training Data



TRAINING




TEST



Cross Validation

- Here $K = 5$



TRAINING



TEST



Cross Validation

- Train on K-1 folds and Validate on 1 Fold





Cross Validation

- Obtain an error metric for this fold:



ERROR 1




TEST



Cross Validation

- Repeat for another combination



ERROR 1




TEST

ERROR 2



Cross Validation

- Continue for all fold combinations



ERROR 1



TEST

ERROR 2

ERROR 3


ERROR 4

ERROR 5



Cross Validation

- Use mean error for parameter adjustments



ERROR 1

ERROR 2

ERROR 3

ERROR 4

ERROR 5

AVG

ERROR





TEST



Cross Validation

- Get final metrics from final test set.





Cross Validation

- The **cross_val_score** function uses a model and training set (along with a K and chosen metric) to perform all of this for us automatically!
- This allows for K-Fold cross validation to be performed on any model.



Cross Validation

Using the `cross_validate` function



Cross Validation

- The **cross_validate** function allows us to view multiple performance metrics from cross validation on a model and explore how much time fitting and testing took.



Grid Search



Grid Search

- Often more complex models have multiple adjustable hyperparameters.
- A grid search is a way of training and validating a model on every possible combination of multiple hyperparameter options.



Grid Search

- Scikit-Learn includes a **GridSearchCV** class capable of testing a dictionary of multiple hyperparameter options through cross-validation.
- This allows for both cross-validation and a grid search to be performed in a generalized way for any model.