

Product identity and scope

Model B30-6206 - single-row deep-groove bearing

DOCUMENT ID
DS-CAND-B
EFFECTIVE DATE
2026-09-12
CLASSIFICATION
Synthetic hackathon fixture

REVISION
1
OWNER
Supplier Beta Engineering

Identification

- Candidate ID: CAND-B
- Supplier part: B30-6206
- Bearing family: 6206
- Nominal bore class: 30 mm

Document scope

- Catalog data for the identified product revision.
- Application fit and plant release require separate review.

Synthetic supplier fixture. Technical evidence does not grant release.

Dimensions

Controlled dimensions for Candidate B

DOCUMENT ID DS-CAND-B	REVISION 1
EFFECTIVE DATE 2026-09-12	OWNER Supplier Beta Engineering
CLASSIFICATION Synthetic hackathon fixture	

Dimensions table

- Bore diameter | 30 mm | tolerance 0 / -0.010 mm
- Outside diameter | 62 mm | tolerance 0 / -0.013 mm
- Width | 16 mm | tolerance 0 / -0.120 mm
- Corner radius | 1.0 mm maximum

Fit warning

- Assembly A requires a 25 mm bearing seat.
- This 30 mm bore cannot be installed on BEARING-SEAT-25MM without redesign.

The bore difference is a hard dimensional mismatch for Assembly A.

Load ratings

Catalog ratings under supplier reference conditions

DOCUMENT ID DS-CAND-B	REVISION 1
EFFECTIVE DATE 2026-09-12	OWNER Supplier Beta Engineering
CLASSIFICATION Synthetic hackathon fixture	

Load ratings table

- Basic dynamic load rating | 18 kN
- Basic static load rating | 9.5 kN
- Reference speed | 11,000 rpm
- Limiting speed | 14,000 rpm

Rating basis

- Dynamic load exceeds the 14 kN minimum in REQ-LOAD-001.
- Passing one requirement does not override a hard dimensional mismatch.

Lubrication operating range

Application note for high-temperature grease package

DOCUMENT ID
DS-CAND-B
EFFECTIVE DATE
2026-09-12
CLASSIFICATION
Synthetic hackathon fixture

REVISION
1
OWNER
Supplier Beta Engineering

Qualified configuration

- Grease package: Beta HT-120
- Continuous operating range: -20 C to 120 C
- Application class: HIGH-TEMP-LUBRICATION
- Supplier test reference: BETA-LUBE-HT-441

Applicability

- The stated configuration is suitable for the Assembly A lubricant temperature requirement.
- Plant-A qualification release remains a separate gate.