

Assembly definition

Bearing station A-01

DOCUMENT ID
DWG-ASSY-A
EFFECTIVE DATE
2026-07-14
CLASSIFICATION
Synthetic hackathon fixture

REVISION
A
OWNER
Plant-A Mechanical Engineering

Drawing references

- Assembly: ASSEMBLY-A
- Material: MAT-BRG-001
- Interface: BEARING-SEAT-25MM
- Units: millimeters unless stated

Control note

- Use only the current drawing revision for fit decisions.
- Supplier catalog dimensions do not replace this interface definition.

Bearing seat dimensions

Hard dimensional interface requirements

DOCUMENT ID
DWG-ASSY-A
EFFECTIVE DATE
2026-07-14
CLASSIFICATION
Synthetic hackathon fixture

REVISION
A
OWNER
Plant-A Mechanical Engineering

Interface dimensions

- Required bearing bore | 25.000 mm nominal
- Shaft seat | 25.000 mm nominal
- Maximum bearing width | 15.2 mm
- Maximum outside diameter | 52.1 mm

Requirement mapping

- REQ-BORE-001 | Bore diameter = 25 mm | HARD
- A bore other than 25 mm is a fit mismatch.

Dimensional mismatch requires rejection, not qualification by inference.

Engineering notes

Application controls

DOCUMENT ID
DWG-ASSY-A
EFFECTIVE DATE
2026-07-14
CLASSIFICATION
Synthetic hackathon fixture

REVISION
A
OWNER
Plant-A Mechanical Engineering

Notes

- Bearing supports continuous assembly duty.
- Dynamic load and lubricant suitability are controlled by the application requirements document.
- Any alternative part requires evidence review and Plant-A Quality release.

Related documents

- Bearing_Application_Requirements.pdf revision 1
- Quality_Release_Procedure.pdf revision 3