```python
import heapq

graph = {
    'A': ['B', 'C'],
    'B': ['D', 'E'],
    'C': ['F', 'G'],
    'D': [],
    'E': [],
    'F': [],
    'G': []
}

h = {'A': 7, 'B': 6, 'C': 4, 'D': 5, 'E': 3, 'F': 2, 'G': 0}

def greedy_search(start, goal):
    queue = [(h[start], start, [start])]
    visited = set()

    while queue:
        cost, node, path = heapq.heappop(queue)

        if node in visited:
            continue

        visited.add(node)
        print("Visiting:", node, "Heuristic:", h[node])

        if node == goal:
            print("Final Path:", " -> ".join(path))
            print("Total Steps:", len(path) - 1)
            return

        for neighbor in graph[node]:
            if neighbor not in visited:
                heapq.heappush(queue, (h[neighbor], neighbor, path + [neighbo

    print("Path not found")

greedy_search('A', 'G')
```

```
Python 3.13.1 (tags/v3.13.1:0671451, Dec  3 2024, 19:06:28) [MSC v.1942
64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
========== RESTART: C:/Users/user/Downloads/AIES.py ==========
========
Visiting: A Heuristic: 7
Visiting: C Heuristic: 4
Visiting: G Heuristic: 0
Final Path: A -> C -> G
Total Steps: 2
>>>
```