

Towards Automated Merging of Code Clones in Object-Oriented Programming Languages - Work in Progress -

Simon Baars
University of Amsterdam
Amsterdam, Netherlands
simon.mailadres@gmail.com

Ana Oprescu
University of Amsterdam
Amsterdam, Netherlands
A.M.Oprescu@uva.nl

Abstract

Duplication in source code can have a major negative impact on the maintainability of source code. There are several techniques that can be used in order to merge clones, reduce duplication, improve the design of the code and potentially also reduce the total volume of a software system. In this study, we look into the opportunities to aid in the process of refactoring these duplication problems for object-oriented programming languages. Measurements that have been conducted so far have indicated that more than half of the duplication in code is related to each other through inheritance, making it easier to refactor these clones in a clean way. Approximately a fifth of the duplication can be refactored through method extraction, the other clones require other techniques to be applied. More measurements will be conducted to get a detailed overview of in what contexts clones occur, and what this means for the refactoring processes of these clones. As the desired output, we strive to construct a model that automatically applies refactorings for a large part of the detected duplication problems. This model will be implemented for the Java programming language.

Copyright © by the paper's authors. Copying permitted for private and academic purposes.

In: A. Editor, B. Coeditor (eds.): Proceedings of the XYZ Workshop, Location, Country, DD-MMM-YYYY, published at <http://ceur-ws.org>

1 Introduction

Duplication in source code is often seen as one of the most harmful types of technical debt. In Martin Fowler's "Refactoring" book [Fow99], he exclaims that *"Number one in the stink parade is duplicated code. If you see the same code structure in more than one place, you can be sure that your program will be better if you find a way to unify them."* In this research, we take a look at the challenges and opportunities in automatically refactoring duplicated code, also known as "code clones". The main goal is to improve the maintainability of the refactored code.

Refactoring is used to improve the quality related attributes of a codebase (maintainability, performance, etc.) without changing the functionality. There are many methods that have been introduced to help with the process of refactoring [Fow99, Wak04], that are integrated into most modern IDE's. However, most of these methods still require a manual assessment of where and when to apply them. Because of this, refactoring takes up a significant portion of the development process [LST78, MT04], or does not happen at all [MVD⁺03]. For a large part, refactoring requires domain knowledge to do it right. However, there are also refactoring opportunities that are rather trivial and repetitive to execute. In this research, we will look at to what extent code clones can be automatically refactored.

Code clones can be found anywhere in a codebase. The location of a clone in the code has an impact on how it has to be refactored. Because of this, we will first look at where clones can be found. Using this information we can determine in which locations clones are found the most, on basis of which the refactoring will be prioritized. Apart from that, we will look at different types of clones. A duplicate part in a codebase does not always have to be an exact match with

another part to be called a clone. We will look at the definitions of different types of clones and what the opportunities are to refactor duplicate parts of code if it's not an exact match. All of these measurements are performed on a large corpus of open source projects. We lay the main focus on the Java programming language as refactoring opportunities feature paradigm and programming language dependent aspects [CYI⁺11]. However, most practices featured in this research will also be applicable to other object-oriented languages, like C#.

1.1 Background

As code clones are seen as one of the most harmful types of technical debt, they have been studied very extensively. A survey by Roy et al [RC07] states definitions for various important concepts in code clone research. In this survey, he mentions the concept “clone pair”, which is *a set of two code portions/fragments which are identical or similar to each other*. Furthermore, he defined “clone class” as *the union of all clone pairs*. Apart from this, we use the definition “clone instance”, which is a single code portion/fragment that is part of either a clone pair or clone class.

A tool called DCRA (Duplicated Code Refactoring Advisor) looks into refactoring opportunities for clone pairs [FZZ12]. This tool chooses to only focus on refactoring clone pairs because they argue that *clone pairs are much easier to manage when considered singularly*. As intermediate steps, the authors measure a corpus of Java systems for some clone-related properties of the systems, like the relation (in terms of inheritance) between code fragments in a clone pair.

Another tool called Aries [HKK⁺04, HKI08] focuses on the detection of refactoring oriented clones. In this paper, the authors describe a few variables by which a clone can be assessed for refactoring suitability. This tool looks however only at the possibility to merge clones, rather than whether clones should be merged. Also, this tool only suggests refactorings and does not apply them.

There are many other publications that look into code clone refactoring [Alw17, CKS18, KN01]. However, none of the publications describing a refactoring tool have published their source code or application for refactoring support. Furthermore, all of these tools only support a subset of all harmful clones that are found. Also, these publications/tools are limited to suggesting refactoring opportunities for clones found, rather than actually applying refactorings where suitable. Finally, all published approaches have limitations, for instance, false positives when detecting clones [CKS18] or being limited to clone pairs [HKI08].

For this research, we strive to improve upon the cur-

rent state-of-the-art in clone refactoring by building a clone refactoring tool that applies refactorings to a large percentage of clones found. The design decisions for this tool will be made on basis of data gathered from a large corpus of software systems. The tool will be developed on GitHub and stored in the Software Heritage [DCZ17] archives to ensure long term preservation. This way we strive to make the problem of duplication in source code easier to deal with.

2 Clone Detection

As duplication in source code is a serious problem in many software systems, there are a lot of researches that look into code clones. Many tools have been proposed to detect various types of code clones. Two surveys of modern clone detection tools [SK16, SR14] together show an overview of the most-popular clone detection tools up until 2016. To be able to refactor detected clones, it is useful to have the ability to rewrite the AST. We considered a set of clone detection tools for their ability to support the refactoring process automatically. None of the tools we consider seemed completely fit for this purpose, so we decided to implement our own clone detection tool: CloneRefactor¹.

2.1 CloneRefactor

A 2016 survey by Gautam [GS16] focuses more on various techniques for clone detection. For our tool, we decided to combine AST- and Graph-based approaches for clone detection, similar to Scorpio (which is a clone detection tool that's part of TinyPDG: a library for building intraprocedural program dependency graphs for Java programs). We decided to base our tool on the JavaParser library [SvBT18], as it supports rewriting the AST back to Java code and is useable with all modern Java versions (Java 1-12). We collect each statement and declaration and compare those to find duplicates. This way we build a graph of each statement/declaration linking to each subsequent statement/declaration (horizontally) and linking to each of its duplicates (vertically). This is displayed in figure 1.

¹CloneRefactor (WIP) is available on GitHub: <https://github.com/SimonBaars/CloneRefactor>



Figure 1: Abstract figure of the graph representation built by CloneRefactor

2.2 Thresholds

CloneRefactor works on basis of three thresholds for finding clones:

1. **Number of statements/declarations:** The number of statements/declarations that should be equal/similar for it to be considered a clone.
2. **Number of tokens:** The number of tokens (excluding whitespace, end-of-line terminators and comments) that should be equal/similar for it to be considered a clone.
3. **Number of lines:** The minimum amount of lines (excluding lines that do not contain any tokens, for tokens same exclusions apply) that should be equal/similar for it to be considered a clone.

Of course, if we put any of these thresholds to zero it won't be taken into account anymore, so not all thresholds have to be used at all times. We consider "number of lines" to be the least important, as it highly depends on the programmer of the codebase (and we do not want this kind of dependence!). On basis of manual assessment, we have determined that setting the "number of statements/declarations" to 6 ensures that most non-harmful clones are filtered out. On the downside, this also filters out some harmful antipatterns, for instance, if a cloned line has many tokens we might want to consider a clone if it spans less than 6 statements (as a cloned line with many tokens is more harmful than one with few).

For the measurements in the next chapter we have chosen to apply the following thresholds:

- **Number of statements/declarations:** 6
- **Number of tokens:** 10
- **Number of lines:** 6

3 Code Clone Context

To be able to refactor code clones, it is very important to consider the context of the clone. We define the following aspects of the clone as its context:

1. The relation of clone instances among each other (for example two clone instances in a clone class are part of the same object).
2. Where a clone instance occurs in the code (for instance: a method-level clone is a clone instance that is (a part of) a single method).
3. The contents of a clone instance (for instance: the clone instance consists of a one method declaration, a foreach statement, and two variable declarations).

Everything in the context of a clone has a big impact on how it has to be refactored. For this study, we performed measurements on the context of clones in a large corpus of open source projects.

3.1 The corpus

For our measurements we use a large corpus of open source projects [AS13]². This corpus has been assembled to contain relatively higher quality projects (by filtering by forks). Also, any duplicate projects were removed from this corpus. This results in a variety of Java projects that reflect the quality of average open source Java systems and are useful to perform measurements on.

We then filtered the corpus further to make sure we are not including any test classes or generated classes. Many Java/Maven projects use a structure where they separate the application and its tests in the different folders ("src/main/java" and "src/test/java" respectively). Because of this, we chose to only use projects from the corpus which use this structure (and had at least a "src/main/java" folder). To limit the execution time of the script, we also decided to limit the maximum amount of source files in a single project to 1.000 (projects with more source files were not considered, which filtered only 5 extra projects out of the corpus). Of the 14.436 projects in the corpus over 3.848 remained, which is plenty for our purposes. The script to filter the corpus is included in our GitHub repository³.

Running our clone detection script, CloneRefactor, over this corpus gives the results displayed in table 1.

²The corpus can be downloaded from the following URL: http://groups.inf.ed.ac.uk/cup/javaGithub/java_projects.tar.gz

³The script we use to filter the corpus: <https://github.com/SimonBaars/CloneRefactor/blob/MeasurementsVersion1/src/main/java/com/simonbaars/clonerefactor/scripts/PrepareProjectsFolder.java>

Table 1: CloneRefactor results for Java projects corpus [AS13].

| | |
|---|------------|
| Amount of projects | 3,848 |
| Amount of lines | 8,284,140 |
| Amount of lines (excluding whitespace, comments, etc.) | 8,163,429 |
| Amount of statements/declarations | 6,863,725 |
| Amount of tokens | 66,964,270 |
| Amount of lines cloned | 1,341,094 |
| Amount of lines cloned (excluding whitespace, comments, etc.) | 815,799 |
| Amount of statements/declarations cloned | 747,993 |
| Amount of tokens cloned | 9,800,819 |
| Amount of clone classes | 34,367 |

3.2 Relations Between Clone Instances

When merging code clones in object-oriented languages, it is very important to consider the relation between clone instances. This relation has a big impact on how a clone should be merged, in order to improve the software design in the process.

3.2.1 Categorizing Clone Instance Relations

A paper by Fontana et al [FZ15] performs measurements on 50 open source projects on the relation of clone instances to each other. To do this, they first define several categories for the relation between clone instances in object-oriented languages. These categories are as follows:

1. **Same method:** All instances of the clone class are in the same method.
2. **Same class:** All instances of the clone class are in the same class.
3. **Superclass:** All instances of the clone class are children and parents of each other.
4. **Ancestor class:** All instances of the clone class are superclasses except for the direct superclass.
5. **Sibling class:** All instances of the clone class have the same parent class.
6. **First cousin class:** All instances of the clone class have the same grandparent class.
7. **Common hierarchy class:** All instances of the clone class belong to the same hierarchy, but do not belong to any of the other categories.

8. **Same external superclass:** All instances of the clone class have the same superclass, but this superclass is not included in the project but part of a library.

9. **Unrelated class:** There is at least one instance in the clone class that is not in the same hierarchy.

Please note that no of these categories allow external classes (except for “same external superclass”). So if two clone instances are related through external classes but do not share a common external superclass, it will be flagged as “unrelated”. The main reason for this is that it is (often) not possible to refactor to external classes.

The ranking of the previous list of categories also matters as it shows the different levels in which clones were assessed. For instance, if two clone instances of a clone class belong to the “same method” category but the third belongs to the “same class”, we will always choose the item lowest on the list.

3.2.2 Our measurements

We have recreated table 3 of Fontana et al [FZ15], but with the following differences in our setup:

- We consider clone classes rather than clone pairs.
- We use different thresholds regarding when a clone should be considered.
- We seek by statement/declaration rather than SLOC.
- We test a broader range of projects (they use a set of 50 relatively large projects, we use a large corpus that was assembled by a machine learning algorithm testing java projects on GitHub for quality, which contains projects of all sizes and with differing code quality).

Table 2 contains our results regarding the relations between clone instances.

Table 2: Clone relations

| Relation | Amount | Percentage |
|---------------------|--------|------------|
| Unrelated | 13,529 | 39.37 |
| Same Class | 8,341 | 24.28 |
| Sibling | 5,978 | 17.40 |
| Same Method | 2,456 | 7.15 |
| External Superclass | 2,402 | 6.99 |
| First Cousin | 695 | 2.02 |
| Superclass | 489 | 1.42 |
| Common Hierarchy | 442 | 1.29 |
| Ancestor | 28 | 0.08 |

Comparing it to the results of Fontana et al [FZ15], we find way more unrelated clones. This might be due to the fact that we consider clone classes rather than clone pairs, and mark the clone class “Unrelated” even if just one of the clone instances is outside a hierarchy. It could also be that the corpus which we use, as it has generally smaller projects, use more classes from outside the project (which are marked UNRELATED if they do not have a common external superclass). On the second place, we have the “Same Class” clones. On the third place come the “Sibling” clones.

3.3 Clone instance location

After mapping the relations between individual clones, we looked at the location of individual clone instances. A paper by Lozano et al [LWN07] discusses the harmfulness of cloning. In this paper, the author argues that 98% are produced at method-level. However, this claim is based on a small dataset and based on human copy-paste behavior rather than static code analysis. We validated this claim over the corpus we use. For this, we chose the following categories:

1. **Method/Constructor Level:** A clone instance that does not exceed the boundaries of a single method or constructor (optionally including the declaration of the method or constructor itself).
2. **Class Level:** A clone instance in a class, that exceeds the boundaries of a single method or contains something else in the class (like field declarations, other methods, etc.).
3. **Interface Level:** A clone that is (a part of) an interface.
4. **Enumeration Level:** A clone that is (a part of) an enumeration.

The results for the clone instance locations are shown in table 3.

Table 3: Clone instance locations

| Location | Amount | Percentage |
|-------------------|--------|------------|
| Method Level | 19,818 | 57.68 |
| Class Level | 13,259 | 38.59 |
| Constructor Level | 1,099 | 3.20 |
| Interface Level | 110 | 0.32 |
| Enum Level | 74 | 0.22 |

From these results, we can see that the claim of 98% of clones being produced at method-level is nowhere near correct. In fact, around 58% of the clones are produced at method-level. About 39% of clones either

span several methods/constructors or contain something like a field declaration. Another 3% of the clones are found in constructors. The amount of clones found in interfaces and enumerations is very low.

3.4 Clone instance contents

Finally, we looked at the contents of individual clone instances: what kind of declarations and statements do they span. We selected the following categories to be relevant for refactoring:

1. **Full Method/Class/Interface/Enumeration:** A clone that spans a full class, method, constructor, interface or enumeration, including its declaration.
2. **Partial Method/Constructor:** A clone that spans a method partially, optionally including its declaration.
3. **Several Methods:** A clone that spans over two or more methods, either fully or partially, but does not span anything but methods (so not fields or anything in between).
4. **Only Fields:** A clone that spans only global variables.
5. **Includes Fields/Constructor:** A clone that spans a combination of fields and other things, like methods.
6. **Method/Class/Interface/Enumeration Declaration:** A clone that contains the declaration (usually the first line) of a class, method, interface or enumeration.
7. **Other:** Anything that does not match with above-stated categories.

The results for these categories are displayed in table 4.

Table 4: Clone instance contents

| Contents | Amount | Percentage |
|--------------------------------|--------|------------|
| Partial Method | 19,264 | 56.07 |
| Several Methods | 9,076 | 26.41 |
| Includes Constructor | 1,528 | 4.45 |
| Includes Field | 1,149 | 3.34 |
| Partial Constructor | 1,098 | 3.20 |
| Only Fields | 565 | 1.64 |
| Full Method | 554 | 1.61 |
| Includes Class Declaration | 445 | 1.30 |
| Other | 369 | 1.07 |
| Full Class | 192 | 0.56 |
| Includes Enum Constant | 52 | 0.15 |
| Includes Enum Declaration | 47 | 0.14 |
| Includes Interface Declaration | 10 | 0.03 |
| Full Interface | 6 | 0.02 |
| Full Enumeration | 4 | 0.01 |

Unsurprisingly, most clones span a part of a method. Just 1.6% of the methods are cloned fully. More than a quarter of the clones spans over several methods, which is surprising. Simply extracting methods won't work in a case where a clone spans over several methods. About 4.5% of clones include a constructor. About 3.3% of clones include a global variable defined in a class.

4 Redefining type 1, 2 and type 3 clones

In a 2007 survey by Roy et al [RC07] he defined four types of clones:

Type 1: Identical code fragments except for variations in whitespace (may be also variations in layout) and comments.

Type 2: Structurally/syntactically identical fragments except for variations in identifiers, literals, types, layout and comments.

Type 3: Copied fragments with further modifications. Statements can be changed, added or removed in addition to variations in identifiers, literals, types, layout, and comments.

Type 4: Two or more code fragments that perform the same computation but implemented through different syntactic variants.

A higher type of clone means that it's harder to detect. It also makes the clone harder to refactor, as more transformations would be required. Higher clone

types also become more disputable whether they actually indicate a harmful antipattern (as not every clone is harmful [JX10, KG08]). Type 1 clones are most often, if not always with the right thresholds, harmful. Type 2 and type 3 clones are more disputable whether they are harmful and whether they can be merged in a way that improves the design of the code. In this chapter, we will redefine type 2 and type 3 clones to increase the chance that we can merge the clone while improving the design. Type-4 clones are, because of the serious challenges involved in their detection and refactoring, out of the scope for this study.

4.1 Type 1 clones

Type 1 clones are identical clone fragments except for variations in whitespace and comments. However, when two clone fragments are textually identical, does not yet indicate that they are actually identical. Even when textually equal, method calls can refer to different methods, type declarations can refer to different types and even variables can be of a different type. This could invalidate a refactoring opportunity for such a code fragment. Because of that, we recommend to redefine type-1 clones for refactoring. We propose to:

- **Compare the equality of the fully qualified method signature for method references.** This way we can validate whether two method references, like method calls, are actually equal. In this method signature not only the fully qualified identifier of the method should be considered, but also of the type of all its arguments. This way we can be sure that two potentially cloned method references do not point to overloaded variants (in a case that the data type of arguments is overloaded).
- **Compare the equality of the fully qualified identifier for type references.** This way we can be sure that two referenced types are actually equal, and that they are not just two types with the same name.
- **Compare the equality the fully qualified identifier for variable usages.** Two cloned lines might use a variable with the same name, but different types. This might pose serious challenges on refactoring, as the variables might not concern the same object or primitive. To check this, we need to track the declaration of variables and from this infer the fully qualified identifier of its type.

4.2 Type 2 clones

Type 2 clones, by definition, allow any change in identifiers, literals, types, layout, and comments. For

refactoring purposes, this doesn't always make a lot of sense. If we allow any change in identifiers, literals, and types, we cannot distinguish between different variables, different types and different method calls anymore. This could render two methods that have an entirely different functionality as clones. Merging such clones, if possible at all, might only prove to be harmful.

Because of that, for this research, we have looked into a redefinition of type 2 clones to be able to detect such clones that can and should be merged. Our definition ensures functional similarity by applying the following changes to type 2 clones:

- **Considering types:** The definition of type 2 clones states that types should not be considered. We disagree because types can make a significant change to the meaning of a code segment and thus whether this segment should be considered a clone. For instance, we should not say that an Apple type object is the same as an object of Orange type (don't compare apples with oranges).
- **Having a distinction between different variables:** By the definition of type 2 clones, any identifiers would not be taken into account. We agree that a difference in identifiers may still result in a harmful clone, but we should still consider the distinction between different variables. For instance, if we call a method like this: *myMethod(var1, var2)*, or call this method like this: *myMethod(var1, var1)*. Even if the variables have the same type, the distinction between the variables is important to ensure the functionality is the same after merging.
- **Defining a threshold for variability in literals:** By the definition of type 2 clones any literals would not be taken into account. We agree, as when merging the clone (for instance by extracting a method), we can simply turn the literal into a method parameter. However, we would argue that thresholds matter here. How many literals may differ for the segment still to be considered a clone with another segment? We need to define a threshold to be sure that, by merging, we are not replacing a code fragment by a worse maintainable design.
- **Consider method call signatures and define a threshold for variability in method calls:** As type-2 clones allows change in identifiers, also the names of called methods may vary. However, because of this, completely different methods can be called in cloned fragments as a result. This poses serious challenges on refactoring, and makes

it more disputable whether such a clone is actually harmful. This is because different method identifiers can describe a completely different functionality. Because of that, we recommend to consider the call signatures of cloned methods. We also recommend defining a threshold for variability in method call expressions, so only a limited number of method calls can vary.

4.3 Type 3 clones

Type 3 clones are even more permissive than type 2 clones, allowing added and removed statements. Thresholds matter a lot here to make sure that not the whole project is detected to be cloned. The main question for this study regarding type 3 clones is: "how can we merge type 3 clones while improving the design?"

Clone instances in type 3 clones are almost always different in functionality. As we have to ensure equal functionality after merging the clone, we have to wrap the difference in statements between the clone instances in conditional blocks (either if-statements or switch-statements). We can then pass a variable as to which path should be taken through the code (either a boolean or an enumeration). Such a refactoring would make added statements that are contiguous less harmful for the design than added statements that are separated by statements that both clone instances have in common.

We also want to argue that statements that are not common between two clone instances, should not count towards the size of the clone (and thus towards the threshold which determines whether the clone will be taken into account). Also, clones should not start and not end with an added statement (as that would be nonsense: such a thing could be done for any clone).

As for the detection of type 3 clones, we think the easiest opportunity to detect these clones is to consider it as a postprocessing step after clone detection. By trying to find short gaps between clones, we can find opportunities to merge clone classes into a single type 3 clone class. The amount of statements that this "short gap" can maximally span should be dependent on a threshold value.

5 Merging duplicate code through refactoring

Now we have mapped the contexts in which clones occur, we can start looking at refactoring opportunities. Regarding refactoring, we separate clones in two categories: easy and difficult refactoring opportunities. Easy refactoring opportunities are clones that can easily be automatically refactored. Examples of these opportunities are fully cloned methods or a set of fully cloned statements. According to the relation

between the clone instances, we can propose a refactoring automatically.

However, not always can a clone easily be merged. Sometimes a clone spans a statement partially (like a for-loop of which only its declaration and a part of the body is cloned). Merging the clones can be harder in such instances. Also, cloned code can contain a complex control structure, like labels, return, break, continue, etc. In such instances, more conditions apply to be able to conduct a refactoring, if advisable at all.

The most trivial way to merge a clone is through method extraction. However, method extraction is not always possible. For instance, if a part of a subtree (in a programs’ AST) is matched as a clone. Because of this, we chose to measure what percentage of “Partial Method” clones are refactorable using method extraction. Our results are displayed in table 5.

Table 5: Clone instance contents

| Refactorability | Amount | Percentage |
|------------------------------|--------|------------|
| Cannot directly be extracted | 10,990 | 41.91 |
| Is not a partial method | 9,444 | 36.01 |
| Can be extracted | 5,791 | 22.08 |

From this table, we can see that approximately 22 percent of the clones can be refactored through method extraction. For the other clones, we must first build a catalog of appropriate refactorings.

6 Threats to validity

We noticed that, when measuring over a corpus of this size, the thresholds that we use for the clone detection have a big impact on the results. There does not seem to be one golden set of thresholds, some thresholds work in some situations but fail in others. We have chosen thresholds that, according to our manual assessment, seemed optimal. However, by using these, we definitely miss some harmful clones.

Another thread to validity is that currently, in a very small number of cases, clone detection might result in a false positive. This is in cases where two lines are equal, but they actually call different methods with the same method signature. In such a case, merging such clones might turn out to change the functionality of the program. We have noted this down as a next step, working on basis of a callgraph instead of just the AST.

7 Conclusion and next steps

The study that we have conducted so far analyzes the context of different kinds of clones and prioritizes their refactoring. Firstly, we looked at the inheritance relation of clone instances in a clone class. We have found that most clone classes are unrelated, which means that they have at least one instance that has no relation with the other instances. There were also a lot of clone classes of which all instances are in the same class. At the third place are clone instances that are siblings of each other (share the same superclass).

Secondly, we looked at the location of clone instances. Most clone instances are found at method level, about 58 percent. About 39 percent of clone instances were found at class level. We defined “class level clones” as clones that exceed the boundaries of a single method or contain something else in the class (like field declarations, other methods, etc.).

Thirdly, we looked at the contents of clone instances. Most clones span a part of a method (56 percent). About 26 percent of clones span over several methods. We also looked into the refactorability of clones that span part of a method. Over 22 percent of the clones can directly be refactored by extracting them to a new method (and calling the method at all usages using their relation). The main reason that most clones that span a part of a method cannot directly be refactored by method extraction, is that they are nested in such a way that method extraction would leave side effects (for instance, we cannot extract half of a for-loop).

7.1 Next steps

As a first next step, we will integrate our redefinition of type-2 clones into CloneRefactor. This way, we can run all scripts that we used for all measurements for our redefinition of type-2 clones. We are curious to see how it compares with the results we had for the type-1 clones so far.

As we want to refactor duplicates fully automated, it is very important that both code fragments have exactly the same functionality. Because of this, we want to look into building a SymbolTable of projects we scan and their dependencies. This allows us to further assess the equality of code fragments. Currently, we compare fragments, as most clone detection tools do, on basis of static analysis of only the target project. However, because of this, we omit valuable information like fully qualified identifiers for types. By parsing not only a project, but also its dependencies, we can better assess whether two code fragments are actually equal, or whether they are calling different methods but with the same type signature (we are currently limited in distinguishing these).

Furthermore, we want to start automatically refactoring clones. On basis of our initial results, we have determined that we can best start with the automatic refactoring of clones that can be extracted to a method. If this works, we can already decrease duplication by 22%.

Acknowledgements

We would like to thank the Software Improvement Group (SIG) for their continuous support in this project.

References

- [Alw17] Asif Alwaqfi. *A Refactoring Technique for Large Groups of Software Clones*. PhD thesis, Concordia University, 2017.
- [AS13] Miltiadis Allamanis and Charles Sutton. Mining Source Code Repositories at Massive Scale using Language Modeling. In *The 10th Working Conference on Mining Software Repositories*, pages 207–216. IEEE, 2013.
- [CKS18] Zhiyuan Chen, Young-Woo Kwon, and Myoungkyu Song. Clone refactoring inspection by summarizing clone refactorings and detecting inconsistent changes during software evolution. *Journal of Software: Evolution and Process*, 30(10):e1951, 2018.
- [CYI⁺11] Eunjong Choi, Norihiro Yoshida, Takashi Ishio, Katsuro Inoue, and Tateki Sano. Extracting code clones for refactoring using combinations of clone metrics. In *Proceedings of the 5th International Workshop on Software Clones*, pages 7–13. ACM, 2011.
- [DCZ17] Roberto Di Cosmo and Stefano Zacchiroli. Software heritage: why and how to preserve software source code. In *iPRES 2017-14th International Conference on Digital Preservation*, pages 1–10, 2017.
- [Fow99] Martin Fowler. *Refactoring: improving the design of existing code*. Addison-Wesley Professional, 1999.
- [FZ15] Francesca Arcelli Fontana and Marco Zanoni. A duplicated code refactoring advisor. In *International Conference on Agile Software Development*, pages 3–14. Springer, 2015.
- [FZZ12] Francesca Arcelli Fontana, Marco Zanoni, and Francesco Zanoni. Duplicated code refactoring advisor (dcra): a tool aimed at suggesting the best refactoring techniques of java code clones. Università degli Studi di Milano-Bicocca, 2012.
- [GS16] Pratiksha Gautam and Hemraj Saini. Various code clone detection techniques and tools: A comprehensive survey. pages 655–667, 08 2016.
- [HKI08] Yoshiki Higo, Shinji Kusumoto, and Katsuro Inoue. A metric-based approach to identifying refactoring opportunities for merging code clones in a java software system. *Journal of Software Maintenance and Evolution: Research and Practice*, 20(6):435–461, 2008.
- [HKK⁺04] Yoshiki Higo, Toshihiro Kamiya, Shinji Kusumoto, Katsuro Inoue, and K Words. Aries: Refactoring support environment based on code clone analysis. In *IASTED Conf. on Software Engineering and Applications*, pages 222–229, 2004.
- [JX10] Stan Jarzabek and Yinxing Xue. Are clones harmful for maintenance? 2010.
- [KG08] Cory J Kapser and Michael W Godfrey. “cloning considered harmful” considered harmful: patterns of cloning in software. *Empirical Software Engineering*, 13(6):645, 2008.
- [KN01] Georges Golomingi Koni-N’Sapu. A scenario based approach for refactoring duplicated code in object oriented systems. *Master’s thesis, University of Bern*, 2001.
- [LST78] Bennet P Lientz, E. Burton Swanson, and Gail E Tompkins. Characteristics of application software maintenance. *Communications of the ACM*, 21(6):466–471, 1978.
- [LWN07] Angela Lozano, Michel Wermelinger, and Bashar Nuseibeh. Evaluating the harmfulness of cloning: A change based experiment. In *Fourth International Workshop on Mining Software Repositories (MSR’07: ICSE Workshops 2007)*, pages 18–18. IEEE, 2007.
- [MT04] Tom Mens and Tom Tourwé. A survey of software refactoring. *IEEE Transactions on software engineering*, 30(2):126–139, 2004.

- [MVD⁺03] Tom Mens, Arie Van Deursen, et al. Refactoring: Emerging trends and open problems. In *Proceedings First International Workshop on REFactoring: Achievements, Challenges, Effects (REFACE)*, 2003.
- [RC07] Chanchal Kumar Roy and James R Cordy. A survey on software clone detection research. *Queen's School of Computing TR*, 541(115):64–68, 2007.
- [SK16] Abdullah Sheneamer and Jugal Kalita. A survey of software clone detection techniques. *International Journal of Computer Applications*, 137(10):1–21, 2016.
- [SR14] Jeffrey Svajlenko and Chanchal K Roy. Evaluating modern clone detection tools. In *2014 IEEE International Conference on Software Maintenance and Evolution*, pages 321–330. IEEE, 2014.
- [SvBT18] Nicholas Smith, Danny van Bruggen, and Federico Tomassetti. Javaparser, 05 2018.
- [Wak04] William C Wake. *Refactoring workbook*. Addison-Wesley Professional, 2004.