LAST PASS · AGENT METHOD · 2026-09-16

How the agent prepares a form and reads errors

https://github.com/SimonBarnett/agentic_fomprep @ `543015f384a3c23b8e1380603c93c60632559d34`
Gap A–F are in code (parse, JSONL, no restore-on-timeout, last-result helper). This page is the method. Do not invent a second executor.

Preconditions the agent cannot create: unlocked DEV1 desktop, and a live C:\Priority\tmp\agent-formprep\si-web-state.json. If the probe says recapture cookies, stop and ask a human. Do not SQL-flip UPD. Do not click Ignore Duplicate. Do not run AllUnprepared.

0. What “worked” means

Prepared = EXECPREPLOCK.UPD='N' AND LASTPREPDATE (bigint) increased. ok=true only if every requested name is in prepared[], restoreOk, parkedCount==restoredCount. Playwright finishing is not success. winrun exit 0 is not success. CLI is default-off.

1. Where you run

Check	Must be
Host	CE-PRIORITY-DEV / CE-PRIORITY-DEV1, interactive desktop
Repo	M:\ai\agentic_fomprep (or current checkout). ExecutionPolicy Bypass
SQL / web	10.220.0.5\DEV system ; https://prioritydev.clarksonevans.co.uk
Company click	D - Clarkson Evans Live only (DEV base). Never D-Test / D-Global Swap 4
Cookies	C:\Priority\tmp\agent-formprep\si-web-state.json exists and probe is not login
OPEN parks	SELECT COUNT(*) FROM dbo.AGENT_FORMPREP_PARK WHERE restored_at IS NULL = 0

2. Command — prepare

One form first. SkipCli is already the default on the CLI wrapper.

```
cd M:\ai\agentic_fomprep
powershell -NoProfile -ExecutionPolicy Bypass -File src\Prepare-Forms.ps1 `
  -Names ZCLA_PARTLONGDESC -Environment DEV -WhatIf

powershell -NoProfile -ExecutionPolicy Bypass -File src\Prepare-Forms.ps1 `
  -Names ZCLA_PARTLONGDESC -Environment DEV -TimeoutMinutes 15
```

WhatIf must print the exec id and not write parks. Real run: headed Chromium will open. Leave it. Timeout 15 minutes. If exit 2 and reason contains auth / recapture / login / storage_state — stop. Human recaptures with tools\Save-WebStorageState.ps1.

Three names max until isolation is boring:

```
powershell -NoProfile -ExecutionPolicy Bypass -File src\Prepare-Forms.ps1 `
  -Names ZCLA_PARTLONGDESC,ZCLA_PARTLONGDHIST,ZCLA_PARTLONGDREV `
  -Environment DEV -TimeoutMinutes 15
```

3. Command — get errors

```
powershell -NoProfile -ExecutionPolicy Bypass -File tools\Get-LastFormPrepResult.ps1
```

Reads C:\Priority\tmp\agent-formprep\last.json (or -RunId <guid>). Prints prepared[], stillUnprepared[], errors[] (capped 200). Per-line sources: emsg, prep.err, errors-report (from capture\errors-report.jsonl). Name mention is Warning, not Blocker. ok stays SQL-gated.

Files you may cite, never commit:

Path	Use
...\agent-formprep\last.json	Contract for the agent
...\agent-formprep\<runId>\result.json	Same payload for that run
...\<runId>\capture\errors-report.jsonl	Scraped Errors Report rows
...\<runId>\capture\emsg.txt	Raw fallback if JSON is thin
si-web-state.json / HTML screenshots	Human only. Not model context.

4. How to read exit codes

Exit	Meaning	Agent next step
0 + ok=true	Named forms compiled; park restored	Read errors[]. Fix form in Priority if Warning lines exist. Do not re-prep unless stillUnprepared is empty and you still see compile text.
0 + whatIf	Dry run	If names resolved, run without -WhatIf
2	Refused, no park (auth, mutex, host, AllUnprepared, missing name)	If auth/login: human cookies. If open_park: RepairOpenParks. Else stop.
3	Parked but failed, or idle-timeout left OPEN parks	RepairOpenParks -RunId from the error text. Do not start a second Prepare-Forms until OPEN=0.
4	Compiled but FORMKEYS hook failed	Keys dump is empty — treat as compiled; do not INSERT keys.

5. Crash / leftover park

```
powershell -NoProfile -ExecutionPolicy Bypass -File src\Prepare-Forms.ps1 `
  -RepairOpenParks -Environment DEV
# if it lists a run guid:
powershell -NoProfile -ExecutionPolicy Bypass -File src\Prepare-Forms.ps1 `
  -RepairOpenParks -RunId <guid> -Environment DEV
```

6. Hard stops (do not “help”)

- UPDATE EXECPREPLOCK.UPD='N' and call it prepared.
- AllUnprepared / more than 10 names / any host that is not DEV1.
- Click Ignore, Yes, index rebuild, D-Test, D-Global Swap 4.
- Commit cookies, result JSON that looks like a password, or Errors Report HTML.
- Enable CLI hoping winrun will compile. It exits 0 and does not move LASTPREPDATE on this box.
- Headless Chromium. It misses the framed dashboard.
- Second Prepare-Forms while AGENT_FORMPREP_PARK has restored_at IS NULL.

7. Residual (known, accepted for this method)

Session dies; a human must recapture cookies. Playwright needs the desktop. JSONL scrape is new code — first live run may still say “html present but no JSONL”; then use emsg.txt lines. Idle wait is 120s; if Form Prep is slow, exit 3 + OPEN park is correct. Repair, do not restore-by-hand in SSMS. Sibling forms can still move if the server compiles them before idle is detected; prefer one name per run.

8. First task for the agent

1) WhatIf ZCLA_PARTLONGDESC. 2) If cookies dead, stop. 3) Prepare that one name. 4) Get-LastFormPrepResult. 5) Report ok, lastPrep before→after, restoreOk, and the errors[] lines. 6) If exit 3, RepairOpenParks only. That is the whole loop.

HEAD 543015f384a3c23b8e1380603c93c60632559d34. Reviews under reviews/ are history. This file is the method.