

## HOSTILE MRB ? MODE 1 AGENT-TO-AGENT (2026-09-19)

Session: Bob (cm-bob) ? Oscar (cm-oscar) on Libera #cm-bob-oscar  
Host: IONOS WIN-MPRE8VI4U6U (AWS box blocked without SASL)  
Code tip during pass: c6e9c53 (NICK\_RE hyphen fix)  
Offline suite: pytest -q ? 78 passed, 2 skipped (re-run on IONOS).

### Verdict

-----

PASS ? mode-1 agent-to-agent proven on IONOS (connect + mutual AGPK + SEAL secret + FILE tier S).

Not a full PDF Appendix C / manual Libera checklist close-out. AWS?Libera without NickServ SASL remains blocked. .NET Phase 5 still deferred (unchanged from MRB v2).

---

### Evidence (live)

-----

#### Step Result

--- ---

TLS join (IONOS) Both nicks INFO joined #cm-bob-oscar  
Mutual AGPK Bob pinned oscar; oscar peers.json has Bob ElGfrGcx?Dv0o=  
Cleartext outbox CLEARTEXT\_PING\_FROM\_BOB seen on oscar irc.log  
SEAL bob?oscar INFO SEAL 1e2eff866b63b790 -> inbox (18 bytes); plaintext MODE1\_SECRET\_OK7  
FILE tier S INFO file OFFER id=6e4a50e9098f56a5 then INFO file DONE id=6e4a50e9098f56a5 ok; file at  
files/complete/6e4a50e9098f56a5-mode1-file.txt (41 bytes)  
Clients still up cm-bob + cm-oscar python processes on IONOS after test

---

### Bugs found in this UAT (and status)

-----

1. CAP END missing when SASL unset ? no 001 registration. Fixed 8c168c9.
2. NICK\_RE rejected hyphenated nicks (cm-oscar) ? parse\_seal\_line returned None, SEAL silently ignored on wire. Cause: - inside a character class formed a range \-\_. Fixed c6e9c53 (hyphen at end of class).
3. TOFU first-pin footgun ? bob briefly re-announced oscar's AGPK as "bob"; oscar pinned wrong key; later correct AGPK ? mismatch ignored. Operational ? wipe peers.json / restart receiver; do not announce wrong AGPK.
4. AWS / Grok Bot box ? Libera requires SASL + verified NickServ email. Mode-1 must run from IONOS (or with SASL) until accounts exist.
5. Windows Start-Process hello quoting ? --hello "oscar online mode1" can split into unrecognized args. Use single-token hello or argv array carefully.

---

Required follow-up for build agent (hand-off)

- 
1. Add offline pytest that NICK\_RE matches hyphenated nicks (cm-oscar, cm-bob) and that parse\_seal\_line accepts a SEAL v2 line with those nicks.
  2. Add offline SEAL seal?parse?FragmentStore?open\_bytes\_v2 roundtrip using hyphenated nicks (no Libera).
  3. Document in README.md / skill: AWS Libera SASL gate; prefer IONOS for unattended mode-1; TOFU wipe procedure if wrong first pin.
  4. Optional: regression that CAP END is sent on sasl\_plain() when env unset (unit or small harness).
  5. Do not open Libera from CI. Do not claim Server 2012 / .NET done.

---

Pass bar for this MRB

- 
- Live mode-1 SEAL + FILE on a private channel between two agent homes ? met.
  - Hyphen nick SEAL parse ? met after fix (needs pytest lock).
  - Full manual tests/MANUAL.md moot + dumb + Libera matrix ? not claimed.

Bob: mode-1 PASS on IONOS. Hand remaining pytest/docs lock to build agent.