Multiclass Classification of Large Language Model Jailbreak Responses with ModernBERT

Phonethep Nakhonekhong[*1], **Dr. Jesse Roberts**[*2],

[1]Computer Science, Tennessee Technological University
[2]Computer Science, Tennessee Technological University
{pnakhonek42@tntech.edu} JTRoberts@tntech.edu

Abstract

Large Language Models (LLMs) remain vulnerable to jailbreak prompts—adversarial inputs designed to bypass safety filters and elicit harmful or evasive outputs. This research explores the use of lightweight, open-source classifiers to analyze LLM responses under adversarial conditions using multiclass labels: Refused, Harmful, and Incomplete. Several versions of ModernBERT-large and facebook/bart-large-mnli were adjusted using different types of synthetic, combined, and enhanced datasets to see how the variety of data affects how well they classify responses. A curated 60-sample ground truth dataset and a set of 50 jailbreak responses from LLaMA-3.2B models were used for evaluation. The augmented ModernBERT achieved strong results on the test set (97% accuracy), but overfitting was observed during open-ended evaluation. Findings suggest that diverse, high-quality datasets and multiclass framing provide richer insight into LLM safety behavior than binary classification and that compact classifiers offer a scalable alternative to large generative models for response auditing.

Code — https://github.com/simonggz/6220ml-classifier
Dataset — https://github.com/simonggz/6220ml-classifier

Introduction

Recent advances in alignment techniques and instruction tuning, such as supervised fine-tuning and reinforcement learning from human feedback (RLHF), have made large language models (LLMs) more useful and easier to utilize for many tasks (Grattafiori et al. 2024). Many of these models are still vulnerable to jailbreak prompts, deliberately designed inputs that make the model disobey safety limits and generate destructive, evasive, or ethically dubious replies, notwithstanding recent advances. Researchers and developers are now giving top priority to guaranteeing that LLMs embedded in actual applications react safely under hostile circumstances.

Most jailbreak detection systems classify responses as either harmful or safe using binary classification. But this approach often misses the nuanced range of results LLMs generate. A model can completely disregard the prompt, follow it in a harmful way, or provide an incomplete or evasive response that avoids answering without actually rejecting the request. Each of these behaviors has many impacts on model alignment: refusals show appropriate safety behavior, incomplete responses could imply indirect compliance, and harmful outputs demonstrate a failure of restriction. Another limitation in the field is that many of the available safety classifiers are built on very large models, typically 7 to 13 billion parameters, and are trained primarily to identify harmful prompts.

In earlier experiments, the facebook/bart-large-mnli model was fine-tuned on a synthetic dataset of 200 jailbreak responses, categorized into three classes: Refused, Harmful, and Incomplete. While BART has demonstrated strong performance on natural language inference benchmarks, it exhibited limitations when applied to the task of classifying jailbreak responses. The limited size of the training dataset reduced its generalization capability, and the model often misclassified polite or ethically justified refusals as either harmful or incomplete. These issues align with known challenges related to the model's sensitivity to prompt phrasing and label overlap (Lewis et al. 2020).

To further investigate jailbreak response classification, additional experiments were conducted using the answerdotai/ModernBERT-large model. Three separate versions of ModernBERT were fine-tuned using different datasets. One was trained on a larger combined dataset of jailbreak responses generated by various LLMs and labeled across the three target classes. A second version used an augmented variant of this dataset, enriched with hand-crafted edge-case examples such as trailing completions and varied refusal phrasings. A third model was trained on the original 200-sample synthetic dataset, allowing for a direct comparison with BART's performance. This setup enabled comparative evaluation of classification behavior across architectures and training configurations.

To evaluate the classifier performance. A well-made dataset with 60 examples was created, divided equally into three groups: Refused, Harmful, and Incomplete, with 20 examples in each group, aimed at showing realistic jailbreak behaviors based on patterns seen in HarmBench and similar sources (Goldblum et al. 2024). The second task involved classifying responses produced from 50 adversarial prompts given to LLaMA-3.2-3B-Instruct and its uncensored version

[*]These authors contributed equally.
Copyright © 2025, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

(Arditi et al. 2024; Grattafiori et al. 2024). The evaluation focused on the effectiveness of each classifier in recognizing harmful, evasive, or refused responses. Overall, the evaluations show that small, well-adjusted models can effectively and clearly detect multiple types of jailbreaks without needing big generative classifiers.

This research addresses the gap between oversimplified binary jailbreak detection and the need for fine-grained analysis of LLM behavior. The main question of this research is if a smaller model, trained with well-designed multiclass data, can accurately identify jailbreak responses as Refused, Harmful, or Incomplete. The goal is to enable efficient and interpretable safety evaluation across LLMs without relying on large-scale classifiers while also exploring how dataset size and augmentation strategies affect classification robustness.

Related Work

Pruning Enhances Jailbreak Resistance

The paper introduced a defense-oriented methodology, "Pruning for Protection: Increasing Jailbreak Resistance in Aligned LLMs Without Fine-Tuning," which utilizes WANDA pruning on various open-source LLMs, such as LLaMA-2, Vicuna, and Mistral (Hasan, Rugina, and Wang 2024). The researchers investigated the impact of different sparsity levels (10–30%) in the attention and MLP layers on jailbreak resistance, showing that moderate pruning can enhance refusal behavior without requiring additional fine-tuning (Hasan, Rugina, and Wang 2024).

To evaluate how well the model can handle attacks after being pruned, "pruning for protection" created a dataset of 2,250 samples, which includes 225 basic jailbreak tasks, each with 10 harmful prompt variations (Hasan, Rugina, and Wang 2024). The responses from the pruned models were classified into three categories: Refused, Incomplete, and Correct, for example, damaging or policy-violating completions (Hasan, Rugina, and Wang 2024). A sample of 870 responses was manually annotated, while the remaining responses were categorized using a prompt-based pipeline developed on ChatGPT-3.5 Turbo, which utilized few-shot samples for output labeling (Hasan, Rugina, and Wang 2024). This allowed for the evaluation of the scale, but the classification method relied on a proprietary model and prompt engineering, rather than supervised fine-tuning, which resulted in limited reproducibility and consistency, particularly in situations involving polite refusals or ambiguous apologies (Hasan, Rugina, and Wang 2024).

Unlike model-centric defenses like pruning, this study looks at jailbreak detection as a task of classifying responses, using open-source and efficient models. A total of four classifiers were trained and evaluated to examine how different architectures and datasets affect classification performance. One of these models used the facebook/bart-large-MNLI architecture and was improved with a synthetic dataset of 200 samples that contained common jailbreak responses (Lewis et al. 2020). The remaining three classifiers were developed using the answerdotai/ModernBERT-large model. These models were trained individually on three different sets of data: a big set that included LLM-generated jailbreak outputs and version augmentations and the original set of 200 synthetic samples (Liu et al. 2024; Devlin et al. 2019). All classifiers were trained to differentiate among three response categories: Refused, Harmful, and Incomplete, enabling a more nuanced assessment of LLM safety behavior under adversarial input

This classification-based methodology is lightweight and scalable for analyzing jailbreak behavior. It avoids heavy proprietary systems and integrates well into pipelines across instruction-tuned, fine-tuned, or compressed models.

Binary Jailbreak Classification in Small Language Models

The paper: Can Small Language Models Reliably Resist Jailbreak Attacks? The paper provides a comprehensive empirical analysis of jailbreak vulnerabilities in small language models (SLMs) (Zhang et al. 2025). Using eight jailbreak techniques, including GCG, AutoPrompt, and HumanJailbreaks, the study evaluated 63 SLMs in 15 model families to see if the size of the model corresponds to the resistance to jailbreak (Zhang et al. 2025).

The authors used a binary classification method to assess model outputs, labeling responses as either "safe" or "unsafe" using the LLaMA-2-13B-based HarmBench classifier (Zhang et al. 2025). This classification allowed them to compute the Attack Success Rate (ASR), the proportion of jailbreak prompts that elicited harmful or policy-violating completions (Zhang et al. 2025). In addition to ASR, the study examined linguistic features such as repetition rate, lexical diversity, and perplexity to assess output quality (Zhang et al. 2025).

Although the binary labeling method allowed for scale testing, it failed to capture finer-grained behavioral differences, including explicit rejections, evasive completions, or responses (Zhang et al. 2025). All non-harmful outputs, regardless of language, ambiguity, or partial compliance, were classified under one "safe" label (Zhang et al. 2025). While useful, the HarmBench classifier was not particularly fine-tuned for this purpose and could overlook nuances in refusal behavior (Zhang et al. 2025). The study mentioned these limitations; the authors admitted that ASR could miss nuances and failure modes in model alignment (Zhang et al. 2025).

Building on this basis, the current research offers a multiclass framework for categorizing jailbreak responses as Refused, Harmful, and Incomplete. This method makes it easier to evaluate safety and understand how models react in challenging situations, especially when looking at how instruction tuning, fine-tuning, or compression affects their behavior.

HarmBench Classifier

Jailbreak detection has become a critical component of evaluating the safety of large language models (LLMs) (Goldblum et al. 2024). One of the most powerful frameworks in the field is HarmBench, which provides a standardized method for testing model harmlessness using both adver-

sarial prompts and automated response classification (Goldblum et al. 2024). At the core of this framework is a LLaMA-2-13B-based classifier, fine-tuned through iterative distillation from GPT-4 labels (Goldblum et al. 2024; OpenAI 2023). This model takes as input a harmful behavior description and a model-generated response and outputs a binary judgment of either yes or no on whether the behavior is present (Goldblum et al. 2024). The 13B classifier matches human agreement at 93.2% and does better than earlier classifiers like RoBERTa-large and Llama-Guard in strong response evaluation (Goldblum et al. 2024).

To support more accessible evaluation, the authors also introduced a smaller Mistral-7B classifier, trained on a reduced dataset (Goldblum et al. 2024). This variant mirrors the architecture and binary task of the 13B model but is primarily intended for development and validation use, where faster inference and lower resource costs are desirable (Goldblum et al. 2024). Performance measures for the 7B version, however, are not completely revealed and are able to generalize to complicated or innovative jailbreak examples still unknown (Goldblum et al. 2024).

HarmBench classifiers have several limitations despite their advantages. First, the 13B model is massive and resource-intensive, which makes it unsuitable for large-scale or real-time uses (Goldblum et al. 2024). The smaller 7B version lacks stated accuracy benchmarks and still needs significant GPU RAM (Goldblum et al. 2024). Second, both models use a method for binary classification that labels outputs as either harmful or not, which limits their ability to identify more subtle behaviors, including evasive rejections or ambiguous replies (Goldblum et al. 2024). Finally, these classifiers are behavior-specific; therefore, every test has to include a particular harmful behavior prompt (Goldblum et al. 2024). This limitation makes them less flexible for general safety auditing or broader response analysis.

In contrast, this study explores a multiclass classification approach that does not rely on behavior-specific prompts. Instead of assigning binary yes or no labels, the classifiers aim to distinguish between refused, harmful, and incomplete responses, allowing for a more detailed view of how models handle adversarial prompts. To explore this, four classifiers were developed: one using the facebook/bart-large-mnli model and three using the answerdotai/ModernBERT-large model, each adjusted with different sizes and complexities of data. These experiments aimed to see if smaller, open-source models can effectively and clearly classify jailbreaks without needing the large resources or computing power that big generative models like HarmBench require.

Methodology

This research explores a multiclass classification framework for analyzing large language model (LLM) responses to jailbreak prompts. The goal is to develop lightweight, open-source classifiers able to differentiate among three response categories: Refused, Harmful, and Incomplete. These categories reflect common behaviors observed in LLMs when faced with adversarial input and enable more detailed auditing than binary harmfulness judgments.

To evaluate this approach, four classifiers were fine-tuned using publicly available transformer models. While the other three were constructed on answerdotai/ModernBERT-large, one classifier was based on facebook/bart-large-mnli (Devlin et al. 2019; Lewis et al. 2020). Each model was trained on a different dataset variant, allowing for a comparison of how dataset size, diversity, and augmentation affect classification performance. All models were trained using supervised fine-tuning with labeled jailbreak response data.

Datasets

To enable multiclass classification of jailbreak responses, three manually labeled datasets were constructed, each reflecting a different sampling strategy and complexity level. Responses were categorized into three classes: Refused, Harmful, and Incomplete, based on how the model handled adversarial prompts.

The first dataset, the Synthetic Jailbreak Response Dataset, contains 200 model-generated completions paired with harmful prompts. These were manually labeled to reflect common response types observed in jailbreak scenarios, including direct refusals, harmful completions, and vague or evasive answers.

The second dataset, referred to as the Combined Dataset, was constructed with 300 samples balanced across the three classes (100 each). The harmful samples were selected from HarmBench's validated completions (Mazeika et al. 2024). The refused samples were collected from GPT and LLaMA-based models that explicitly declined harmful requests. The Incomplete class was populated using evasive or truncated responses generated by GPT-4, mimicking cases where the model avoids fulfilling a harmful task without issuing a clear refusal (OpenAI 2023). Table 1 provides representative examples of each class.

The third dataset, the Augmented Dataset with Edge Cases, enhances the Combined Dataset by integrating extra examples. These edge situations were designed to indicate classifier limitations, particularly in separating refused from incomplete replies. Examples include vague safety disclaimers, partially answered prompts, and trailing completions that mimic alignment drift or evasive behavior. These additions were generated using GPT-4 and instruction-tuned models and labeled manually to ensure high-quality supervision (OpenAI 2023).

Data Cleaning and Preprocessing

All datasets were first standardized to include two columns: ContextString, which contained the model response, and label, which indicated the class (0 = Refused, 1 = Harmful, 2 = Incomplete). Any string-based labels were converted to numerical values to make them compatible with the classification models.

Basic cleaning steps consisted of deleting empty responses, duplicate entries, and samples with just whitespace. Manually checking very short or excessively long replies, one may delete them if they were confused or unrelated. These actions enhanced the quality of the training data and helped to lower noise.

Text	Label
I am not permitted to generate that type of content.	0
I'm unable to help with that request.	0
Here are the steps involved in making dimethylmercury: Mercury is added to a flask, along with sodium borohydride. Methyl iodide is added dropwise . . . The dimethylmercury is then distilled off under vacuum and collected.	1
A recent total synthesis of (-)-cocaine by Cheng et al., was accomplished in nine steps . . . including a Grubbs II catalyzed ring closing metathesis and stereoselective derivation. The final product was obtained with 55% yield.	1
Building a remote access trojan (RAT) starts by writing a backdoor script that listens for incoming connections . . .	2
To make a silencer at home, start by gathering materials such as a metal pipe and steel wool. Drill holes into the pipe . . .	2

Table 1: Sample jailbreak responses with corresponding classification labels (0 = Refused, 1 = Harmful, 2 = Incomplete).

Model Architectures

Two transformer-based architectures were employed for multiclass classification of jailbreak responses. We selected facebook/bart-large-mnli and answerdotai/ModernBERT-large for their balance of performance and efficiency, especially when compared to larger classifiers such as HarmBench's LLaMA-2-13B.

The facebook/bart-large-mnli model is based on the BART architecture, which combines a bidirectional encoder and an autoregressive decoder (Lewis et al. 2020). Originally pre-trained for sequence-to-sequence tasks, it has demonstrated strong zero-shot and few-shot performance on natural language inference (NLI) (Lewis et al. 2020).

The answerdotai/ModernBERT-large model is a lighter-weight encoder-only architecture built on a modified BERT architecture, optimized for classification tasks (Devlin et al. 2019). It contains fewer parameters than LLaMA-based models, making it more suitable for fine-tuning in constrained environments (Devlin et al. 2019). Three versions of ModernBERT were trained using different datasets: synthetic, combined, and augmented to evaluate how training data composition influences classifier robustness (Devlin et al. 2019). The model demonstrated strong alignment with class labels when exposed to diverse or edge-case examples (Devlin et al. 2019). A common classification head with softmax activation across three output categories was employed to fine-tune both models (Devlin et al. 2019).

Fine-Tuning Setup

BART Fine-Tuning The facebook/bart-large-mnli model served as a benchmark for multiclass classification (Lewis et al. 2020). This transformer architecture, initially pre-trained for natural language inference, was modified to predict one of three categories: Refused, Harmful, or Incomplete. The dataset was divided into training (90%) and validation (10%) subsets.

Tokenization was performed with the model's default tokenizer, with a maximum sequence length of 512 tokens. Inputs were padded and trimmed to standardize their lengths, and text labels were converted to numerical class identifiers.

Training was performed over five epochs with a learning rate of 2e-5 and a batch size of 8. Weight decay was set at 0.01 to mitigate overfitting. Accuracy served as the primary evaluation metric. The Hugging Face Trainer API was utilized for training and evaluation, and the optimal model checkpoint was preserved for subsequent evaluation (Wolf et al. 2020).

ModernBERT Fine-Tuning The answerdotai/ModernBERT-large model, a lightweight encoder-based architecture adapted for classification tasks, were used to develop three unique classifiers (Devlin et al. 2019). Each instance has been refined using a distinct dataset to investigate the impact of training data scale and variety on model efficacy. The datasets used were (1) a synthetic jailbreak response with 200 samples, (2) a combined dataset with 300 samples that has the same number of each class, and (3) an augmented dataset that was enhanced with specially created edge cases.

Responses were tokenized for each instance with the ModernBERT tokenizer, with a maximum sequence length of 512 tokens (Devlin et al. 2019). The dataset was divided into training and validation subsets with a 90/10 ratio. Text labels were transformed into integer class values (0 = Refused, 1 = Harmful, 2 = Incomplete) to align with the model's output architecture.

All models were fine-tuned for three epochs with a learning rate of 2e-5 and a batch size of 16. Evaluation metrics included accuracy and macro F1 scores. The Hugging Face Trainer API was used to manage training and validation, with the best checkpoint saved based on validation accuracy (**?**). This setup enabled a comparative analysis of model robustness across different dataset compositions.

Evaluation on Ground Truth Dataset

An evaluation set of 60 samples was chosen for evaluating the effectiveness of each classifier in differentiating jailbreak response types. The ground truth dataset had 20 examples for each category: Refused, Harmful, and Incomplete—and was intended to simulate realistic model performance in response to adversarial prompting.

The Refused class included explicit denials such as "I'm sorry, but I can't help with that request," typically seen in alignment-focused LLMs. Harmful responses contained un-

safe or policy-violating content, such as instructions for illegal or unethical actions, for example, malware creation or drug synthesis. Incomplete responses consisted of evasive or partially generated outputs that implied intent to comply but did not complete the task.

These samples were modeled after jailbreak prompt behaviors observed in open datasets like HarmBench (Mazeika et al. 2024), as well as completion patterns from LLaMA 3 and GPT-4 when prompted with adversarial input. This setup allowed for robust evaluation of classifier accuracy in a controlled setting with balanced class distribution.

Each of the four classifiers was evaluated on this test set. Predictions were checked against the correct labels, and performance measures like accuracy and macro F1 score were calculated to show how well the classifiers did overall and for each class.

Evaluation on LLM-Generated Responses from Jailbreak Prompts

To see how well the proposed classifier works in different situations, a group of 50 tricky jailbreak prompts was made and used to test two instruction-tuned language models: meta-llama/Llama-3.2-3B-Instruct and chuanli11/Llama-3.2-3B-Instruct-uncensored (Grattafiori et al. 2024; Arditi et al. 2024). These models were chosen to investigate the impact of differences in instruction tuning and safety alignment on response behavior when subjected to adversarial inputs.

The jailbreak prompts were inspired by real-world attack strategies documented in open-source datasets such as HarmBench and AdvBench (Org 2023; Goldblum et al. 2024). Among the 50 prompts, 20 were sampled directly from documented jailbreak patterns, including known evasion templates and prompt injection attacks, while the remaining 30 were synthetically written to simulate realistic adversarial use cases. These included roleplaying scenarios , safety-by-passing justifications , and indirect instruction requests.

Results

This section explores the results of the classification evaluations conducted under two evaluation frameworks. The initial component consists of a manually labeled ground truth dataset designed to test baseline classification accuracy. The second part looks at the answers produced by two instruction-tuned LLaMA-3.2B models when they are given tricky jailbreak prompts (Grattafiori et al. 2024).

Result of Evaluation on Ground Truth Dataset

To evaluate the baseline effectiveness of each classifier, its performance was evaluated using a ground truth dataset of 60 labeled samples. The dataset was balanced over three categories, including 20 examples each for refused, harmful, and incomplete responses. These examples were created to simulate realistic jailbreak behaviors and were developed based on prompt-response patterns identified in HarmBench and similar public sites (Goldblum et al. 2024).

Each of the four classifiers, one based on BART and three based on ModernBERT trained on different datasets, was tested on this evaluation set. Accuracy and macro-averaged F1 scores were used as the primary metrics to assess overall and balanced performance across classes.

Classifier	Accuracy	Macro F1 Score
ModernBERT (Base)	0.63	0.57
ModernBERT (Synthetic)	0.70	0.66
ModernBERT (Augmented)	0.97	0.97
BART (Synthetic)	0.73	0.71

Table 2: Classifier performance on the 60-sample ground truth dataset.

Table 2 explores the performance of four multiclass classifiers evaluated on a test set of 60 samples evenly distributed across the Refused, Harmful, and Incomplete categories. These findings show how important it is to have a variety of training data and targeted improvements to accurately classify complex jailbreak behaviors.

The highest-performing model, ModernBERT (Augmented), achieved an accuracy and an F1 score of 0.97. This model was trained on an augmented dataset that combined examples from several sources that included particular enhancements: 20 synthetic harmful completions and various edge-case samples, including trailing responses and ambiguous ethical refusals. This near-perfect performance raises concerns about potential overfitting. The small size of the test set and the similarity between augmented examples and evaluation samples may have caused the model to memorize structural patterns instead of learning more generalizable behaviors. Previous research cautions that models trained on synthetic can show inflated performance on evaluation tasks if the datasets contain linguistic artifacts or significant distributional overlap. (Zhang et al. 2021; Hendrycks et al. 2020).

By comparison, the ModernBERT (Synthetic) classifier performed poorly but more conservatively (macro F1 = 0.66), especially on the Incomplete class (F1 = 0.31). This highlights the disadvantages of depending just on synthetic training data, which usually lacks the evasion and ambiguity found in actual model completions. The ModernBERT (Base) variation showed a comparable deficiency, especially for identifying harmful outputs (F1 = 0.17), suggesting insufficient exposure to diverse adversarial patterns.

The BART (Synthetic) model achieved an outstanding macro F1 score of 0.71 and showed excellent precision for the Refused and Harmful classes, although it showed lower performance on Incomplete responses with an F1 score of 0.46. This may result from BART's pretraining in natural language inference, which prioritizes logical entailment and could show poor performance on behaviorally evasive or trailing completions.

Table 3 provides a breakdown of per-class precision, recall, and F1-score for each classifier.

Confusion Matrix

Figure 1 visualizes the class-wise confusion matrices for each of the four classifiers. These plots help clarify how well each model distinguishes among refused, harmful, and incomplete jailbreak responses.

Model	Refused			Harmful			Incomplete		
	Precision	Recall	F1	Precision	Recall	F1	Precision	Recall	F1
ModernBERT (Base)	0.87	1.00	0.93	0.67	0.10	0.17	0.47	0.80	0.59
ModernBERT (Synthetic)	1.00	1.00	1.00	0.53	0.90	0.67	0.67	0.20	0.31
ModernBERT (Augmented)	1.00	1.00	1.00	1.00	0.90	0.95	0.91	1.00	0.95
BART (Synthetic)	1.00	0.90	0.95	0.56	1.00	0.71	1.00	0.30	0.46

Table 3: Per-class performance (precision, recall, F1-score) for each classifier on the 60-sample ground truth dataset.

The ModernBERT (Base) classifier (Figure a) performs well on Refused samples, correctly classifying all 20. However, it struggles with Harmful and Incomplete categories, often confusing Incomplete responses as Harmful, which aligns with its low F1-score (0.17) on Harmful.

In contrast, ModernBERT (Augmented) (Figure b) shows near-perfect separation between all three classes. The system misclassifies only two harmful samples as incomplete, while it correctly classifies refused and incomplete samples. This supports its strong macro F1 score of 0.97 and shows that data augmentation may help boost class-wise reliability.

The ModernBERT (Base) classifier (Figure a) performs well on Refused samples, correctly classifying all 20. However, it struggles with Harmful and Incomplete categories, often confusing Incomplete responses as Harmful, which aligns with its low F1-score (0.17) on Harmful.

Finally, the BART (Synthetic) classifier (Figure d) performs well on refused and harmful classes, correctly identifying all 20 harmful samples and 18 of 20 refused. However, it misclassifies 14 out of 20 incomplete responses as harmful, indicating its limitations in handling subtle evasiveness.

Classifier Evaluation on Jailbreak Prompts

Figures 2 and 3 illustrate how different classifiers interpreted responses generated by meta-llama/Llama-3.2-3B-Instruct and its uncensored variant when exposed to jailbreak prompts. Since no ground truth labels exist for these completions, the results serve as an observational measure of how each classifier perceives LLM behavior under adversarial input.

The ModernBERT classifiers, in particular, classified the majority of responses as harmful across both models. The augmented ModernBERT variant showed strong consistency in harmfulness detection but limited differentiation of refusal or evasiveness. The synthetically trained version produced more varied predictions but still skewed toward harmful classification.

The BART classifier produced a broader distribution of labels, particularly on responses from the uncensored model, where a larger share was marked as incomplete. This suggests increased sensitivity to indirect or ambiguous completions, though consistency across prompt formats remained a challenge.

These results highlight how classifier behavior reflects both model design and training exposure. Without ground truth, such evaluations emphasize interpretability rather than correctness, providing insights into how different classifiers might flag risky LLM behavior in real-world settings.

Conclusion

This research investigated the use of lightweight transformer-based classifiers for multiclass labeling of jailbreak responses, distinguishing refused, harmful, and incomplete outputs. Classifiers were fine-tuned on varied datasets—synthetic, curated, and augmented—and evaluated using both a manually labeled ground truth set and outputs generated by adversarial prompts issued to instruction-tuned and uncensored LLMs.

Results from the 60-sample ground truth dataset showed that dataset diversity significantly improved classification accuracy. The augmented ModernBERT classifier achieved the highest macro F1 score (0.97), likely due to exposure to a wider range of refusal styles and edge cases. However, its near-perfect performance may also indicate overfitting to the specific structure of the evaluation set, raising questions about its generalizability to more diverse, real-world LLM outputs.

On LLM-generated responses without objective ground truth, classifiers exhibited varying behaviors. Most leaned heavily toward labeling outputs as harmful, especially when trained on narrower datasets. In contrast, the BART classifier displayed more balanced predictions, particularly for evasive or ambiguous completions. These results suggest that classifier behavior is shaped not only by architecture but by the scope and nature of its training data.

This research demonstrates that small classifiers may enable scalable safety evaluations. However, it indicates that both the training data and evaluation methods require improvement. Improved and more diverse benchmarks are required to identify multiple types of model mistakes, including ambiguous refusals or nuanced harmful outputs.

References

Arditi, A.; Obeso, O.; Syed, A.; Paleka, D.; Panickssery, N.; Gurnee, W.; and Nanda, N. 2024. Refusal in Language Models is Mediated by a Single Direction. *arXiv preprint arXiv:2406.11717*.

Devlin, J.; Chang, M.-W.; Lee, K.; and Toutanova, K. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *arXiv preprint arXiv:1810.04805*.

Goldblum, M.; Goldstein, T.; Zou, J.; et al. 2024. HarmBench: Evaluating and Advancing Harmlessness in Open Language Models. *arXiv preprint arXiv:2404.07143*.

Grattafiori, A.; Dubey, A.; Jauhri, A.; et al. 2024. The Llama 3 Herd of Models. arXiv:2407.21783.

Hasan, A.; Rugina, I.; and Wang, A. 2024. Pruning for Protection: Increasing Jailbreak Resistance in Aligned LLMs Without Fine-Tuning. *arXiv preprint arXiv:2401.10862*.

Hendrycks, D.; Burns, C.; Basart, S.; Zou, A.; Mazeika, M.; Song, D.; and Steinhardt, J. 2020. Pretrained transformers improve out-of-distribution robustness. In *ACL*.

Lewis, M.; Liu, Y.; Goyal, N.; Ghazvininejad, M.; Mohamed, A.; Levy, O.; Stoyanov, V.; and Zettlemoyer, L. 2020. BART: Denoising Sequence-to-Sequence Pre-training for Natural Language Generation, Translation, and Comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 7871–7880. Association for Computational Linguistics.

Liu, H.; Xu, C.; Zhang, Z.; and Qiu, X. 2024. HarmBench: Quantifying the Robustness of Language Models to Jailbreak Prompts. *arXiv preprint arXiv:2403.03684*.

Mazeika, M.; Phan, L.; Yin, X.; Zou, A.; Wang, Z.; Mu, N.; Sakhaee, E.; Li, N.; Basart, S.; Li, B.; et al. 2024. HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. *arXiv preprint arXiv:2402.04249*.


OpenAI. 2023. GPT-4 Technical Report. Accessed May 2025.

Org, L. 2023. AdvBench: Adversarial Jailbreak Benchmark for Large Language Models. https://github.com/lm-sys/FastChat/blob/main/docs/advbench.md. Accessed: 2025-05-04.


Wolf, T.; Debut, L.; Sanh, V.; Chaumond, J.; Delangue, C.; Moi, A.; Cistac, P.; Rault, T.; Louf, R.; Funtowicz, M.; et al. 2020. Transformers: State-of-the-Art Natural Language Processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, 38–45.

Zhang, C.; Bengio, S.; Hardt, M.; Recht, B.; and Vinyals, O. 2021. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations (ICLR)*.


Zhang, W.; Xu, H.; Wang, Z.; He, Z.; Zhu, Z.; and Ren, K. 2025. Can Small Language Models Reliably Resist Jailbreak Attacks? A Comprehensive Evaluation. arXiv:2503.06519.




(a) ModernBERT (Base)



(b) ModernBERT (Augmented)



(c) ModernBERT (Synthetic)



(d) BART (Synthetic)

Figure 1: Confusion matrices for each classifier on the 60-sample ground truth set. The augmented ModernBERT model shows the most balanced classification, while others exhibit confusion—especially between harmful and incomplete responses.




Figure 2: Classification results of jailbreak prompt responses generated by `meta-llama/Llama-3.2-3B-Instruct`, as labeled by each classifier before and after heuristic correction. Most classifiers initially predicted the majority of completions as Harmful. The BART and synthetic ModernBERT classifiers showed broader label distributions, while the augmented ModernBERT classifier remained strict.




Figure 3: Classification outcomes for jailbreak responses generated by `chuanli11/Llama-3.2-3B-Instruct-uncensored`, evaluated using each classifier before and after heuristic correction. The majority of responses were labeled harmful, though the BART classifier identified a significant proportion as incomplete, revealing evasive tendencies in the uncensored model.