



Workshop: Data Wrangling of Web Data in R

Simon Ress | Ruhr-Universität Bochum

October 18, 2021

1. Setup
2. Functions
3. Iteration: Loops & Apply-family
4. Dplyr - Grammar of Data Manipulation
5. Purr
6. Helpful Sources

Setup

Meta information

- Finanzausschuss
- Ausschüsse der 19. Wahlperiode (2017-2021)
- Öffentliche Anhörungen

URL: <https://www.bundestag.de/webarchiv/Ausschuesse/ausschuesse19/a07/Anhoerungen>

Unit information

- Committees

URL: Needs to be scraped from main page

Configure & Start Selenium/Browser

```
library(RSelenium)
library(rvest) #for read_html(), html_elements()...
#Free all ports
  system("taskkill /im java.exe /f", intern=FALSE,
    ↪ ignore.stdout=FALSE)
#Start a selenium & Assign client to an R-object
rD <- rsDriver(port = 4561L, browser = "firefox")
remDr <- rD[["client"]]
```

Functions

Overview

- Functions are **blocks of codes** which can be executed repeatedly by calling them
- **Parameters** (data) can be passed into them, which are used by the code inside
- **Data can be returned** from a function

Syntax:

```
function_name <- function(arg_1, arg_2, ...) {  
  Function body  
}
```

Function Components

The four parts of a function are:

- **Function Name:** This is the actual name of the function. It is stored in R environment as an object with this name.
- **Arguments (*optional*):** An argument is a placeholder. When a function is invoked, you pass a value to the argument. Arguments *can* have default values.
- **Function Body:** The function body contains a collection of statements that defines what the function does.
- **Return Value:** The return value of a function is the last expression in the function body to be evaluated.

Exemplary Function

```
square <- function(value = 1, factor = 1) {  
  return(value^factor)  
}  
square() #use default args
```

```
## [1] 1
```

```
square(2,3) #use args by position
```

```
## [1] 8
```

```
square(factor=2, value=5) #use args by name
```

```
## [1] 25
```

Define savepage()

```
#Load url & return content as r-object
savepage <- function(url){
  #Navigate to starting page
  remDr$navigate(url)
  #Wait until page is loaded
  Sys.sleep(abs(rnorm(1, 2, 1)))
  #Save content to an R-object
  remDr$getPageSource(header = TRUE)[[1]] %>%
    read_html() %>%
    return()
}
```

Note: `[[1]]` behind `getPageSource()` unlist the output -> makes it searchable

Usage of savepage()

```
#navigate to url & save content as r-object  
page <- savepage("https://www.bundestag.de/  
  ↪ webarchiv/Ausschuesse/ausschuesse19/a07/  
  ↪ Anhoerungen")  
page
```

```
## {html_document}  
## <html xml:lang="de" dir="ltr" class="detection-firefox"  
## [1] <head>\n<meta http-equiv="Content-Type" content="te  
## [2] <body class="bt-archived-page">\n  <div class="bt-a
```

Iteration: Loops & Apply-family

Overview

- Often specific tasks need to be executed multiple times
- Iteration can be performed using loops or apply-functions

Example:

```
#Extract urls of all indiv. meetings
  urls <- html_elements(page, xpath =
  ↪  "/html//ul/li/a") %>%
    html_attr("href") %>%
    paste0("https://www.bundestag.de",..)
#Save content of pages
  meeting1 <- savepage(urls[1])
  meeting2 <- savepage(urls[2])
  meeting3 <- savepage(urls[3])
  ...
```

for-loop

- A for loop is used for iterating over a sequence:
- With the break statement, we can stop the loop before it has looped through all the items:
- With the next statement, we can skip an iteration without terminating the loop:

```
for (x in names(iris[1:4])) {  
  print(mean(iris[,x]))  
}
```

```
## [1] 5.843333  
## [1] 3.057333  
## [1] 3.758  
## [1] 1.199333
```

for-loop: break

Breaking the loop at certain conditions

```
for (x in cars$dist) {  
  if (x > 20) break  
  print(x)  
}
```

```
## [1] 2  
## [1] 10  
## [1] 4
```

for-loop: next

Skip the code below and start over at certain conditions

```
fruits <- list("apple", "banana", "cherry")
```

```
for (x in fruits) {  
  if (x == "banana") next  
  print(x)  
}
```

```
## [1] "apple"  
## [1] "cherry"
```


loop over urls

- Create an empty list
- save content of page pages as list within first list

```
meetings <- list()
for (i in 1:length(urls)) {
  meetings[i] <- savepage(urls[i]) %>% list()
}
```

while-loop

- Execute a set of statements as long as a condition is TRUE
- *break* statement stops the loop (even if while-condition=TRUE):
- *next* statement skips an iteration without terminating the loop:

```
i <- 0
while (i < 3) {
  i <- i + 1
  print(i)
}
```

```
## [1] 1
## [1] 2
## [1] 3
```

while-loop: break

Breaking the loop at certain conditions

```
i <- 0
while (i < 20) {
  i <- i + 1
  if (i == 5) break
  print(i)
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
```

while-loop: next

Skip the code below and start over at certain conditions

```
i <- 0
while (i < 10) {
  i <- i + 1
  if (i %% 2) next
  print(i)
}
```

```
## [1] 2
## [1] 4
## [1] 6
## [1] 8
## [1] 10
```

Collect urls of all meetings

```
page <-
  ↪ savepage("https://www.bundestag.de/webarchiv/Ausschuesse/aus
button <- 1
while (length(button)>0) {
  page <- remDr$getPageSource(header = TRUE)[[1]] %>%
    read_html()
  urls <- html_elements(page, xpath =
    ↪ "/html/body/main/section/div[2]/div/div/div/div/div/ul/li/a"
    ↪ %>%
    html_attr("href") %>%
    paste0("https://www.bundestag.de",..)

  webElem <- remDr$findElement("css", "body")
  webElem$sendKeysToElement(list(key = "end"))

  # find the element
  button <-
    ↪ remDr$findElements("/html/body/main/section/div[2]/div/div/d
    ↪ = "xpath")
  if(length(button)>0) {
    button[[1]]$clickElement()
  }
}
```

- The apply in R function can be feed with many functions to perform redundant application on a collection of object (data frame, list, vector, etc.).
- The purpose of `apply()` is primarily to avoid explicit uses of loop constructs.
- Any function can be passed into

Main apply functions

Function	Arguments	Objective	Input	Output
apply	apply(x, MARGIN, FUN)	Apply a function to the rows or columns or both	Data frame or matrix	vector, list, array
lapply (list)	lapply(X, FUN)	Apply a function to all the elements of the input	List, vector or data frame	list
sapply (simple)	sapply(X, FUN)	Apply a function to all the elements of the input	List, vector or data frame	vector or matrix
tapply (tagged)	tapply(X, grouping, FUN)	Apply a function for each factor variable in an vector	Vector	matrix or array

apply()-usage

```
apply(x, MARGIN, FUN)
```

```
m1 <- matrix(C<-(1:10),nrow=4, ncol=4)
```

```
apply(m1, 1, sum) #1=by row
```

```
## [1] 18 22 16 20
```

```
apply(m1, 2, sum) #2=by column
```

```
## [1] 10 26 22 18
```


lapply()-usage

```
lapply(X, FUN)
```

```
lapply(cars, mean)
```

```
## $speed  
## [1] 15.4  
##  
## $dist  
## [1] 42.98
```

sapply()-usage

```
sapply(X, FUN)
```

```
sapply(1:4, print)
```

```
## [1] 1
```

```
## [1] 2
```

```
## [1] 3
```

```
## [1] 4
```

```
## [1] 1 2 3 4
```

tapply()-usage

```
tapply(X, grouping, FUN)
```

```
tapply(iris$Sepal.Length , list(iris$Species), mean)
```

```
##      setosa versicolor  virginica  
##      5.006      5.936      6.588
```

Similar to `tapply()` is `aggregate()` which returns a data frame

```
aggregate(iris$Sepal.Length , list(iris$Species), mean)
```

```
##      Group.1      x  
## 1      setosa 5.006  
## 2 versicolor 5.936  
## 3  virginica 6.588
```

Dplyr - Grammar of Data Manipulation

Overview

Pipe-Operator

filter()

summarise()

across

group_by()

ungroup()

rowwise()

mutate()

select

Purrr

“purrr enhances R’s functional programming (FP) toolkit by providing a complete and consistent set of tools for working with functions and vectors.”

map-functions:

- transform input by applying a function to each element of a list or atomic vector
- returning an object of the same length as the input

map()

```
if(!require("purrr")) install.packages("purrr")
library(purrr) # for fill()
mtcars %>%
  split(.$cyl) %>% # from base R
  map(~ lm(mpg ~ wt, data = .)) %>%
  map(summary) %>%
  map_dbl("r.squared")
```

```
##           4           6           8
## 0.5086326 0.4645102 0.4229655
```

Extract dates of meetings

```
page <-  
  ↪ savepage("https://www.bundestag.de/webarchiv/Ausschuess  
date <- html_elements(page, xpath =  
  ↪ "/html/body/main/section/div[2]/div/div/div/div/div[@c  
  ↪ 'bt-listenteaaser']") %>%  
  map(function(x)  
    rep(html_element(x, xpath = "./h4") %>%  
      html_text(),  
      length(html_elements(x, xpath = "./a"))))  
date[3]
```

```
## [[1]]  
## [1] "17. Mai 2021" "17. Mai 2021"
```

Helpful Sources

Helpful Sources

- `purrr`: Overview
- `purrr`: References
- `purrr`: Cheat Sheet
- `dplyr`: Cheat Sheet