

Photon-Weave

Simon Sekavčnik¹, Kareem El-Safty¹, and Janis Nötzel¹

¹ Technical University of Munich, Theoretical Quantum System Design, Munich, Germany

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Photon Weave is a quantum systems simulator designed to offer intuitive abstractions for simulating photonic quantum systems and their interactions in a Fock space (Fock, 1932) along with any custom Hilbert space. The simulator focuses on simplifying complex quantum state representations, such as photon pulses (envelopes) with polarization, making it more approachable for specialized quantum simulations. While general-purpose quantum simulation libraries such as QuTiP (Johansson et al., 2012) provide robust tools for quantum state manipulations, they often require meticulous operations organization for complex simulations that might require professional experience in software skills. Photon Weave addresses this by abstracting such details, streamlining the simulation process, and allowing quantum systems to interact naturally as the simulation progresses.

In contrast to other frameworks such as Qiskit (Aleksandrowicz & others, 2019), which are primarily designed for qubit-based computations, Photon Weave excels at simulating continuous-variable quantum systems, mainly photons, as well as custom quantum states that can interact dynamically. Furthermore, Photon Weave offers a balance of flexibility and automation by deferring the joining of quantum spaces until necessary, enhancing computational efficiency. The simulator supports both CPU and GPU execution, ensuring scalability and performance for large-scale simulations. This is achieved by using the JAX (Bradbury et al., 2018) library.

Statement of Need

Tools like QuTiP, Qiskit, Piquasso, and Strawberry Fields (Killoran et al., 2019; Kolarovszki et al., 2024) already exist for modeling quantum phenomena, but many of them either require extensive user control (QuTiP) or enforce rigid circuit structures (Strawberry Fields). Researchers in quantum optics and related fields need a tool that simplifies photonic systems simulations, supports dynamic interactions between custom quantum systems, and eliminates the need for a circuit model. Such a tool could be used to generate a library of devices and gates that closely model real-world devices, fostering greater collaboration among scientists in those fields.

Photon Weave Overview

Photon Weave is a quantum simulation library designed for simulating any system, provided that simulating hardware meets the resource requirements. With this simulator, users can easily create, manipulate, and measure quantum systems.

Photon Weave Implementation Details

In the following sections, we will describe the main features of Photon Weave; details about implementations and usage can be found in [the documentation](#).

38 State Containers

39 Photon Weave's core functionality revolves around quantum state containers. States can
40 be represented in three forms: Label, Vector, or Matrix, which progressively require more
41 memory. Photon Weave automatically manages these representations, which will shrink repre-
42 sentations where applicable to save resources. The framework provides state containers such as
43 Fock, Polarization, Envelope, and CustomState. Fock, Polarization, and CustomState
44 are essential state containers that hold the quantum state in any valid representation until
45 the state is joined with other states. When states are joined, these containers store references
46 to the Envelope, CompositeEnvelope, or both. This allows each container to understand its
47 place within a larger product space and how it is tensorized.

48 Envelopes

49 Photon Weave places a particular emphasis on the Envelope concept. An Envelope represents
50 a pulse of light, where all photons are indistinguishable and share the same polarization,
51 representing the $\mathcal{F} \otimes \mathcal{P}$ space. Initially, when the states are separable, their states are stored
52 in the respective Fock and Polarization containers. In addition to the states, an Envelope
53 holds essential metadata such as wavelength and temporal profile.

54 Composite Envelopes

55 When envelopes interact, such as at a beam-splitter (Xiang-Bin, 2002), their states need to be
56 joined. In these cases, the necessary state data is extracted from their respective containers
57 and tensorized into a product state. A CompositeEnvelope can contain multiple product
58 spaces, which can be accessed from any of the contributing state containers. Additionally,
59 CompositeEnvelope instances can be merged, allowing states within both envelopes to interact.
60 Since any custom state can, in principle, interact with any other state, CustomState instances
61 can also be included in a CompositeEnvelope.

62 Operations

63 Photon Weave provides several ways to perform operations on quantum states. All op-
64 erations are created using specialized classes (FockOperation, PolarizationOperation,
65 CustomStateOperation, and CompositeOperation), each designed to work on a specific type
66 of state. Operations can be predefined, manually constructed, or generated using expressions
67 with a context.

```
context = {
    "n": Lambda dims: number_operator(dims[0])
}
op = Operation(
    FockOperationType.Expression,
    expr=("expm", ("s_mult", -1j, jnp.pi, "n")),
    context=context,
)
```

68 Photon Weave optimizes resource usage by automatically adjusting the dimensionality of
69 the Fock space when necessary, even within product states. This ensures that only the
70 minimal required space is used, dynamically resizing the quantum state representation to avoid
71 unnecessary memory consumption.

72 Once an operation is defined, it can be applied to the state at any level. If the state is part of
73 a product state, Photon Weave ensures that the operation is applied to the correct subspace.
74 Additionally, quantum channels defined by Kraus operators can be applied to any desired state
75 space.

76 Measuring

77 Photon Weave offers a robust measurement framework for any state. By default, Fock spaces
78 are measured in number basis, Polarization spaces are measured in computational basis, and
79 CustomState is measured in the respective basis. Photon Weave also supports more precise
80 measurement definitions, such as POVM measurement.

81 Conclusion

82 Photon Weave is an open-source quantum system simulator under the Apache-2.0 license,
83 targeting researchers and developers who need an easy-to-use yet powerful simulation tool.
84 One of the intended outcomes is to build a library of interoperable quantum device models
85 powered by the Photon Weave framework.

86 Acknowledgments

87 This work was financed by the Federal Ministry of Education and Research of Germany via
88 grants 16KIS1598K, 16KISQ039, 16KISQ077 and 16KISQ168 as well as in the programme of
89 "Souverän. Digital. Vernetzt.". Joint project 6G-life, project identification number: 16KISK002.
90 We acknowledge further funding from the DFG via grant NO 1129/2-1 and by the Bavarian
91 Ministry for Economic Affairs (StMWi) via the project 6GQT and by the Munich Quantum
92 Valley.

93 References

- 94 Aleksandrowicz, G., & others. (2019). *Qiskit: An open-source framework for quantum*
95 *computing*.
- 96 Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G.,
97 Paszke, A., VanderPlas, J., Wanderman-Milne, S., & Zhang, Q. (2018). *JAX: Composable*
98 *transformations of Python+NumPy programs* (Version 0.3.13). [http://github.com/jax-ml/](http://github.com/jax-ml/jax)
99 [jax](http://github.com/jax-ml/jax)
- 100 Fock, V. (1932). Konfigurationsraum und zweite quantelung. *Zeitschrift f r Physik*, 75(9–10),
101 622–647. <https://doi.org/10.1007/bf01344458>
- 102 Johansson, J. R., Nation, P. D., & Nori, F. (2012). QuTiP: An open-source python framework
103 for the dynamics of open quantum systems. *Computer Physics Communications*, 183(8),
104 1760–1772.
- 105 Killoran, N., Izaac, J., Quesada, N., Bergholm, V., Amy, M., & Weedbrook, C. (2019).
106 Strawberry fields: A software platform for photonic quantum computing. *Quantum*, 3, 129.
- 107 Kolarovszki, Z., Rybotycki, T., Rakytá, P., Kaposi, Á., Poór, B., Jóczik, S., Nagy, D. T.
108 R., Varga, H., El-Safty, K. H., Morse, G., Oszmaniec, M., Kozsik, T., & Zimborás, Z.
109 (2024). *Piquasso: A photonic quantum computer simulation software platform*. <https://arxiv.org/abs/2403.04006>
- 110
- 111 Xiang-Bin, W. (2002). Theorem for the beam-splitter entangler. *Physical Review A*, 66(2),
112 024303.