

Demonstration Installation and Setup

- Copy or unload the demo files to a local directory
- cd to the directory containing the demo files
- Uncompress all files if necessary

```
find . -name "*" -exec uncompress {} \;
```
- Start I-DEAS
 - Project = Any
 - Model File = No model file
 - Application = Design
 - Task = Master Modeler
- File, Import, I-DEAS Design Universal File
 '2Dstart.unv'
- Do the following manually or run
 '2Dstart.prg'
- Enter Drafting, import clip.asc to start the demo.


- Options, units, MM
- Display Filters, Workplane=off, Parts, Coordinate Sys=off, Centerpoints/centerlines=off, OK, Assembly, Assembly Name (Top)=off, OK
- Shading Options, Hardware support, Backlighting=On, OK
 Outline=Black, OK
- Line Options, Line Attributes, Iso Lines=Off, Seams=Off, OK, OK
- Line Options, Line Attributes, Silhouette=Off, OK, OK
- Manage Bins, get Initial and Cartridge parts
- Iso view
- Run the 'symbols.prg' program file

- Save - use any name you like, (i.e., '2D')

Demonstration Overview

This demonstration is intended to show an overview of the process to get 2D data into a 3D solids environment. The ability to use undimensioned geometry should be highlighted during the demo. This is a distinct competitive advantage.





MS6 assembly capability is also shown toward the end of the demo. Assembly constraints, VGX part, assembly constraint browser, as well as animation is included.



Solid Modeling Drafting

File Open


Open clip.asc



File Export - fx from the keyboard

Pull down "To Solids"
 N = Demo (Any suitable file name except "clip"
 Done
 N - front
 Select wireframe, click in front view, autochain
 outside border, Done

 N - Top
 Wireframe, click in top view, autochain outside




wrr - from the keyboard

Global symbol to read existing file clip.unv and bring the three wireframe parts to the workbench.


Build Section

Build sections as shown. Select and arc to begin the sections shown (This determines a plane in one pick)

Measure



Direction



Pull down for measure

Distance

☐ Draft Angle



Protrude
 Cutout
 Intersect
 New Part

Protrude

Select the section, MB2, measure, measure from two points shown, MB2, New Part, OK

Benefit

- Ability to access 2D geometry quickly
No need to add dimensions to create solid part



Modify

Select part, MB2, wireframe

Constrain and dimension

Autoconstrain, pick the opened section

Drag



Select various dimensions and drag, cancel to keep at original values

Drag witness line of 9.17mm linear dimension, reattach it to the left side vertical line

Update

Benefit


- Can dynamically redefine the dimensioning scheme
No need to delete and reapply dimensions




Protrude

Select each section, intersect to create the part shown. Measure the distance off of the part for the intersect distance for each feature.

Measure extrude distance



Build section, attach workplane and add lower line



Build Section

Select the section

Attach Workplane

Attach the workplane to the new section

Polyline



Connect the lower points of the section with a line

Modify

Modify the section and add the newly created line

Extrude

Select the section, MB2, measure distance (1 mm),
new part, OK



Delete

Select a wireframe line, MB3 all, MB2, OK

Join

MB3, relations off, Select the newly created part, select the large part.


Drag

Select the face shown, drag until the lower slot face is highlighted to establish a coplanar condition

Update

Benefit

- Ability to add design intent directly on the part using VGx technology



Delete this dimension

Drag this end of the
6.65 dimension

Modify

Double click the lower slot, quick wireframe

Constrain and Dimension

Autoconstrain, pick the section, MB2

Delete

Delete the 7.44mm dimension shown

Drag

Select the 6.65mm dimension shown, MB3 to cancel



Update

Benefit

- Through the use of VGX, we can see the affect of a dimension change - even on a feature created AFTER the feature being modified.
- Strength of Variational technology.

Attach Workplane

Pick edges



Resultant edge

Sketch in Place



Pick surface shown

Protrude

MB3, section options, autochain off, OK
 MB3, split surface, pick the two edges, MB2,
 OK (Thru all), MB2(All surfaces), MB2

Benefit

- Ability to add detail (parting line) to solid easier than on drawing



Draft

Pick direction of pull (pointing away from parting line)

Select four outside surfaces, MB2



Select four stationary edges, MB2, MB2

Constant angle = 5,, Preview

Constant angle = 1, OK

Benefit

- Ease of adding draft detail to part
- Strength of preview in all of Master Series



Name Parts


Pick the part, rename it to clip

Manage Bins

Get drive assembly

Dynamic Orient

Select the clip, drag to the side, MB3 Rotate
Orient to approximate orientation shown



Master Model ... Master Assembly

Heirarchy

Highlight Top Level
Add Instance, Select the clip from the screen
Dismiss


C11 - Turns center line on

Redisplay

Constrain and Dimension


Coincident and Colinear

MB3 Filter, centerline, Pick Only
Select the clip centerline, and the
upper pin centerline






Coincident and Colinear

MB3, Filter, Surfaces - Pick only
Select the two surfaces shown





Dimension

Select the two surfaces
shown



Browse Relations

Select the clip instance
Show the relationships, click on the constraint symbols and show the associated surfaces highlight




Modify

Select the angular dimension, $d=30$
 Select the dimension again, animate
 enter 0 and 30, turn on Sequence button,
 drag the horizontal bar to the left, Forward

Animate Hardware

Start



Modify

Change the angular dimension to $d=15$ degrees.


Modify

Select the clip, MB2 to show the dimensions

Drag

Select the 6.65 mm dimension to control the slot/tab combination position, drag to about 9 mm

Update



Heirarchy

Show all instances