

EXPERIMENT-2

Program:

SOURCE CODE

```
#include<stdio.h>
#define PI 3.14
int main(void)
{
    int radius;
    float area;
    printf("Enter the radius:");
    scanf("%d",&radius);
    area=PI*radius*radius;
    printf("Area=%f\n",area);
    return 0;
}
```

Explanation of codes:

`#include<stdio.h>` is a preprocessor directive to include bulletin header file.

`#define PI 3.14` is used to define a symbolic constant or macro.

`int radius` is a variable definition.

`printf( )` is a bulletin function to display output string.

`scanf( )` is a bulletin function to get inputs

This program is used for calculating area of circle of radius 2 cm. It takes the radius as input from user, applies formula and

displays the answer calculated.

PROGRAM OUTPUT:

```
(kali㉿kali)-[~]  
$ pwd  
/home/kali  
  
(kali㉿kali)-[~]  
$ vi notes.c  
  
(kali㉿kali)-[~]  
$ gcc notes.c -o area  
  
(kali㉿kali)-[~]  
$ ./area  
Enter the radius:2  
Area=12.560000  
  
(kali㉿kali)-[~]  
$
```

As the radius given by the user is 2cm.

So the area calculated is 12.560000 which we can see in the output.

OUTPUT EXPLANATION:

pwd command is used for showing Present Working Directory .

vi notesc – This command is used to open and create a C- source code file named as notes.c using the text vi text editor.

gcc notes.c-o ,this command is used for saving and compiling.

./area command is used for running the program