

for $t = 1: T$

$$\max_{\underline{\delta}_i, \bar{\delta}_i} \sum_{i=1}^p \bar{\delta}_i^{(t)} - \sum_{i=1}^p \underline{\delta}_i^{(t)}$$

for $i = 1, \dots, p$

p is number of generators,
 n is dimension of state space
 and t is current time step
 $t=0$ corresponds to initial
 condition

subject to $-1 \leq \underline{\delta}_i^{(t)} \leq 1$

$-1 \leq \bar{\delta}_i^{(t)} \leq 1$

$\underline{\delta}_i^{(t)} + \epsilon \leq \bar{\delta}_i^{(t)}$, ϵ is small number > 0
 to ensure intervals are nonempty

// scaling is within constraint set

$$\begin{aligned} (C^{(t-1)} + G^{(t-1)} \cdot \Delta_c^{(t)}) + |G^{(t-1)}| \cdot \Delta_x^{(t)} &\leq X_{cs}^{\max} \\ (C^{(t-1)} + G^{(t-1)} \cdot \Delta_c^{(t)}) - |G^{(t-1)}| \cdot \Delta_x^{(t)} &\geq X_{cs}^{\min} \end{aligned}$$

previous center
 previous generator matrix, generators are concatenated horizontally: $n \times p$ where p is number of generators
 center shift scalars: $p \times 1$
 generator scalars: $p \times 1$
 constraint set minimum

$$G^{(t-1)} \Delta_c^{(t)} = \sum_{i=1}^n g_i^{(t-1)} \cdot \Delta_i^{(t)} \leftarrow (100\% \text{ sure this is equivalent})$$

// reach set of scaling is within constraint set

$$\begin{aligned} A_d \cdot (C^{(t-1)} + G^{(t-1)} \cdot \Delta_c^{(t)}) + |A_d \cdot G^{(t-1)}| \cdot \Delta_x^{(t)} &\leq X_{cs}^{\max} \\ A_d \cdot (C^{(t-1)} + G^{(t-1)} \cdot \Delta_c^{(t)}) - |A_d \cdot G^{(t-1)}| \cdot \Delta_x^{(t)} &\geq X_{cs}^{\min} \end{aligned}$$

discretized continuous
 more next page

// When $t=1$ additionally check that scaled initial set ^{with generators} is inside unscaled initial set without generators.

$$(C^{(t-1)} + G^{(t-1)} \cdot d_c^{(t)}) + |G^{(t-1)}| \cdot d_x^{(t)} \leq x_{IC}^{\max} \leftarrow \text{initial set}$$

$$(C^{(t-1)} + G^{(t-1)} \cdot d_c^{(t)}) - |G^{(t-1)}| \cdot d_x^{(t)} \geq x_{IC}^{\min}$$

Now, $d_c = \frac{\bar{\delta} + \underline{\delta}}{2}$ in vector form, or individually,

$$d_x = \frac{\bar{\delta} - \underline{\delta}}{2}$$

$$d_{c_i} = \frac{\bar{\delta}_i + \underline{\delta}_i}{2}$$

$$d_{x_i} = \frac{\bar{\delta}_i - \underline{\delta}_i}{2}$$

After each optimization, I construct d_c and d_x to be used for both forward reachability in the next iteration, as well as for mapping backward in the end to get the "safe set".

Forward:

$$Z^{(t)} = \left\langle Ad^{(t)} \left(C^{(t-1)} + G^{(t-1)} \cdot d_c^{(t)} \right), d_1^{(t)} \cdot Ad^{(t)} g_1^{(t-1)}, \dots, d_p^{(t)} \cdot Ad^{(t)} g_p^{(t-1)} \right\rangle$$

Final Backward computation for safe set:

$$\left\langle C^{(0)} + \sum_{t=1}^T (A_d^{(t-1)}) \cdot G^{(t-1)} \cdot d_c^{(t)} ; \prod_{t=1}^T d_{x_1}^{(t)} \cdot g_1^{(0)}, \dots, \prod_{t=1}^T d_{x_p}^{(t)} \cdot g_p^{(0)} \right\rangle$$

\swarrow exponent \swarrow superscript
 $(t-1)$ $(t-1)$ (t)