

## TTT4120 Digital Signal Processing Fall 2020

### Modeling of Stochastic Processes: Parametric Spectral Estimation

Prof. Stefan Werner  
stefan.werner@ntnu.no  
Office B329

Department of Electronic Systems  
© Stefan Werner

1

## Lecture in course book\*

---

- Proakis, Manolakis Digital Signal Processing, 4<sup>th</sup> Ed.
  - 12.2 Innovations representation of stationary random processes
  - 14.3 Parametric methods for spectral estimation
- A comprehensive overview of topics treated in the lecture, see “[Introduksjon til statistisk signalbehandling](#)” on Blackboard

\*Level of detail is defined by lectures and problem sets

2

2


## Contents and learning outcomes

- Non-parametric versus parametric models
- Innovations representation
- Rational power spectra: AR, MA, ARMA
- AR models and Yule-Walker equations

3


3

## Nonparametric PSD estimation



=

$$\hat{y}_{XX}[l] = \frac{1}{N} \sum_{n=0}^{N-|l|-1} x[n]x[n+|l|] = w_R[l] \gamma_{XX}[l]$$




$$\Gamma_{XX}(f) = \mathcal{F}\{\hat{y}_{XX}[l]\} = \frac{1}{N} \left| \sum_{n=0}^{N-1} x[n] e^{-j2\pi f n} \right|^2$$

- **Nonparametric power spectrum estimation:** Assume that stochastic process  $X[n]$  is wide-sense stationarity and ergodic
  - + Simple and easy to compute using the  $\text{FFT}_N$
  - Requires long data records for good frequency resolution
  - Spectral leakage due to windowing  $\Rightarrow$  Can mask weak signals

4

4

## Nonparametric PSD estimation...



- Basic limitations of nonparametric spectrum estimation
  - Inherent assumption that  $\hat{\gamma}_{XX}[l] = 0$  for some  $l \geq N$
  - Inherent assumption that the data is periodic with  $N$

5

5

## Parametric PSD estimation

- Consider methods that can **extrapolate** the values of the autocorrelation function for  $l \geq N$

$$\hat{\gamma}_{XX}[l], |l| \leq N - 1 \Rightarrow \hat{\gamma}_{XX}[l], |l| \geq N$$

- Requires **a priori** information on how data signal is generated
- A **parametric model** for the signal generation is constructed
  - Sufficient to find the values of the model parameters
  - Often provides us with a better description of the process, whenever the model is close to reality
  - Eliminates need for windowing and assumption that  $\hat{\gamma}_{XX}[m] = 0$  for some  $m \geq N$

6

6

## Parametric PSD estimation...


- Parametric modeling does not provide an exact representation
  - approximation characterized by a few parameters
  - enhanced spectral resolution: especially for finite data records, e.g., due to time-variant or transient phenomena
  - Efficient signal compression (e.g., LPC of speech)
- Different parametric models
  - rational models
  - all-pole models lead to linear equation systems

7

7

## Parametric PSD estimation...


- Example: Model a speech signal (parameters change every 20ms)



8

8

## Innovations representations




- Wide-sense stationary random processes can be represented as the output of a **causal and causally invertible system** excited by a white noise process
- This representation is called the **Wold representation**

9

9

## Innovations representations...




- Consequently, a WSS random process can be represented by the output of the inverse system, which is a white process
  - a random process can be **transformed into a white process** by passing  $X[n]$  through a linear filter
  - $H_I(z)$  is called a **whitening filter**

10

10

## Innovations representations...



- Restrict our attention to cases where the PSD of  $X[n]$  is rational


$$\Gamma_{XX}(f) = \frac{\sigma_W^2 B(z)B(z^{-1})}{A(z)A(z^{-1})} \Big|_{z=e^{j2\pi f}} \text{ or } H(z) = \frac{B(z)}{A(z)}$$

- $H(z)$  is causal stable and minimum-phase  $\Rightarrow H_I(z)$  is also causal stable and minimum phase
- By knowing  $H(z)$ , described by a few parameters, we can go from the statistical properties of  $W[n]$  to  $X[n]$ , and vice versa

11

11

## Model types: AR process



- For an **autoregressive (AR) process**, filter  $H(z)$  has only poles,

$$H(z) = \frac{1}{A(z)} = \frac{1}{1 + \sum_{k=1}^p a_k z^{-k}}$$


and is described in time domain as

$$X[n] = -\sum_{k=1}^p a_k X[n-k] + W[n]$$

12

12

## Model types: MA process



- For a **moving average (MA) process**, filter  $H(z)$  has only zeros,

$$H(z) = B(z) = \sum_{k=0}^q b_k z^{-k}$$


and is described in time domain as

$$X[n] = \sum_{k=0}^q b_k W[n-k]$$

13

13

## Model types: ARMA process



- For an **autoregressive moving average (ARMA) process**, filter  $H(z)$  has both zeros and poles,

$$H(z) = \frac{B(z)}{A(z)} = \frac{\sum_{k=0}^q b_k z^{-k}}{1 + \sum_{k=1}^p a_k z^{-k}}$$

and is described in time domain as

$$X[n] = -\sum_{k=1}^p a_k X[n-k] + \sum_{k=0}^q b_k W[n-k]$$

14

14

## Parameter estimation

$$W[n] \longrightarrow \boxed{H(z)} \longrightarrow X[n] = -\sum_{k=1}^p a_k X[n-k] + \sum_{k=0}^q b_k W[n-k]$$

- The models are described by a few parameters:  $\{a_k\}$ ,  $\{b_k\}$ , and  $\sigma_W^2$
- Parameter values are unknown  $\Rightarrow$  need to estimate them from  $X[n]$
- We need to find the parameters such that the model “resembles,” or is “close” to, the true process
- Restrict our study to AR models

15

15

## Parameter estimation...

$$W[n] \longrightarrow \boxed{H(z)} \longrightarrow X[n] = -\sum_{k=1}^p a_k X[n-k] + W[n]$$

- Restrict our study to AR models
  - can model processes characterized by sharp peaks in the spectrum
  - other types of spectra can be modeled by increasing the model order, i.e., the number of filter coefficients
  - suitable for many practical physical processes, e.g., speech


16

16



## Statistical description of AR( $p$ ) process

- Model the problem with linear system



- WGN process  $W[n]$ :  $E\{W[n]W[n-l]\} = \sigma_W^2 \delta[l]$
- The AR( $p$ ) process has  $p$  filter coefficients  $\{a_k\}_{k=1}^p$
- Find a relation between  $\gamma_{XX}[l]$  and coefficients  $a_k$  and  $\sigma_W^2$

17

17

## Statistical description of AR( $p$ ) process

- Autocorrelation function  $\gamma_{XX}[l]$ :

$$\begin{aligned} \gamma_{XX}[l] &= E\{X[n]X[n-l]\} \\ &= E\left\{\left(-\sum_{k=1}^p a_k X[n-k] + W[n]\right)X[n-l]\right\} \\ &= E\left\{-\sum_{k=1}^p a_k X[n-k]X[n-l] + W[n]X[n-l]\right\} \\ &= -\sum_{k=1}^p a_k E\{X[n-k]X[n-l]\} + E\{W[n]X[n-l]\} \\ &= -\sum_{k=1}^p a_k \gamma_{XX}[l-k] + \gamma_{WX}[l] \end{aligned}$$

- Take a closer look at the crosscorrelation term  $\gamma_{WX}[l]$

18

18

## Statistical description of AR( $p$ ) process...

- Crosscorrelation term  $\gamma_{WX}[l]$ :

$$\begin{aligned}\gamma_{WX}[l] &= E\{W[n]X[n-l]\} = E\{W[n+l]X[n]\} \\ &= E\{W[n+l](-\sum_{k=1}^p a_k X[n-k] + W[n])\} \\ &= E\{-\sum_{k=1}^p a_k W[n+l]X[n-k] + W[n+l]W[n]\} \\ &= -\sum_{k=1}^p a_k E\{W[n+l]X[n-k]\} + E\{W[n+l]W[n]\} \\ &= 0 + \sigma_W^2 \delta[l]\end{aligned}$$

- Crosscorrelation term only take non-zero value at lag  $l = 0$

19

19

## Statistical description of AR( $p$ ) process...

- Autocorrelation function  $\gamma_{XX}[l]$  for an AR( $p$ ) process:

$$\gamma_{XX}[|l|] = -\sum_{k=1}^p a_k \gamma_{XX}[|l| - k] + \sigma_W^2 \delta[l]$$

- Discussion:** How can we use the above equation to find  $\gamma_{XX}[l]$  for all  $l$ , and what knowledge is required?

20

20

## Statistical description of AR( $p$ ) process...

- Autocorrelation function  $\gamma_{XX}[l]$  for an AR( $p$ ) process:

$$\gamma_{XX}[|l|] = -\sum_{k=1}^p a_k \gamma_{XX}[|l| - k] + \sigma_W^2 \delta[l]$$

- Discussion:** How can we use the above equation to find...
  - Crosscorrelation function  $\gamma_{XX}[l]$  is specified for all  $l$  when
    - the  $p$  filter coefficients  $\{a_k\}_{k=1}^p$ , and;
    - the  $p+1$  first values of  $\gamma_{XX}[l]$ , i.e.,  $\gamma_{XX}[0], \gamma_{XX}[1], \dots, \gamma_{XX}[p]$
- How to find model parameters to the model  $\{a_k\}_{k=1}^p$  given  $\gamma_{XX}[l]$

21

21

## Statistical description of AR( $p$ ) process...

$$\gamma_{XX}[|l|] = -\sum_{k=1}^p a_k \gamma_{XX}[|l| - k] + \sigma_W^2 \delta[l]$$

- Linear equation system ( $\gamma_{XX}[l] = \gamma_{XX}[-l]$ ):
 
$$\begin{aligned}
 l = 1: & -\gamma_{XX}[1] = a_1 \gamma_{XX}[0] + a_2 \gamma_{XX}[1] + \dots + a_p \gamma_{XX}[p-1] \\
 l = 2: & -\gamma_{XX}[2] = a_1 \gamma_{XX}[1] + a_2 \gamma_{XX}[0] + \dots + a_p \gamma_{XX}[p-2] \\
 l = 3: & -\gamma_{XX}[3] = a_1 \gamma_{XX}[2] + a_2 \gamma_{XX}[1] + \dots + a_p \gamma_{XX}[p-3] \\
 & \vdots \\
 l = p: & -\gamma_{XX}[p] = a_1 \gamma_{XX}[p-1] + a_2 \gamma_{XX}[p-2] + \dots + a_p \gamma_{XX}[0]
 \end{aligned}$$

22

22

## Statistical description of AR(p) process...

- Linear equation system in matrix form (Yule-Walker equations):

$$\underbrace{\begin{bmatrix} \gamma_{XX}[0] & \gamma_{XX}[1] & \dots & \gamma_{XX}[p-1] \\ \gamma_{XX}[1] & \gamma_{XX}[0] & \dots & \gamma_{XX}[p-2] \\ \vdots & \ddots & \ddots & \vdots \\ \gamma_{XX}[p-1] & \gamma_{XX}[p-2] & \dots & \gamma_{XX}[0] \end{bmatrix}}_{\Gamma_{XX}} \underbrace{\begin{bmatrix} a_1 \\ a_2 \\ \vdots \\ a_p \end{bmatrix}}_{\mathbf{a}} = - \underbrace{\begin{bmatrix} \gamma_{XX}[1] \\ \gamma_{XX}[2] \\ \vdots \\ \gamma_{XX}[p] \end{bmatrix}}_{\boldsymbol{\gamma}_{XX}}$$

and

$$\sigma_W^2 = \gamma_{XX}[0] + \sum_{k=1}^p a_k \gamma_{XX}[k]$$

- Solve for coefficients

$$\mathbf{a} = -\Gamma_{XX}^{-1} \boldsymbol{\gamma}_{XX}$$

23

23

## Statistical description of AR(p) process...

- Sanity check: Model process  $X[n] = -aX[n-1] + W[n]$  using an AR(2) process, and find parameters  $a_1$  and  $a_2$

$$\text{AR(1) process: } \gamma_{XX}[l] = \sigma_W^2 \frac{(-a)^{|l|}}{1-a^2}, |l| \geq 0$$

Yule-Walker equations:

$$\underbrace{\begin{bmatrix} \gamma_{XX}[0] & \gamma_{XX}[1] \\ \gamma_{XX}[1] & \gamma_{XX}[0] \end{bmatrix}}_{\Gamma_{XX}} \underbrace{\begin{bmatrix} a_1 \\ a_2 \end{bmatrix}}_{\mathbf{a}} = - \underbrace{\begin{bmatrix} \gamma_{XX}[1] \\ \gamma_{XX}[2] \end{bmatrix}}_{\boldsymbol{\gamma}_{XX}}$$

$$\begin{bmatrix} 1 & -a \\ -a & 1 \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \end{bmatrix} = - \begin{bmatrix} -a \\ a^2 \end{bmatrix} \Rightarrow \begin{bmatrix} a_1 \\ a_2 \end{bmatrix} = - \begin{bmatrix} 1 & -a \\ -a & 1 \end{bmatrix}^{-1} \begin{bmatrix} -a \\ a^2 \end{bmatrix}$$

Solve for coefficients:  $a_1 = ?$ ,  $a_2 = ?$

24

24

## PSD of an AR(p) process

- Once we have filter coefficients  $\{a_k\}_{k=1}^p$  we can compute the PSD

$$\begin{array}{ccc}
 W[n] \longrightarrow & \boxed{h[n]} & \longrightarrow X[n] = -\sum_{k=1}^p a_k X[n-k] + W[n] \\
 \gamma_{WW}[k] = \sigma_W^2 \delta[k], & & \Gamma_{XX}(f) = |H(f)|^2 \Gamma_{WW}(f) = |H(f)|^2 \sigma_W^2 \\
 \Gamma_{WW}(f) = \sigma_W^2 & &
 \end{array}$$

- Frequency response of filter

$$H(f) = \frac{1}{1 + \tilde{A}(f)}, \text{ with } \tilde{A}(z) = \sum_{k=1}^p a_k z^{-k}$$

- Finally we obtain the PSD as

$$\Gamma_{XX}(f) = \frac{\sigma_W^2}{|1 + \tilde{A}(f)|^2}$$

25

25

## PSD of an AR(p) process...

- Example: Model  $X[n] = W[n] - bW[n-1]$ ,  $W[n] \sim N(0,1)$  using an AR(2) process, and find parameters  $a_1$  and  $a_2$
- Autocorrelation:  $\gamma_{XX}[l] = (1 + b^2)\delta[l] - b\delta[l-1] - b\delta[l+1]$
- Yule-Walker equations:

$$\begin{bmatrix} 1 + b^2 & -b \\ -b & 1 + b^2 \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \end{bmatrix} = - \begin{bmatrix} -b \\ 0 \end{bmatrix} \Rightarrow \begin{bmatrix} a_1 \\ a_2 \end{bmatrix} = \begin{bmatrix} 1 + b^2 & -b \\ -b & 1 + b^2 \end{bmatrix}^{-1} \begin{bmatrix} b \\ 0 \end{bmatrix}$$

$$\text{Solve for coefficients: } a_1 = \frac{b(1+b^2)}{b^2(1+b^2)+1}, a_2 = \frac{b^2}{b^2(1+b^2)+1}$$


$$\sigma_W^2 = \gamma_{XX}[0] + a_1 \gamma_{XX}[1] + a_2 \gamma_{XX}[2]$$

26

26

## PSD of an AR( $p$ ) process...

- Example: Model  $X[n] = W[n] - 0.5W[n - 1]$ ,  $W[n] \sim N(0,1)$




27

27

## PSD of an AR( $p$ ) process...

- Example: Model  $X[n] = W[n] - 0.5W[n - 1]$ ,  $W[n] \sim N(0,1)$



28

28

## PSD of an AR( $p$ ) process...

- Example: Power spectrum of an AR process is given by

$$\Gamma_{XX}(f) = \frac{\sigma_W^2}{|A(f)|^2} = \frac{25}{\left|1 - e^{-j2\pi f} + \frac{1}{2}e^{-j4\pi f}\right|^2}$$

where  $\sigma_W^2$  is the variance of the input sequence.

- Determine the difference equation that generates the AR process when the excitation is white noise
- Determine the system function for the whitening filter

29

29

## PSD of an AR( $p$ ) process...

- Only access to finite-length realization,  $x[n]$ , of process  $X[n]$ 
  - True  $\gamma_{XX}[l]$  must be estimated from  $x[n] \Rightarrow \hat{\gamma}_{XX}[l]$
  - Parameter values computed using  $\hat{\gamma}_{XX}[l]$  becomes parameter estimates  $\{\hat{a}_k\} \Rightarrow$  Power spectrum estimate

$$\hat{\Gamma}_{XX}(f) = \frac{\hat{\sigma}_W^2}{|\hat{A}(f)|^2} = \frac{\hat{\sigma}_W^2}{|1 + \sum_{k=1}^p \hat{a}_k e^{-j2\pi f k}|^2}$$

$$\gamma_{XX}[l] \rightarrow \{a_k\} \rightarrow \Gamma_{XX}(f)$$

↓ (estimation)

$$\hat{\gamma}_{XX}[l] \rightarrow \{\hat{a}_k\} \rightarrow \hat{\Gamma}_{XX}(f)$$

30

30

## PSD of an AR( $p$ ) process...

- Example: Estimate  $\Gamma_{XX}(f)$  from an  $N$ -point realization of  $X[n] = aX[n-1] + W[n]$ ,  $W[n] \sim N(0, \sigma_w^2)$

1. Compute estimates of  $\hat{\gamma}_{XX}[0]$  and  $\hat{\gamma}_{XX}[1]$ :

$$\hat{\gamma}_{XX}[l] = \frac{1}{N} \sum_{n=0}^{N-|l|-1} x[n]x[n+|l|], l = 0, 1$$

2. Estimate AR(1) parameter and noise variance (Yule-Walker):

$$\hat{a} = -\frac{\hat{\gamma}_{XX}[1]}{\hat{\gamma}_{XX}[0]}, \sigma_W^2 = \hat{\gamma}_{XX}[0] + \hat{a}\hat{\gamma}_{XX}[1]$$







3. Power spectrum estimate:

$$\hat{\Gamma}_{XX}(f) = \frac{\hat{\sigma}_W^2}{|\hat{A}(f)|^2} = \frac{\hat{\sigma}_W^2}{|1 + \hat{a}e^{-j2\pi f k}|^2}$$

31

31

## PSD of an AR(1) process...



32

32



## PSD of an AR(1) process...

---

### Matlab

```
% AR process
a = [1 -0.25];
[H, Omega] = freqz(1, a, 1024); % True spectrum

% WGN
N = 2^14;
W = randn(N, 1);

% Observed AR process
X = filter(1, a, W);

% Estimate AR process
[a_e, sigmaW2_e] = aryule(X, 1); % Estimate
[He, W] = freqz(sigmaW2_e, a_e, 1024);

plot(W/pi, 10*log10(abs(H))), hold on
plot(W/pi, 10*log10(abs(He)))
```

33

33

## Summary

---

- Today we discussed:
  - Parametric spectral estimation
- Next:
  - Linear prediction

34

34