

Cross-compiling HOWTO

In a machine running Debian 7 (MiniPC 2)

Cross-compile `simplemux.c` with ROHC 1.7.0 in a Debian 7 machine, for running it in a TP-Link TL-WR1043ND (version 2) Access Point.

Some ideas here: <http://wiki.openwrt.org/doc/devel/crosscompile>

In the Debian machine (it must be 64 bits, as the TP-Link), download the Toolchain from OpenWRT.org

Go to <https://downloads.openwrt.org/snapshots/trunk/>

And download the version you need. In “binary releases” you have the latest version.

You can also download “historic releases”. For example, this is the Barrier Breaker version:

https://downloads.openwrt.org/barrier_breaker/14.07/

I have downloaded from this one:

https://downloads.openwrt.org/barrier_breaker/14.07/ar71xx/mikrotik/

Download this Toolchain file:

https://downloads.openwrt.org/barrier_breaker/14.07/ar71xx/mikrotik/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-linaro_uClibc-0.9.33.2.tar.bz2

Extract it in

`/home/proyecto` (if the username is “proyecto”)

In the Debian machine, modify the environment variable “CC”

Modify the CC variable in order to make the compiler be the MIPS one:

```
# export CC=/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-0.9.33.2/bin/mips-openwrt-linux-gcc
```

Modify the STAGING_DIR variable in order to make the compiler be the MIPS one:

```
# export STAGING_DIR=/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-0.9.33.2/
```

Use `#set | more` to confirm that CC has this value:

(...)

```
BASH_VERSION='4.2.37(1)-release'
```

```
CC=/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-0.9.33.2/bin/mips-openwrt-linux-gcc
```

```
COLORTERM=gnome-terminal
```

(...)

In the Debian machine, download ROHC (file `rohc-1.7.0.tar.xz` from the ROHC web site)

Download the ROHC file from the web:

<http://rohc-lib.org/download/rohc-1.7.x/1.7.0/rohc-1.7.0.tar.xz>

Extract the file to the toolchain directory:

```
/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-
linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-
0.9.33.2/rohc-1.7.0
```

In the Debian machine, install the ROHC library in the toolchain

Go to this directory

```
/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-
linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-
0.9.33.2/rohc-1.7.0/
```

Run configure:

```
#!/configure --disable-app-fuzzer --disable-app-performance --disable-
app-sniffer --enable-app-tunnel --disable-app-stats --disable-linux-
kernel-module --disable-doc --disable-doc-man --host=mips --
prefix=/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-
linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-
0.9.33.2/
```

```
#make clean
```

```
#make
```

Note: make all may not work properly
make check does not work properly

```
#make install
```

After this, you have created in the lib folder of the toolchain the .a files required for compiling with static libraries (librohc-common.a librohc-comp.a y librohc-decomp.a)

Check if these files are in the folder:

```
~/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-linaro_uClibc-
0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-0.9.33.2/lib
```

In the Debian machine, compile the .c file

This is the cross-compiling instruction:

The source file name is /home/proyecto/simplemux/simplemux.c

The created executable will be created in /home/proyecto/simplemux-mips

```
#!/home/proyecto/OpenWrt-Toolchain-ar71xx-for-mips_34kc-gcc-4.8-
linaro_uClibc-0.9.33.2/toolchain-mips_34kc_gcc-4.8-linaro_uClibc-
0.9.33.2/bin/ ./mips-openwrt-linux-gcc -o /home/proyecto/simplemux-
mips -g -Wall /home/proyecto/simplemux/simplemux.c -I ./include/ -L
./lib/ -lrohc_comp -lrohc -lrohc_common -lrohc_decomp -static
```

Now you can copy the executable file to the Access Point with MIPS architecture and run it there.