# Managing backups for Cloud Volumes ONTAP

Cloud Manager

Tom Onacki, Ben Cammett May 28, 2020

 $This\ PDF\ was\ generated\ from\ https://docs.netapp.com/us-en/occm/task\_managing\_backups.html\ on\ June\ 15,\ 2020.$  Always\ check\ docs.netapp.com\ for\ the\ latest.



## **Table of Contents**

V.	Ianaging backups for Cloud Volumes ONTAP	. 1
	Changing the schedule and backup retention	. 1
	Restoring a volume	. 2
	Deleting backups	. 3
	Disabling Backup to Cloud	. 4

## Managing backups for Cloud Volumes ONTAP

Manage backups for Cloud Volumes ONTAP by changing the backup schedule, restoring volumes, and more.

## Changing the schedule and backup retention


The default policy backs up volumes every day and retains the most recent 30 backup copies of each volume. You can change to weekly or monthly backups and you can change the number of backup copies to retain. You can also select one of the system-defined policies that provide more options, such as *NetappRecommended2* that provides 30 daily, 13 weekly, and 12 monthly backups.



Changing the backup policy affects all future backups. It doesn't affect any previous backups that were created.

#### Steps

- 1. Open the working environment.
- 2. Click the backup settings icon.



3. Change the schedule and backup retention and then click Save.




Policy - Retention & Schedule	Create New Policy     Use Existing Policy
	Backup Every  Number of backups to retain  30
Resource Group	You created a new resource group with a storage account for the Blob container. resource group name: "Resource_Group_1"

## Restoring a volume


When you restore data from a backup, Cloud Manager performs a full volume restore to a *new* volume. You can restore the data to the same working environment or to a different working environment that's located in the same AWS account as the source working environment.

#### Steps


- 1. At the top of Cloud Manager, click **Backup**.
- 2. Select the volume that you want to restore.



3. Find the backup that you want to restore from and click the restore icon.



- 4. Select the working environment to which you want to restore the volume.
- 5. Enter a name for the volume.
- 6. Click **Restore**.



## **Deleting backups**

Backup to Cloud enables you to delete *all* backups of a specific volume. You can't delete *individual* backups.

You might do this if you deleted a volume or if you deleted a Cloud Volumes ONTAP system. Backup to Cloud doesn't automatically delete backups when you delete a volume or when you delete a system.

#### Steps

- 1. At the top of Cloud Manager, click **Backup**.
- 2. Click View Backup List for a volume.
- 3. Click the menu and select **Delete All Backups**.

#### Result


Cloud Manager deletes all backups for the selected volume.

## **Disabling Backup to Cloud**

Disabling Backup to Cloud disables backups of each volume on the system. Any existing backups will not be deleted.

#### Steps

- 1. Open the working environment.
- 2. Click the backup settings icon.



3. Disable Automatically back up all volumes and then click Save.

## **Copyright Information**

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.