

Young's Double Slit Lab

Tristan, Ibrahim, Oliver, Aaliya

December 8, 2022

Purpose

The purpose of this lab was to measure the wave length (λ) of a projected laser travelling through a slit then calculate the error percentage produced by our result.

Materials

- **One** Slit
- **One** Line of measuring tape
- **One** Red Laser
- **One** Projector
- **Two** Rulers
- **One** Piece of Paper

Procedure

1. The sheet of paper was taped to the black-board.
2. The laser was held infront of the slit.
3. Using a pencil, the blocks made by the laser and slit were marked on the taped piece of paper.
4. The distance between two of the blocks made by the slits was measured. (Δx)
5. The distance from the slit to the black-board was measured. (L)
6. The width of the slit was measured using the projector, two rulers, and the slit itself. (d)

Observations

The observations below exhibit the distance from the split to the black board (L) and the distance from the middle of two blocks projected by the laser travelling through our provided slit. (Δx)

- $L \approx 73cm \approx 7.3 \times 10^{-1} m$
- $\Delta x \approx 0.7cm \approx 7.0 \times 10^{-3} m$

Calculations: Solve for d

Before solving for λ , we must find d (the width of the slit). To do this we used a projector and the formula below.

$$\therefore d = \frac{(1mm)(\text{slit width in projector})}{(mm \text{ in projector})} = \frac{(1mm)(3.2mm)}{(6.1mm)} \approx 5.24 \times 10^{-4}m$$

Calculations: Solve for λ

After finding d we can solve for λ using the standard formula shown below. The result is meant to be near the size of a *nanometer* ($n \times 10^{-1}m$), thus our own calculations will produce a high error percentage.

$$\therefore \lambda = \frac{\Delta x d}{L} = \frac{(7.0 \times 10^{-3})(5.24 \times 10^{-4})}{(7.3 \times 10^{-1})} \approx 5.02 \times 10^{-6}m$$

Calculations: Error Percentage

After solving for an experimental result, we use the standard formula to calculate the error percentage.

$$\therefore \text{Error \%} = \left(\frac{\text{Experimental} - \text{Theoretical}}{\text{Theoretical}} \right) \times 100$$
$$\therefore \text{Error \%} = \left(\frac{(5.02 \times 10^{-6}) - (6.53 \times 10^{-9})}{(6.53 \times 10^{-9})} \right) \times 100 \approx 7.6 \times 10^5 \%$$

Sources of Errors

1. The blocks produced by the laser travelling through the slit were too close together. This made measuring the distances far harder and far more inaccurate.
2. Measuring from the projector can produce inaccurate results. Because of how large and pixelated the projection is, achieving accurate measurements can be difficult.
3. The laser was too far away / close to the slit.

Solutions to Errors

1. Move to a larger space so we can station the items accordingly.
2. Use a higher resolution projector or have multiple group members measure values then use the average of the results.
3. Measure an appropriate distance for the laser away from the slit.

Conclusion

Therefore, by the conclusion of this lab, it was determined that the wave length (λ) of a laser travelling through a slit was approximately $5.02 \times 10^{-6}m$ though because of the experimental errors noted above, this result had produced a high error percentage of approximately $7.6 \times 10^5 \%$

Pictures

The image below is the result of the laser travelling through our provided slit. As you can see, the blocks created by the laser and slit were very close together which made achieving accurate measurements far more difficult.

