

```
In [1]: import math
import random
import csv
```

```
In [2]: def encode_class(mydata):
    classes = []
    for i in range(len(mydata)):
        if mydata[i][-1] not in classes:
            classes.append(mydata[i][-1])
            for i in range(len(classes)):
                for j in range(len(mydata)):
                    if mydata[j][-1] == classes[i]:
                        mydata[j][-1] = i
    return mydata
```

```
In [3]: def splitting(mydata, ratio):
    train_num = int(len(mydata) * ratio)
    train = []
    # initially testset will have all the dataset
    test = list(mydata)
    while len(train) < train_num:
        # index generated randomly from range 0
        # to length of testset
        index = random.randrange(len(test))
        # from testset, pop data rows and put it in train
        train.append(test.pop(index))
    return train, test
```

```
In [4]: def groupUnderClass(mydata):
    dict = {}
    for i in range(len(mydata)):
        if (mydata[i][-1] not in dict):
            dict[mydata[i][-1]] = []
            dict[mydata[i][-1]].append(mydata[i])
    return dict
```

```
In [5]: # Calculating Mean
def mean(numbers):
    return sum(numbers) / float(len(numbers))
```

```
In [6]: # Calculating Standard Deviation
def std_dev(numbers):
    avg = mean(numbers)
    variance = sum([pow(x - avg, 2) for x in numbers]) / float(len(numbers) - 1)
    return math.sqrt(variance)
```

```
In [7]: def MeanAndStdDev(mydata):
    info = [(mean(attribute), std_dev(attribute)) for attribute in zip(*mydata)]
    # eg: List = [ [a, b, c], [m, n, o], [x, y, z]]
    # here mean of 1st attribute =(a + m+x), mean of 2nd attribute = (b + n+y)/3
    # delete summaries of last class
    del info[-1]
    return info
```

```
In [8]: # find Mean and Standard Deviation under each class
def MeanAndStdDevForClass(mydata):
    info = {}
    dict = groupUnderClass(mydata)
    for classValue, instances in dict.items():
        info[classValue] = MeanAndStdDev(instances)
    return info
```

```
In [9]: # Calculate Gaussian Probability Density Function
def calculateGaussianProbability(x, mean, stdev):
    expo = math.exp(-(math.pow(x - mean, 2) / (2 * math.pow(stdev, 2))))
    return (1 / (math.sqrt(2 * math.pi) * stdev)) * expo
```

```
In [10]: # Calculate Class Probabilities
def calculateClassProbabilities(info, test):
    probabilities = {}
    for classValue, classSummaries in info.items():
        probabilities[classValue] = 1
        for i in range(len(classSummaries)):
            mean, std_dev = classSummaries[i]
            x = test[i]
            probabilities[classValue] *= calculateGaussianProbability(x, mean, std_d
    return probabilities
```

```
In [11]: # Make prediction - highest probability is the prediction
def predict(info, test):
    probabilities = calculateClassProbabilities(info, test)
    bestLabel, bestProb = None, -1
    for classValue, probability in probabilities.items():
        if bestLabel is None or probability > bestProb:
            bestProb = probability
            bestLabel = classValue
    return bestLabel
```

```
In [12]: # returns predictions for a set of examples
def getPredictions(info, test):
    predictions = []
    for i in range(len(test)):
        result = predict(info, test[i])
        predictions.append(result)
    return predictions
```

```
In [13]: # Accuracy score
def accuracy_rate(test, predictions):
    correct = 0
    for i in range(len(test)):
        if test[i][-1] == predictions[i]:
            correct += 1
    return (correct / float(len(test))) * 100.0
```

```
In [14]: filename = 'pima-indians-diabetes.csv'
# Load the file and store it in mydata list
mydata = csv.reader(open(filename, "rt"))
mydata = list(mydata)
mydata = encode_class(mydata)
```

```
for i in range(len(mydata)):
    mydata[i] = [float(x) for x in mydata[i]]
```

```
In [15]: # split ratio = 0.7
# 70% of data is training data and 30% is test data used for testing
ratio = 0.7
train_data, test_data = splitting(mydata, ratio)
print('Total number of examples are: ', len(mydata))
print('Out of these, training examples are: ', len(train_data))
print("Test examples are: ", len(test_data))
```

Total number of examples are: 768  
Out of these, training examples are: 537  
Test examples are: 231

```
In [16]: # prepare model
info = MeanAndStdDevForClass(train_data)
```

```
In [17]: # test model
predictions = getPredictions(info, test_data)
accuracy = accuracy_rate(test_data, predictions)
print("Accuracy of your model is: ", accuracy)
```

Accuracy of your model is: 69.26406926406926

```
In [ ]:
```