

Lab # 04

Working with SQL Operators and Scalar Functions



National University
of computer and emerging sciences

Database Systems Lab (CL-2005)

Semester: Spring 2026

Section: BCS-4k

Course Instructor: Ms. Ramsha Iqbal

LAB # 04

Working with SQL Operators and Scalar Functions

Objectives:

After completing this lab, students will be able to:

- Apply arithmetic operators in SQL queries.
- Use logical operators for conditional expressions.
- Understand and apply operator precedence correctly.
- Recognize and use essential SQL keywords such as DISTINCT, ORDER BY, and aliases.
- Understand scalar functions in SQL.
- Use built-in scalar functions for data manipulation.

Arithmetic Operators

Arithmetic operators are used to perform basic mathematical calculations on numeric operands. These operators allow us to carry out common arithmetic operations such as addition, subtraction, multiplication, and division.

The main arithmetic operators are addition (+), subtraction (−), multiplication (*), and division (/). In addition to performing operations on numbers, the plus (+) and minus (−) operators can also be used in date arithmetic, such as adding days to a date or calculating the difference between two dates.

Operator	Description
+	Add
-	Subtract
*	Multiply
/	Divide
%	Modulo

Table 1: Arithmetic Operators in SQL

Lab # 04

Working with SQL Operators and Scalar Functions

Syntax:

```
SELECT expression <arithmetic operator> expression  
FROM table_name  
WHERE condition;
```

Example:

Query: Display marks increased by 5 for all students from Student table.

```
SELECT marks + 5 AS updated_marks  
FROM Student;
```

Logical Operators

AND, OR & NOT operator:

The WHERE clause can be combined with AND, OR, and NOT operators.

The AND and OR operators are used to filter records based on more than one condition:

- The AND operator displays a record if all the conditions separated by AND are TRUE.
- The OR operator displays a record if any of the conditions separated by OR is TRUE.

The NOT operator displays a record if the condition(s) is NOT TRUE.

AND Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE condition1 AND condition2 AND condition3 ...;
```

OR Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE condition1 OR condition2 OR condition3 ...;
```

Lab # 04

Working with SQL Operators and Scalar Functions

NOT Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE NOT condition;
```

BETWEEN operator:

The BETWEEN operator selects values within a given range. The values can be numbers, text, or dates.

The BETWEEN operator is inclusive: begin and end values are included.

Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE column_name BETWEEN value1 AND value2;
```

LIKE operator:

The LIKE operator is used in a WHERE clause to search for a specified pattern in a column.

There are two wildcards often used in conjunction with the LIKE operator:

“%” → The percent sign represents zero, one, or multiple characters

“_” → The underscore represents a single character

The percent sign and the underscore can also be used in combinations!

Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE column_name LIKE pattern;
```

Here are some examples showing different LIKE operators with '%' and '_' wildcards:

LIKE Operator	Description
WHERE CustomerName LIKE 'a%'	Finds any values that start with "a"
WHERE CustomerName LIKE '%a_'	Finds any values that 2 nd last char is "a"
WHERE CustomerName LIKE '%or%'	Finds any values that have "or" in any position
WHERE CustomerName LIKE '_r%'	Finds any values that have "r" in the second position

Lab # 04

Working with SQL Operators and Scalar Functions

WHERE CustomerName LIKE 'a__%'	Finds any values that start with "a" and are at least 3 characters in length
WHERE ContactName LIKE 'a%o'	Finds any values that start with "a" and ends with "o"

Example:

Query: Display all records of employees whose first name starts with “E”.

```
SELECT *  
FROM employees  
WHERE FIRST_NAME LIKE 'E%';
```

IN Operator:

The IN operator allows you to specify multiple values in a WHERE clause.

The IN operator is a shorthand for multiple OR conditions.

Syntax:

```
SELECT column1, column2, ...  
FROM table_name  
WHERE column_name IN (value1, value2, value3, ...);
```

Example:

Query: Display all employees whose department ID is 10, 20, or 30.

```
SELECT *  
FROM employees  
WHERE department_id IN (10, 20, 30);
```

Lab # 04

Working with SQL Operators and Scalar Functions

Operator Precedence

Operator precedence describes the order in which operations are performed when an expression is evaluated.

Operations with a higher precedence are performed before those with a lower precedence.

Parentheses have the highest precedence and OR has the lowest.

Precedence	Operator Type	Examples
1	Parentheses	()
2	Arithmetic	*, /, +, -
3	Comparison	=, !=, <>, <, >, <=, >=, BETWEEN, IN, LIKE, IS NULL
4	Logical NOT	NOT
5	Logical AND	AND
6	Logical OR	OR

Table 2: Operator Precedence Table

DISTINCT Statement

The SELECT DISTINCT statement is used to return only distinct (different) values.

Inside a table, a column often contains many duplicate values; and sometimes you only want to list the different (distinct) values.

Syntax:

```
SELECT DISTINCT column1, column2, ...  
FROM table_name;
```

Aliases

SQL aliases are used to give a table, or a column in a table, a temporary name. Aliases are often used to make column names more readable.

An alias only exists for the duration of the query.

Lab # 04

Working with SQL Operators and Scalar Functions

Alias Column Syntax:

```
SELECT column_name AS alias_name  
FROM table_name;
```

Alias Table Syntax:

```
SELECT column_name(s)  
FROM table_name AS alias_name;
```

ORDER BY Keyword

The ORDER BY keyword is used to sort the result-set in ascending or descending order.

The ORDER BY keyword sorts the records in ascending order by default. To sort the records in descending order, use the DESC keyword.

Syntax:

```
SELECT column_name(s)  
FROM table_name  
ORDER BY column1, column2, ... ASC|DESC
```

SELECT Top Clause

The SELECT TOP clause is used to specify the number of records to return.

It is useful on large tables with thousands of records because returning too many records can impact performance.

Note: Not all database systems support the SELECT TOP clause.

- MySQL uses the **LIMIT** clause to select a limited number of records.
- Oracle uses **ROWNUM** or **FETCH FIRST** to achieve the same result.

Oracle Syntax Using ROWNUM

```
SELECT *  
FROM table_name  
WHERE ROWNUM <= number;
```

Example:

Query: Return the first 5 rows:

```
SELECT *  
FROM employees  
WHERE ROWNUM <= 5;
```

Lab # 04

Working with SQL Operators and Scalar Functions

Oracle Syntax Using FETCH FIRST (Oracle 12c and later)

```
SELECT *  
FROM table_name  
ORDER BY column_name  
FETCH FIRST number ROWS ONLY;
```

Example:

Query: Return the first 5 rows ordered by employee_id:

```
SELECT *  
FROM employees  
ORDER BY employee_id  
FETCH FIRST 5 ROWS ONLY;
```

Offset in Oracle

In Oracle, the **OFFSET** keyword is used to skip a number of rows:

```
SELECT *  
FROM table_name  
ORDER BY column_name  
OFFSET offset_number ROWS  
FETCH NEXT number ROWS ONLY;
```

Example:

Query: Skip first 5 rows, return next 5 rows:

```
SELECT *  
FROM employees  
ORDER BY employee_id  
OFFSET 5 ROWS  
FETCH NEXT 5 ROWS ONLY;
```

Functions with SELECT Statement

There are some functions that can be used in select statement.

Syntax:

```
SELECT function_name()  
FROM table_name;
```

Functions are: MIN, MAX, AVG, SUM, COUNT, UPPER, LOWER, LENGTH, etc.

Lab # 04

Working with SQL Operators and Scalar Functions

SQL Functions

A function is a predefined formula which takes one or more arguments as input then process the arguments and returns an output.

SQL Functions:

There are two types of SQL functions, aggregate functions, and scalar (non-aggregate) functions.

1. Scalar (Non-Aggregate) / Single Row Functions

Non-aggregate functions operate on each record independently.

OR

These functions operate of single rows only and return one result per row and can be used in SELECT, WHERE and ORDER BY clause.

2. Aggregate / Multiple Rows Functions

Aggregate functions operate on many records and produce a summary, works with GROUP BY.

OR

These functions manipulate group of rows to give one and only one result per group of rows.

There are so many built-in functions in SQL to do various calculations on data.

Types of Scalar Functions

1. **Character Functions:** Accept character input and can return number or character value.
2. **Numeric Functions:** Accept numeric input and returns numeric values.
3. **Date Functions:** Operate on values of date data type. It always return a date value except the MONTHS_BETWEEN function, which returns a number.
4. **Conversion Functions:** Converts a value from one data type to another.
5. **General Functions:** Usually contains NULL handling functions.

1. Character Functions

LOWER() function

LOWER() function is used to convert all characters of a string to lower case.

Syntax:

```
SELECT LOWER(string)
```

UPPER() function

UPPER() function is used to convert all characters of a string to uppercase.

Syntax:

```
SELECT UPPER(string)
```


Lab # 04

Working with SQL Operators and Scalar Functions

TRIM() function

The TRIM() function removes leading and trailing spaces from a string.

Syntax:

```
TRIM(string)
```

CONCAT() function

The CONCAT() function adds two or more expressions together.

Syntax:

```
CONCAT(expression1, expression2, expression3,...)
```

LENGTH Function

The LENGTH() function returns the length of a string.

Syntax:

```
LENGTH(string)
```

REPLACE() Function

The REPLACE() function replaces all occurrences of a substring within a string, with a new substring.

Note: This function performs a case-sensitive replacement.

Syntax:

```
REPLACE(string, from_string, new_string)
```

SUBSTR() Function

These functions extract a substring from a string (starting at any position).

Syntax:

```
SELECT SUBSTR(string, start, length)
```

Parameter	Description
string	Required. The string to extract from
start	Required. The start position. Can be both a positive or negative number. If it is a positive number, this function extracts from the beginning of the string. If it is a negative number, this function extracts from the end of the string
length	Required. The number of characters to extract

Lab # 04

Working with SQL Operators and Scalar Functions

INSTR() Function

The INSTR() function returns the position of the first occurrence of a string in another string. This function performs a case-insensitive search.

Syntax:

INSTR(string1, string2)	
Parameter	Description
string1	Required. The string that will be searched
string2	Required. The string to search for in string1. If string2 is not found, this function returns 0

2. Number Functions

MOD() Function

The MOD() function returns the remainder of a number divided by another number.

Syntax:

MOD(*x*, *y*)

ROUND() Function

The ROUND() function rounds a number to a specified number of decimal places.

Syntax:

ROUND(*number*, *decimals*)

TRUNC() Function

The TRUNC() function truncates a number to the specified number of decimal places.

Syntax:

TRUNC(*number*, *decimals*)

CEIL() Function

The CEIL() function returns the smallest integer value that is bigger than or equal to a number.

Syntax:

CEIL(*number*)

3. Date Functions

Date Difference

In Oracle, subtracting two dates returns the number of days between them.

Lab # 04

Working with SQL Operators and Scalar Functions

Syntax:

date2 - date1

Example:

```
SELECT TO_DATE('2026-02-10','YYYY-MM-DD') - TO_DATE('2026-02-05','YYYY-MM-DD') AS days_diff
FROM dual;
```

Add Date / Time

Add days or months to a date using arithmetic or ADD_MONTHS().

Add days: date + number_of_days

Add months: ADD_MONTHS(date, number_of_months)

Example:

```
SELECT SYSDATE + 10 AS future_date,
ADD_MONTHS(SYSDATE, 2) AS future_month
FROM dual;
```

CURRENT_DATE() Function

The CURRENT_DATE function returns the current date in the session time zone.

Syntax:

CURRENT_DATE

Example:

```
SELECT CURRENT_DATE FROM dual;
```

CURRENT_TIME() Function

The CURRENT_TIME function returns the current time.

Syntax:

CURRENT_TIME

Example:

```
SELECT CURRENT_TIME FROM dual;
```

CURRENT_TIMESTAMP() Function

The CURRENT_TIMESTAMP function returns the current date and time.

Syntax:

CURRENT_TIMESTAMP

Example:

```
SELECT CURRENT_TIMESTAMP FROM dual;
```

Lab # 04

Working with SQL Operators and Scalar Functions

TRUNC() Function

The TRUNC() function extracts the date part from a datetime value (removes the time portion).

Syntax:

TRUNC(date)

Example:

```
SELECT TRUNC(SYSDATE) AS today_date FROM dual;
```

Other Date Functions

- EXTRACT(MINUTE FROM date) — Returns the minute part (0–59)
- EXTRACT(HOUR FROM date) — Returns the hour part (0–23)
- EXTRACT(DAY FROM date) — Returns the day of the month (1–31)
- EXTRACT(MONTH FROM date) — Returns the month (1–12)
- EXTRACT(YEAR FROM date) — Returns the year (1000–9999)

Example:

```
SELECT EXTRACT(DAY FROM SYSDATE) AS day,  
EXTRACT(MONTH FROM SYSDATE) AS month,  
EXTRACT(YEAR FROM SYSDATE) AS year  
FROM dual;
```

4. Conversion Functions

TO_CHAR() Function

The TO_CHAR() function formats a **DATE** value into a specified string format.

Syntax:

TO_CHAR(date, format)

Example:

```
TO_CHAR(DATE '2017-06-15', 'Month DD YYYY')
```

TO_CHAR() Function

The TO_CHAR() function formats a **NUMBER** into a specified numeric format and returns it as a string.

Syntax:

TO_CHAR(number, format)

Example:

```
TO_CHAR(1234567.89, '9,999,999.99')
```

Lab # 04

Working with SQL Operators and Scalar Functions

CAST()

Converts a value from one datatype to another using SQL standard syntax.

Syntax:

CAST(value AS datatype)

Example:

```
CAST('2500' AS INTEGER)
```

5. General Functions

NULLIF() Function

The NULLIF() function compares two expressions and returns NULL if they are equal; otherwise, it returns the first expression.

Syntax:

NULLIF(expr1, expr2)

Example:

```
SELECT NULLIF(10, 10) FROM dual; -- returns NULL
SELECT NULLIF(10, 5) FROM dual; -- returns 10
```

COALESCE() Function

The COALESCE() function returns the first non-NULL value from a list of expressions.

Syntax:

COALESCE(val1, val2, ..., val_n)

Example:

```
SELECT COALESCE(NULL, NULL, 25, 50) FROM dual; -- returns 25
```

NVL() Function

The NVL() function returns a specified value if the expression is NULL; otherwise, it returns the expression itself.

Syntax:

NVL(expression, alt_value)

Example:

```
SELECT NVL(NULL, 100) FROM dual; -- returns 100
SELECT NVL(50, 100) FROM dual; -- returns 50
```

THE END!