


Type 2 Liverpool Ringing Simulator

06 – Technical Reference Guide



Author: Andrew Instone-Cowie

Date: 25 August 2021

Version: 1.3

Contents

Index of Figures	5
Index of Tables	7
Document History	8
Licence	8
Documentation Map	9
About This Guide.....	10
Typical Type 2 Simulator Installations	11
Basic Configuration	11
Second PC Module	12
Basic Serial Splitter Module	13
Simulator Overview	14
Bell Sensing Methods.....	14
Sensor Types	14
Single vs Dual Trigger	15
Dual Triggers	15
Single Trigger.....	16
Simulator Interface Module Hardware	18
Overview	18
Hardware Options.....	18
Hardware Interrupts	18
Microcontroller Hardware	19
Serial Line Driver	19
Microcontroller Configuration	20
Microcontroller I/O Pins	20
Microcontroller Fuse Settings	21
Power Supply	22
Typical Current Requirements	22
Microcontroller Package Ratings	22
Voltage Regulator	22
Cable Voltage Drop	22
Heat Dissipation	23
Hardware Compatibility	24

Basic Serial Splitter Module Hardware	25
Overview	25
Serial Line Drivers.....	25
PCB Design	25
Power Supply	25
Downstream Data	26
Fan-Out Calculation	27
Upstream Data	28
Transmitter Disabling	29
Circuit Protection	31
Over-Current Protection	31
Polarity Protection	31
Transient Voltage Suppression	32
Uni-Directional TVS Diodes	33
Bi-Directional TVS Diodes.....	35
Leakage Current Issues	36
Connector Pin-Outs.....	38
Multiple Device Conventions	38
Sensor Module Connector	39
Simulator Interface Module Sensor Connector	40
Simulator Interface Module Power/Data Connector.....	41
Power Module Power/Data Connector	42
Second PC Module Connector	43
Basic Serial Splitter Module Connector	44
DB9 Serial Connectors.....	45
DTEs & DCEs	45
Power Module.....	46
Second PC Module	46
Basic Serial Splitter Module	47
Simulator Interface Module Firmware	48
Sensor Characteristics.....	48
Firmware Design	49
Interrupt Driven vs Polling	49
State Machine Operation.....	50

Timer Issues	52
Sensor De-Bouncing	52
Debugging & Timing Features	53
Serial Input & Command Line Interface	55
Sensor Enable/Disable	55
Memory Footprint.....	56
Metrics	57
Inter-Blow Interval Requirements	57
Inter-Row Interval Requirements	58
Sensor Pulse Duration.....	58
Potential Problems.....	60
Missed Sensor Signals	60
Duplicated Sensor Signals	60
Variable Odd-Struckness.....	61
Latency	62
Software Development & Compatibility.....	65
Development Environment.....	65
Source Code Availability.....	65
Simulator Software Compatibility.....	65
USB-to-Serial Adapters	66
Driver Installation.....	67
Driver Verification.....	69
COM Port Reconfiguration.....	72
Appendices.....	76
Appendix A: MBI Protocol Description	76
Appendix B: MBI Protocol Commands.....	77
Appendix C: Metrics Tables.....	78
Inter-Blow & Inter-Row Interval	78
Sensor Pulse Duration.....	79
BDC-to-Strike Intervals.....	80
Appendix D: CLI Command Reference	81
Appendix E: Diagnostic LED Codes.....	83
Appendix F: Useful Links	84
Appendix G: A Quarter Peal of Cambridge Surprise Minor	85

Licensing & Disclaimers.....	86
Documentation	86
Software	86
Acknowledgements.....	87

Index of Figures

Figure 1 – Documentation Map	9
Figure 2 – Simulator General Arrangement.....	11
Figure 3 – Second PC Module General Arrangement	12
Figure 4 – Basic Serial Splitter Modules General Arrangement.....	13
Figure 5 – Dual Triggers – Backstroke Strike Point	15
Figure 6 – Dual Triggers – Handstroke Strike Point	15
Figure 7 – Single Trigger – Backstroke Strike Point.....	16
Figure 8 – Single Trigger – Handstroke Strike Point.....	16
Figure 9 – Basic Serial Splitter Downstream Data Flow	26
Figure 10 – Basic Serial Splitter Upstream Data Flow.....	28
Figure 11 – Basic Serial Splitter Transmitter Control.....	29
Figure 12 – Polarity Protection – Correct	31
Figure 13 – Polarity Protection – Reversed.....	32
Figure 14 – TVS Diode Characteristic Curves	33
Figure 15 – Uni-Directional TVS Diode.....	34
Figure 16 – Spike Dissipation (Uni-Directional)	34
Figure 17 – Bi-Directional TVS Diode	35
Figure 18 – Spike Dissipation (Bi-Directional)	36
Figure 19 – Leakage Current "Voltage Divider" Effect	37
Figure 20 – Leakage Current – Supplementary Pull-Up Resistor	37
Figure 21 – Sensor Module Connector	39
Figure 22 – Sensor Chain Inter-Connection	39
Figure 23 – Simulator Interface Module Sensor Connector	40
Figure 24 – Simulator Interface 4-Gang Connector	40
Figure 25 – Simulator Interface Module Power/Data Connector.....	41
Figure 26 – Power Module Power/Data Connector	42

Figure 27 – Second PC Module Connector	43
Figure 28 – Basic Serial Splitter Connector	44
Figure 29 – Power Module DB9 Serial Connector.....	46
Figure 30 – Second PC Module DB9 Serial Connector	46
Figure 31 – Basic Serial Splitter DB9 Serial Connectors	47
Figure 32 – Simulator Interface Main Loop Timing	49
Figure 33 – State Machine Transitions Illustration	50
Figure 34 – Sensor De-Bounce Illustration.....	52
Figure 35 – Sensor Pulse Duration Illustration	59
Figure 36 – Missed Sensor Signals Illustration.....	60
Figure 37 – Duplicated Sensor Signals Illustration.....	61
Figure 38 – Variable Odd-Struckness Illustration	62
Figure 39 – Simulator Interface Latency	63
Figure 40 – Logic Analyser Decode	64
Figure 41 – Example of a USB-to-Serial Adapter.....	66
Figure 42 – Prolific Driver Installation.....	67
Figure 43 – Driver Installation Complete	68
Figure 44 – Found New Hardware Message	68
Figure 45 – My Computer Context Menu (Windows XP).....	69
Figure 46 – Computer Context Menu (Windows 7).....	69
Figure 47 – System Properties Hardware Tab (Windows XP)	70
Figure 48 – System Properties Hardware Tab (Windows 7)	70
Figure 49 – Device Manager (Driver Installed)	71
Figure 50 – Device Manager (Driver Missing).....	71
Figure 51 – Device Manager (Port COM14)	72
Figure 52 – Device Manager Context Menu	73
Figure 53 – COM Port Properties.....	73
Figure 54 – COM Port Advanced Settings (Prolific)	74
Figure 55 – COM Port Advanced Settings (FTDI)	74
Figure 56 – Device Manager (Reconfigured Port COM3).....	75
Figure 57 – Liverpool Cathedral Odd-Struckness Chart.....	80
Figure 58 – Quarter Peal Sensor Head Test Timings.....	85

Index of Tables

Table 1 – Microcontroller I/O Pin Assignments	20
Table 2 – ATmega328P Fuse Settings – Board Rev A to D	21
Table 3 – ATmega328P Fuse Settings – Board Rev E onwards	21
Table 4 – TVS Diode Key Properties	32
Table 5 – MBI Protocol Commands.....	77
Table 6 – Inter-Blow & Inter-Row Intervals	78
Table 7 – Sensor Pulse Durations – Liverpool Cathedral	79
Table 8 – Theoretical Sensor Pulse Durations – Other Towers.....	79
Table 9 – CLI Command Reference	81
Table 10 – LED Signal Codes.....	83
Table 11 – Useful Links.....	84

Document History

Version	Author	Date	Changes
0.1	A J Instone-Cowie	26/12/2019	First Draft.
1.0	A J Instone-Cowie	28/12/2019	First Release.
1.1	A J Instone-Cowie	02/01/2020	Add Basic Serial Splitter hardware details, more cabling information, logic analyser trace.
1.2	A J Instone-Cowie	18/08/2020	Minor update.
1.3	A J Instone-Cowie	25/08/2021	Add Circuit Protection, DB9 pin-outs, minor corrections.

Copyright ©2019-21 Andrew Instone-Cowie.

Cover image: Type 2 Simulator Interface PCB Design.

Licence



This work is licensed under a Creative Commons Attribution-ShareAlike 4.0 International License.¹

Unless otherwise separately undertaken by the Licensor, to the extent possible, the Licensor offers the Licensed Material as-is and as-available, and makes no representations or warranties of any kind concerning the Licensed Material, whether express, implied, statutory, or other. This includes, without limitation, warranties of title, merchantability, fitness for a particular purpose, non-infringement, absence of latent or other defects, accuracy, or the presence or absence of errors, whether or not known or discoverable. Where disclaimers of warranties are not allowed in full or in part, this disclaimer may not apply to You.

To the extent possible, in no event will the Licensor be liable to You on any legal theory (including, without limitation, negligence) or otherwise for any direct, special, indirect, incidental, consequential, punitive, exemplary, or other losses, costs, expenses, or damages arising out of this Public License or use of the Licensed Material, even if the Licensor has been advised of the possibility of such losses, costs, expenses, or damages. Where a limitation of liability is not allowed in full or in part, this limitation may not apply to You.

¹ <http://creativecommons.org/licenses/by-sa/4.0/>

Documentation Map




Figure 1 – Documentation Map

About This Guide

The Type 2 Liverpool Ringing Simulator allows sensors, attached to one or more real tower bells or teaching dumb bells, to be connected to a computer Simulator Software Package such as Abel², Beltower³ or Virtual Belfry⁴. This allows you to extend and augment the teaching and practice opportunities in your tower.

This **Technical Reference Guide** contains background information on the design of the simulator hardware and firmware, and other reference material which may be useful.

Configuration guides for the main Simulator Software Packages are available separately, as are the detailed **Build & Installation Guide** and **Multi-PC Guide**.

Please note that this is a Build-it-Yourself project. No pre-built hardware is available.

² <http://www.abelsim.co.uk/>

³ <http://www.beltower.co.uk/>

⁴ <http://www.belfryware.com/>

Typical Type 2 Simulator Installations

Basic Configuration

The following diagram illustrates the general arrangement of a simulator installation using a sensor aggregation hardware interface like the Liverpool Ringing Simulator.

Multiple Sensor Modules in the belfry, one per bell, are connected to a Simulator Interface Module. A single data cable transmits the aggregated signals from the Simulator Interface Module to the Simulator PC in the ringing room. The same cable feeds power from a low voltage power supply in the ringing room, via a Power Module, back up to the Simulator Interface to power both Interface and Sensor Modules. The Type 2 simulator supports up to 16 sensors (only 12 shown on the diagram to save space).

In the ringing room, a PC runs a Simulator Software Package which interprets the received signals and turns them into the simulated sound of bells.




Figure 2 – Simulator General Arrangement

Second PC Module

As an option, multiple Simulator PCs may be used concurrently, using either a Second PC Module, or the Basic Serial Splitter Module.

A second Simulator PC can be connected via a Second PC Module. This module utilises the second transmitter in the Simulator Interface MAX233 RS-232 serial line driver IC, and a spare core in the Power/Data cable, to provide a separate data feed to the Second PC.

A typical configuration with a Second PC Module is illustrated in the following diagram (only a subset of sensors are shown to save space):




Figure 3 – Second PC Module General Arrangement

Basic Serial Splitter Module

The Basic Serial Splitter Module uses additional RS-232 receiver and line driver ICs to copy the stream of signals from the Simulator Interface to multiple PCs. The minimum configuration of the Basic Serial Splitter (the “Master Board”) supports up to four PCs, but this can be linked to a second “Expander Board” which supports four more PCs.

Two Basic Serial Splitter Modules can be daisy-chained between the Power Module and the Simulator Interface Module on RJ45 cables, supporting a maximum of 16 Simulator PCs. The maximum configuration of two daisy-chained Basic Serial Splitters is illustrated in the following diagram (all sensors are omitted to save space):




Figure 4 – Basic Serial Splitter Modules General Arrangement

All Simulator PCs receive a read-only copy of the same signals from the Simulator Interface. Each PC runs its own copy of the Simulator Software Package (or even of different software packages), and the Simulator Software on each PC is configured to filter out unwanted signals.

Any one PC connected to the Basic Serial Splitter can be used to send configuration data to the Simulator Interface, selectable by a switch on the splitter. (If two Basic Serial Splitters are daisy-chained together, only PCs connected to the Splitter nearest to the Power module can be used to configure the Interface.)

Simulator Overview

Bell Sensing Methods

Sensor Types

Over the years a number of different approaches have been used for detecting the position of a tied or dumb bell, and translating that position into a signal for use by a simulator.

- Mechanical switches or contacts suffer from reliability problems, including mechanical fatigue and environmental damage (e.g. corrosion or ingress of dirt), and are not now widely used. Mechanical switches also typically suffer from a high degree of contact “bounce”.
- Electro-Magnetic sensors, typically consisting of a glass-encapsulated reed switch attached to the bell frame and a small magnet attached to the wheel shroud, have also been used, but typically require very close alignment of switch and magnet. They can also suffer from fatigue and contact bounce.
- Inductive sensors, which have a fixed detector circuit attached to the bell frame, and a wire coil fitted to the wheel shroud, have also been used. In principle the absence of moving parts should make these a very reliable option. However a key component of the original design⁵ is no longer available, and parts for an alternative design⁶ are described as difficult to obtain.
- Aidan Hedley has produced a sensor design⁷ using a Honeywell magneto-resistive sensor, activated by a small, powerful rare earth magnet mounted on the wheel shroud. The standard magneto-resistive sensor used by the Type 2 Liverpool Ringing Simulator is derived from this design.
- A wireless, accelerometer-based sensor has been developed and prototyped as the Belfree simulator⁸. This sensor is mounted on the wheel of the bell and communicates with the Simulator PC via a radio link. At the time of writing these not currently available.
- Optical sensor heads using visible light typically consist of a light source, usually a fixed red Light Emitting Diode (LED), mounted parallel to a photo-diode or photo-transistor detector, in an enclosure attached to the bell frame; and a reflector mounted on the wheel shroud. Visible light optical sensors are widely used, are very reliable, and this is the approach adopted by the Bagley MBI sensor heads⁹. Their use can be problematic in areas with high ambient light levels. Other designs include additional pulse-shaping or timing circuitry¹⁰.
- Optical sensor heads using infra-red light are similar in general design, but have reduced susceptibility to ambient visible light levels. A sensor design using a low cost commercially available modulating infra-red detector has been developed as an alternative sensor for the Type 2 Simulator.

⁵ <http://www.abelsim.co.uk/doc/tbellex2.htm>

⁶ http://www.gremlyn.plus.com/ahme/prox_sen.html

⁷ http://www.gremlyn.plus.com/ahme/mag_sen.html

⁸ <http://belfree.co.uk/>

⁹ <http://www.ringing.demon.co.uk/sensors/sensors.htm>

¹⁰ <http://www.abelsim.co.uk/doc/tbellex1.htm>

Single vs Dual Trigger

There are generally two approaches used by simulators when detecting signals from sensors:

- The dual trigger approach uses two triggers (for example, optical reflectors) on the shroud of the wheel of each bell, one of which triggers at the moment that the bell would strike at handstroke, the other at the moment that the bell would strike at backstroke.
- The single trigger approach uses one trigger, which triggers as the bell passes through the bottom dead centre (BDC) of its swing. A delay is then applied (either in the Simulator Interface or the Simulator Software Package) before the simulator triggers the simulated sound of the bell.

The Liverpool Ringing Simulator project adopts the single trigger approach, on the grounds of simplicity of installation and compatibility with other similar systems. This is discussed in more detail in a later section of this guide.

Dual Triggers

The dual trigger approach uses two triggers (for example, optical reflectors or magnets) on the shroud of the wheel of each bell, one of which triggers at the moment that the bell would strike at handstroke, the other at the moment that the bell would strike at backstroke. The simulator triggers the simulated sound of the bell as soon as the signal pulse is received (from the trigger travelling past the sensor as the bell is on its way up to the balance), and then ignores the next signal pulse (as the first trigger travels back past the sensor as the bell is on its way down), and so on.

This approach is illustrated in the following diagrams. In Figure 5 the bell is rising towards the handstroke position, and is passing through the backstroke strike point. The backstroke trigger passes the sensor and generates a signal to the Simulator. Figure 6 shows the opposite stroke as the bell rises towards the backstroke position and passes through the handstroke strike point.




Figure 5 – Dual Triggers – Backstroke Strike Point




Figure 6 – Dual Triggers – Handstroke Strike Point

The sensor is shown at the BDC position only for clarity. The sensor may be located anywhere around the wheel, provided that the geometrical relationship between the sensor and the two triggers is maintained.

This approach has the capacity to provide a very accurate representation of the striking of a bell, but equally requires very accurate placement of the triggers to match the strike points of the bell in motion. This may be difficult and time-consuming to determine.

Single Trigger

The single trigger approach uses one trigger, which triggers as the bell passes through the bottom dead centre (BDC) of its swing. A delay is then applied (either in the Simulator Interface or the Simulator Software Package) before the simulator triggers the simulated sound of the bell.

This approach is illustrated in the following diagrams. In Figure 7 the bell is rising towards the handstroke position. The trigger passed the sensor at BDC, and a delay is applied so that the signal to the Simulator is generated later, as the bell passes through the backstroke strike point. Figure 8 shows the opposite stroke as the bell rises towards the backstroke position and passes through the handstroke strike point.




Figure 7 – Single Trigger – Backstroke Strike Point




Figure 8 – Single Trigger – Handstroke Strike Point

The sensor is again shown at BDC only for clarity. The sensor may be located anywhere around the wheel, provided that the geometrical relationship between the sensor and the trigger is maintained, the trigger being positioned directly opposite the sensor when the bell is down.

This approach is simpler to implement, and the single trigger is much easier to align accurately against the Sensor Head with the bell down. Work by John Norris¹¹ has shown that this approach can provide an acceptable degree of accuracy, with any errors considered too small to be detectable to the human ear.

¹¹ <http://www.jnnorris.co.uk/strike.html>

The Type 2 Liverpool Ringing Simulator adopts the single trigger approach, on the grounds of simplicity of installation, and compatibility with other similar systems.

Simulator Interface Module Hardware

Overview

The Simulator Interface Module hardware consists of three main functional blocks:

- A 5V regulated power supply, which provides power for the interface electronics and for the sensor.
- A digital microcontroller, which detects incoming signals from the sensors, and then sends aggregated signals to the Simulator PC in the form of a stream of ASCII characters.
- A RS-232 serial line driver, which converts the TTL-level signals from the microcontroller to higher voltage RS-232 signals, for transmission over longer distances to the Simulator PC.

All the components of these functional blocks are mounted on a single custom PCB. The same core hardware (and firmware) can connect to any number of Sensors Modules from one to 16.

Hardware Options

Over recent years several low-cost electronic prototyping platforms have been brought to the market, with a number of different architectures, and suitable for a wide range of experimental and embedded functions. These include single board computers running feature-rich operating systems, such as the Raspberry Pi and Beagle Board, and simpler microcontroller-based products such as the Arduino family, PICAXE, ARM Cortex and others.

New devices and variants are released frequently.

The Arduino Uno development platform (based on the Microchip (formerly Atmel) ATmega328P microcontroller¹²) was originally selected as the prototyping platform for the Liverpool Cathedral Simulator project, on the grounds of:

- Simplicity & low cost
- Established user base & wide community support
- Wide availability of additional prototyping peripheral hardware (“shields”)

The use of the same microcontroller family has been continued for the Type 2 Liverpool Ringing Simulator, allowing the same well-supported and freely available tool chain to be used for code development and deployment.

Hardware Interrupts

The choice of the ATmega328P imposes an important constraint on the firmware design for the Simulator Interface, in that the microcontroller has limited support for hardware interrupt inputs. This is described in more detail in a later section of this guide.

¹² <https://www.microchip.com/wwwproducts/en/atmega328p>

Microcontroller Hardware

The Simulator Interface is based on the same Microchip (formerly Atmel) ATmega328P microcontroller as the Arduino Uno used in the first prototype interfaces. Using the same microcontroller makes it very easy to port the Simulator Interface firmware to the new hardware.

- The Simulator Interface¹³ makes use of an external 8MHz resonator as a clock source. Although this is less accurate than a crystal oscillator, it is still adequate for the purposes of the Simulator Interface, and this reduces the overall component count and complexity of the interface board by omitting crystal load capacitors.
- Although the Simulator Interface uses the ATmega328P microcontroller and development tool chain, it does not use the Arduino boot loader program. The ATmega328P is programmed via an ICSP header using a programmer (the *Arduino-as-ISP* method is suggested and is described in more detail in the **Build & Installation Guide**.)

Serial Line Driver

- The Simulator Interface uses the Maxim MAX233 RS-232 serial line driver¹⁴. The MAX233 has the advantage over other line driver ICs of requiring no external charge pump capacitors, also reducing the overall component count. It also provides two RS-232 transmitters, simplifying support for multiple Simulator PCs.

¹³ From Rev E onwards.

¹⁴ <http://www.maximintegrated.com/en/products/interface/transceivers/MAX233.html>

Microcontroller Configuration

Microcontroller I/O Pins

The following table shows the ATmega328P pin assignments for the Type 2 Simulator Interface:

Table 1 – Microcontroller I/O Pin Assignments

Arduino I/O Pin ¹⁵	ATmega328P Physical Pin	Function
0	2	Serial Port Receive
1	3	Serial Port Transmit
2	4	Sensor #12 (T)
3	5	Sensor #10 (O)
4	6	Diagnostic LED
5	11	CRO Timing Pin (enabled in development code only)
6	12	Sensor #1
7	13	Sensor #2
8	14	Sensor #3
9	15	Sensor #4
10	16	Sensor #5
11	17	Sensor #6
12	18	Sensor #7
13	19	Sensor #8
14 (A0)	23	Sensor #9
15 (A1)	24	Sensor #11 (E)
16 (A2)	25	Sensor #13 (A)
17 (A3)	26	Sensor #14 (B)
18 (A4)	27	Sensor #15 (C)
19 (A5)	28	Sensor #16 (D)

¹⁵ Pin numbers as referenced in the Arduino programming environment.

Microcontroller Fuse Settings

The ATmega328P microcontroller has several configuration registers known as *fuses*. These are used to control the behaviour of the microcontroller¹⁶. Fuse values are contained in the file *boards.txt* described in the section on uploading firmware below, and are only written during the *burn bootloader* phase of programming.

Warning: Setting incorrect fuse values can render the microcontroller unusable or prevent further reprogramming without specialist hardware.

The appropriate set of fuses is selected in the Arduino IDE by selecting the correct board type in the Liverpool Ringing Simulator Boards set.

Table 2 – ATmega328P Fuse Settings – Board Rev A to D

Fuse	Value	Notes
Low	0xE2	8MHz internal oscillator, maximum clock startup delay. (SUT0, CKSEL3, CKSEL2, CKSEL0)
High	0XDF	Enable serial programming, boot reset vector disabled. (SPIEN)
Extended	0xFD	Brown-out detection level 1 (2.7V). (BODLEVEL1)

For more details of these fuse settings and their functions, refer to the ATmega328P data sheet, or see the online fuse calculator at:

<http://eleccelerator.com/fusecalc/fusecalc.php?chip=atmega328p&LOW=E2&HIGH=DF&EXTENDED=FD>.

Table 3 – ATmega328P Fuse Settings – Board Rev E onwards

Fuse	Value	Notes
Low	0xCF	8MHz external resonator, maximum clock startup delay. (SUT0, SUT1)
High	0XDF	Enable serial programming, boot reset vector disabled. (SPIEN)
Extended	0xFD	Brown-out detection level 1 (2.7V). (BODLEVEL1)

For more details of these fuse settings and their functions, refer to the ATmega328P data sheet, or see the online fuse calculator at:

<http://eleccelerator.com/fusecalc/fusecalc.php?chip=atmega328p&LOW=CF&HIGH=DF&EXTENDED=FD>.

Note that unlike the Type 1 Simulator Interface, EEPROM contents are cleared on firmware load (high fuse bit 3, EESAVE, is not set, giving 0xDF instead of 0xD7). This is to be confident of having a workable default configuration even if the interface has not yet been configured by the user.

¹⁶ Fuse tutorial: <http://www.martyncurrey.com/arduino-atmega-328p-fuse-settings/>

Power Supply

DC power is supplied to the Simulator Interface over the Power/Data Cable at a higher voltage than required, to overcome the effects of losses due to the resistance of the Power/Data Cable. Incoming power is fed to a conventional linear 5V regulator on the Simulator Interface PCB. An alternative to a conventional linear regulator is described in the **Build & Installation Guide**, for installations with higher current requirements.

Typical Current Requirements

The Simulator Interface Module and Sensor Modules all operate at 5V DC.

- The Simulator Interface current consumption is approximately 25mA.
- The current consumption of the standard Magneto-Resistive Sensor Modules is approximately 8mA per module in the triggered state (i.e. with the LED lit).
- The current consumption of the Infra-Red Sensor Modules is approximately 25mA per module in the triggered state.
- The total current requirement with a full set of 16 Magneto-Resistive Sensor Modules is therefore approximately 153mA.
- The total current requirement with a full set of 16 Infra-Red Sensor Modules is approximately 425mA.

These values are well below the 1A maximum current rating of the specified 5V voltage regulator, however heatsinking may be required for configurations with many Infra-Red Sensor Modules, as noted below.

Microcontroller Package Ratings

The ATmega328P microcontroller has a source/sink current limit of 40mA per pin, and a total device package current limit of 200mA. The majority of the microcontroller pins will be connected to sensor inputs, and these were measured to sink approximately 130 μ A each when triggered, so neither of the microcontroller limits should present a problem. Other pins drive the diagnostic LED and the RS-232 line driver, and in total these do not draw more than a few milliamps.

Voltage Regulator

The Simulator Interface uses a standard linear voltage regulator to provide a regulated 5V DC supply. The voltage regulator requires at least 7V DC at its input pin in order to maintain a stable 5V DC output. The voltage regulator is fed via a polarity protection diode, which drops approximately 0.7V, giving a minimum input voltage requirement of 7.7V at the Simulator Interface input.

Cable Voltage Drop

CAT5 Ethernet cable is specified¹⁷ as having a DC loop resistance of <0.188 Ω /m.

The effective resistance of the power cores of a 25m cable (considering that the simulator configuration doubles up both power and ground cores) is therefore estimated to be approximately 2.35 Ω . At a peak supply current of 425mA, this would result in a voltage drop of approximately 1V along the 25m cable.

¹⁷ <https://www.macinstallations.com/cat-5-cabling-explained/>

Taking into account the voltage drop across the polarity protection diode, the theoretical minimum supply voltage to the cable is approximately 8.7V in order for the voltage regulator to maintain a stable 5V DC output. In practice a multi-voltage DC plug-in power supply unit rated at 1000mA with the output set to 9V has been found adequate for a cable run up to 25m.

For exceptionally long cable runs a 12V DC supply could be used, but there is no advantage to doing so for shorter runs, and the heat dissipation of the voltage regulator will increase, with a requirement for additional heatsinking.

Heat Dissipation

At peak load, with a full complement of 16 Infra-Red Sensor Modules, the voltage regulator would be dissipating a minimum¹⁸ of approximately 0.85W. The power dissipation will be higher with shorter cable runs or a higher supply voltage. The data sheet for the voltage regulator indicates that this will require a heatsink.

An alternative approach, described in the **Build & Installation Guide**, is to replace the linear voltage regulator with a switched buck regulator. These are available as drop-in replacements for the standard TO-220 regulator package and eliminate the need for a heatsink altogether.

¹⁸ Assuming the minimum required input voltage of 7V at the voltage regulator.

Hardware Compatibility

The Type 2 Liverpool Ringing Simulator has been designed to be compatible, as far as possible, with existing simulator hardware, to allow operation with unmodified Simulator Software Packages which support the MBI protocol. This is described in more detail in later section of this guide. The following hardware design decisions have been made to maximise compatibility and interoperability:

- The Simulator Data Connection uses a RS-232 data link to the Simulator, running at 2400 bps, 8 data bits, 1 stop bit, no parity.
- The sensor inputs of the Simulator Interface operate at 5V DC TTL levels. Under normal (un-triggered) conditions the interface expects that the Sensor Head output pin will be HIGH (nominally +5V), and that when triggered the Sensor Head output pin will drop LOW (nominally 0V) for the duration of the trigger pulse¹⁹.

Unlike the Type 1 design, the simplified cabling used by the Type 2 Simulator Interface means that the sensor inputs do not use the same 4-pin GX16-4 panel mount connectors as the Bagley MBI. Integrating existing sensors into the Type 2 Simulator may be achieved using the Generic Sensor module described in the ***Build & Installation Guide***.

¹⁹ Sensors which operate with reverse logic (normally LOW, going HIGH when triggered) may be accommodated by amending the firmware to look for LOW to HIGH transitions.

Basic Serial Splitter Module Hardware

Overview

The Basic Serial Splitter Module replicates data sent from the Simulator Interface Module (“downstream data”) to up to 8 Simulator PCs. All PCs receive copies of the same data, simultaneously. For example, typically this allows more than one ringer with headphones to use the simulator with a simulated band at the same time, the Simulator Software Package on each ringer’s PC responding only to the Sensor on “their” tower bell.

The Basic Serial Splitter Module also allows any one Simulator PC to send data to the Simulator Interface Module (“upstream data”) for configuration purposes. The active Simulator PC is selected using a DIP switch on the Basic Serial Splitter Module.

Finally, it is possible to daisy-chain two Basic Serial Splitters to allow the connection of up to 16 Simulator PCs. When two Basic Serial Splitters are daisy-chained together, only PCs on the more downstream Splitter Module can be used to send configuration data to the Simulator Interface Module.

The Basic Serial Splitter Module is a passive device and has no microcontroller or firmware.

Serial Line Drivers

The Basic Serial Splitter uses two different Serial Line Driver ICs. Data to and from the upstream Simulator Interface Module is handled by a Maxim MAX3323, and data to and from the Simulator PCs is handled by a Maxim MAX208.

- The MAX3323 has been selected to handle the interface data because it can disable its transmitter and receiver in response to additional control pins (only the ability to disable the transmitter is used in the Basic Serial Splitter Module), and because its receiver has the capacity to fan out to multiple transmitters (calculation below).
- The MAX208 consists of 4 pairs of RS-232 transmitters and receivers in a single package. It can therefore handle signals to and from up to 4 PCs per IC. Note that no RS-232 control lines are connected. A second MAX208 on the expander board supports a further 4 PCs.

PCB Design

The Basic Serial Splitter Module has been designed such that a common PCB can be assembled either as a Master Board with connections to the Simulator Interface Module, Power Module, and up to 4 PCs; or as an Expander Board, which connects to the Master Board and up to 4 further PCs.

The Expander Board requires only a subset of the components normally fitted to a Master Board. This is detailed in the assembly instructions in the *Multi-PC Guide*.

Power Supply

The Basic Serial Splitter derives its power from the Power Module, using the power lines looped through on the RJ45 connectors. Although the Basic Serial Splitter current requirements are very low, a large TO-220 voltage regulator is used to handle the additional heat dissipation if the installation requires a 12V supply instead of the usual 9V.

Downstream Data

The downstream data flow is illustrated in the following diagram:




Figure 9 – Basic Serial Splitter Downstream Data Flow

Data from the Simulator Interface Module is received at RS-232 line levels by the receiver on the MAX3323, which inverts and level shifts it to TTL levels. The data is then fanned out to up to 8 MAX208 transmitters, which invert and level shift it back to RS-232 line levels for the connected Simulator PCs.

Fan-Out Calculation

The MAX3323 can operate on supply voltages between 3.0V and 5.5V. In the Basic Serial Splitter Module design the supply voltage V_{CC} is nominally 5.0V, and the V_L logic supply pin is tied to V_{CC} .

The choice of $V_{CC} = 5.0V$ is driven by the MAX208, which requires a supply voltage of 5.0V.

MAX3323 RS-232 receiver output specification:

Output Voltage Low V_{OL} :

- $I_{OUT} = 1.6mA$, $V_L > 1.8V$, guarantees $V_{OL} < 0.4V$
- $I_{OUT} = 1mA$, $V_L \leq 1.8V$, guarantees $V_{OL} < 0.4V$
- Hence at $V_L = V_{CC} = 5.0V$, the receiver output can sink up to 1.6mA while maintaining V_{OL} below 0.4V.

Output Voltage High V_{OH} :

- $I_{OUT} = -1mA$, $V_L > 1.8V$, guarantees $V_{OH} > V_L - 0.4V$
- $I_{OUT} = -500\mu A$, $V_L \leq 1.8V$, guarantees $V_{OH} > V_L - 0.4V$
- Hence at $V_L = V_{CC} = 5.0V$, the receiver output can source up to 1mA while maintaining V_{OH} above 4.6V.

MAX208 RS-232 transmitter input specification:

Input Voltage Low:

- Input Logic Threshold Low $< 0.8V$
- Input internal pull-up resistor = 400k Ω
- Input current therefore approximately 12.5 μA per transmitter with transmitter input held low.
- One MAX3323 receiver will drive 8 x MAX208 transmitters in a fully populated Basic Serial Splitter Module (master board + expander board).
- 12.5 μA x 8 transmitters = 100 μA
- 100 μA is less than the maximum 1.6mA which the MAX3323E receiver output can sink.
- Hence one MAX3323 RS-232 receiver can maintain $V_{OL} < 0.4V$, which is less than the 0.8V MAX208 RS-232 transmitter logic low threshold, while driving the required 8 x MAX208 RS-232 transmitters.

Input Voltage High:

- Input Logic Threshold High $> 2.0V$
- The MAX208 transmitter input pull-up resistor ensures logic high even if the input is open circuit. No external current source is required.
- Hence one MAX3323 RS-232 receiver output can maintain $V_{OH} > 4.6V$, which is greater than the 2.0V MAX208 RS-232 transmitter logic high threshold, while driving the required 8 x MAX208 RS-232 transmitters.

Upstream Data

The upstream data flow is illustrated in the following diagram:




Figure 10 – Basic Serial Splitter Upstream Data Flow

Data from a Simulator PC is received at RS-232 line levels by a receiver on a MAX208, which inverts and level shifts it to TTL levels. The data from one PC (Simulator PC #1 in the diagram above) is then connected via the DIP switch to the MAX3323 transmitter, which inverts and level shifts it back to RS-232 line levels for the Simulator Interface Module.

It is important to note that only one MAX208 receiver should be connected at any time to the MAX3323 transmitter.

- The MAX208 ensures that the outputs of any receivers not connected to an RS-232 source are held at logic 1 level (logic 1 is high voltage – approximately V_{CC} – on the TTL side).
- Connecting more than one receiver at the same time will result in an effective short circuit from V_{CC} to ground during any data transmission from a connected PC, as the other receiver tries to pull its output low. This may damage the MAX208.

Transmitter Disabling

Two Basic Serial Splitter Modules may be daisy-chained to support a maximum of 16 Simulator PCs.

- Where a single Basic Serial Splitter Module is used, only one Simulator PC can be used to send configuration data to the Simulator Interface Module. The active PC is selected using the 8-position DIP switch on the Basic Serial Splitter Module.
- Where two Basic Serial Splitter Modules are daisy-chained together, only one module can be used to send configuration data to the Simulator Interface Module (the active PC on that module being selected with the DIP switch, as above).
- Only the RS-232 transmitter on the downstream of the two modules is enabled; the transmitter on the upstream module is disabled.
- The disabling of the upstream transmitter is automatic and cannot be configured.

The circuit controlling the transmitter disabling function is illustrated in the following diagram:




Figure 11 – Basic Serial Splitter Transmitter Control

The transmitter disabling function operates as follows:

- The Basic Serial Splitter Modules uses the MAX3323 RS-232 serial line driver IC, which has the capability to disable the serial transmitter via a control pin, making the RS-232 level transmit T1OUT²⁰ pin passive and high impedance²¹.
- When a single Basic Serial Splitter Module is used, the TXENABLE pin is held high via a 10k Ω pull-up resistor.
- The TXENABLE pin is also connected to pin 8 of the *Power Board* connector. This pin is not connected on the Power Module, so the TXENABLE pin is still held high. This enables the RS-232 transmitter.
- Pin 8 on the *Interface* connector is connected to ground (0V). This pin is not used on the Simulator Interface Module, so this has no effect.
- When a second Basic Serial Splitter is connected, pin 8 on the *Power Board* connector of the upstream module is connected to the *Interface* connector of the downstream interface. This has the effect of pulling low the TXENABLE pin of the upstream module's MAX3323.
- This disables the upstream MAX3323's RS-232 transmitter and makes the T1OUT transmit pin high impedance. PCs connected to the upstream module cannot transmit data to the Simulator Interface Module, regardless of the DIP switch setting.
- The TXENABLE pin of the downstream module's MAX3323 is still held high by its pull-up resistor. As above, this pin is connected to pin 8 of the *Power Board* connector, but this is not connected on the Power Module, so the TXENABLE pin is still held high. The downstream module's RS-232 transmitter remains enabled.

²⁰ Pin names as defined in the MAX3323 data sheet.

²¹ The RS-232 receiver can also be disabled, but this functionality is not used in the Basic Serial Splitter Module.

Circuit Protection

Over-Current Protection

Primary over-current protection is provided by the 800mA fuse fitted to the Power Module.

Secondary over-current protection is provided by the selected LM340T-5.0 voltage regulator²² or alternative Traco Power TSR 1-2450 switched buck regulator²³. Both devices have internal short-circuit protection and thermal shutdown features.

The LM340T-5.0 has internal thermal overload protection, and an internal short-circuit current limit of 2.1A.

The short-circuit current limit of the Traco Power TSR 1-2450 is not specified in the data sheet, but the maximum input current is given as 1000mA (1A).

Polarity Protection

The use of polarised connectors on all modules of the Liverpool Ringing Simulator minimises the possibilities for reversed polarity connections between modules. However, many general-purpose plug-in power supply units are provided with a selection of non-polarised reversible connector tips, with the consequent risk of inadvertently connecting the power supply with the polarity reversed.

The Simulator Interface Module and the Basic Serial Splitter Module are therefore provided with a reverse polarity protection diode, connected before the voltage regulator or other polarity sensitive devices.

The diode specified is a 1N4001 device²⁴, which has a maximum peak forward current rating of 1A, and a peak inverse voltage rating of 50V, which is adequate for a fully specified simulator.

With correct power supply polarity, the diode is forward biased and conducts, allowing current to flow to the rest of the Interface or Splitter Module. This is illustrated in the following diagram:




Figure 12 – Polarity Protection – Correct

²² <https://www.ti.com/lit/gpn/LM340>

²³ https://www.tracopower.com/sites/default/files/products/datasheets/tsr1_datasheet.pdf

²⁴ <https://www.vishay.com/docs/88503/1n4001.pdf>

If the power supply is connected with the polarity reversed, the diode is reverse biased and does not allow current to flow, thus protecting the remainder of the electronics. The peak inverse voltage rating of the diode provides protection up to 50V. Reverse polarity connection is illustrated in the following diagram:




Figure 13 – Polarity Protection – Reversed

Transient Voltage Suppression

The Liverpool Ringing Simulator modules are fitted with Transient Voltage Suppression (TVS) diodes to provide a degree of protection against induced over-voltage spikes on the power supply and signal lines, for example resulting from local lightning strikes or electrostatic discharge events.

Uni-directional TVS diodes are used on logic and power supply lines. Bi-directional TVS diodes are used on the RS-232 signal lines.

The key properties of the diodes specified are listed in the following table, taken from the device data sheet:²⁵

Table 4 – TVS Diode Key Properties

Part Number	Reverse Standoff Voltage (V_R)	Breakdown Voltage (V_{BR})	Maximum Clamping Voltage (V_C)	Maximum Peak Pulse Current (I_{PP}) (A)	Maximum Reverse Leakage Current (I_R @ V_R) (μA)
SA5.0A	5.0	6.40 – 7.00	9.2	55.4	600
SA12A	12.0	13.30 – 14.70	19.9	25.6	1
SA15CA*	15.0	16.70 – 18.50	24.4	20.9	1

(* Bi-directional)

TVS diodes will not provide protection against direct lightning strikes. Disconnecting the Simulator Interface cable from the Power Module is recommended when the simulator is not in use.

²⁵

https://www.littelfuse.com/~media/electronics/datasheets/tvs_diodes/littelfuse_tvs_diode_sa_datasheet.pdf

The differences between the behaviour of uni-directional and bi-directional TVS diodes can be seen in the following graphs:²⁶




Figure 14 – TVS Diode Characteristic Curves

When reverse biased up to its Reverse Standoff Voltage, a uni-directional TVS diode does not conduct (apart from the Reverse Leakage Current discussed further below). As the reverse voltage reaches and exceeds the Breakdown Voltage, the diode starts to conduct, restricting the further increase in applied voltage, until the Maximum Peak Pulse Current is reached, at which point the voltage is effectively clamped at the Clamping Voltage.

When forward biased, a uni-directional TVS diode behaves much like a conventional rectifier diode and starts conducting with a very small forward voltage drop.

A bi-directional TVS diode is effectively two diodes connected anode-to-anode. It therefore always behaves as though it is reverse biased.

Note that the quoted values are not continuous ratings. TVS diodes are designed to absorb large amounts of power during sub-millisecond spikes.

Uni-Directional TVS Diodes

12V Reverse Standoff Voltage uni-directional TVS diodes are fitted across the incoming unregulated power supply rails of the following modules:

- Power Module
- 2nd PC Module
- Basic Serial Splitter Module

5V Reverse Standoff Voltage uni-directional TVS diodes are fitted across the 5V regulated power rails of the Simulator Interface Module and the Sensor Modules, and between the 5V signal line and ground on the Sensor Modules.

The uni-directional TVS diodes operate as follows: On power supply rails, the power rail is always expected to be positive relative to ground rail; between +9V and +12V for the unregulated supplies, and +5V for the regulated supplies.

²⁶ From the data sheet, © 2020 Littelfuse, reproduced under fair use.

On data signal lines, the signal line is expected to be at +5V or 0V relative to the ground rail.

The TVS diode is connected as shown in the following diagram and is therefore normally reverse biased at up to²⁷ its rated Reverse Standoff Voltage, and no current flows through the diode:




Figure 15 – Uni-Directional TVS Diode

If a transient voltage event causes the power or signal line voltage to spike above Breakdown Voltage of the TVS diode, the diode starts to conduct, holding the rail down to the Clamping Voltage and dissipating the power of the spike. This is illustrated in the following diagram:




Figure 16 – Spike Dissipation (Uni-Directional)

If a transient voltage event causes the voltage of the ground rail to rise above that of the power rail or signal line, the diode is forward biased and starts to conduct, clamping the two lines together and dissipating the power of the spike.

²⁷ "up to" because the suggested power supply is 9V or 12V depending on the installation.

Bi-Directional TVS Diodes

15V Reverse Standoff Voltage bi-directional TVS diodes are fitted between the RS-232 data lines and ground in the following modules:

- Power Module
- 2nd PC Module
- Basic Serial Splitter Module

RS-232 data lines may operate in the range +15V to -15V relative to the ground rail²⁸, but the typical voltage swing achieved by the line drivers used in the Liverpool Ringing Simulator is $\pm 8V$ (MAX233, MAX208) or $\pm 5.4V$ (MAX3323). These are still within the limits of the RS-232 specification, which deliberately allows for wide ranges.

Because the RS-232 data lines swing both positive and negative relative to ground, uni-directional TVS diodes cannot be used, and bi-directional TVS diodes are required.

The bi-directional TVS diodes operate as follows: Regardless of whether the RS-232 data line is currently positive or negative relative to the ground rail, the TVS diode is always effectively reverse biased at up to its rated Reverse Standoff Voltage, and no current flows through the diode:




Figure 17 – Bi-Directional TVS Diode

²⁸ For introductions to RS-232, see the following: <https://www.maximintegrated.com/en/design/technical-documents/tutorials/8/83.html>, <https://www.arcelect.com/rs232.htm>

If a transient voltage event causes the RS-232 data line spike outside the Breakdown Voltage of the TVS diode (so above +15V, or below -15V), the diode starts to conduct, holding the rail down to the Clamping Voltage and dissipating the power of the spike. The direction in which the diode conducts depends on the polarity of the spike. This is illustrated in the following diagram:




Figure 18 – Spike Dissipation (Bi-Directional)

Leakage Current Issues

As noted above, the TVS diodes pass a Reverse Leakage Current when reverse biased, and for lower voltage diodes this can be substantial. The SA5.0A diode has a leakage current up to 600 μ A at 5V, and this can cause problems with microcontroller inputs.

Most sensors have “open-collector” outputs. When the sensor is triggered, a transistor inside the sensor turns on and connects the output pin to the ground rail, pulling it low. When the sensor is not triggered, the transistor turns off and the output pin “floats”. A pull-up resistor is required to pull the pin high.

The ATmega328P microcontroller requires an input pin to reach approximately 3V (V_{IH} Min) to be considered “high”, and has weak internal pull-up resistors which can be activated in code to pull floating input pins high²⁹. The value of these resistors is not formally specified but is estimated to be in the range 20k Ω – 50k Ω , and may vary between devices.

As well as being pulled high by the microcontroller internal pull-up resistor, the sensor output pin is also connected the ground rail via a TVS diode. Reverse biased, the diode behaves like a resistor, and the weak internal pull-up resistor and the TVS diode “resistor” form a simple voltage divider which can be enough to hold the untriggered pin below the 3V required for it to be registered as high by the microcontroller.

²⁹ See INPUT_PULLUP in the Simulator Interface firmware code, for example.

This is illustrated in the following schematic:




Figure 19 – Leakage Current "Voltage Divider" Effect

To counteract this, the Sensor Modules are also fitted with a supplementary “helper” 10kΩ pull-up resistor, as shows in the following diagram. A value of 10kΩ has been found adequate with the sensors used, but if found necessary the value of this resistor could be reduced further to 4.7kΩ.




Figure 20 – Leakage Current – Supplementary Pull-Up Resistor

Connector Pin-Outs

Multiple Device Conventions

The following conventions are used by the Power/Data connections between the Simulator Interface Module and any downstream devices (such as the Power Module or Multi-PC Modules, where these are used).

- Data is transmitted by the Simulator Interface Module downstream on pin 2, and from board Rev D, also on pin 6, using the second RS-232 transmitter in the MAX233.
- Upstream configuration data is received from the (or a) Simulator PC on pin 4.
- Power pins are doubled up to mitigate the effects of voltage drop in longer cable runs. Pins 5 and 7 are used for the nominal +9V supply to the devices, and pins 1 and 3 are 0V.
- Any downstream device connected to a Simulator Interface should expect to find and to use incoming serial data on pin 2 of the RJ45 Interface connector.
- Any downstream device connected to a Simulator Interface should assume that there may also be incoming serial data on pin 6 of the RJ45 Interface connector³⁰, and should loop pin 6 to pin 2 on any downstream connector³¹.
- Any downstream device which does not require to send data to an upstream Simulator Interface should loop pin 4 of the RJ45 Interface connector to pin 4 on any downstream connector³².
- Any downstream device which requires to send configuration data to an upstream Simulator Interface should do so on pin 4 of the RJ45 Interface connector. This pin should also be looped to pin 4 on any downstream connector.
- Where multiple devices have the potential to send configuration data to an upstream Simulator Interface concurrently, a device should ground pin 8 to assert their right to send on pin 4³³.

³⁰ As there will be from Interface Module Revision D onwards.

³¹ See the Second PC Module and Basic Serial Splitter Module connectors below.

³² For example, the Second PC Module.

³³ For example, the Basic Serial Splitter.

Sensor Module Connector

The Sensor Modules use RJ45 connectors for the downstream cabling connection towards the Simulator Interface, and upstream connections to other Sensor Modules in the same chain.

- Each Sensor Module presents its output signal on pin 8 of the downstream *Interface* connector. Each Sensor Module takes any upstream sensor signals appearing on pins 4, 6 and 8 of the *Next Sensor* connector, and loops them through to pins 2, 4 and 6 respectively of the *Interface* connector.
- Pin 2 of the Next Sensor connector is not used, and hence connecting more than four sensors in one chain is not possible.
- Power pins are doubled up to mitigate the effects of voltage drop in longer cable runs. Pins 5 and 7 are used for the +5V supply to sensors, and pins 1 and 3 are 0V. These pins are looped through between the *Interface* and *Next Sensor* connectors.

The wiring of the female PCB connector is shown in the following diagram:




Figure 21 – Sensor Module Connector

The daisy-chain inter-connection of the sensors is illustrated in the following diagram:




Figure 22 – Sensor Chain Inter-Connection

Simulator Interface Module Sensor Connector

The Simulator Interface Module uses RJ45 connectors for the upstream cabling connection to the Sensor Modules. A 4-gang connector is used, allowing the connection of up to 16 sensors.

The wiring of each female PCB connector is shown in the following diagram:




Figure 23 – Simulator Interface Module Sensor Connector

The layout of the 4-gang RJ45 PCB connector is shown in the following diagram:




Figure 24 – Simulator Interface 4-Gang Connector

Simulator Interface Module Power/Data Connector

The Simulator Interface Module uses an RJ45 connector for the downstream cabling connection to the Power Module (or Multi-PC Modules, where these are used).

- Data is transmitted downstream towards the Power Module on pin 2 (and from board Rev D, also on pin 6, using the second RS-232 transmitter in the MAX233), and upstream configuration data is received from the Simulator PC on pin 4.
- Power pins are doubled up to mitigate the effects of voltage drop in longer cable runs. Pins 5 and 7 are used for the nominal +9V supply to the interface, and pins 1 and 3 are 0V.

The wiring of the female PCB connector is shown in the following diagram:




Figure 25 – Simulator Interface Module Power/Data Connector

Power Module Power/Data Connector

The Power Module uses an RJ45 connector for the upstream cabling connection to the Simulator Interface Module (or Multi-PC Modules, where these are used).

- Data is received from the upstream Simulator Interface Module on pin 2, and upstream configuration data is sent to the interface on pin 4.
- In a basic single PC configuration, any data received on pin 6 is discarded. Pin 6 is connected only to a TVS surge protection diode.
- Power pins are doubled up to mitigate the effects of voltage drop in longer cable runs. Pins 5 and 7 are used for the nominal +9V supply to the interface, and pins 1 and 3 are 0V.
- Pin 8 is not connected. This is required for correct operation when the Basic Serial Splitter Module is used.

The wiring of the female PCB connector is shown in the following diagram:




Figure 26 – Power Module Power/Data Connector

Second PC Module Connector

The Second PC Module uses RJ45 connectors for the upstream cabling connection to the Simulator Interface, and the downstream connection to the Power Module.

- Power pins 1, 3, 5 and 7, and the spare pin 8 are looped through from the *Interface* connector to the *Power Board* connector.
- Pin 4 is used to send data (marked RX – configuration data received from the point of view of the upstream interface module) and is also looped through; this pin is not connected to the 9-pin serial connector on the Second PC Module.
- Sensor data received on Pin 2 of the *Interface* connector (marked TX – sensor data transmitted from the point of view of the upstream interface module) is routed to the 9-pin serial connector on the Second PC Module.
- Sensor data received on Pin 6 of the *Interface* connector (marked TX2) is looped through to pin 2 of the *Power Board* connector.
- Connecting more than two Second PC modules is therefore not possible; only the two most upstream modules will receive data from the Simulator Interface Module.

The wiring of the female PCB connector is shown in the following diagram:




Figure 27 – Second PC Module Connector

Basic Serial Splitter Module Connector

The Basic Serial Splitter Module uses RJ45 connectors for the upstream cabling connection to the Simulator Interface Module, and the downstream connection to the Power Module.

- Power pins 1, 3, 5 and 7 are looped through from the *Interface* connector to the *Power Board* connector.
- Pin 4 is used to send data (marked RX – configuration data received from the point of view of the upstream interface module) and is also looped through; where two Basic Serial Splitter Modules are daisy-chained, the RS-232 transmitter of the upstream splitter module is disabled. This mechanism is discussed in detail in a previous section.
- Sensor data received on Pin 2 of the *Interface* connector (marked TX – sensor data transmitted from the point of view of the upstream interface module) is routed to the PCs connected to the Basic Serial Splitter Module.
- Sensor data received on Pin 6 of the *Interface* connector (marked TX2) is looped through to pin 2 of the *Power Board* connector. This data may be used a second, downstream Basic Serial Splitter Module.
- Pin 8 on each connector is used to enable or disable the RS-232 transmitter of the upstream splitter module where more than one Basic Serial Splitter Module is used.
- Connecting more than two Basic Serial Splitter Modules is therefore not possible; only the two most upstream modules will receive data from the Simulator Interface Module, and the transmitters of all but the most downstream module will be disabled.

The wiring of the female PCB connector is shown in the following diagram:




Figure 28 – Basic Serial Splitter Connector

DB9 Serial Connectors

The Power Module, Second PC Module and Basic Serial Splitter Module all use standard 9-pin female sub-miniature D connectors (“DB9”) for serial data connections to attached Simulator PCs. The pin-outs of these connectors are illustrated below.

DTEs & DCEs

In RS-232 communications, the description of connector pins as *Transmit* or *Receive* can be confusing. Devices can be configured as *Data Terminal Equipment* (DTE) or *Data Communication Equipment* (DCE). Traditionally, for example, a PC would be configured as a DTE, connected to a modem configured as a DCE.

By convention, a DTE has a male connector, a DCE has a female connector, and the DTE-to-DCE connection uses a female-to-male *straight cable*³⁴. A PC acting as DTE transmits data to the DCE from Pin 3 of the PC’s DB9 connector, which would be designated TD or TX; and receives data from the DCE on Pin 2, designated RD or RX³⁵. The DCE uses a female connector, receives data from the DTE on Pin 3, still designated as the “transmit” pin on the DCE, and sends data to the DTE on Pin 2, still designated as the “receive” pin on the DCE³⁶.

The Simulator PC is a DTE. The Simulator Modules are fitted with female DB9 connectors and for simplicity are all wired for use with straight cables, so are technically DCEs and should by convention use DCE pin naming conventions.

However, to make the simulator module designs easier to follow, the schematics follow the transmit and receive pin designations used by the ATmega328P microcontroller UART, and the RS-232 sides of the Maxim MAX233, MAX208 and MAX3323 line drivers. Following these conventions, the module pins used for transmitting sensor data from the Simulator Interface to the attached PC are marked *TX*, and the module pins used for receiving CLI data from the attached PC to the Simulator Interface are marked *RX*. This is the opposite of the usual convention for a DCE.

³⁴ i.e. wired pin 1 to pin 1, pin 2 to pin 2, pin 3 to pin 3, and so on.

³⁵ Just to add to the confusion, the Pin 2 RX and Pin 3 TX pin functions are swapped over on 25-pin (DB25) RS-232 connectors.

³⁶ Refer to the links to introductions to RS-232 given previously.

Power Module

The Power Module uses a female DB9 connector for the downstream cabling connection to the Simulator PC.

- Pin 2 is used for simulator sensor data transmitted to the attached PC.
- Pin 3 is used for CLI data transmitted to the Simulator Interface from the attached PC.

The wiring of this connector is shown in the following diagram:




Figure 29 – Power Module DB9 Serial Connector

Second PC Module

The Second PC Module uses a female DB9 connector for the downstream cabling connection to the Simulator PC.

- Pin 2 is used for simulator sensor data transmitted to the attached PC.
- Pin 3 is not connected. It is not possible to use the CLI from the PC attached to the Second PC Module.

The wiring of this connector is shown in the following diagram:




Figure 30 – Second PC Module DB9 Serial Connector

Basic Serial Splitter Module

The Basic Serial Splitter Module uses female DB9 connectors for the downstream cabling connections to the Simulator PCs.

- Pin 2 is used for duplicated simulator sensor data transmitted to each attached PC.
- As noted previously in the section on *Transmitter Disabling* in the *Basic Serial Splitter Hardware* section of this document, only one selected Simulator PC connected to a Basic Serial Splitter Module can be used to send CLI configuration data to the Simulator Interface Module.
- Pin 3 will be used for CLI data sent to the Simulator Interface from the selected attached PC only. On all other connectors this pin will be connected to an inactive RS-232 receiver.

The wiring of this connector is shown in the following diagram:




Figure 31 – Basic Serial Splitter DB9 Serial Connectors

Simulator Interface Module Firmware

Sensor Characteristics

Over the years several different approaches have been used for detecting the position of a tied or dumb bell and translating that position into a signal for use by a Simulator. These are discussed above.

- For the purposes of the Type 2 Simulator Interface Module, the essential feature of the sensor is that it should generate a signal pulse with a clean change of logic state when the bell is at the bottom dead centre of its swing.
- The Type 2 Simulator Interface Module adopts the convention that the output of a sensor should normally be logic high ($\sim +5V$), falling to logic low ($\sim 0V$) for the duration of the pulse. This approach retains compatibility with other similar systems.
- The minimum practical pulse duration is a few milliseconds, but should be long enough to allow for the positive detection of good signals and the rejection of noise. Practical implementations have shown actual pulse durations in the range 5ms-20ms.
- The design of the Simulator Interface Module firmware is such that the maximum apparent pulse duration may be several hundred milliseconds. The state of the output from the sensor is ignored from the time a good signal is confirmed to the expiry of the “guard timer”.

Firmware Design

Interrupt Driven vs Polling

As noted in the hardware section above, an interrupt-driven approach to the Simulator Interface firmware would be problematic on the Atmel ATmega328P microcontroller hardware. The firmware therefore uses a polling approach. After completing initialization and setup, the main code loop cycles round all the configured bells' inputs, processing signals from the Sensor Modules and sending serial data to the Simulator PC as appropriate. After all bells have been processed, the code loops round and the process starts again.

In the current version of code (v3.5), with the ATmega328P driven by an external 8MHz resonator, each iteration of the main polling loop takes approximately 400µs when configured for 16 sensors, which is fast enough for the disadvantages of polling not to be significant. Enabling debug mode and the CRO timing pin increases the loop time by a few percent, but as these are not intended for active simulator use this is also not significant.

The timing of the main loop using the CRO timing pin is illustrated in the following CRO capture:




Figure 32 – Simulator Interface Main Loop Timing

Processing of serial input from the Simulator, in the form of CLI commands, is triggered by the standard Arduino *serialEvent()* function.

State Machine Operation

The Simulator Interface firmware maintains a set of 16 simple state machines, one for each bell. At any given time, each state machine may be in one of three possible states: *Waiting for Input*, *Waiting for Debounce*, *Waiting for Guard Timer*, *Sensor Disabled*, or *Test Mode*.

These changes of state are illustrated in the following diagram:




Figure 33 – State Machine Transitions Illustration

Waiting for Input

When a channel's state machine is in the *Waiting for Input* state, on each iteration of the polling loop the firmware code reads the state of the input pin connected to the associated channel, and checks for a change in state (since the last poll) from logic HIGH to LOW, which would indicate the start of a signal pulse from the connected Sensor Module.

- If no HIGH to LOW change in state is detected, then the Interface code does nothing other than update its record of the last observed state of the input pin, and the code loop moves on to the next bell.
- If the start of a sensor pulse is detected then the code calculates the time at which the input de-bounce timer should expire (by adding the value of the global de-bounce timer to the current time from the microcontroller's internal clock, in effect setting a timeout value), and switches the state machine into the *Waiting for Debounce* state. The default value for the de-bounce timer is 2ms, but this can be configured through the Simulator Interface CLI.

Waiting for Debounce

When a channel's state machine is in the *Waiting for Debounce* state, on each iteration of the polling loop the firmware code reads the state of the input pin connected to the associated channel.

- If the pin state is detected as HIGH, then the input pulse previously detected has ceased. The code treats this as a "misfire" and switches the state machine back to the *Waiting for Input* state. The code loop moves on to the next bell.
- If the pin state is still LOW, the code compares the value of the de-bounce timeout with the current time from the microcontroller's internal clock.
- If the timeout value has not yet been reached, the code does nothing and moves on to the next bell. The state machine remains in the *Waiting for Debounce* state.
- If the timeout has been reached or has been passed, the code sends the appropriate character over the serial interface to the Simulator PC, and switches the state machine into the *Waiting for Guard Timer* state.

Waiting for Guard Timer

When a channel's state machine is in the *Waiting for Guard Timer* state, the firmware code compares the value of the Guard Timer timeout with the current time from the microcontroller's internal clock.

- If the timeout value has not yet been reached, the code does nothing and moves on to the next bell. The state machine remains in the *Waiting for Guard Timer* state.
- If the timeout has been reached or has been passed, the code switches the state machine back into the *Waiting for Input* state, and the cycle starts again. The default value for the Guard Timer is 10cs (100ms), but this can be configured through the Simulator Interface CLI.
- The channel input pin is not read in the *Waiting for Guard Timer* state (other than for debugging purposes), effectively debouncing the end of the sensor pulse.

Disabled Sensor

When a channel's state machine is in the *Sensor Disabled* state, the firmware code does nothing and moves on to the next bell. *Sensor Disabled* state is enabled through the CLI or from EEPROM configuration data during setup, and the state machine remains in the *Sensor Disabled* state until reset through the CLI.

Note that the number of channels to be scanned on each iteration is determined dynamically with reference to the highest numbered enabled channel: For example, if the highest numbered enabled channel is channel 10, only channels 1 to 10 will be scanned, shortening the loop time. If the highest numbered enabled channel is channel 16, then channels 1 to 16 will be scanned.

Test Mode

The *Test Mode* state implements a very simple test function, ignoring sensor inputs and generating simple test patterns on the serial interface. *Test Mode* state is enabled through the CLI, and persists until the interface is reset. This facility exists primarily for testing other components of a simulator installation.

The foregoing description covers the core simulator functionality. In addition to this, debug code provides additional timing and data gathering functions which are described later.

Timer Issues

The ATmega328P microcontroller lacks a true Real Time Clock. The library inbuilt timing functions (*millis()* and *micros()*) return the number of milliseconds or microseconds respectively since the microcontroller was last powered on or the last hardware reset. All times used within the software are therefore offset times from this baseline.

The Simulator Interface firmware uses both the *millis()* and *micros()* functions for its main timing and delay calculations (*micros()* is used only by debugging code). These functions return 32-bit unsigned long data types; consequently the value returned by *micros()* will increase and then overflow back to zero after approximately 50 power-on days, and the value returned by *millis()* will overflow approximately every 70 minutes.

These overflows would disrupt simulator processing, as state machines may become “stuck” waiting for an overflowed timer to expire.

- In the case of the *micros()* timer, which is used for the sensor debounce timer, the Simulator Interface firmware attempts to catch this overflow, and looks for timer expiry times which are an unreasonably long time into the future.
- For the *millis()* timer, the current version of Simulator Interface firmware will require a power cycle or reset to clear the problem. This issue may be addressed in a future version of the firmware. However, this is considered a low-priority issue because it is unlikely that a Simulator Interface will be left powered up for such extended periods of time.

Sensor De-Bouncing

The Simulator Interface firmware reacts to the start of a pulse from a sensor. In practice the output from some sensor types may be noisy and consist of a number of very short pulses, especially at the start or end of a pulse. This is known as “bounce”, a term derived from the physical elastic bounce of a mechanical contact. This is illustrated in the following diagram:




Figure 34 – Sensor De-Bounce Illustration

The current version of the Simulator Interface code reacts to the first observed transition in the output of the sensor (indicated by the red arrow on the diagram).

The code then requires that the sensor signal remains stable for at least the duration of the global debounce timer (default 2ms, configurable). If the detected signal ceases within that interval then the signal is treated as a “misfire”, is ignored, and the code returns the state machine to the *Waiting for Input* state. The debounce timer is specified in milliseconds, but calculated in microseconds for improved consistency. The resolution of the microsecond timer is 8μs.

When the state machine has switched into the *Waiting for Guard Timer* state, the input pin is not read at all (other than by debug code, which includes specific detection and reporting of multiple pulses), and any sensor bounce is therefore ignored. Provided that the overall sensor pulse is shorter than the duration of the guard timer, this effectively de-bounces the input. Typically, the input pulse from an optical sensor will be a few milliseconds in duration, and the guard time several hundred milliseconds, so this is not a practical issue.

In testing, no evidence of sensor bounce from the standard infra-red optical or magneto-resistive Sensor Modules was observed, within the resolution of the debug timing code and the microsecond timer.

Debugging & Timing Features

In addition to the core timing and delay functions described above, which are required for core Simulator operation, the Simulator Interface firmware implements further timing and data gathering for debugging and experimental purposes. This output is not suitable for sending to Simulator Software package, but may be accessed via a terminal emulator such as PuTTY.

This debugging functionality is not part of the MBI Protocol specification.

Under normal operations, each pulse from a Sensor Module causes one ASCII character (following the conventional ringing notation of 1-9, 0, E, T) to be sent via the serial port for use by the Simulator PC, as defined in the MBI Protocol specification.

The following debugging features are available in firmware v3.5:

Debug Mask

The *Debug Mask* allows for debugging output to be enabled on a specific subset of input channels.

- This may be used to reduce the volume of debug output generated during fault finding. By default, the mask enables debugging on all 16 channels.
- The Debug Mask setting may be saved in non-volatile EEPROM³⁷.
- Note that enabling Debug Mode globally suppresses normal simulator output for all channels, not just those set in the debug mask.

Debug Pulse Timer

When the *Debug Pulse Timer* flag is set, each valid input pulse will generate output on a separate line, with the following space separated data fields:

- The channel number (1-16),
- The mapped ASCII character (1-90ETABCDWXYZ),
- The guard timer expiry offset time in milliseconds,
- The identifier "S",
- The duration of the (first) detected pulse, in microseconds,
- The total number of pulses detected before the expiry of the guard timer.

³⁷ The Debug Mask is saved to EEPROM if the Save Settings CLI command ("S") is invoked when Debug Mode is active.

Note that the pulse length timing code is not entirely robust: the assumption is made that the first Sensor Module pulse will be shorter than the guard timer. If the first pulse has not completed by the time the guard timer expires, a spuriously large result would be displayed for the pulse length, because the last recorded pulse end time (from the previous sensor pulse) will be before the current pulse start time, and the *unsigned long* data type will overflow. This is trapped by the code and displayed as a zero duration. This limitation affects debugging output only.

Debug Show Misfires

When the *Debug Show Misfires* flag is set, pulses shorter than the de-bounce timer will generate output on a separate line, with the following space separated data fields:

- The channel number (1-16),
- The mapped ASCII character (1-90ETABCDWXYZ),
- The debounce timer expiry offset time in microseconds,
- The identifier “M”,
- The duration of the (first) detected pulse, in microseconds.

Debug Show Debounce

When the *Debug Show Debounce* flag is set, pulses longer than the debounce timer will generate output on a separate line, with the following data fields:

- The channel number (1-16),
- The mapped ASCII character (1-90ETABCDWXYZ),
- The debounce timer expiry offset time in microseconds,
- The identifier “D”.

Debug Show LED

When the *Debug Show LED* flag is set, the diagnostic LED output will be enabled for all bells for which debugging is enabled. By default, the diagnostic LED indicates pulses detected on channel 1 only.

Debug Settings

Debug settings other than the Debug Mask are volatile and are not retained in EEPROM. Resetting the Simulator Interface will revert to the following default debug settings:

- Debug Mode: Off
- Debug Flags: *Debug Pulse Timer*
- Debug Mask: EEPROM Value

Note that changes to the configured Debug Flags and the Debug Mask are remembered if Debug Mode is disabled via the CLI, so debugging may be resumed easily with the same settings.

Serial Input & Command Line Interface

The Simulator Interface firmware implements a simple Command Line Interface (CLI), which may be used to configure certain aspects of the Interface, or to gather debugging and timing data. This functionality is not part of the MBI Protocol specification.

The Simulator Interface also must handle legitimate MBI Protocol commands and delay data sent by the Simulator Software, in order to differentiate these from CLI input (even though these data are not used by the Type 2 Simulator Interface). This processing is done inside the Arduino *serialEvent()* function, with the CLI itself handed off to a set of separate functions.

To achieve this, the firmware adopts the following strategy when handling serial input.

- The first byte received is examined. If this byte is a recognised MBI Protocol command (See Appendix B), it is discarded. No responses are sent to MBI commands.
- If the first byte is not a recognised MBI Protocol command, it may be the first of a set of updated delay values. There is no defined command byte defined in the MBI Protocol to precede a set of delay values, so the Simulator Interface attempts to read a full set of 13 bytes (12 values plus the specified terminator byte) within a defined timeout interval (one second in the current v3.5 firmware).
- If 12 values plus the correct terminator byte have been received within the timeout period, these are assumed to be delay values, and all 13 bytes are discarded.
- If a full set of values cannot be read, or the terminator is incorrect, the first (and possibly only) byte read is passed on to the CLI handler for further examination. Any bytes after the first are discarded.
- If the received byte is a recognised CLI command (Appendix B), it is processed, and any appropriate response sent.
- If the received byte is not a recognised CLI command, it is discarded.

The diagnostic LED is used to indicate that a CLI command has been received, or that an error occurred. The CLI command are documented in Appendix D below.

Sensor Enable/Disable

The Simulator Interface firmware can be configured to disable any individual sensor input, for example to bypass temporarily a faulty sensor. Disabled inputs are ignored by the firmware, and generate no serial output, including debugging output. This behaviour is configured using CLI commands (Appendix D), accessed via a terminal emulator. The enabled or disabled state of each input channel is stored in non-volatile EEPROM.

As noted above, the number of channels to be scanned on each iteration is determined dynamically with reference to the highest numbered enabled channel.

Memory Footprint

The ATmega328P has a very limited 2kByte SRAM capacity. The *MemoryFree* software library has been incorporated into the Simulator Interface code to track SRAM usage. This may be displayed via the Interface CLI. Flash (Program) Memory usage is reported by the Arduino IDE when the software sketch is compiled.

The memory footprint of the Simulator Interface firmware v3.5 on an ATmega328P is as follows:

- 12,742 / 32,768 Bytes Flash Memory
- 718 / 2,048 Bytes SRAM
- 23 / 1,024 Bytes EEPROM

The compiler *F()* macro has been used throughout the Interface code to store static text strings into program memory, thus relieving pressure on SRAM. As a result the current v3.5 of the Interface firmware can run on older ATmega128 microcontrollers with 16kBytes of Flash Memory and only 1kByte of SRAM.

Metrics

The effects of three key metrics have been considered in the design of the Simulator Interface firmware. These are:

- The inter-blow interval: The rate at which the Simulator Interface is required to detect and transmit signals from all Sensor Modules to the Simulator during normal ringing.
- The inter-row interval: The rate at which the Simulator Interface is required to detect signals from any one Sensor Module during normal ringing.
- The Sensor Pulse Duration: The length of the pulse from each Sensor Module which the Simulator Interface is required reliably and unambiguously to detect.

Each of these metrics is considered further below.

Inter-Blow Interval Requirements

For any given ring of bells, the inter-blow and inter-row requirements can be estimated from the known speed of ringing.

For example, for the Liverpool Cathedral bells, taking 4h 30m as a representative speed for a peal of 5042 changes of Maximus on the (82cwt) twelve, the inter-blow interval in rounds is given by the calculation:

$$(270 \text{ minutes} \times 60 \text{ seconds}) / (5042 \text{ changes} \times 12 \text{ bells}) = 0.268\text{s or } 268\text{ms}$$

Taking 3h 15m as a representative speed for a peal of 5056 changes of Major on the light (24cwt) eight, the inter-blow interval in rounds is given by the calculation:

$$(195 \text{ minutes} \times 60 \text{ seconds}) / (5056 \text{ changes} \times 8 \text{ bells}) = 0.289\text{s or } 289\text{ms}$$

The serial protocol used by the Simulator Interface Module runs at 2400 bits per second, and sends a single ASCII character for each blow of each bell. Each character comprises 10 bits (8 data bits, plus 1 start bit and 1 stop bit), giving a maximum continuous data rate of 240 characters per second, or approximately 4.2ms per character.

This confirms that the Simulator Data Connection has sufficient capacity, and has a resolution of approximately 1.6% of the inter-blow interval. Put another way, if the bells are fired accurately then the signals from all 12 bells can be sent over the data link to the Simulator PC within 51ms, or less than one fifth of the normal inter-blow interval. (True firing, the simultaneous striking of more than one bell, is not achievable with a Simulator Interface of this design.)

Under normal operation, where one byte at a time is sent to the Simulator PC, the serial print function call is non-blocking and operates asynchronously, so the main code loop is not slowed down or paused while data is sent to the Simulator PC³⁸.

(Note that generating detailed debugging output from a large number of bells can cause the serial output buffer to fill and the serial print function to block. This can cause issues with timing behaviour and debugging output.)

³⁸ <http://blog.arduino.cc/2011/10/04/arduino-1-0/>

A more detailed analysis of the inter-blow intervals for a large sample of rings of bells may be found in Appendix C.

Inter-Row Interval Requirements

The inter-row interval follows from a similar calculation:

For the Liverpool Cathedral bells, taking 4h 30m as a typical speed for a peal of 5042 changes of Maximus, the inter-blow interval in rounds is given by the calculation:

$$(270 \text{ minutes} \times 60 \text{ seconds}) / 5042 \text{ changes} = 3.21\text{s}$$

Taking 3h 15m as a typical speed for a peal of 5056 changes of Major on the light (24cwt) eight, the inter-blow interval in rounds is given by the calculation:

$$(195 \text{ minutes} \times 60 \text{ seconds}) / 5056 \text{ changes} = 2.31\text{s}$$

As discussed below, the Simulator Interface firmware runs with a loop time of approximately 400µs, giving a resolution of less than 0.017% of the typical 12-bell inter-row interval.

A more detailed analysis of the inter-row intervals for a large sample of rings of bells may be found in Appendix C.

Sensor Pulse Duration

For a typical, the theoretical expected duration of the signal pulse from the Sensor Module is a function of the width of the trigger (e.g., 25mm wide reflective tape or 20mm diameter magnets in the current installations) and the linear speed of the rim of the bell wheel as the bell passes through the bottom dead centre trigger point.

This linear speed can be approximated as $4\pi R/T$, where R is the radius of the wheel, and T is the pendulum period of the bell for small oscillations. This calculation is based on the work of Frank King of Cambridge³⁹. Applying the basic equations of motion to these parameters produces theoretical pulse durations of approximately 4ms.

However, this does not take into account the actual size of the sensor head, and the fact that the sensor head may activate before the trigger is fully axially aligned with the module (and will not deactivate until after the trigger has ceased to be fully axially aligned). In addition to this, the detection zone on many sensors is effectively conical, and at the wheel is therefore somewhat larger than the physical diameter of the detector.

³⁹ <http://www.cl.cam.ac.uk/~fhk1/Bells/equations.pdf>

The following diagram illustrates this effect:




Figure 35 – Sensor Pulse Duration Illustration

In the diagram above, the Sensor Module signal pulse starts before the trigger is fully aligned with the sensor (top red arrow), and ends after the trigger has cease to be fully axially aligned (bottom red arrow). Thus, the effective width of the trigger, and the duration of the resulting pulse, are increased.

This is supported by evidence: An analysis of the theoretical and observed sensor pulse durations from the optical Sensor Heads of the original Liverpool Cathedral Simulator installation can be found in Appendix C. The sensor shielding tube has an internal diameter of approximately 17mm, and the observed values of pulse duration, approximately 6ms, indicate that the effective width of the reflector is increased from the actual 25mm to approximately 40mm.

Potential Problems

The use of a polling approach in the Simulator Interface results in a number of potential problems:

Missed Sensor Signals

If the Simulator Interface firmware polling interval is longer than the pulse emanating from a Sensor Module, then there is a risk that some pulses may be missed. If a pulse starts just after the polling loop has examined a particular input pin, the pulse will have completed before the polling loop next returns to that input pin. As a result the pulse will be missed and no signal will be sent to the Simulator.

The following diagram illustrates this problem:




Figure 36 – Missed Sensor Signals Illustration

The red dashed arrows indicate the point at which the polling loop examines a particular input pin. During the remainder of the polling loop an incoming sensor pulse begins and completes without ever being detected.

Given a typical pulse duration of approximately 6ms, and a maximum polling loop duration of approximately 400μs, each pulse therefore lasts approximately 15 polling loop cycles, so this problem does not arise.

Duplicated Sensor Signals

If the Simulator Interface firmware polling interval is shorter than the pulse emanating from a Sensor Module (which, as noted above, is a requirement for reliable detection), then there is a probability that some pulses may be detected more than once. If the polling loop examines a particular input pin just after a pulse starts, then that pulse may still be in progress when the polling loop next returns to the same input pin. As a result the pulse will be detected more than once and duplicate signals would be sent to the Simulator PC.

The following diagram illustrates this problem:




Figure 37 – Duplicated Sensor Signals Illustration

The red arrows indicate the points at which the polling loop examines a particular input pin. Because the incoming sensor pulse is longer than the polling loop, it is still in progress during the next loop, and would be detected again.

This problem is avoided by triggering based on detecting the transition of the input pin state from HIGH to LOW, and keeping state in the Interface code. Therefore, when the polling loop next returns to the input pin, the pin is still LOW, but no state transition is detected, and no duplicate signals are sent.

It will be observed that decreasing the polling loop duration to avoid the Missed Sensor Signals problem results in the manifestation of the Duplicated Sensor Signals problem, and vice-versa.

Variable Odd-Struckness

A further problem arising from the use of a polling architecture in the Simulator Interface is variable odd-struckness.

- If a pulse from any particular Sensor Module starts a fraction of a second before the polling loop examines the associated input pin, the pulse will be detected almost immediately.
- If the pulse starts a fraction of a second after the polling loop examines the associated input pin, the pulse will be detected on the next iteration of the polling loop, in this case approximately 400µs later.
- There is no fixed correlation between the start time of a pulse and the current position of the polling loop in its cycle, and therefore each pulse is subject to an effectively random delay of between zero and 400µs (the duration of the polling loop).
- This would be experienced as the simulated bell striking randomly early or late by between zero and half the polling interval.

The following diagram illustrates this problem:




Figure 38 – Variable Odd-Struckness Illustration

The upper red arrow indicates the polling loop examining a particular input pin just after the start of an incoming sensor pulse. The delay due to polling is effectively zero. The lower red arrow indicates the polling loop examining a particular input pin just before the start of an incoming sensor pulse, and detecting the pulse on the next iteration of the loop. The delay due to polling is effectively equal to the polling loop interval.

Given a typical inter-row interval of say 2.3s, and a maximum polling loop duration of approximately 400μs, the variable odd-struckness contributed due to this problem is therefore between zero and ±0.009% of the inter-row interval, and in practice this is not detectable. Even for much lighter rings of bells with much shorter inter-row intervals this may still be assumed to be negligible.

Scope does exist to reduce the length of the polling loop further. The debug and timing code contribute approximately several tens of microseconds to the loop time, and could be omitted entirely from production code.

Latency

The latency of a simulator system is the delay between the bell triggering the sensor at BDC, and the arrival of the corresponding signal at the Simulator PC.

The latency of the simulator system is not critical in BDC detecting systems, provided it is relatively small (much less than the time between BDC and strike), is reasonably consistent, and is symmetrical about the BDC position. Latencies of up to several tens of milliseconds may be accommodated by tuning the delay time applied by the Simulator PC.

The latency of the simulator consists of the sum of the following:

- The debounce timer,
- The polling loop time,
- The RS-232 serial speed.

The default debounce timer is set to 2ms. As discussed above, the polling approach results in some variation of detection time, and the polling loop time is approximately 400 μ s. Moving the state machine from *Waiting for Input* to *Waiting for Debounce*, and then detecting the end of the debounce timer, involves two polling events. The average latency from the start of a sensor pulse to the start of the serial transmission should therefore be approximately⁴⁰ 2.4 \pm 0.2ms.

The serial line speed is 2400bps. Each ASCII character transmission consists of 10 bits (8 data bits, preceded by one start bit and followed by one stop bit). The time taken to transmit one character is therefore approximately 4.2ms and is constant.

The theoretical total latency of the simulator is therefore approximately 6.6 \pm 0.2ms. Any additional latency arising in the Simulator Software Package is beyond the scope of this discussion but may be compensated for by tuning the delay time applied by the software.

The typical latency of the Simulator Interface is illustrated in the following annotated CRO capture:




Figure 39 – Simulator Interface Latency

- The upper yellow trace represents a simulated sensor pulse measured on a Simulator Interface Module input pin. The duration of the pulse is approximately 5ms, and the pin transitions from +5V to 0V at the start of the pulse.
- The lower blue trace represents the RS-232 serial transmission, measured on the serial transmit pin of the same interface.
- On the serial line, logic 0 is a high voltage (approximately +8V), logic 1 is low (approximately -8V), and the bus idles at the logic 1 level⁴¹. The start bit is logic 0, the stop bit is logic 1, and hence the end of the stop bit cannot be distinguished from the idle level.

⁴⁰ This estimate does not consider the resolution of the microsecond timer, 8 μ s.

⁴¹ Note that these are for the RS-232 serial interface. The TTL serial interfaces between the microcontroller and the line driver operates between 0V and +5V, with inverted logic.

- The character transmitted is ASCII “1” (0x31), binary 00110001, and is transmitted LSB first. Reading from left to right, the total bit stream is therefore “0100011001” (10 bits: a logic 0 start bit, ASCII “1” LSB first, and a logic 1 stop bit).
- The delay between the start of the sensor pulse and the start of the serial transmission is measured over multiple pulses as being between 2.200ms and 2.660ms, average 2.442ms. The latency start to end of the serial transmission can be estimated as approximately 4.2ms. These values are very close to the theoretical predictions.

The following logic analyser decode taken at the MAX233 transmitter input shows the same effect:




Figure 40 – Logic Analyser Decode

- Trace D0 is taken from the TTL level signal at the MAX233 transmitter input. The signal is therefore inverted with respect to the transmitter output recoded by the previous oscilloscope trace.
- Trace D1 is the trigger, taken from the channel 1 sensor line. Recording started at Time 0 when this line transitioned to logic 0. This was a manual trigger, so the end of the trace is not visible as the pulse was more than 8ms long.

Software Development & Compatibility

Development Environment

The Simulator Interface firmware has been developed on the following versions of operating systems, development tools and Simulator Software packages. Later versions of tools are expected to be compatible:

- Microsoft Windows 7 SP1 32-bit
- Arduino IDE 1.6.12
- PuTTY 0.70
- PortMon 3.03

Source Code Availability

The current version of the firmware for the Simulator Interface is available from the project GitHub repository at <https://github.com/Simulators>. The firmware is released under the GNU General Public Licence (GPL), Version 3.

Simulator Software Compatibility

Tested Configurations

The Type 2 Liverpool Ringing Simulator Interface has been tested successfully with Simulator Software Packages up to the following versions:

- Abel 3.10.1a
- Beltower 2017 (12.35)
- Virtual Belfry⁴² 3.5

Untested Configurations

Compatibility with the Bagley Ringleader hardware simulator has not been tested. This device has been unavailable for purchase for some time due to key components no longer being available.

Future Simulator Support

The Simulator Interface software has also been structured to allow for the future addition of support for other simulators should this be necessary.

⁴² 3.1b is the minimum version of Virtual Belfry required for proper handling of interfaces of this type.

USB-to-Serial Adapters

If the Simulator PC does not have an available RS-232 serial port, then a USB-to-Serial adapter may be used. These are available from a variety of manufacturers, but mainly use controller chips manufactured by Prolific and FTDI.

Adapters usually require the installation of a software driver. Drivers for adapters based on Prolific⁴³ and FTDI⁴⁴ controllers are available from the respective websites; the driver required is the *Virtual COM Port* or *VCP* version.

A typical USB-to-Serial adapter (in this case from Prolific) is shown in the following photograph.



Figure 41 – Example of a USB-to-Serial Adapter

⁴³ http://www.prolific.com.tw/US/ShowProduct.aspx?p_id=225&pcid=41

⁴⁴ <http://www.ftdichip.com/Drivers/VCP.htm>

Driver Installation

Follow the installation instructions supplied with the USB-to-Serial port driver software package. This example uses adapters and drivers with both Prolific and FTDI chipsets, but the approach is similar for adapters from other vendors.

1. Run the installer supplied with the driver software package. Both Prolific and FTDI drivers use a standard Windows installer.




Figure 42 – Prolific Driver Installation

2. When the installation is complete, close the installer. A restart of the PC may be required.




Figure 43 – Driver Installation Complete

3. Connect the USB-to-Serial adapter to a spare USB port on the Simulator PC. To ensure consistent COM port numbering and avoid the need to reconfigure the Simulator Software Package, it is best always to use the same USB port for the adapter.
4. The Simulator PC should detect the USB-to-Serial adapter, configure the driver, and a confirmation balloon message should appear briefly above the Windows system tray.




Figure 44 – Found New Hardware Message

Driver Verification

To verify that the USB-to-Serial adapter driver is correctly configured, open the Windows Device Manager and look for the adapter in the Ports section.

1. Right-click the *Computer* or *My Computer* icon on the Windows desktop and select the *Properties* menu item. These examples are from Windows XP and Windows 7 PCs, the process and appearance may vary for other versions of Windows.




Figure 45 – My Computer Context Menu (Windows XP)




Figure 46 – Computer Context Menu (Windows 7)

2. On Windows XP, click on the *Hardware* tab, and then click the *Device Manager* button.




Figure 47 – System Properties Hardware Tab (Windows XP)

3. On Windows 7, click the *Device Manager* button.




Figure 48 – System Properties Hardware Tab (Windows 7)

- Expand the *Ports (COM & LPT)* section of the Device Manager list. The USB-to-Serial adapter should be listed, and the COM port number identified. In this example the adapter has been assigned the Virtual COM Port number *COM3*.




Figure 49 – Device Manager (Driver Installed)

- If the device driver software has not been installed correctly, the adapter may be found with a warning marker in the *Other Devices* section of the device list. Install the device driver software or refer to the documentation for the USB-to-Serial adapter.




Figure 50 – Device Manager (Driver Missing)

COM Port Reconfiguration

Current versions of specific Simulator Software Packages require that the Virtual COM Port number assigned to a USB-to-Serial adapter is in a specified range⁴⁵. If the adapter has been assigned a COM port number outside the supported range, the port must be reconfigured to lower value⁴⁶.

1. Open the Windows Device Manager as described above.
2. Expand the *Ports (COM & LPT)* section of the Device Manager list. The USB-to-Serial adapter should be listed, and the COM port number identified. In this example the Prolific adapter has been assigned the Virtual COM Port number *COM14*, which is beyond the range supported by Abel.




Figure 51 – Device Manager (Port COM14)

⁴⁵ Abel: COM1 – 8. Beltower: COM1 – 8 (32 from Beltower 2016).

⁴⁶ Virtual Belfry does not have this requirement.

3. Right-click the USB-to-Serial adapter entry and select the Properties menu item.




Figure 52 – Device Manager Context Menu

4. Click on the *Port Settings* tab, and then click the *Advanced...* button.




Figure 53 – COM Port Properties

5. Use the *COM Port Number* dropdown to select a COM port number in the range COM1 to COM8. Then click *OK*. Note that some values may be listed as “in use” if they have ever been assigned (for example, if other USB devices have been attached to the PC in the past). Use the Device Manager to determine which COM ports are in use.




Figure 54 – COM Port Advanced Settings (Prolific)

6. The *Advanced Settings* window for the FTDI driver is more complex, but the reconfiguration method is the same.




Figure 55 – COM Port Advanced Settings (FTDI)

7. It may be necessary to unplug the USB-to-Serial adapter, then plug it back before the adapter is correctly identified and initialised with the new COM port number.




Figure 56 – Device Manager (Reconfigured Port COM3)

Appendices

Appendix A: MBI Protocol Description

Note that although the Type 2 Liverpool Ringing Simulator uses the basic MBI serial protocol described below, it does not upload or store the delay timers in the Simulator Interface Module, and those parts of the protocol are not implemented. Delays are instead applied by the Simulator Software Package on the Simulator PC. This allows the simulator to support more than 12 sensors and allows more flexibility, for example in the simulation of raising and lowering.

The following description of the MBI Protocol is derived from information supplied by David Bagley and Chris Hughes.

The MBI aggregates signals from a number of sensors, one per bell, into a stream of ASCII characters sent over a RS-232 serial data link to the Simulator. This link operates at 2400 bps, 8 data bits, 1 stop bit, no parity.

Within the MBI, each bell has a delay timer value configured which corresponds to the time between the bell passing through the bottom dead centre of its swing, and the time the clapper would normally strike the bell. These delay values are uploaded by the Simulator PC and stored by the MBI in non-volatile memory.

When a signal from a Sensor Head is detected, the MBI applies the delay timer (appropriate to that bell), and at the expiry of that timer the MBI sends the corresponding single ASCII character to the Simulator, which then produces the simulated sound of that bell. The characters are defined using the usual change ringing convention of “O”, “E” & “T” for bells 10, 11 & 12. At present a maximum of 12 bells are supported by the protocol.

The MBI Protocol also includes provision for connecting up to 4 external command switches, for which the characters sent are “W”, “X”, “Y” & “Z”. This behaviour is not currently supported by Bagley MBI interface hardware, but Abel has support for the protocol functionality.

The MBI also receives serial input from the Simulator. The command set defined by the protocol is described in Appendix B. Not all features of the command set are used by all Simulator applications.

Appendix B: MBI Protocol Commands

The following table lists the commands defined in the MBI Protocol.

Table 5 – MBI Protocol Commands

Command	Function
0xFD	<p>The 0xFD command is used to detect the presence of a Simulator Interface. The expected response is for the Interface to return one byte, hexadecimal value 0xFD.</p> <ul style="list-style-type: none"> • This command does not appear to be used by tested versions of either Abel, Beltower or Virtual Belfry. • This command is not used or supported by the Type 2 Liverpool Ringing Simulator firmware.
0xFE	<p>The 0xFE command is used to retrieve the current timer delay versions from the Simulator Interface. The expected response is for the Interface to return 13 bytes, one byte for each bell in the order 1 to 12, containing the current delay value in centiseconds expressed as a hexadecimal value, and a trailing termination byte, hexadecimal value 0xFF.</p> <ul style="list-style-type: none"> • This command is used by the tested version of Beltower when operating in MBI mode. • This command does not appear to be used by the tested versions of Abel or Virtual Belfry. • This command is not used or supported by the Type 2 Liverpool Ringing Simulator firmware.
0xNN ... 0xFF	<p>Timer delay data is sent to the Simulator Interface by the Simulator Software Package as a series of 13 bytes, one byte for each bell in the order 1 to 12, containing the new delay value in centiseconds expressed as a hexadecimal value, and a trailing termination byte, hexadecimal value 0xFF. All 12 values are always sent, even if fewer than 12 bells are configured. In this case the data is padded with 0x00 bytes.</p> <ul style="list-style-type: none"> • This command is used by tested versions of Abel, Beltower and Virtual Belfry when operating in MBI mode. • This command is not used or supported by the Type 2 Liverpool Ringing Simulator firmware.

Appendix C: Metrics Tables

Inter-Blow & Inter-Row Interval

This appendix contains a more detailed analysis of the inter-blow and inter-row intervals for a large sample of rings of bells. A total of 4096 records of peals and quarter peals were downloaded from the *Ringling World Bell Board* database using the experimental XML API.

This data was then sanitised to remove all hand bell performances, any performances for which the duration or number of changes was not specified, and to convert the duration to consistent units. This left a total of 3080 performances comprising 54.7 Million blows for analysis.

The following table shows the results of this analysis:

Table 6 – Inter-Blow & Inter-Row Intervals

Bells ⁴⁷	Total Performances	Total Blows	Inter-Row Interval (s)	Inter-Blow Interval (ms)	
12	111	4452144	2.93	244	Max
			1.96	164	Min
			2.41	200	Mean
10	265	8554130	2.84	284	Max
			1.67	167	Min
			2.22	222	Mean
8	1203	25199176	2.69	336	Max
			1.25	157	Min
			2.10	262	Mean
7	9	81396	2.26	323	Max
			2.05	292	Min
			2.18	312	Mean
6	1341	15074688	2.68	447	Max
			1.06	177	Min
			2.01	334	Mean
5	116	1168285	3.00	600	Max
			1.12	224	Min
			1.99	398	Mean
4	23	149088	2.26	566	Max
			1.57	393	Min
			1.88	471	Mean
3	12	45432	2.10	698	Max
			1.67	556	Min
			1.95	651	Mean
All	3080	54724339	3.00	698	Max
			1.06	157	Min

⁴⁷ Including the cover bell, if any.

Sensor Pulse Duration

The following table shows the small pendulum period, wheel radius, estimated wheel rim speed and theoretical pulse duration for each bell at Liverpool Cathedral, based on a reflector tape 25mm wide; and the observed pulse duration measured during development by the Simulator Interface firmware in debug mode, using infra-red detectors.

The wheel rim speed is calculated as $4\pi R/T$, where R is the radius of the wheel, and T is the pendulum period of the bell for small oscillations.

Table 7 – Sensor Pulse Durations – Liverpool Cathedral

Bell	Period T (s)	Wheel Radius R (m)	Estimated Wheel Rim Speed (m/s)	Theoretical Pulse Duration (ms)	Observed Pulse Duration (Range) (ms)
1	1.60	0.81	6.38	3.9	5.7 (5.6 - 6.2)
2	1.60	0.84	6.58	3.8	6.2 (6.1 - 6.3)
3	1.60	0.86	6.78	3.7	6.0 (5.9 - 6.1)
4	1.70	0.86	6.38	3.9	6.2 (6.0 - 6.3)
5	1.75	0.89	6.38	3.9	6.4 (6.3 - 7.2)
6	1.80	0.89	6.21	4.0	5.9 (5.7 - 6.2)
7	2.00	0.99	6.22	4.0	6.3 (5.8 - 6.4)
8	2.05	1.07	6.54	3.8	7.7 (7.5 - 7.8)
9	2.25	1.14	6.38	3.9	6.6 (6.4 - 6.7)
10	2.40	1.22	6.38	3.9	6.5 (6.1 - 6.7)
11	2.40	1.32	6.92	3.6	6.7 (6.5 - 6.9)
12	2.60	1.50	7.24	3.5	6.1 (6.0 - 6.3)

The effect of the “overlap” effect described in the main text on the observed pulse durations is evident when the theoretical and observed duration figures are compared.

Similar measurements of period and wheel radius have been made on a number of other smaller bells, and these yield similar results. This suggests that, in this regard at least, the Cathedral bells are unexceptional, and the sensing approach adopted may be re-used elsewhere. The following table shows the results of these investigations. No simulators are currently fitted to these bells and no actual pulse duration measurements have been made.

Table 8 – Theoretical Sensor Pulse Durations – Other Towers

Bell	Period T (s)	Wheel Radius R (m)	Estimated Wheel Rim Speed (m/s)	Theoretical Pulse Duration (ms)
<i>St John the Baptist, Tuebrook</i>				
1	1.60	0.80	6.28	4.0
5	1.70	0.88	6.47	3.9
8	2.00	0.98	6.16	4.1
<i>St Helen, Sefton</i>				
1	1.50	0.71	5.95	4.2
4	1.60	0.77	6.01	4.2
7	1.80	0.87	6.04	4.1

BDC-to-Strike Intervals

The following chart shows the average time differences obtained during development between the triggering of an infra-red optical Sensor Module and a sound operated sensor for each bell at Liverpool Cathedral. Separate average values are shown for handstroke, backstroke, and both strokes combined. The total sample size was 93 blows.




Figure 57 – Liverpool Cathedral Odd-Struckness Chart

Appendix D: CLI Command Reference

The following table lists the additional CLI commands supported by the Type 2 Simulator Interface firmware, and their functions, as of version 3.5.

Table 9 – CLI Command Reference

Command	Function
?	Display current settings This command sends a detailed set of configuration and operational values to the serial port for review.
B/b	Set the de-bounce timer (1ms -> 20ms, default 2ms). This command prompts for the value of the de-bounce time, in milliseconds. See also command "S".
G/g	Set the guard timer (1cs -> 50cs, default 10cs). This command prompts for the value of the guard time, in centiseconds (1cs = 10ms). See also command "S".
E/e	Enable/disable sensors. This command prompts for the enable mask bit to be set or unset for each input channel. This determines which channels will generate output, and can be used for example to bypass a faulty Sensor Module. See also command "S".
R/r	Remaps Sensor Module channel numbers (1 to 16) to Simulator output signals, following the usual conventions for bell numbers (0-90ETABCD). Can also be used to map channels to the MBI external switch codes (WXYZ), supported by Abel only.
S/s	Save settings to EEPROM. This command saves the value set by the "B", "G", "E" and "R" commands to non-volatile memory. If Debug Mode is enabled, the Debug Mask ("M") is also saved.
P/p	Set the serial port speed. The serial port speed may be set to 2400, 4800 or 9600bps with this command. The new speed is stored in EEPROM immediately and an interface reset is required to make it active. This command is provided for debugging use only, all tested Simulator Software packages support 2400bps only.
T/t	Enable test mode. Generates several useful test patterns on the serial interface. A hardware reset is required to exit test mode.
H/h	Display CLI help text.
D	Turn debug mode ON, or set debug flags. If Debug Mode is off, this command turns it on. If Debug Mode is on, this command prompts the user to enable or disable each Debug Flag. This output is intended to be accessed via a terminal emulator and is not suitable for use by the Simulator. Debug mode should be disabled before starting the Simulator Software Package.
d	Turn debug mode OFF
<i>The following commands are available in Debug Mode only.</i>	

M/m	<p>Set or unset the debug mask bits. (Debug Mode only)</p> <p>This command is available only when Debug Mode is turned on, and prompts for the debug mask bit to be set or unset for each input channel. This determines which channels will generate debug output and can be used to reduce the volume of debug messages when troubleshooting a specific channel or Sensor Module. See also command “S”.</p>
Z/z	<p>Set defaults. (Debug Mode only)</p> <p>This command is available only when Debug Mode is turned on, and sets default values for all the configurable settings. See also command “S”.</p>
0 ... 9	<p>Print debug markers (Debug Mode only)</p> <p>This command is available only when Debug Mode is turned on, and sends the text “DEBUG MARKER <i>N</i>” to the serial port, where <i>N</i> = 0 to 9. This is useful for identifying areas of interest in the output when logging debug output with a terminal emulator.</p>
L/l	<p>Display CLI debug mode help text (Debug Mode only)</p>

Appendix E: Diagnostic LED Codes

The following tables list the meanings of the codes shown by the flashes of the diagnostic LED on the Simulator Interface Module. This list is correct as of firmware v3.5.

- The LED flashes slowly when test mode is running.

The following table lists the signal codes displayed on the yellow LED of the Simulator Interface.

Table 10 – LED Signal Codes

Long	Short	Meaning	CLI Command
<i>N</i>	<i>M</i>	Announces the firmware version on power-on.	-
1	0	The LED gives one long flash every time the Sensor Module connected to Channel 1 is triggered. The LED lights when the signal from the Sensor Module is received, and extinguishes when the corresponding guard timer expires (the length of this flash is therefore equal to the setting of the guard timer). The <i>Debug Show LED</i> debug flag enables this behaviour for all channels for which debugging has been selected.	-
On Steady		On after power-on: Port speed is not 2400bps, or a sensor channel is disabled (Debug mode only).	-
0	1	CLI key press acknowledgement.	-
1	1	MBI Protocol command 0xFD received.	-
1	2	MBI Protocol command 0xFE received.	-
1	3	MBI Protocol delay timers (and terminator byte) received.	-
2	3	De-bounce timer set.	B
2	4	Guard timer set.	G
2	5	Settings saved to EEPROM.	S
2	6	Enabled channels set.	E
2	7	Serial port speed set in EEPROM.	P
2	8	Debug mode on.	D
2	9	Debug mode off.	d
2	10	Debug mask set.	M
2	11	Channels remapped.	R
3	0	Invalid character or timeout on serial interface, data discarded.	-

Appendix F: Useful Links

Table 11 – Useful Links

Description		Link
Software		
GitHub	Software Repository	https://github.com/Simulators
Abel	Simulator Software	http://www.abelsim.co.uk
Beltower	Simulator Software	http://www.beltower.co.uk
Virtual Belfry	Simulator Software	http://www.belfryware.com
Hardware		
JLPCB	PCBs	https://jlpcb.com/
Seeed	PCBs	https://www.seeedstudio.com/
OSH Park	PCBs	https://oshpark.com/
David Bagley	MBI, Sensors	http://www.ringing.demon.co.uk
Belfree	Wireless Ringing System	https://belfree.co.uk/
Microchip	Microcontrollers (formerly Atmel)	https://www.microchip.com
Maxim	Serial Line Drivers	https://www.maximintegrated.com/
Information		
John Norris	“When does a bell strike?”	http://www.jrnorris.co.uk/strike.html
Frank King	Equations of Motion of a Free Bell and Clapper	https://www.cl.cam.ac.uk/~fhk1/Bells/equations.pdf
Tools		
Arduino	Electronic Prototyping	https://arduino.cc/
PuTTY	Free Terminal Emulator	https://www.chiark.greenend.org.uk/~sgtatham/putty/
PortMon	Serial Port Monitor	https://technet.microsoft.com/en-us/library/bb896644.aspx
FTDI	USB-Serial Adapter Drivers	https://www.ftdichip.com/Drivers/VCP.htm
Prolific	USB-Serial Adapter Drivers	http://www.prolific.com.tw/US/ShowProduct.aspx?p_id=225&pcid=41
Audacity	Sound Editing Package	https://www.audacityteam.org

Appendix G: A Quarter Peal of Cambridge Surprise Minor

The following chart was constructed from debug output generated by a prototype Simulator Interface during development of the Liverpool Cathedral Simulator, and shows the relative time between blows of a sensor on the 3rd, which was being rung as the treble to a quarter peal of Cambridge Surprise Minor of the light (24cwt) six. This output showed that triggering and detection of the Sensor Module was reliable, with no missed signals (which would have been indicated as very high values) or spurious triggers (very low values).




Figure 58 – Quarter Peal Sensor Head Test Timings

Licensing & Disclaimers

Documentation

All original manuals and other documentation (including PCB layout CAD files and schematics) released as part of the Liverpool Ringing Simulator project⁴⁸ are released under the Creative Commons Attribution-ShareAlike 4.0 International License (CC BY-SA),⁴⁹ which includes the following disclaimers:

Unless otherwise separately undertaken by the Licensor, to the extent possible, the Licensor offers the Licensed Material as-is and as-available, and makes no representations or warranties of any kind concerning the Licensed Material, whether express, implied, statutory, or other. This includes, without limitation, warranties of title, merchantability, fitness for a particular purpose, non-infringement, absence of latent or other defects, accuracy, or the presence or absence of errors, whether or not known or discoverable. Where disclaimers of warranties are not allowed in full or in part, this disclaimer may not apply to You.

To the extent possible, in no event will the Licensor be liable to You on any legal theory (including, without limitation, negligence) or otherwise for any direct, special, indirect, incidental, consequential, punitive, exemplary, or other losses, costs, expenses, or damages arising out of this Public License or use of the Licensed Material, even if the Licensor has been advised of the possibility of such losses, costs, expenses, or damages. Where a limitation of liability is not allowed in full or in part, this limitation may not apply to You.

Software

All original software released as part of the Liverpool Ringing Simulator project is released under the GNU General Public Licence (GPL), Version 3⁵⁰, and carries the following disclaimers:

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

⁴⁸ <http://www.simulators.org.uk>

⁴⁹ <http://creativecommons.org/licenses/by-sa/4.0/>

⁵⁰ <http://www.gnu.org/licenses/gpl-3.0.en.html>

Acknowledgements

The Liverpool Ringing Simulator project relies extensively on work already undertaken by others, notably David Bagley (developer of the Bagley MBI), Chris Hughes and Simon Feather (developers of the Abel simulator software package), Derek Ballard (developer of the Beltower simulator software package), Doug Nichols (developer of the Virtual Belfry simulator software package), and others. Their invaluable contributions are hereby acknowledged. Sources used are referenced in the footnotes throughout.

Assistance with aspects of the Basic Serial Splitter Module design provided the technical support engineers at Maxim Integrated, Inc.

Thanks are also owed to the Ringing Masters and ringers of the following towers for their willingness to be the crash test dummies of simulator design and testing.

- Liverpool Cathedral
- St George's, Isle of Man
- St Mary, Chirk, Wrexham
- St John, Higham, Kent
- St Margaret, Crick, Northamptonshire
- St Mary & St Peter, Lois Weedon, Northamptonshire