Implementation of the Dehbi (2008) Continuous Random Walk Model as an ANSYS Fluent UDF

Technical report: aerosol deposition in a 90° pipe bend

Sina Karbakhsh Ravari, Shiraz University · Project supervisor: Dr. Ebrahim Ghahramani

Revision 3, November 2026; supersedes the project report of March 2026.

Abstract

The continuous random walk (CRW) model of Dehbi (2008), which integrates a normalised Langevin equation for the fluid velocity seen by a particle, was implemented as a compiled ANSYS Fluent user-defined function (UDF). It was applied to aerosol deposition in a 90° pipe bend (diameter 20 mm, curvature ratio 4, Reynolds number 4.1 × 10^3) on a Reynolds-stress-model flow field, with 10^4 particles per size class. The computed deposition fraction increases from 16.7 % for the smallest class (nominally 10 µm; Stokes number 0.09) to 98.0 % at 50 µm (Stokes number 2.3). At equal Stokes number it differs from the bend correlation of Pui et al. (1987) by −5.5 to +1.4 percentage points; because the geometry and flow conditions differ from those of the experiments, this comparison is qualitative. Source inspection and a statistical test identify three departures from the published model: the near-wall statistics and the drift correction act only in wall-adjacent cells, the Langevin state is not transformed between reference frames, and successive random deviates are correlated.

1. Introduction

Discrete random walk (DRW) models sample velocity fluctuations from locally isotropic turbulence. In inhomogeneous near-wall turbulence they produce a spurious drift of low-inertia particles towards the wall, which violates the well-mixed condition (Thomson, 1987) and leads to over-prediction of small-particle deposition (Dehbi, 2008). Dehbi (2008) replaced the DRW with a normalised Langevin equation that uses anisotropic near-wall rms profiles and a drift term proportional to the wall-normal gradient of the rms velocity. This report documents an implementation of that model as a compiled ANSYS Fluent UDF, its application to a 90° pipe bend for particle diameters of 10 to 50 µm, a comparison with the bend correlation of Pui et al. (1987), and the points at which the implementation departs from the published model.

2. Case set-up

Table 1. Geometry, flow conditions and solver settings.


Item	Value
Pipe diameter D; curvature ratio $R_0 = R/r$ (bend radius over pipe radius)	20 mm; 4 (R = 40 mm)
Straight inlet and outlet sections	$5D$ each
Fluid	air, ρ = 1.225 kg m^{-3}, μ = 1.81 × 10^{-5} Pa s
Inlet; outlet	uniform velocity U = 3.0 m s^{-1}; pressure outlet
Reynolds number $\rho U D/\mu$; friction Reynolds number $u_\tau r/\nu$	4.06 × 10^3; ≈ 140 (Blasius estimate)
Mesh	structured hexahedral, ≈ 5.3 × 10^6 cells, wall $y^+ \approx 1$
Solver	ANSYS Fluent 2024 R2, pressure based, steady, SIMPLE
Turbulence model	Reynolds stress model (RSM), linear pressure–strain, enhanced wall treatment

Item	Value
Discretisation	least-squares gradients, second-order pressure, second-order upwind
Discrete phase	inert spheres, one-way coupling, steady tracking, 10^4 particles per size class, built-in dispersion model disabled
Particles	density 1000 kg m^{-3}, released at the gas velocity (UDF header; see Section 6)
Deposition	particle stopped at first wall contact (reported by Fluent as “aborted”)



Figure 1. Computational domain: 5D straight inlet, 90° bend (R_0 = 4) and 5D straight outlet; D = 20 mm.

Refined mesh, 5.3 × 10^6 cells	Baseline mesh, 2.5 × 10^6 cells






Figure 2. Bend cross-sections of the refined and baseline meshes (screenshots not at the same scale). The refined mesh was used for all results; results on the baseline mesh are not archived.




Figure 3. Wall y^+ on the bend surface; the values lie below about 1.2 (colour scale 0–5).

After about 950 iterations the scaled residuals of the continuous phase were between 7 × 10⁻⁴ (ε) and 2 × 10⁻⁶ and still decreasing slowly (`figures/residuals.png`; the legend of the archived screenshot is truncated). No integral-quantity monitors were archived. The Fluent dialogs for the turbulence model, solution methods, discrete-phase numerics, UDF hooks and injection, and the start of Fluent from the Visual Studio command prompt used to compile the UDF, are archived in `figures/setup/`.

3. Model and implementation

Line numbers refer to `udf/crw_dehbi2008_rev10.c`. Its executable code is identical to the file first uploaded to this repository (commit `dfa9cad`, May 2026); only comments have been revised since.

Coupling. Fluent integrates the particle momentum equation with the mean slip velocity. The UDF adds the drag of the fluid velocity fluctuation u_i' as a body force per unit mass (lines 644–738):

$$\frac{F_i}{m_p} = f_D\, u_i', \qquad f_D = \frac{1 + 0.15\, Re_p^{0.687}}{\tau_p}, \qquad \tau_p = \frac{\rho_p d_p^2}{18\,\mu},$$

where Re_p is the particle Reynolds number based on the mean slip velocity. If Fluent's default spherical drag law (Morsi and Alexander, 1972) was used for the mean drag, the two drag factors differ by up to about 6 % for $0.1 < Re_p < 1$; the drag law selected in the case is not recorded.

Langevin equation. The normalised fluctuation $\eta_i = u_i'/\sigma_i$, where σ_i is the rms fluid velocity, obeys $d\eta_i = -\eta_i\, dt/\tau_L + A_i\, dt + \sqrt{2/\tau_L}\, dW_i$. Here τ_L is the Lagrangian integral time scale of the fluid seen by the particle, A_i is a drift term and dW_i is a Wiener increment. The equation is advanced with a semi-implicit Euler–Maruyama scheme (lines 397–399, 427–429), in which ξ_i are standard normal deviates (Section 5):

$$\eta_i^{n+1} = \frac{\eta_i^n + \sqrt{2\,\Delta t/\tau_L}\,\xi_i + A_i\,\Delta t}{1 + \Delta t/\tau_L}.$$

Near-wall branch (wall-adjacent cells). Dehbi (2008) uses anisotropic statistics for $y^+ < 100$ in a body-fitted frame. In the UDF, e_2 is the wall normal pointing into the fluid, e_1 the local mean-flow direction made orthogonal

to e_2 (streamwise) and $e_3 = e_1 \times e_2$ (spanwise) (lines 225–275). The on-demand function `init_wall_udm` (lines 498–625) stores the friction velocity u_τ, the y^+ of the cell centroid and the wall normal for cells adjacent to a wall only. Every other cell is assigned $y^+ = 101$ at run time and uses the bulk branch (lines 374–383). The near-wall branch is therefore active only in the first cell layer, where $y^+ \approx 0.5$–1 on the present mesh. Its rms profiles are the DNS-based fits given by Dehbi (2008) (lines 131–148):

$$\frac{\sigma_1}{u_\tau} = \frac{0.40\, y^+}{1 + 0.0239\,(y^+)^{1.496}},$$

$$\frac{\sigma_2}{u_\tau} = \frac{0.0116\,(y^+)^2}{1 + 0.203\, y^+ + 0.00140\,(y^+)^{2.421}},$$

$$\frac{\sigma_3}{u_\tau} = \frac{0.19\, y^+}{1 + 0.0361\,(y^+)^{1.322}}.$$

The Lagrangian time scale follows Kallio and Reeks (1989): $\tau_L^+ = \tau_L u_\tau^2/\nu = 10$ for $y^+ \le 5$ and $\tau_L^+ = 7.122 + 0.5731\, y^+ - 0.00129\,(y^+)^2$ otherwise (lines 196–214). Only the wall-normal component carries a drift, reduced by the local Stokes number $St_L = \tau_p/\tau_L$; its derivative is evaluated analytically (lines 163–188, 421–422):

$$A_2 = \frac{1}{1 + St_L}\,\frac{\partial \sigma_2}{\partial y}, \qquad A_1 = A_3 = 0.$$

Bulk branch (all other cells). Isotropic turbulence with $\sigma = (2k/3)^{1/2}$ and $\tau_L = (2/C_0)\,k/\varepsilon$, $C_0 = 14$, where k is the turbulent kinetic energy and ε its dissipation rate (lines 444–474). Dehbi (2008) includes a drift proportional to ∇k; it is omitted here because accessing the cell gradient of k under the RSM caused a solver failure. Between the second cell layer ($y^+ \approx 1.5$) and $y^+ = 100$, about 70 % of the pipe radius, the wall-normal fluctuation is therefore modelled with the isotropic value and without drift. With k taken from the fits above, the isotropic value exceeds σ_2 by factors of about 7 at $y^+ = 5$ and 2 at $y^+ = 30$. The well-mixed condition is not enforced in this region, and because the extent of the near-wall branch is set by the first-cell height, the model itself depends on the near-wall mesh.

Wall interaction and time step. `dehbi_wall_bc` (lines 749–752) stops a particle when its trajectory reaches a wall face. The particle time step is limited to $\min(10^{-6}\ \mathrm{s},\ 0.1\,\tau_p)$ (lines 765–797), which is 10^{-6} s for all diameters considered.

Table 2. Departures of the implementation from the published model.

Element	Dehbi (2008)	Present implementation
Near-wall statistics and drift	applied for $y^+ < 100$	applied only in wall-adjacent cells, at the cell centroid
Bulk drift	proportional to ∇k	omitted
Frame of the Langevin state	body-fitted near the wall, Cartesian in the bulk	the same, but the state is not transformed when a particle changes branch
Random forcing	independent Gaussian increments	deviates hashed from particle address and time; serially correlated (Section 5)
Deposition	particle centre within one particle radius of the wall	particle trajectory reaches a wall face

4. Results

The Stokes number is $Stk = 2\tau_p U/D = \rho_p d_p^2 U/(9\mu D)$, based on the bulk velocity and the pipe radius as in Pui et al. (1987), and is evaluated with ρ_p = 1000 kg m⁻³ and without Cunningham correction. The deposition fraction is DF = N_{dep}/N, where N is the number of tracked particles and N_{dep} the number reported as "aborted"; it equals the deposition efficiency (one minus the penetration) of Pui et al. (1987) and may include deposition in the straight sections (Section 6). The binomial standard error $\sqrt{DF(1-DF)/N}$ assumes statistically independent particle histories; because the generator correlates particles (Section 5), it is a lower bound.

Table 3. Deposition fraction (DF) from the Fluent DPM summaries of the size classes whose summaries are archived (`data/deposition_fraction.csv`), and the correlation of Pui et al. (1987) at the same Stokes number.

d_p (µm)	Stk	Tracked	Escaped	Deposited	DF (%)	Standard error (%)	Pui et al. (%)
10[a]	0.092	10,000	8,329	1,671	16.7	0.37	18.5
20	0.368	10,000	4,279	5,721	57.2	0.49	55.8
30	0.829	10,000	2,142	7,858	78.6	0.41	84.1
40	1.473	10,000	546	9,454	94.5	0.23	96.2[b]
50	2.302	10,000	199	9,801	98.0	0.14	99.4[b]

[a] Nominal diameter; see Section 6. [b] Beyond the measured range of the correlation.




Figure 4. Deposition fraction against Stokes number (ρ_p = 1000 kg m⁻³ assumed), with the correlation of Pui et al. (1987) for R_0 = 5.7 and Re = 6000–10,000, drawn dashed beyond the measured range. Binomial 95 % intervals are smaller than the markers. Generated by `tools/plot_deposition.py`.

The deposition fraction increases monotonically with Stk, from 16.7 % at Stk = 0.09, where particle inertia is small, to near-complete deposition at $Stk > 1.5$. The correlation of Pui et al. (1987), $DF = 1 - 10^{-0.963\,Stk}$, was fitted to measurements in 90° bends with tube diameters of 5.03–8.51 mm, R_0 = 5.7 and Re = 6000–10,000; the largest measured Stokes number is about 1.35 (Sippola and Nazaroff, 2002, Eq. 121, Table 8 and Fig. 6). At equal Stk the computed deposition fractions differ from the correlation by −5.5 to +1.4 percentage points. The present case differs in curvature ratio (4), Reynolds number (4.1 × 10³) and inlet condition (uniform velocity 5D upstream of the bend), its deposition fraction may include the straight sections, and its two largest Stokes numbers lie beyond the measured range. With ρ_p = 1550 kg m⁻³, the default density of the material named in the archived

injection dialog, the correlation would give 27.1, 71.8 and 94.2 % at the three smallest diameters. Given these differences and the departures in Table 2, the comparison is qualitative and is not a validation of the model.

5. Random-number generator test

The function `gauss_rand` (lines 94–121) generates Box–Muller deviates from a hash of the particle memory address and the particle time, without a stored state. The program `tools/rng_check.c` runs a functionally identical copy (types adapted to run outside Fluent) at the time step of the present runs.

Table 4. Statistics of the UDF generator at $\Delta t = 10^{-6}$ s (output of `tools/rng_check.c`; the test number is given in brackets).

Statistic	Ideal	Result
[1] Mean, variance (2×10^5 samples)	0, 1	+0.001, 1.003
[1] Autocorrelation, lags 1 to 5	0	+0.22, +0.06, −0.11, −0.29, −0.23
[2] Correlation of two particles at equal time, address gaps 8 B, 32 B, 448 B, 8 KiB	0	+0.85, −0.49, +0.13, −0.65
[4] Normalised variance of the sum of 1000 successive deviates, 2000 particle addresses	1	median 0.48; 5–95 % range 0.20–2.7; maximum 60
[5] Time average of η^2 in the Langevin update over 0.044 s (τ_L = 3.32 ms, $\tau_L^+ = 10$), 2000 particle addresses	1 (ideal generator: median 0.94, 5–95 % range 0.51–1.70)	median 0.41; 5–95 % range 0.15–2.9; maximum 465

The mean and variance agree with those of a standard normal distribution. Because the particle time advances in equal steps, successive deviates of one particle are correlated, and deviates of two particles at the same time can be strongly correlated. Driven by this generator, the Langevin update gives a time-averaged variance of the modelled fluid velocity below its target for most particles and far above it for a few. The random forcing, and with it the effective turbulent diffusivity, therefore varies between particles, and the standard errors in Table 3 underestimate the statistical uncertainty.

6. Limitations and further work

Recorded settings. The archived injection dialog for the smallest size class (`figures/setup/injection.png`) specifies d_p = 5 µm, the material “anthracite” and zero initial velocity, whereas Table 3 assumes 10 µm and 1000 kg m^{-3} and the UDF header specifies release at the gas velocity; at 5 µm, Stk for this class would be 0.023. Gravity, the inlet turbulence, the drag law, the DPM step limit, the solver precision and the assignment of `dehbi_wall_bc` to the three wall zones (inlet pipe, bend, outlet pipe) are not recorded in the archived dialogs, and deposition was not recorded per wall zone.

Implementation. The departures in Table 2 are expected to matter most for the smallest particles, whose deposition depends on turbulent dispersion rather than on inertial impaction. Whether Fluent reuses particle memory between particles, which would make particles share random sequences, has not been tested.

Further work. A quantitative assessment of the model requires (i) a per-particle random-number state, (ii) near-wall statistics evaluated at the particle position throughout $y^+ < 100$, (iii) a consistent transformation of the Langevin state between frames, (iv) a well-mixed tracer test, (v) the confirmed injection settings, and (vi) a comparison with bend experiments at matched curvature ratio and Reynolds number.

7. Conclusions

The CRW model of Dehbi (2008) was implemented as a compiled ANSYS Fluent UDF and applied to a 90° pipe bend at Re = 4.1 × 10³. The computed deposition fraction increases from 16.7 % at Stk = 0.09 to 98.0 % at Stk = 2.3 and differs from the correlation of Pui et al. (1987) by −5.5 to +1.4 percentage points at equal Stokes number. The implementation departs from the published model in three respects: the near-wall statistics and drift are applied only in wall-adjacent cells, the Langevin state is not transformed between the near-wall and bulk frames, and successive random deviates are correlated. The results show that the model can be coupled to Fluent's discrete phase model through body-force and boundary-condition UDFs; a quantitative test of the model requires the changes listed in Section 6.

Software

The Cursor code editor was used during UDF development to debug C syntax and compilation errors related to the Fluent UDF macros. The PDF version of this report is generated from the Markdown source with pandoc and Chromium.

References

1. Dehbi, A. (2008). Turbulent particle dispersion in arbitrary wall-bounded geometries: A coupled CFD-Langevin-equation based approach. *International Journal of Multiphase Flow*, 34(9), 819–828. https://doi.org/10.1016/j.ijmultiphaseflow.2008.03.001
2. Kallio, G. A., & Reeks, M. W. (1989). A numerical simulation of particle deposition in turbulent boundary layers. *International Journal of Multiphase Flow*, 15(3), 433–446. https://doi.org/10.1016/0301-9322(89)90012-8
3. Morsi, S. A., & Alexander, A. J. (1972). An investigation of particle trajectories in two-phase flow systems. *Journal of Fluid Mechanics*, 55(2), 193–208. https://doi.org/10.1017/S0022112072001806
4. Pui, D. Y. H., Romay-Novas, F., & Liu, B. Y. H. (1987). Experimental study of particle deposition in bends of circular cross section. *Aerosol Science and Technology*, 7(3), 301–315. https://doi.org/10.1080/02786828708959166
5. Sippola, M. R., & Nazaroff, W. W. (2002). *Particle deposition from turbulent flow: Review of published research and its applicability to ventilation ducts in commercial buildings* (Report LBNL-51432). Lawrence Berkeley National Laboratory. https://doi.org/10.2172/815478
6. Thomson, D. J. (1987). Criteria for the selection of stochastic models of particle trajectories in turbulent flow. *Journal of Fluid Mechanics*, 180, 529–556. https://doi.org/10.1017/S0022112087001940