

Project 1: Design of a Heat Exchanger

Sharif University of Technology
Department of Mechanical Engineering

Sina Zerehposh – 401170829

Course Instructor: Dr. Pakzad
Winter 2025

1 Introduction and Process Description

The Ilam Gas Refinery is responsible for treating sour gas and separating impurities such as CO_2 and H_2S . In the gas sweetening unit, in order to regenerate the solvent (amine) and separate the acid gases, heat must be supplied at the bottom of the regeneration column (stripper).

The objective of this project is to design a Reboiler-type heat exchanger that vaporizes the process fluid (consisting of 50% water, 25% ammonia, and 25% benzene by weight) using low-pressure steam (LP-Steam).

2 Basis for Selection of Design Parameters (Part A)

In this section, the geometric and operational parameters of the exchanger chosen by the designer are described, along with their technical justification based on engineering standards (TEMA and API) and operating conditions.

2.1 Fluid Allocation

Selecting the flow path of each fluid (shell side or tube side) is one of the most critical design steps. In this project:

- **Tube Side: Process Fluid**

- *Reason 1 (Corrosion)*: The process fluid contains 25% ammonia, which exhibits strong corrosiveness. Controlling corrosion inside the tubes by selecting an appropriate resistant tube metallurgy is far more economical than fabricating the entire pressure shell from expensive corrosion-resistant alloys.
- *Reason 2 (Pressure)*: The operating pressure of the process fluid (7.0 bar) is higher than that of the heating steam (3.5 bar). Standard practice dictates that

higher-pressure fluids should flow inside the tubes to minimize the required shell wall thickness and vessel fabrication cost.

- **Shell Side: LP-Steam**

- *Reason:* Steam is a clean, non-corrosive fluid with low viscosity. Condensation of steam across the external surfaces of the bundle provides an extremely high convective heat transfer coefficient and exhibits a minimal fouling factor (approximately $0.00018 \text{ m}^2\text{K/W}$).

2.2 Exchanger Type Selection

Based on the TEMA standard, a **BEM**-type heat exchanger was selected:

- **Front Head – Type B (Bonnet):** The simplest and most economical header type. Since frequent internal inspection of the tubes is not necessary for this service, the bolted bonnet provides an optimal and secure closure.
- **Shell – Type E (One Pass):** The standard single-pass shell configuration for phase-change and single-phase industrial thermal duties.
- **Rear Head – Type M (Fixed Tubesheet):** Since the shellside fluid (condensing steam) is exceptionally clean with minimal fouling tendency, there is no operational need for bundle pullout for mechanical cleaning (chemical cleaning is fully sufficient). Fixed-tubesheet exchangers feature the lowest capital cost, and due to the complete absence of internal floating-head gaskets, internal leakage risks of toxic ammonia and volatile benzene are eliminated, ensuring safe high-pressure containment.

2.3 Material Selection

- **Tube Material:** Austenitic Stainless Steel 304 (18Cr, 8Ni)

Justification: The presence of ammonia in the process fluid strictly rules out the use of copper-based alloys (such as brass or bronze), as ammonia aggressively attacks copper alloys via stress corrosion and dissolution. Stainless Steel 304 provides proven corrosion immunity in hot ammonia-water-benzene environments.

- **Shell Material:** Carbon Steel

Justification: The shell envelope contacts only utility steam, which is non-corrosive under normal water treatment. Carbon steel provides maximum structural strength at minimal economic cost.

2.4 Tube Geometric Specifications and Layout

- **Tube Outer Diameter and Thickness:** $OD = 22.225 \text{ mm}$ (7/8 inch), average wall thickness $t_w = 2.108 \text{ mm}$. This geometry represents an established refinery standard that provides an ideal trade-off between heat transfer area, mechanical rigidity, and hydraulic pressure drop.

- **Tube Length:** 6.706 m. Sizing with longer tubes reduces the shell internal diameter, resulting in a slimmer, longer vessel that significantly reduces fabrication and flange costs compared to large-diameter shells.
- **Tube Layout Pattern:** 30° Triangular pitch.
Justification: A 30° triangular pitch provides the maximum packing density and highest heat transfer area per unit volume. Because mechanical lane cleaning on the shell side is not required for condensing steam, a square layout (which introduces excessive dead space) is unnecessary.
- **Pitch Ratio:** 1.33 (Pitch = 29.559 mm). TEMA requires a minimum center-to-center pitch ratio of 1.25. A ratio of 1.33 ensures adequate ligament thickness for reliable mechanical tube expansion into the tubesheet.

2.5 Baffle Geometry

- **Type:** Single-Segmental Carbon Steel baffles
- **Baffle Cut:** 25% diametral cut
- **Spacing:** Central spacing of approximately 233 mm (24 crosspasses)

This layout was selected to promote crossflow across the condensing vapor while providing structural support to eliminate flow-induced acoustic and mechanical vibrations.

3 Summary of Design Operating Conditions

Table 1 summarizes the thermodynamic and operational boundary conditions applied in HTRI based on project criteria and engineering decisions.

Parameter	Tube Side (Process Fluid)	Shell Side (LP-Steam)
Mass Flow Rate	25,000 kg/hr	5646.8 kg/hr (Calculated)
Temperature (In → Out)	70.00°C → 111.33°C	138.94°C → 137.61°C
Operating Pressure	7.0 bar (700 kPa)	3.5 bar (350 kPa)
Vapor Fraction ($x_{in} \rightarrow x_{out}$)	0.0 → 0.50 (Boiling)	1.0 → 0.0 (Condensing)
Fouling Factor	0.000350 m ² K/W	0.000180 m ² K/W
Design Pressure	22 bar (2200 kPaG)	10 bar (1000 kPaG)
Design Temperature	200°C	150°C
Number of Tube Passes	2 passes	1 pass

Table 1: Summary of process boundary conditions and operational inputs.

Note on the Number of Tube Passes: Although a single tube pass was initially assumed as a baseline, the final design incorporates 2 tube passes. This configuration increases tubeside fluid velocity, enhances the boiling heat transfer coefficient, and mitigates stratified flow and localized film boiling risks.

3.1 Conclusion of Part A

Based on the parameters above, a TEMA BEM heat exchanger with 285 Stainless Steel 304 tubes of 6.706 m length was designed. This configuration delivers the required process duty of 3.41 MW while satisfying all hydraulic pressure drop and fouling constraints.

3.2 HTRI Specification Sheet – Base Case (25,000 kg/hr)


HTRI		HEAT EXCHANGER SPECIFICATION SHEET				Page 1 SI Units																																																																																																																																																																											
Customer				Job No.																																																																																																																																																																													
Address				Reference No.																																																																																																																																																																													
Plant Location				Proposal No.																																																																																																																																																																													
Service of Unit				Date 2/7/2026 Rev																																																																																																																																																																													
Size 584.2 x 6706 mm Type BEM Horizontal				Item No.																																																																																																																																																																													
Surf/Unit (Gross/Eff) 133.44 / 131.04 m ²				Connected In 1 Parallel 1 Series																																																																																																																																																																													
Shell/Unit 1				Surf/Shell (Gross/Eff) 133.44 / 131.04 m ²																																																																																																																																																																													
PERFORMANCE OF ONE UNIT																																																																																																																																																																																	
Fluid Allocation		Shell Side			Tube Side																																																																																																																																																																												
Fluid Name		LP-Steam			Process																																																																																																																																																																												
Fluid Quantity, Total kg/hr		5646.8			25000																																																																																																																																																																												
Vapor (In/Out)		5646.8			12500																																																																																																																																																																												
Liquid		5646.8			12500																																																																																																																																																																												
Steam		5646.8			1127.0																																																																																																																																																																												
Water		5646.8			5740.0																																																																																																																																																																												
Noncondensables																																																																																																																																																																																	
Temperature (In/Out) C		138.94			70.00																																																																																																																																																																												
Specific Gravity		0.9155			0.8183																																																																																																																																																																												
Viscosity mN-s/m ²		0.0135			0.3007																																																																																																																																																																												
Molecular Weight, Vapor					0.0110 V/L 0.2094																																																																																																																																																																												
Molecular Weight, Noncondensables																																																																																																																																																																																	
Specific Heat kJ/kg-C		1.9544			2.9816																																																																																																																																																																												
Thermal Conductivity W/m-C		0.0276			0.0263 V/L 0.3803																																																																																																																																																																												
Latent Heat kJ/kg		2164.5			1008.1																																																																																																																																																																												
Inlet Pressure kPa		350.00			700.00																																																																																																																																																																												
Velocity m/s		8.25			5.01																																																																																																																																																																												
Pressure Drop, Allow/Calc kPa		30.000			30.000																																																																																																																																																																												
Fouling Resistance (min) m ² -K/W		0.000180			0.000350																																																																																																																																																																												
Heat Exchanged 3406885 W		Clean 1623.7 W/m ² -K			MTD (Corrected) 38.0 C																																																																																																																																																																												
Transfer Rate, Service 683.40 W/m ² -K					Actual 814.46 W/m ² -K																																																																																																																																																																												
CONSTRUCTION OF ONE SHELL																																																																																																																																																																																	
Design/Test Pressure kPaG		1000.0 /			2200.0 /																																																																																																																																																																												
Design Temperature C		150.00			200.00																																																																																																																																																																												
No Passes per Shell		1			2																																																																																																																																																																												
Corrosion Allowance mm		3.200			3.200																																																																																																																																																																												
Connections		1 @ 205.00			1 @ 77.927																																																																																																																																																																												
Size & Rating		1 @ 102.26			1 @ 205.00																																																																																																																																																																												
Sketch (Bundle/Nozzle Orientation)																																																																																																																																																																																	
<table border="1"> <tr> <td>Tube No.</td> <td>285</td> <td>OD</td> <td>22.225 mm</td> <td>Thk(Avg)</td> <td>2.108 mm</td> <td>Length</td> <td>6.706 m</td> <td>Pitch</td> <td>29.559 mm</td> </tr> <tr> <td>Tube Type</td> <td>Plain</td> <td></td> <td></td> <td></td> <td></td> <td>Material</td> <td>304 Stainless steel (18 Cr, 8 Ni)</td> <td></td> <td>Tube pattern 30</td> </tr> <tr> <td>Shell</td> <td>Carbon steel</td> <td>ID</td> <td>584.20</td> <td>OD</td> <td>603.25 mm</td> <td>Shell Cover</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Channel or Bonnet</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Channel Cover</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Tubesheet-Stationary</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Tubesheet-Floating</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Floating Head Cover</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Impingement Plate</td> <td>Rods</td> <td></td> <td></td> </tr> <tr> <td>Baffles-Cross</td> <td>Type Single-Seg.</td> <td>%Cut (Diam)</td> <td>25</td> <td>Spacing(c/c)</td> <td>232.97</td> <td>Inlet</td> <td>786.11 mm</td> <td></td> <td></td> </tr> <tr> <td>Baffles-Long</td> <td></td> <td>Seal Type</td> <td>None</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Supports-Tube</td> <td></td> <td>U-Bend</td> <td></td> <td></td> <td></td> <td>Type</td> <td>None</td> <td></td> <td></td> </tr> <tr> <td>Bypass Seal Arrangement</td> <td>0 pairs seal strips</td> <td>Tube-Tubesheet Joint</td> <td>Expanded (No groove)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Expansion Joint</td> <td></td> <td>Type</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rho-V2-Inlet Nozzle</td> <td>1199.8 kg/m-s²</td> <td>Bundle Entrance</td> <td>137.52</td> <td>Bundle Exit</td> <td>2.11</td> <td>kg/m-s²</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Gaskets-Shell Side</td> <td>Mach. Mtl. (Kammprofile/Flex. Face)</td> <td>Tube Side</td> <td>Mach. Mtl. (Kammprofile/Flex. Face)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="10">- Floating Head</td> </tr> <tr> <td colspan="10">Code Requirements</td> </tr> <tr> <td>Weight/Shell</td> <td>3913.1 kg</td> <td>Filled with Water</td> <td>5755.8 kg</td> <td>TEMA Class</td> <td>R</td> <td>Bundle</td> <td>2328.3 kg</td> <td></td> <td></td> </tr> <tr> <td colspan="10">Remarks:</td> </tr> </table>								Tube No.	285	OD	22.225 mm	Thk(Avg)	2.108 mm	Length	6.706 m	Pitch	29.559 mm	Tube Type	Plain					Material	304 Stainless steel (18 Cr, 8 Ni)		Tube pattern 30	Shell	Carbon steel	ID	584.20	OD	603.25 mm	Shell Cover				Channel or Bonnet						Channel Cover				Tubesheet-Stationary						Tubesheet-Floating				Floating Head Cover						Impingement Plate	Rods			Baffles-Cross	Type Single-Seg.	%Cut (Diam)	25	Spacing(c/c)	232.97	Inlet	786.11 mm			Baffles-Long		Seal Type	None							Supports-Tube		U-Bend				Type	None			Bypass Seal Arrangement	0 pairs seal strips	Tube-Tubesheet Joint	Expanded (No groove)							Expansion Joint		Type								Rho-V2-Inlet Nozzle	1199.8 kg/m-s ²	Bundle Entrance	137.52	Bundle Exit	2.11	kg/m-s ²				Gaskets-Shell Side	Mach. Mtl. (Kammprofile/Flex. Face)	Tube Side	Mach. Mtl. (Kammprofile/Flex. Face)							- Floating Head										Code Requirements										Weight/Shell	3913.1 kg	Filled with Water	5755.8 kg	TEMA Class	R	Bundle	2328.3 kg			Remarks:									
Tube No.	285	OD	22.225 mm	Thk(Avg)	2.108 mm	Length	6.706 m	Pitch	29.559 mm																																																																																																																																																																								
Tube Type	Plain					Material	304 Stainless steel (18 Cr, 8 Ni)		Tube pattern 30																																																																																																																																																																								
Shell	Carbon steel	ID	584.20	OD	603.25 mm	Shell Cover																																																																																																																																																																											
Channel or Bonnet						Channel Cover																																																																																																																																																																											
Tubesheet-Stationary						Tubesheet-Floating																																																																																																																																																																											
Floating Head Cover						Impingement Plate	Rods																																																																																																																																																																										
Baffles-Cross	Type Single-Seg.	%Cut (Diam)	25	Spacing(c/c)	232.97	Inlet	786.11 mm																																																																																																																																																																										
Baffles-Long		Seal Type	None																																																																																																																																																																														
Supports-Tube		U-Bend				Type	None																																																																																																																																																																										
Bypass Seal Arrangement	0 pairs seal strips	Tube-Tubesheet Joint	Expanded (No groove)																																																																																																																																																																														
Expansion Joint		Type																																																																																																																																																																															
Rho-V2-Inlet Nozzle	1199.8 kg/m-s ²	Bundle Entrance	137.52	Bundle Exit	2.11	kg/m-s ²																																																																																																																																																																											
Gaskets-Shell Side	Mach. Mtl. (Kammprofile/Flex. Face)	Tube Side	Mach. Mtl. (Kammprofile/Flex. Face)																																																																																																																																																																														
- Floating Head																																																																																																																																																																																	
Code Requirements																																																																																																																																																																																	
Weight/Shell	3913.1 kg	Filled with Water	5755.8 kg	TEMA Class	R	Bundle	2328.3 kg																																																																																																																																																																										
Remarks:																																																																																																																																																																																	
Reprinted with Permission (v7.3.2)																																																																																																																																																																																	

Figure 1: HTRI Heat Exchanger Specification Sheet – Base Case (25,000 kg/hr).

3.3 HTRI Output Summary – Base Case

Design: Horizontal Multipass Flow TEMA BEM Shell With Single-Segmental Baffles. No Data Check Messages (see Runtime Message Report for Warning Messages).

Process Conditions	Hot Shellside (LP-Steam)	Cold Tubeside (Process)
Flow Rate (kg/s)	1.5686	6.9444
Inlet/Outlet Vapor Fraction (Wt.)	1.0000 / 0.0000	0.0000 / 0.5000
Inlet/Outlet Temperature (°C)	138.94 / 137.61	70.00 / 111.33
Inlet Pressure / Avg (kPa)	350.00 / 343.51	700.00 / 690.00
ΔP Calculated / Allowable (kPa)	12.974 / 30.000	19.999 / 30.000
Fouling Resistance (m ² -K/W)	0.000180	0.000350

Exchanger Performance			
Shell h (W/m ² -K)	16,090	Actual U (W/m ² -K)	814.46
Tube h (W/m ² -K)	2971.9	Required U (W/m ² -K)	683.40
Hot Regime	Transition	Duty (MW)	3.4069
Cold Regime	Transition	Effective Area (m ²)	131.04
EMTD (°C)	38.0	Overdesign (%)	19.18

Shell Geometry		Baffle Geometry	
TEMA Type	BEM	Baffle Type	Single-Segmental
Shell ID (mm)	584.20	Baffle Cut (% Dia.)	25
Series / Parallel	1 / 1	Central Spacing (mm)	232.97
Orientation (deg)	0.00	Crosspasses	24

Tube Geometry		Nozzles	
Tube Type	Plain	Shell Inlet / Outlet (mm)	205.00 / 102.26
Tube OD (mm)	22.225	Shell Nozzle Heights (In/Out)	28.36 / 15.13 mm
Tube Length (m)	6.706	Tube Inlet / Outlet (mm)	77.93 / 205.00
Pitch Ratio / Layout	1.3300 / 30°	Tube Pass Count	2
Tube Count	285		

Thermal Resistance Breakdown (%)		Velocities (m/s)		
Shell Condensing Film	5.06		Min	Max
Tube Boiling Film	33.82	Tubeside	0.24	10.50
Fouling Resistance	49.84	Crossflow	0.19	13.74
Tube Metal Wall	11.28	Window	0.026	13.75
Flow Fractions				
Stream A	0.198			
Stream B	0.470			
Stream C	0.100			
Stream E	0.149			
Stream F	0.083			

Table 2: HTRI Output Summary – Base Case (25,000 kg/hr).

4 Performance Analysis Under Increased Capacity (Part B)

4.1 Comparison of Design Data

Table 3 presents a side-by-side comparison between the baseline design (25,000 kg/hr) and the debottlenecked case (30,000 kg/hr). In this analysis, tube diameter and tube length were held constant to isolate the net impact of the throughput increase.

Parameter	Base Design	Expanded Design	% Change / Engineering Notes
Tubeside Mass Flow Rate	25,000 kg/hr	30,000 kg/hr	+20.0%
Thermal Duty (Q)	3.407 MW	4.086 MW	+19.9% (Directly proportional)
Tube Outer Diameter	22.225 mm	22.225 mm	Fixed (Standard)
Tubeside Passes	2 passes	2 passes	Fixed (Maintains velocity)
Total Tube Count	285	333	Increased to provide required area
Tubeside Pressure Drop	19.99 kPa	21.56 kPa	Modest increase (< 30 kPa allowable)
Overall Heat Transfer Coeff.	814.5 W/m ² K	823.49 W/m ² K	+1.1% (Enhanced convective turbulence)
Overdesign Margin	19.18%	17.86%	Maintained at safe operational levels

Table 3: Comparison of thermal-hydraulic data between base and increased-capacity operations.

4.2 Technical Analysis of Results

4.2.1 Thermal Capability at High Flow Rate

Software convergence indicates that when the flow rate is scaled to 30,000 kg/hr:

- **Thermal Duty:** Expands to 4.086 MW, achieving the target outlet vapor fraction ($x = 0.50$).

- **Overdesign Margin:** Remains robust at 17.86%. This confirms that the unit operates reliably under expanded capacity while retaining adequate surplus area to absorb long-term fouling.

4.2.2 Hydraulic Behavior and Pressure Losses

- **Tubeside Pressure Drop:** Evaluated at 21.56 kPa, well below the allowable limit of 30.0 kPa.
- **Fluid Velocity:** The in-tube velocity (5.10 m/s max mixture velocity) remains within allowable erosion and vibration thresholds, maintaining a high convective film coefficient.

4.3 HTRI Specification Sheet – Increased-Capacity Case (30,000 kg/hr)

HTRI		HEAT EXCHANGER SPECIFICATION SHEET		Page 1 SI Units																																																																																																																																																																											
Customer			Job No.																																																																																																																																																																												
Address			Reference No.																																																																																																																																																																												
Plant Location			Proposal No.																																																																																																																																																																												
Service of Unit			Date 2/7/2026 Rev																																																																																																																																																																												
Size 635 x 6706 mm Type BEM Horizontal			Item No.																																																																																																																																																																												
Surf/Unit (Gross/Eff) 155.92 / 152.97 m2			Connected In 1 Parallel 1 Series																																																																																																																																																																												
Surf/Shell (Gross/Eff) 155.92 / 152.97 m2			Surf/Shell (Gross/Eff) 155.92 / 152.97 m2																																																																																																																																																																												
PERFORMANCE OF ONE UNIT																																																																																																																																																																															
Fluid Allocation		Shell Side		Tube Side																																																																																																																																																																											
Fluid Name		LP-Steam		Process																																																																																																																																																																											
Fluid Quantity, Total kg/hr		6775.0		30000																																																																																																																																																																											
Vapor (In/Out)		6775.0		15000																																																																																																																																																																											
Liquid		6775.0		15000																																																																																																																																																																											
Steam		6775.0		1351.6																																																																																																																																																																											
Water		6775.0		6888.4																																																																																																																																																																											
Noncondensables																																																																																																																																																																															
Temperature (In/Out) C		138.94		70.00																																																																																																																																																																											
Specific Gravity		0.9154		0.8183																																																																																																																																																																											
Viscosity mN-s/m2		0.0135		0.0110 V/L 0.2096																																																																																																																																																																											
Molecular Weight, Vapor																																																																																																																																																																															
Molecular Weight, Noncondensables																																																																																																																																																																															
Specific Heat kJ/kg-C		1.9544		2.9816																																																																																																																																																																											
Thermal Conductivity W/m-C		0.0276		0.0262 V/L 0.3803																																																																																																																																																																											
Latent Heat kJ/kg		2164.5		1008.1																																																																																																																																																																											
Inlet Pressure kPa		350.00		700.00																																																																																																																																																																											
Velocity m/s		8.37		5.10																																																																																																																																																																											
Pressure Drop, Allow/Calc kPa		30.000		30.000																																																																																																																																																																											
Fouling Resistance (min) m2-K/W		0.000180		0.000350																																																																																																																																																																											
Heat Exchanged 4086328 W		MTD (Corrected) 38.2 C																																																																																																																																																																													
Transfer Rate, Service 698.71 W/m2-K		Clean 1660.0 W/m2-K		Actual 823.49 W/m2-K																																																																																																																																																																											
CONSTRUCTION OF ONE SHELL																																																																																																																																																																															
		Shell Side		Tube Side																																																																																																																																																																											
Design/Test Pressure kPaG		1000.0 /		2200.0 /																																																																																																																																																																											
Design Temperature C		150.00		200.00																																																																																																																																																																											
No Passes per Shell		1		2																																																																																																																																																																											
Corrosion Allowance mm		3.200		3.200																																																																																																																																																																											
Connections In mm		1 @ 258.88		1 @ 77.927																																																																																																																																																																											
Size & Out mm		1 @ 102.26		1 @ 258.88																																																																																																																																																																											
Rating Intermediate		@		@																																																																																																																																																																											
																																																																																																																																																																															
<table border="1"> <tr> <td>Tube No.</td> <td>333</td> <td>OD</td> <td>22.225 mm</td> <td>Thk(Avg)</td> <td>2.108 mm</td> <td>Length</td> <td>6.706 m</td> <td>Pitch</td> <td>29.559 mm</td> </tr> <tr> <td>Tube Type</td> <td>Plain</td> <td></td> <td></td> <td></td> <td></td> <td>Material</td> <td>304 Stainless steel (18 Cr, 8 Ni)</td> <td></td> <td>Tube pattern 30</td> </tr> <tr> <td>Shell</td> <td>Carbon steel</td> <td>ID</td> <td>635.00</td> <td>OD</td> <td>654.05 mm</td> <td>Shell Cover</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Channel or Bonnet</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Channel Cover</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Tubesheet-Stationary</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Tubesheet-Floating</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Floating Head Cover</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Impingement Plate</td> <td>Rods</td> <td></td> <td></td> </tr> <tr> <td>Baffles-Cross</td> <td></td> <td>Type</td> <td>Single-Seg.</td> <td>%Cut (Diam)</td> <td>25</td> <td>Spacing(c/c)</td> <td>264.43</td> <td>Inlet</td> <td>837.25 mm</td> </tr> <tr> <td>Baffles-Long</td> <td></td> <td></td> <td></td> <td>Seal Type</td> <td>None</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Supports-Tube</td> <td></td> <td></td> <td></td> <td>U-Bend</td> <td></td> <td>Type</td> <td>None</td> <td></td> <td></td> </tr> <tr> <td>Bypass Seal Arrangement</td> <td>0</td> <td>pairs seal strips</td> <td></td> <td>Tube-Tubesheet Joint</td> <td>Expanded (No groove)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Expansion Joint</td> <td></td> <td></td> <td></td> <td>Type</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rho-V2-Inlet Nozzle</td> <td>679.18</td> <td>kg/m-s2</td> <td></td> <td>Bundle Entrance</td> <td>142.22</td> <td>Bundle Exit</td> <td>1.66</td> <td>kg/m-s2</td> <td></td> </tr> <tr> <td>Gaskets-Shell Side</td> <td>Mach. Mtl. (Kammprofile/Flex. Face)</td> <td></td> <td></td> <td>Tube Side</td> <td>Mach. Mtl. (Kammprofile/Flex. Face)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>- Floating Head</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Code Requirements</td> <td></td> <td></td> <td></td> <td>TEMA Class</td> <td>R</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Weight/Shell</td> <td>4451.3</td> <td>kg</td> <td>Filled with Water</td> <td>6698.1</td> <td>kg</td> <td>Bundle</td> <td>2713.4</td> <td>kg</td> <td></td> </tr> <tr> <td colspan="10">Remarks:</td> </tr> </table>						Tube No.	333	OD	22.225 mm	Thk(Avg)	2.108 mm	Length	6.706 m	Pitch	29.559 mm	Tube Type	Plain					Material	304 Stainless steel (18 Cr, 8 Ni)		Tube pattern 30	Shell	Carbon steel	ID	635.00	OD	654.05 mm	Shell Cover				Channel or Bonnet						Channel Cover				Tubesheet-Stationary						Tubesheet-Floating				Floating Head Cover						Impingement Plate	Rods			Baffles-Cross		Type	Single-Seg.	%Cut (Diam)	25	Spacing(c/c)	264.43	Inlet	837.25 mm	Baffles-Long				Seal Type	None					Supports-Tube				U-Bend		Type	None			Bypass Seal Arrangement	0	pairs seal strips		Tube-Tubesheet Joint	Expanded (No groove)					Expansion Joint				Type						Rho-V2-Inlet Nozzle	679.18	kg/m-s2		Bundle Entrance	142.22	Bundle Exit	1.66	kg/m-s2		Gaskets-Shell Side	Mach. Mtl. (Kammprofile/Flex. Face)			Tube Side	Mach. Mtl. (Kammprofile/Flex. Face)					- Floating Head										Code Requirements				TEMA Class	R					Weight/Shell	4451.3	kg	Filled with Water	6698.1	kg	Bundle	2713.4	kg		Remarks:									
Tube No.	333	OD	22.225 mm	Thk(Avg)	2.108 mm	Length	6.706 m	Pitch	29.559 mm																																																																																																																																																																						
Tube Type	Plain					Material	304 Stainless steel (18 Cr, 8 Ni)		Tube pattern 30																																																																																																																																																																						
Shell	Carbon steel	ID	635.00	OD	654.05 mm	Shell Cover																																																																																																																																																																									
Channel or Bonnet						Channel Cover																																																																																																																																																																									
Tubesheet-Stationary						Tubesheet-Floating																																																																																																																																																																									
Floating Head Cover						Impingement Plate	Rods																																																																																																																																																																								
Baffles-Cross		Type	Single-Seg.	%Cut (Diam)	25	Spacing(c/c)	264.43	Inlet	837.25 mm																																																																																																																																																																						
Baffles-Long				Seal Type	None																																																																																																																																																																										
Supports-Tube				U-Bend		Type	None																																																																																																																																																																								
Bypass Seal Arrangement	0	pairs seal strips		Tube-Tubesheet Joint	Expanded (No groove)																																																																																																																																																																										
Expansion Joint				Type																																																																																																																																																																											
Rho-V2-Inlet Nozzle	679.18	kg/m-s2		Bundle Entrance	142.22	Bundle Exit	1.66	kg/m-s2																																																																																																																																																																							
Gaskets-Shell Side	Mach. Mtl. (Kammprofile/Flex. Face)			Tube Side	Mach. Mtl. (Kammprofile/Flex. Face)																																																																																																																																																																										
- Floating Head																																																																																																																																																																															
Code Requirements				TEMA Class	R																																																																																																																																																																										
Weight/Shell	4451.3	kg	Filled with Water	6698.1	kg	Bundle	2713.4	kg																																																																																																																																																																							
Remarks:																																																																																																																																																																															
Reprinted with Permission (v7.3.2)																																																																																																																																																																															

Figure 2: HTRI Heat Exchanger Specification Sheet – Increased-Capacity Case (30,000 kg/hr).

4.4 HTRI Output Summary – Increased-Capacity Case

Design: Horizontal Multipass Flow TEMA BEM Shell With Single-Segmental Baffles. No Data Check Messages (see Runtime Message Report for Warning Messages).

Process Conditions	Hot Shellside (LP-Steam)	Cold Tubeside (Process)
Flow Rate (kg/s)	1.8819	8.3333
Inlet/Outlet Vapor Fraction (Wt.)	1.0000 / 0.0000	0.0000 / 0.5000
Inlet/Outlet Temperature (°C)	138.94 / 137.75	70.00 / 111.25
Inlet Pressure / Avg (kPa)	350.00 / 344.21	700.00 / 689.22
ΔP Calculated / Allowable (kPa)	11.572 / 30.000	21.561 / 30.000
Fouling Resistance (m ² -K/W)	0.000180	0.000350

Exchanger Performance			
Shell h (W/m ² -K)	15,854	Actual U (W/m ² -K)	823.49
Tube h (W/m ² -K)	3078.6	Required U (W/m ² -K)	698.71
Hot Regime	Transition	Duty (MW)	4.0863
Cold Regime	Transition	Effective Area (m ²)	152.97
EMTD (°C)	38.2	Overdesign (%)	17.86

Shell Geometry		Baffle Geometry	
TEMA Type	BEM	Baffle Type	Single-Segmental
Shell ID (mm)	635.00	Baffle Cut (% Dia.)	25
Series / Parallel	1 / 1	Central Spacing (mm)	264.43
Orientation (deg)	0.00	Crosspasses	21

Tube Geometry		Nozzles	
Tube Type	Plain	Shell Inlet / Outlet (mm)	258.88 / 102.26
Tube OD (mm)	22.225	Shell Nozzle Heights (In/Out)	40.30 / 21.25 mm
Tube Length (m)	6.706	Tube Inlet / Outlet (mm)	77.93 / 258.88
Pitch Ratio / Layout	1.3300 / 30°	Tube Pass Count	2
Tube Count	333		

Thermal Resistance Breakdown (%)		Velocities (m/s)		
Shell Condensing Film	5.19		Min	Max
Tube Boiling Film	33.01	Tubeside	0.24	10.94
Fouling Resistance	50.39	Crossflow	0.20	13.48
Tube Metal Wall	11.40	Window	0.027	13.71
Flow Fractions				
Stream A	0.198			
Stream B	0.470			
Stream C	0.106			
Stream E	0.139			
Stream F	0.087			

Table 4: HTRI Output Summary – Increased-Capacity Case (30,000 kg/hr).

5 Response to the Project Question: Linearity of Area vs. Flow Rate

Question: Is the relationship between the percentage increase in process flow rate and the required heat transfer surface area strictly linear (+20% flow $\rightarrow$ +20% area)?

Analysis and Answer: No, the relationship is sub-linear. The required heat transfer area increases by only +16.74% (131.04 m² $\rightarrow$ 152.97 m²) for a +20.0% expansion in throughput.

Governing formulation:

$$Q = U \cdot A \cdot \Delta T_{LM} \quad (1)$$

1. Increasing process flow rate by 20% proportionally increases the thermal duty Q by approximately 20%.
2. Simultaneously, higher mass flux elevates fluid velocity inside the tubes, which increases the Reynolds number (Re).
3. Because the convective boiling coefficient obeys $h_i \propto Re^{0.8}$, higher turbulence increases h_{tube} from 2971.9 to 3078.6 W/m²K, which in turn raises the overall heat transfer coefficient U from 814.5 to 823.5 W/m²K.
4. Because the overall heat transfer coefficient U increases, the required heat transfer surface area A does not need to scale by the full 20%.

Conclusion: Capacity expansion improves the convective transport coefficient, causing the required area growth slope to be lower than the mass throughput increase ($dA/d\dot{m} < A_0/\dot{m}_0$).

6 Review of Error and Warning Messages (Part C)

“The calculated or specified terminal temperatures are impossible. Check the specified physical properties and process conditions, and rerun the case. Run Failed.”

Resolution of Pressure and Temperature Inconsistency: The software encountered terminal temperature contradictions during initial thermodynamic calculations. Specifying operating pressures consistently in Pascal units and re-verifying stream thermodynamic property curves eliminated this fatal error.

“Wavy stratified flow and partial dryout are expected in horizontal tubes. We recommend increasing flow rate or reducing tube diameter to avoid stratified flow because of its poor heat transfer performance and high uncertainty in predicting boiling heat transfer coefficients in this flow regime.”

Resolution of Stratified Flow and Dryout Warning: Selecting a 2-pass tube arrangement increased in-tube liquid-vapor velocity, maintaining an annular/intermittent flow regime and avoiding poor wetted-perimeter heat transfer associated with wavy stratified flow.

“Impingement rod width ratio has been reduced to fit the array into the shell while permitting a one-half diameter bundle of tubes.”

Correction by Adjusting Impingement Protection: To mitigate shellside inlet erosive forces ($\rho V^2 > 1000 \text{ kg/m} \cdot \text{s}^2$), impingement rods were introduced. The rod diameter ratio was adjusted to fit the array into the shell while preserving bundle entrance area.

“Unspecified channelside gasket – defaulting to gasket code 5054 – Kammprofile.”

Channel Gasket Definition: Resolved by assigning gasket code 5054 (Kammprofile metal core with flexible graphite facing), which matches high-pressure sour service criteria.

“ASME Section VIII Div. 1 Code was used to ESTIMATE all pressure vessel dimensions and weights. The dimensions in this report cannot be used to fabricate the vessel.”

This is a standard informational disclaimer from HTRI stating that mechanical shell thicknesses and vessel weights are preliminary estimates for thermal simulation and must be confirmed via structural code calculations (such as PVElite).

“Transition boiling has been predicted in at least one increment on the tube side. To confirm, check tubeside monitor for increments in transition boiling.”

This message indicates localized transition between nucleate and film boiling due to elevated wall heat fluxes. Because the mean temperature driving force is moderate (EMTD $\approx 38^\circ\text{C}$), local wall heat fluxes remain safely below critical heat flux ($q'' < q''_{\text{CHF}}$), ensuring stable operation without sustained dryout.

		Output Summary		Page 1	
		Released to the following company:			
		989144785264			
Xist 7.3.2 2/7/2026 22:14 SN: 46639-				SI Units	
Design - Horizontal Multipass Flow TEMA BEM Shell With Single-Segmental Baffles					
No Data Check Messages.					
See Runtime Message Report for Warning Messages.					
Process Conditions		Hot Shellside		Cold Tubeside	
Fluid name		LP-Steam		Process	
Flow rate	(kg/s)	1.5686		6.9444	
Inlet/Outlet Y	(Wt. frac vap.)	1.0000	0.0000	0.0000	0.5000
Inlet/Outlet T	(Deg C)	138.94	137.61	70.00	111.33
Inlet P/Avg	(kPa)	350.00	343.51	700.00	690.00
dP/Allow.	(kPa)	12.974	30.000	19.999	30.000
Fouling	(m2-K/W)	0.000180		0.000350	
Exchanger Performance					
Shell h	(W/m2-K)	16090	Actual U	(W/m2-K)	814.46
Tube h	(W/m2-K)	2971.9	Required U	(W/m2-K)	683.40
Hot regime	(--)	Transition	Duty	(MegaWatts)	3.4069
Cold regime	(--)	Tran	Eff. area	(m2)	131.04
EMTD	(Deg C)	38.0	Overdesign	(%)	19.18
Shell Geometry			Baffle Geometry		
TEMA type	(--)	BEM	Baffle type	Single-Seg.	
Shell ID	(mm)	584.20	Baffle cut	(Pct Dia.)	25
Series	(--)	1	Baffle orientation	(--)	Parallel
Parallel	(--)	1	Central spacing	(mm)	232.97
Orientation	(deg)	0.00	Crosspasses	(--)	24
Tube Geometry			Nozzles		
Tube type	(--)	Plain	Shell inlet	(mm)	205.00
Tube OD	(mm)	22.225	Shell outlet	(mm)	102.26
Length	(m)	6.706	Inlet height	(mm)	28.357
Pitch ratio	(--)	1.3300	Outlet height	(mm)	15.127
Layout	(deg)	30	Tube inlet	(mm)	77.927
Tubecount	(--)	285	Tube outlet	(mm)	205.00
Tube Pass	(--)	2			
Thermal Resistance, %		Velocities, m/s		Flow Fractions	
Shell	5.06	Min	Max	A	0.198
Tube	33.82	Shellside	0.24 10.50	B	0.470
Fouling	49.84	Crossflow	0.19 13.74	C	0.100
Metal	11.28	Window	2.64e-2 13.75	E	0.149
				F	0.083

Figure 3: HTRI Output.

		Output Summary		Page 1	
		Released to the following company: sharif shayan			
Xist 7.3.2 2/9/2026 21:51 SN: 46639-				SI Units	
Design - Horizontal Multipass Flow TEMA BEM Shell With Single-Segmental Baffles					
No Data Check Messages.					
See Runtime Message Report for Warning Messages.					
Process Conditions		Hot Shellside		Cold Tubeside	
Fluid name		LP-Steam		Process	
Flow rate (kg/s)		1.8819		8.3333	
Inlet/Outlet Y (Wt. frac vap.)		1.0000	0.0000	0.0000	0.5000
Inlet/Outlet T (Deg C)		138.94	137.75	70.00	111.25
Inlet P/Avg (kPa)		350.00	344.21	700.00	689.22
dP/Allow. (kPa)		11.572	30.000	21.561	30.000
Fouling (m2-K/W)		0.000180		0.000350	
Exchanger Performance					
Shell h (W/m2-K)		15854	Actual U (W/m2-K)	823.49	
Tube h (W/m2-K)		3078.6	Required U (W/m2-K)	698.71	
Hot regime (--)		Transition	Duty (MegaWatts)	4.0863	
Cold regime (--)		Tran	Eff. area (m2)	152.97	
EMTD (Deg C)		38.2	Overdesign (%)	17.86	
Shell Geometry			Baffle Geometry		
TEMA type (--)		BEM	Baffle type		Single-Seg.
Shell ID (mm)		635.00	Baffle cut (Pct Dia.)		25
Series (--)		1	Baffle orientation (--)		Parallel
Parallel (--)		1	Central spacing (mm)		264.43
Orientation (deg)		0.00	Crosspasses (--)		21
Tube Geometry			Nozzles		
Tube type (--)		Plain	Shell inlet (mm)		258.88
Tube OD (mm)		22.225	Shell outlet (mm)		102.26
Length (m)		6.706	Inlet height (mm)		40.303
Pitch ratio (--)		1.3300	Outlet height (mm)		21.247
Layout (deg)		30	Tube inlet (mm)		77.927
Tubecount (--)		333	Tube outlet (mm)		258.88
Tube Pass (--)		2			
Thermal Resistance, %		Velocities, m/s		Flow Fractions	
Shell 5.19		Min	Max	A	0.198
Tube 33.01		Tubeside 0.24	10.94	B	0.470
Fouling 50.39		Crossflow 0.20	13.48	C	0.106
Metal 11.40		Window 2.70e-2	13.71	E	0.139
				F	0.087

Figure 4: HTRI Output.

7 Summary

The thermal-hydraulic design developed in this project provides a reliable solution across both operating throughputs:

- **Configuration:** TEMA BEM Shell-and-Tube Exchanger ($D_{\text{shell}} = 584.2$ mm for base design, expanding to 635.0 mm for debottlenecked case).
- **Tubing:** Stainless Steel 304 plain tubes ($D_o = 22.225$ mm, length $L = 6.706$ m, 2 passes).
- **Base Operations (25,000 kg/hr):** Requires 285 tubes, transferring 3.41 MW with 19.18% overdesign and a low pressure drop ($\Delta P_t = 19.99$ kPa, $\Delta P_s = 12.97$ kPa).
- **Expanded Operations (30,000 kg/hr):** Debottlenecked to 333 tubes, transferring 4.09 MW with 17.86% overdesign and safe hydraulic margins ($\Delta P_t = 21.56$ kPa < 30 kPa).