

Rajalakshmi Engineering College

Name: Sinehan A
Email: 240801325@rajalakshmi.edu.in
Roll no: 240801325
Phone: 6381242076
Branch: REC
Department: I ECE AF
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {  
    if (dict->size == dict->capacity) {  
        dict->capacity *= 2;  
        dict->pairs = (KeyValuePair *)realloc(  
            dict->pairs,  
            dict->capacity * sizeof(KeyValuePair)
```

```
    });  
}
```

```
    strcpy(dict->pairs[dict->size].key, key);  
    strcpy(dict->pairs[dict->size].value, value);  
    dict->size++;  
}
```

```
void removeKeyValuePair(Dictionary *dict, const char *key) {  
    int idx = -1;
```

```
    for (int i = 0; i < dict->size; i++) {  
        if (strcmp(dict->pairs[i].key, key) == 0) {  
            idx = i;  
            break;  
        }  
    }  
}
```

```
if (idx < 0) return;
```

```
for (int j = idx; j < dict->size - 1; j++) {  
    dict->pairs[j] = dict->pairs[j + 1];  
}
```

```
dict->size--;  
}
```

```
int doesKeyExist(Dictionary *dict, const char *key) {  
    for (int i = 0; i < dict->size; i++) {  
        if (strcmp(dict->pairs[i].key, key) == 0) {  
            return 1;  
        }  
    }  
    return 0;  
}
```

```
void printDictionary(Dictionary *dict) {  
    for (int i = 0; i < dict->size; i++) {  
        printf("Key: %s; Value: %s\n",  
            dict->pairs[i].key,  
            dict->pairs[i].value);  
    }  
}
```

}

Status : Correct

Marks : 10/10