




Dimension: (Unit: mm)



Motor Connctions



Common Rating

Step angle	1.8°
Position accuracy	18±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MΩhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(load 4.50g)
Axial play	Max.0.08mm(load 900g)

Specification

Current /phase	1.5 A
Voltage	3.5V
DC Resistance/phase	±10% 2.3Ω
Inductance/phase	±20% 4.3 mH
Holding torque	0.45 N·M
Inertia	0.054 kg·cm²
Weight	0.5 kg
Encoder Resolution	1000 cpr

Encoder Signals

颜色	黑	红	白	黄	绿	蓝
定义	EA+	VCC	EGND	EB+	EB-	EA-

设计	杨陶	日期	2018.5.4	材料	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.		
审核	王洪松		2018.5.4	第一角画法 First Angle projection	比例	混合伺服电机	
批准	黄捷建		2018.5.4	版本/版次 A/01	图例	42CME04-PR MS30	
料号 Part No.	LS-MT-01-07A			共 1 套 第 1 套	Sheet 1 of 1	图号 DWG. NO.	LS-42CME04-PR MS30