




Dimension: (Unit: mm)



Motor Connctions



Encoder Signals



Common Rating

Step angle	1.8°
Position accuracy	18±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MΩhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max:0.02mm(load 4.50g)
Axial play	Max:0.08mm(load 900g)

Specification:

Current/phase	5.0 A
Voltage	2 V
DC Resistance/phase ±10%	0.4 Ω
Inductance/phase ±20%	1.8mH
Holding torque	3.1 N·M
Inertia	0.84, kg·cm <sup>2</sup>
Weight	1.6 kg
Encoder resolution	1000 cpr

设计	王源松	日期	18.03.06	材料	深圳市雷赛智能控制股份有限公司
审核	袁雄立	18.03.06	第一角画法	First Angle projection	SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.
批准	袁雄立	18.03.06	版本/版次	比例 Scale	混合伺服电机
图号	Part No.	LS-MT-01-07A	共 1 套	第 1 套	Sheet 1 of 1
图号	Part No.	LS-D57CME31-C MS30	共 1 套	第 1 套	Sheet 1 of 1